


The relational model

- The learning objectives for this week are:
 - Knowing what is a **data model**
 - Knowing what is the **relational data model**
 - Knowing the core terminology of the relational model
 - Knowing what are the properties of database **relations**
 - Knowing what are **domain integrity**, **entity integrity**, and **referential integrity** rules
 - Knowing how to identify **candidate keys**, **primary keys**, **alternate keys**, and **foreign keys**
 - Knowing how to formulate **relation schemas** and **relational schemas**
 - Knowing how tables are used to represent data

A substantial portion of these materials is derived from the work of Kari Silpiö. Any use, reproduction, or distribution of this content requires prior written permission from him.

Data Model



- A **data model** is a conceptual model that defines how data is structured, stored, and accessed in a system
- For example, **entity-relationship model** describes **entities** (things about which data is stored), **attributes** (details about each entity), and **relationships** (how entities are connected)
- In case of a simple online store, a **Customer** **entity** consists of **attributes** such as **name** and **email**
- The **Customer** entity could have a **relationship** with the **Order** entity, describing which orders a specific customer has placed
- Data model **helps design the structure** of a database and **makes data requirements easier to understand**, ensuring that both technical and non-technical stakeholders share a common understanding of the data

Components of a data model

- A data model consists of three components:
 1. **Structural part:** what types of data exist and how they relate to each other. For example data model could consist of `CourseImplementation` and `Teacher` entities, and `Teacher` entity has a relationship with the `CourseImplementation` entity (the teacher teaching the course implementation)
 2. **Integrity part:** how the data can be used, validated, and maintained. For example `credits` attribute of a `Course` entity should be a number between 0 and 10
 3. **Manipulative part:** what can be done with the data (like creating, reading, updating, deleting)

The relational model

- When all data model's data is logically structured within **relations**, the model is a **relational model**
- **Relation** (informally called a **table**) represents a data entity organized in a specific structure, such as `Course`
- Each relation consists of **attributes** (informally called **columns**) that define its properties, such as `name` and `credits`
- Attributes have a set of allowable values, which is referred to as the attribute's **domain**. For example, `Course` relation's `credits` attribute could be an integer value between 1 and 10
- The actual data is in relations's **tuples** (informally called **rows**)
- **Relationships** between two relations are established using a **foreign key**, which references other relation's unique **primary key**. For example `CourseImplementation` relation has a `teacherno` foreign key referencing the `Teacher` relation's `teacherno` attribute

The relational model

code	name	credits	programme code
HIS201	World History	5	HIS
MATH201	Calculus II	3	MATH
ENG150	Academic Writing	2	LING
CSC102	Introduction to Programming	5	CS

- The following data represents a **Course relation**
- The relation has four **attributes** `code`, `name`, `credits` and `programme code`
- There are four **tuples** containing the actual data
- The `code` attribute is a **primary key**, which uniquely identifies each tuple (no two tuples have the same value for the attribute)

Properties of relations

- Each relation has a name that is **distinct from all other relation names**
- Each attribute of a relation has a **distinct name within the relation**
- Each relation has a **primary key** attribute, which **unique identifies each tuple** and makes sure, there's no duplicate values. For example `code` primary key for `Course` relation and `studentnumber` primary key for `Student` relation
- Each attribute is **atomic**, meaning that each tuple's cell contains exactly one value. For example, it is not possible to have a `emails` attribute representing multiple email addresses
- Values of an attribute are all **from the same domain**. For example, `name` attribute values are only text and `credits` attribute values are only numbers

Integrity constraints

order_id	customer_id	order_date	total_amount
1	102	2025-01-13	-50.00
1	NULL	2025-01-14	150.00
6	104	02.02.2025	200.00

- The quality of the data directly determines the quality of the whole database
- Therefore preventing entry of incorrect data is one of the most important functions of a DBMS
- **Integrity constraints** are different kind of rules used to control the legal database states enforcing database **integrity**
- If the database satisfies all the integrity constraints specified on the database schema, it is in a legal state

Superkey, candidate key and primary key

- A **superkey** is an attribute or group of attributes that **uniquely identifies** each tuple of a relation
- Superkey consisting of a group of attributes is called a **composite key**
- Relation can have multiple superkeys, for example in the `Course` relation the `code` attribute, and group of `code` and `name` attributes (composite key) are superkeys
- **?** What other superkeys does the `Course` relation have?

code	name	credits	programme code
CS102	Introduction to Programming	5	CS
MATH201	Calculus II	4	MATH
ENG150	Academic Writing	2	LING

Superkey, candidate key and primary key

- A composite **candidate key** is a superkey that satisfies the property of **minimality**
- Minimality is satisfied if an attribute can't be removed from the composite key without breaking the uniqueness property
- In the `Course` relation the group of `code` and `name` attributes doesn't satisfy minimality, so it isn't a candidate key
-  What other candidate keys does the `Course` relation have?

code	name	credits	programme code
CS102	Introduction to Programming	5	CS
MATH201	Calculus II	4	MATH
ENG150	Academic Writing	2	LING

Entity integrity

- From the set of candidate keys for the relation, **exactly one** candidate key is chosen to be the **primary key**
- The other candidate keys become **alternate keys**
- Each tuple has a value for the primary key, **it can't be missing**
- Primary key's value **should not change**. For example person's name or phone number might sound tempting options for a primary key but are actually subject to change
- **Primary key constraint** prevents duplicate tuples to exist for the relation
- Primary key constraints enforce **entity integrity**

Surrogate keys

- If there is initially no candidate key available for a relation, then we cannot determine a **natural primary key**. For example, in the `Message` relation, representing email messages:

from	to	title	body
kalle.ilves@haaga-helia.fi	john.doe@gmail.com	Greeting	Hello John!
john.doe@gmail.com	kalle.ilves@haaga-helia.fi	Response	Hello Kalle!

Surrogate keys

- We can solve this situation by **including an additional attribute** with a unique value in the relation to act as the primary key. For example, a `messageid` attribute that holds a unique number for each tuple:

messageid	from	to	title	body
1	kalle.ilves@haaga-helia.fi	john.doe@gmail.com	Greeting	Hello John!
2	john.doe@gmail.com	kalle.ilves@haaga-helia.fi	Response	Hello Kalle!

Surrogate keys

- The `messageid` primary key is an example of a **surrogate key**, which is a system-generated identifier that carries no business meaning and is not derived from application data
- Surrogate key value is commonly **automatically generated** by the DBMS once a tuple is inserted
- For example, automatically increasing numbers (1, 2, 3, ...) or randomly generated values can be used to generate unique surrogate key values

Choosing a primary key


- Let's consider a suitable primary key in the following cases:
 - ? Is `Student` relation's `phonenum` attribute a good option for a primary key? Why or why not?
 - ? A `Customer` relation has attributes `address`, `name`, `email` and `social_security_number`. What would be suitable primary key for this relation and why?

<code>social_security_number</code>	<code>name</code>	<code>address</code>	<code>email</code>
123-45-6789	Alice Johnson	742 Evergreen Terrace	alicejohnson@gmail.com
987-65-4321	Bob Smith	221B Baker Street	bobthebot87@hotmail.com
555-12-3456	Carol Nguyen	1600 Pennsylvania Avenue	carolnguyen123@gmail.com

Referential Integrity

- **Foreign key** is a attribute or group attributes whose values are required to match those of the primary key of the referenced relation
- There can be several foreign keys in a relation
- Foreign-to-primary-key matching is the “glue” which holds the database together
- **Foreign key constraint** prevents foreign key not being matched by a primary key in the referenced relation
- Foreign key constraints enforce **referential integrity**

Referential Integrity



- In this example we have two relations: **Employee** and **Department**
- Each employee belongs to one department, where they work in
- This relationship is established between entities by using a **foreign key** attribute **deptno** in the **Employee** relation, which is linked to the **Department** relation's **primary key** attribute **deptno**
- ⚠ A general rule is, that foreign key **always** **references a primary key**

Example of primary and foreign keys

PLAYER

playerid	firstname	surname
1	Emma	Johnson
2	Liam	Williams
3	Olivia	Brown
4	Noah	Davis
5	Sophia	Miller

TEAM

teamid	name	captainid
10	Hawks	1
20	Tigers	2
30	Sharks	3

TEAMPLAYER

playerid	teamid
1	10
2	20
3	10
3	30
4	20
5	30

- Let's consider the following question related to these Player , Team and TeamPlayer relations:
 - ? What are the **primary keys** for each table?
 - ? What are the **foreign keys** for each table?

Relation schema and relational schema

- To provide a textual presentation of relation or a collection related relations, we can use **relation schemas** and **relational schemas**
- **Relation schema** describes a single relation. It includes the name of the relation, the names of attributes and the primary key attribute underlined

```
Course (courseCode, courseName, credits)
```

- **Relational schema** describes collection of relations and their relationships established with foreign keys

```
Course (courseCode, courseName, credits)
```

```
Student (studentNumber, familyName, givenName, birthdate)
```

```
CourseGrade (courseCode, studentNumber, grade)
```

```
FOREIGN KEY (courseCode) REFERENCES Course (courseCode)
```

```
FOREIGN KEY (studentNumber) REFERENCES Student (studentNumber)
```

Domain integrity

- A **domain constraint** specifies the set of allowable values for an attribute
- It includes attribute's **type-based restriction** (e.g. integer, string, or date) and further restrictions based on user-defined rules. For example:
 - Valid grade marks are integers between 0 and 5
 - Student's birth date is a valid date before today's date
 - Student's email should be a string in format %@%.%
- Domain constraints enforce **domain integrity**

Not null constraint

studentid	name	phonenumber	major
2001	Emma Thompson	(415) 555-0198	Computer Science
2002	Liam Martinez	NULL	Computer Science
2003	Sophia Chen	(212) 555-0843	Psychology

- **Null** is a marker for a missing attribute value
- Null is not the same as e.g. blanks or zero. Null represents **absence of a value**
- The **not null constraint** is a restriction placed on an attribute, which enforces that in every tuple of data the attribute **must have a value**
- For example, it would make sense that in the `Employee` relation, the `deptno` attribute has a not null constraint, meaning that every employee belongs to a department

Database manipulation

- A **manipulation mechanism** is among the most important parts of a data model
- A manipulation mechanism allows the data to be retrieved and updated
- **Structured Query Language** (SQL) is the standard database language for relational databases.

With SQL we can:

- Create the database and relation structures
- Perform insertion, modification, and deletion of data from the relations
- Perform database queries
- Instead of using formal terms of relations, attributes, and tuples, the terms **tables**, **columns**, and **rows** are used in the SQL standard

SQL

- An **SQL query** is a single statement in which you describe what kind of data we want to **retrieve from the database** or **how we want to manipulate it** (insert, update, delete)
- While retrieving data, the query operates on tables and builds a result table from one or more tables in the database
- Here's an example of an SQL query and its result table:

```
SELECT code, name, credits  
FROM course  
WHERE name = 'Data Management and Databases';
```

code	name	credits
CS220	Data Management and Databases	5

Summary

- A **data model** consists of three components: the **structural part**, the **integrity part** and the **manipulative part**
- In the **relational model**, all data is logically structured within relations that have attributes and tuples
- **SQL** is the standard database language for relational databases
- **Integrity constraints** are rules which make sure that the database is in a legal state
- **Domain constraint** specifies the set of allowable values for an attribute
- **Primary key constraint** prevents duplicate tuples to exist for the relation
- **Foreign key constraint** prevents foreign key not being matched by a primary key in the referenced relation
- **Not null constraint** enforces that in every tuple of data the specified attribute **must have a value**