

1 get-encryption-key.md

Encryption

The transport between client applications and Lenco is secured using TLS/SSL, which means data is encrypted by default when transmitted across networks.

In addition, certain endpoints of the Lenco API make use of JSON Web Encryption (JWE) to provide end-to-end payload encryption to secure sensitive data. For instance, the [Card Collection API](<https://lenco-api.readme.io/v2.0/reference/initiate-collection-from-card>) must comply with the Payment Card Industry Data Security Standard in dealing with cardholder Personally Identifying Information (PII).

JSON Web Encryption (JWE) represents encrypted content using JSON-based data structures and base64url encoding. Lenco uses JWE compact serialization for the encryption of sensitive data.

Lenco encryption uses AES in GCM (Galois/Counter Mode) mode with PKCS#7 padding and RSA with OAEP (Optimal Asymmetric Encryption Padding).

The Encryption Keys

RSA\

Encryption involves a 2048-bit RSA public/private key pair. Data encrypted using a public key can only be decrypted using the corresponding private key.

The client application will get an RSA public key using the [Get Encryption Key](<https://lenco-api.readme.io/v2.0/reference/get-encryption-key>) endpoint, which allows to encrypt the request payload.

AES\

For performance reasons, RSA asymmetric encryption is combined with AES symmetric encryption. For that, a one-time usage 256-bit AES session key is generated and encrypted using the RSA public key. The encrypted (or wrapped) key is sent in the payload along with the encrypted data.

The Encryption Process

Here are the steps for sending an encrypted payload:

1. An AES session key is generated along with some encryption parameters
2. Sensitive data are encrypted using the AES key

3. The AES key is encrypted using the RSA public key gotten from the [Get Encryption Key](https://lenco-api.readme.io/v2.0/reference/get-encryption-key) endpoint

4. The payload is sent with the encrypted session key and parameters

How to Encrypt Payload

The encrypted payload is structured in JSON Web Encryption (JWE) format, the plain text JSON body is encrypted to form a JWE encrypted payload that is sent as the request body (replacing the plain text data).

****Step 1**:** Construct the original JSON per the API specification.

****Step 2**:** Get the RSA public key using from the [Get Encryption Key](https://lenco-api.readme.io/v2.0/reference/get-encryption-key) endpoint. Beware that this key might change anytime and therefore should not be stored and reused.

****Step 3**:** Use JWE to encrypt the original request in compact serialized form using the below JOSE headers:

JOSE Header	Value	Description
:	:	:
enc	A256GCM	encryption algorithm
alg	RSA-OAEP-256	Key encryption algorithm
cty	application/json	content type of the encrypted payload
kid	`kid` property of the RSA public key (JWK)	Public Fingerprint ID which is used to identify the private key needed to decrypt the message

****Step 4**:** Construct request payload as shown below:

```
```json
{
 "encryptedPayload": "JWE encrypted payload"
}
```
```


Examples:

```
```go
package main

import (
 "github.com/lestrrat-go/jwx/jwa"
 "github.com/lestrrat-go/jwx/jwe"
 "github.com/lestrrat-go/jwx/jwk"
)

func encrypt(payload []byte) (string, error) {
 jwkJSON := `{
 "kty": "RSA",
 "use": "enc",
 "n": "nApb8LyyFrZw4A(...)W1RpGR6Z7zcNikiZcQ",
 "e": "AQAB",
 "kid": "2bbb0d(...)2f68aa"
 }`

 rsaPublicKey, err := jwk.ParseKey([]byte(jwkJSON))
 if err != nil {
 return "", err
 }

 encrypted, err := jwe.Encrypt(payload, jwa.RSA_OAEP_256, rsaPublicKey,
jwa.A256GCM, jwa.NoCompress)
 if err != nil {
 return "", err
 }

 return string(encrypted[:]), nil
}
```

```node
const jose = require("jose");

async function encrypt(payload) {
 const jwkData = {
 "kty": "RSA",
 "use": "enc",
 "n": "nApb8LyyFrZw4A(...)W1RpGR6Z7zcNikiZcQ",
 "e": "AQAB",
 "kid": "2bbb0d(...)2f68aa"
 };
};
```

```

const rsaPublicKey = await jose.importJWK(jwkData);
const text = JSON.stringify(payload);
const jwe = await new jose.CompactEncrypt(new TextEncoder().encode(text))
 .setProtectedHeader({
 alg: 'RSA-OAEP-256',
 enc: 'A256GCM',
 cty: 'application/json',
 kid: jwkData.kid
 })
 .encrypt(rsaPublicKey);

return jwe;
}
...

```

>  NB

>

> The examples above are just code samples to help get you started. Lenco does not in any way recommend the use of these libraries.\

> It is important that you scrutinise / audit any third party library or package before using it in production.

## 2 encryption.md

### # Encryption

The transport between client applications and Lenco is secured using TLS/SSL, which means data is encrypted by default when transmitted across networks.

In addition, certain endpoints of the Lenco API make use of JSON Web Encryption (JWE) to provide end-to-end payload encryption to secure sensitive data. For instance, the [Card Collection API](<https://lenco-api.readme.io/v2.0/reference/initiate-collection-from-card>) must comply with the Payment Card Industry Data Security Standard in dealing with cardholder Personally Identifying Information (PII).

JSON Web Encryption (JWE) represents encrypted content using JSON-based data structures and base64url encoding. Lenco uses JWE compact serialization for the encryption of sensitive data.

Lenco encryption uses AES in GCM (Galois/Counter Mode) mode with PKCS#7 padding and RSA with OAEP (Optimal Asymmetric Encryption Padding).

<br />

### ### The Encryption Keys

## **\*\*RSA\*\*\**

Encryption involves a 2048-bit RSA public/private key pair. Data encrypted using a public key can only be decrypted using the corresponding private key.

The client application will get an RSA public key using the [Get Encryption Key](https://lenco-api.readme.io/v2.0/reference/get-encryption-key) endpoint, which allows to encrypt the request payload.

## **\*\*AES\*\*\**

For performance reasons, RSA asymmetric encryption is combined with AES symmetric encryption. For that, a one-time usage 256-bit AES session key is generated and encrypted using the RSA public key. The encrypted (or wrapped) key is sent in the payload along with the encrypted data.

<br />

### **### The Encryption Process**

Here are the steps for sending an encrypted payload:

1. An AES session key is generated along with some encryption parameters
2. Sensitive data are encrypted using the AES key
3. The AES key is encrypted using the RSA public key gotten from the [Get Encryption Key](https://lenco-api.readme.io/v2.0/reference/get-encryption-key) endpoint
4. The payload is sent with the encrypted session key and parameters

<br />

### **### How to Encrypt Payload**

The encrypted payload is structured in JSON Web Encryption (JWE) format, the plain text JSON body is encrypted to form a JWE encrypted payload that is sent as the request body (replacing the plain text data).

**\*\*Step 1\*\*:** Construct the original JSON per the API specification.

**\*\*Step 2\*\*:** Get the RSA public key using from the [Get Encryption Key](https://lenco-api.readme.io/v2.0/reference/get-encryption-key) endpoint. Beware that this key might change anytime and therefore should not be stored and reused.

**\*\*Step 3\*\*:** Use JWE to encrypt the original request in compact serialized form using the below JOSE headers:

JOSE Header	Value
Description	

	-----	-----	-----
enc	A256GCM		encryption
algorithm			
alg	RSA-OAEP-256		Key encryption
algorithm			
cty	application/json		content type of the encrypted payload
kid	`kid` property of the RSA public key (JWK) Public Fingerprint ID which is used to identify the private key needed to decrypt the message		

**\*\*Step 4\*\***: Construct request payload as shown below:

```
```json
{
  "encryptedPayload": "JWE encrypted payload"
}
```
```

<br />

Examples:

```
```go
package main

import (
    "github.com/lestrrat-go/jwx/jwa"
    "github.com/lestrrat-go/jwx/jwe"
    "github.com/lestrrat-go/jwx/jwk"
)

func encrypt(payload []byte) (string, error) {
    jwkJSON := `{
        "kty": "RSA",
        "use": "enc",
        "n": "nApb8LyyFrZw4A(...)W1RpGR6Z7zcNikiZcQ",
        "e": "AQAB",
        "kid": "2bbb0d(...)2f68aa"
    }`

    rsaPublicKey, err := jwk.ParseKey([]byte(jwkJSON))
    if err != nil {
        return "", err
    }
}
```

```

    }

    encrypted, err := jwe.Encrypt(payload, jwa.RSA_OAEP_256, rsaPublicKey,
jwa.A256GCM, jwa.NoCompress)
    if err != nil {
        return "", err
    }

    return string(encrypted[:]), nil
}
...
```node
const jose = require("jose");

async function encrypt(payload) {
 const jwkData = {
 "kty": "RSA",
 "use": "enc",
 "n": "nApb8LyyFrZw4A(...)W1RpGR6Z7zcNikiZcQ",
 "e": "AQAB",
 "kid": "2bbb0d(...)2f68aa"
 };

 const rsaPublicKey = await jose.importJWK(jwkData);
 const text = JSON.stringify(payload);
 const jwe = await new jose.CompactEncrypt(new TextEncoder().encode(text))
 .setProtectedHeader({
 alg: 'RSA-OAEP-256',
 enc: 'A256GCM',
 cty: 'application/json',
 kid: jwkData.kid
 })
 .encrypt(rsaPublicKey);

 return jwe;
}
...

```

>  NB

>

> The examples above are just code samples to help get you started. Lenco does not in any way recommend the use of these libraries.\

> It is important that you scrutinise / audit any third party library or package before using it in production.

### 3 webhooks.md

#### # Webhooks

Learn how to listen to events whenever certain actions occur on your integration.

#### ## What are webhooks?

Whenever certain actions occur on your Lenco account or API integration, we trigger events which your application can listen to. This is where webhooks come in. A webhook is a URL on your server where we send payloads for such events. For example, if you implement webhooks, once a transfer is successful, we will immediately notify your server with a ``transfer.successful`` event. Here is a [list of events](#types-of-events) we can send to your webhook URL.

> 

>

> **\*\*NB\*\***: You may not be able to rely completely on webhooks to get notified. An example is if your server is experiencing a downtime and your hook endpoints are affected, some customers might still be transacting independently of that and the hook call triggered would fail because your server was unreachable.

>

> *\*In such cases we advise that developers set up a re-query service that goes to poll for the transaction status at regular intervals e.g. every 30 minutes using the ``/transfers/:id`` or ``/transfers/status/:reference`` endpoint, till a successful or failed response is returned.\**

To setup your webhook URL, kindly reach out to <[support@lenco.co](mailto:support@lenco.co)>

**\*\*Here are some things to note when setting up a webhook URL:\*\***

1. If using .htaccess, remember to add the trailing / to the url you set.
2. Do a test post to your URL and ensure the script gets the post body.
3. Ensure your webhook URL is publicly available (localhost URLs cannot receive events)

#### ## Receiving an event

All you have to do to receive the event is to create an unauthenticated POST route on your application. The event object is sent as JSON in the request body.

```
```javascript
Node
// Using Express
app.post("/my/webhook/url", function(req, res) {
  // Retrieve the request's body
  var event = req.body;
});
```



```

    // Do something with event
    res.send(200);
  });
  ...
  ```php
 <?php
 // Retrieve the request's body and parse it as JSON
 $input = @file_get_contents("php://input");
 $event = json_decode($input);
 // Do something with $event
 http_response_code(200); // PHP 5.4 or greater
 ?>
 ...

```

## ## Verifying events

It is important to verify that events originate from Lenco to avoid delivering value based on a counterfeit event.\

Valid events are raised with an header ``X-Lenco-Signature`` which is essentially a HMAC SHA512 signature of the event payload signed using your ``webhook_hash_key``.\

The ``webhook_hash_key`` is a SHA256 hash of your API token.

```

  ```javascript Node
  var crypto = require('crypto');
  var apiToken = process.env.API_TOKEN;
  var webhookHashKey =
  crypto.createHash("sha256").update(apiToken).digest("hex");
  // Using Express
  app.post("/my/webhook/url", function(req, res) {
    //validate event
    var hash = crypto.createHmac('sha512',
webhookHashKey).update(JSON.stringify(req.body)).digest('hex');
    if (hash === req.headers['x-lenco-signature']) {
      // Retrieve the request's body
      var event = req.body;
      // Do something with event
    }
    res.send(200);
  });
  ...
  ```php
 <?php
 // only a post with lenco signature header gets our attention
 if ((strtoupper($_SERVER['REQUEST_METHOD']) != 'POST')
 || !array_key_exists('HTTP_X_LENCO_SIGNATURE', $_SERVER))
 exit();
 // Retrieve the request's body

```

```

$input = @file_get_contents("php://input");
define('LENCO_API_TOKEN', 'API_TOKEN');
$webhook_hash_key = hash("sha256", LENCO_API_TOKEN);
// validate event do all at once to avoid timing attack
if($_SERVER['HTTP_X_LENCO_SIGNATURE'] !== hash_hmac('sha512', $input,
$webhook_hash_key))
 exit();
http_response_code(200);
// parse event (which is json string) as object
// Do something - that will not take long - with $event
$event = json_decode($input);
exit();
?>
```

```

Responding to an event

You should respond to an event with a ``200`` OK. We consider this an acknowledgement by your application. If your application responds with any status outside of either ``200``, ``201``, or ``202``, we will consider it unacknowledged and thus, continue to send it every 30 minutes for 24 hours. You don't need to send a request body or some other parameter as it would be discarded - we only pay attention to the status code.

If your application is likely to start a long running task in response to the event, Lenco may timeout waiting for the response and would ultimately consider the event unacknowledged and queue to be raised later. You can mitigate duplicity by having your application respond immediately with a 200 before it goes on to perform the rest of the task.

Types of events

Here are the events we currently raise. We would add more to this list as we hook into more actions in the future.

| Event | Description |
|--|-------------|
| <pre> :----- :----- `transfer.successful` A transfer was successfully completed from any of the accounts linked to your API token `transfer.failed` A transfer you attempted from any of the accounts linked to your API token has failed `collection.successful` A collection you attempted was successfully completed `collection.failed` A collection you attempted has failed </pre> | |

| | |
|----------------------|---|
| `collection.settled` | Your account was credited for a |
| collection | |
| `transaction.credit` | An account linked to your API token was |
| credited | |
| `transaction.debit` | An account linked to your API token was |
| debited | |

```
```json transfer.successful
```

```
{
 "event": "transfer.successful",
 "data": {
 "id": string,
 "amount": string,
 "fee": string,
 "currency": string,
 "narration": string,
 "initiatedAt": date-time,
 "completedAt": date-time | null,
 "accountId": string,
 "creditAccount": {
 "id": string | null,
 "type": string,
 "accountName": string,
 "accountNumber": string | null,
 "bank": {
 "id": string,
 "name": string,
 "country": string
 } | null,
 "phone": string | null,
 "operator": string | null,
 "walletNumber": string | null,
 "tillNumber": string | null
 },
 "status": "pending" | "successful" | "failed",
 "reasonForFailure": string | null,
 "reference": string | null,
 "lencoReference": string,
 "extraData": {
 "nipSessionId": string | null,
 },
 "source": "banking-app" | "api"
 }
}
```

```
}
```
```

```
```json transfer.failed
```

```
{
 "event": "transfer.failed",
```

```

 "data": {
 "id": string,
 "amount": string,
 "fee": string,
 "currency": string,
 "narration": string,
 "initiatedAt": date-time,
 "completedAt": date-time | null,
 "accountId": string,
 "creditAccount": {
 "id": string | null,
 "type": string,
 "accountName": string,
 "accountNumber": string | null,
 "bank": {
 "id": string,
 "name": string,
 "country": string
 } | null,
 "phone": string | null,
 "operator": string | null,
 "walletNumber": string | null,
 "tillNumber": string | null
 },
 "status": "pending" | "successful" | "failed",
 "reasonForFailure": string | null,
 "reference": string | null,
 "lencoReference": string,
 "extraData": {
 "nipSessionId": string | null,
 },
 "source": "banking-app" | "api"
 }
 }
 ...
  ```json collection.successful
  {
    "event": "collection.successful",
    "data": {
      "id": string,
      "initiatedAt": date-time,
      "completedAt": date-time | null,
      "amount": string,
      "fee": string | null,
      "bearer": "merchant" | "customer",
      "currency": string,
      "reference": string | null,
      "lencoReference": string,

```

```

    "type": "card" / "mobile-money" / "bank-account" / null,
    "status": "pending" / "successful" / "failed" / "pay-offline",
    "source": "banking-app" / "api",
    "reasonForFailure": string / null,
    "settlementStatus": "pending" / "settled" / null,
    "settlement": {
      "id": string,
      "amountSettled": string,
      "currency": string,
      "createdAt": date-time,
      "settledAt": date-time / null,
      "status": "pending" / "settled",
      "type": "instant" / "next-day",
      "accountId": string,
    } / null,
    "mobileMoneyDetails": {
      "country": string,
      "phone": string,
      "operator": string,
      "accountName": string / null,
      "operatorTransactionId": string / null,
    } / null,
    "bankAccountDetails": null,
    "cardDetails": null,
  }
}
...
```json collection.failed
{
 "event": "collection.failed",
 "data": {
 "id": string,
 "initiatedAt": date-time,
 "completedAt": date-time / null,
 "amount": string,
 "fee": string / null,
 "bearer": "merchant" / "customer",
 "currency": string,
 "reference": string / null,
 "lencoReference": string,
 "type": "card" / "mobile-money" / "bank-account" / null,
 "status": "pending" / "successful" / "failed" / "pay-offline",
 "source": "banking-app" / "api",
 "reasonForFailure": string / null,
 "settlementStatus": "pending" / "settled" / null,
 "settlement": {
 "id": string,
 "amountSettled": string,

```

```

 "currency": string,
 "createdAt": date-time,
 "settledAt": date-time | null,
 "status": "pending" | "settled",
 "type": "instant" | "next-day",
 "accountId": string,
 } / null,
 "mobileMoneyDetails": {
 "country": string,
 "phone": string,
 "operator": string,
 "accountName": string | null,
 "operatorTransactionId": string | null,
 } / null,
 "bankAccountDetails": null,
 "cardDetails": null,
}
}
...
```json collection.settled
{
    "event": "collection.settled",
    "data": {
        "id": string,
        "initiatedAt": date-time,
        "completedAt": date-time | null,
        "amount": string,
        "fee": string | null,
        "bearer": "merchant" | "customer",
        "currency": string,
        "reference": string | null,
        "lencoReference": string,
        "type": "card" | "mobile-money" | "bank-account" | null,
        "status": "pending" | "successful" | "failed" | "pay-offline",
        "source": "banking-app" | "api",
        "reasonForFailure": string | null,
        "settlementStatus": "pending" | "settled" | null,
        "settlement": {
            "id": string,
            "amountSettled": string,
            "currency": string,
            "createdAt": date-time,
            "settledAt": date-time | null,
            "status": "pending" | "settled",
            "type": "instant" | "next-day",
            "accountId": string,
        } / null,
        "mobileMoneyDetails": {

```

```

        "country": string,
        "phone": string,
        "operator": string,
        "accountName": string | null,
        "operatorTransactionId": string | null,
    } | null,
    "bankAccountDetails": null,
    "cardDetails": null,
}
}
...
```json transaction.credit
{
 "event": "transaction.credit",
 "data": {
 "id": string,
 "amount": string,
 "currency": string,
 "narration": string,
 "type": "credit" | "debit",
 "datetime": date-time,
 "accountId": string,
 "balance": string | null
 }
}
...
```json transaction.debit
{
    "event": "transaction.debit",
    "data": {
        "id": string,
        "amount": string,
        "currency": string,
        "narration": string,
        "type": "credit" | "debit",
        "datetime": date-time,
        "accountId": string,
        "balance": string | null
    }
}
}
...

```

4 introduction.md

```
# Welcome to Lenco's API doc
```

With Lenco API, you can access all your accounts and sub-accounts and their transaction histories. You'll learn how to build amazing web and mobile integration payment experiences with the Lenco API.

These docs will cover the available endpoints and provide example code for using the API. They will hopefully help you build your own admin tools or automate processes that previously had to be performed manually.

If you have any questions, just send us an email at [<support@lenco.co>](mailto:support@lenco.co).

5 get-started.md

Getting Started

This page will help you get started with Lenco API

To get your API token (also referred to as api key or secret key), kindly reach out to [<support@lenco.co>](mailto:support@lenco.co)

Securing Your API Token

Someone who steals your Lenco API token can interact with your accounts on your behalf, so treat it as securely as you would treat any password. Tokens should never be stored in source control. If you accidentally publicize a token via version control or other methods, you should immediately reach out to [<support@lenco.co>](mailto:support@lenco.co) to generate a new API token.

Using the Token

Authenticate your API calls by including your api token in the Authorization header of every request you make.\

Authorization headers should be in the following format: Authorization:

``Bearer API_TOKEN``

```

`curl -H "Authorization: Bearer xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"`

```

API requests made without authentication will fail with the status code ``401: Unauthorized``. All API requests must be made over HTTPS.

Requests and Response

Both request body data and response data are formatted as JSON. Content type for responses will always be ``application/json``. Generally, all responses will be in the following format:

Response Format


```

```json
{
 "status": [boolean], // Only true if the details provided could be
processed and no error occurred while processing
 "message": [string], // Explains why status is false... Entirely
informational. Please only log this but do not use for your checks
 "data": [object] // contains actionable result of processing if present
}
```

```

While we generally recommend that developers use HTTP status codes to determine the result of an API call, we have provided a handy status key to let you know upfront if the request was successful or not.

The message key is a string which will contain a summary of the response and its status. For instance when trying to retrieve a list of recipients, message might read “Recipients retrieved”. In the event of an error, the message key will contain a description of the error as with the authorization header situation above. This is the only key that is universal across requests.

The data key is where you want to look at for the result of your request. It can either be an object, or an array depending on the request made. For instance, a request to retrieve a single recipient will return a recipient object in the data key, while the key would be an array of recipients if a list is requested instead.

The meta key is used to provide context for the contents of the data key. For instance, when retrieving the list of transactions, pagination parameters can be passed along to limit the result set. The meta key will then contain an object with the following attributes:

Meta Key Structure

```

```json
"meta": {
 "total": 2,
 "perPage": 50,
 "currentPage": 1,
 "pageCount": 1
}
```

```

Keys

****total**** number\
This is the total number of records.

****perPage**** number\

This is the maximum number of records that will be returned per request.

****currentPage**** number\

This is the current ``page`` being returned. This is dependent on what page was requested using the ``page`` query parameter. ****Default: 1****

****pageCount**** number\

This is how many pages in total are available for retrieval considering the maximum number of records returned per request (i.e. ``perPage``). For context, if there are 101 records and ``perPage`` is 100, ``pageCount`` will have a value of 2.

Errors

Lenco's API is RESTful and as such, uses conventional HTTP response codes to indicate the success or failure of requests.\

The common error codes can be found below:

****200, 201****\

Request was successful and intended action was carried out. Note that we will always send a 200 if a transfer or collection request was made. Do check the data object to know how the request went (i.e. successful or failed).

****400****\

A validation or client side error occurred and the request was not fulfilled.

****401****\

The request was not authorized. This can be triggered by passing an invalid API token in the authorization header or the lack of one.

****404****\

Request could not be fulfilled as the request resource does not exist.

****500, 501, 502, 503, 504****\

Request could not be fulfilled due to an error on Lenco's end. This shouldn't happen so please report as soon as you encounter any instance of this.

If the HTTP response code is not 200 (or 201), the response would optionally include ``errorCode``.\

Possible values for ``errorCode`` is given in the table below.

| Error Code | Details |
|------------|---------|
| :----- | :----- |
| ----- | |

| | |
|----|--|
| 01 | Validation error. One or more parameters could not be validated correctly. |
| 02 | Insufficient funds in account |
| 03 | The transfer limit on the account has been exceeded |
| 04 | Invalid or duplicate reference |
| 05 | Invalid recipient account |
| 06 | Restriction on debit account |
| 07 | Invalid or duplicate bulk transfer reference |
| 08 | Invalid number of objects in bulk transfer `transfers` parameter |
| 09 | Invalid auth token or authorization denied |
| 10 | General error |
| 11 | Resource not found |
| 12 | Invalid mobile number |
| 13 | Access to resource denied |

6 get-transfer-by-reference.md

`/transfers/status/:reference`

Retrieve information about a specific transfer using the reference you used when initiating the transfer

Response Schema:

```
```json
{
 "status": boolean,
 "message": string,
 "data": {
 "id": string,
 "amount": string,
 "fee": string,
 "currency": string,
 "narration": string,
 "initiatedAt": date-time,
 "completedAt": date-time | null,
 }
}
```

```

 "accountId": string,
 "creditAccount": {
 "id": string / null,
 "type": string,
 "accountName": string,
 "accountNumber": string / null,
 "bank": {
 "id": string,
 "name": string,
 "country": string
 } / null,
 "phone": string / null,
 "operator": string / null,
 "walletNumber": string / null,
 "tillNumber": string / null
 },
 "status": "pending" / "successful" / "failed",
 "reasonForFailure": string / null,
 "reference": string / null,
 "lencoReference": string,
 "extraData": {
 "nipSessionId": string / null,
 },
 "source": string
 }
}
...

```

#### # OpenAPI definition

```

```json
{
  "openapi": "3.1.0",
  "info": {
    "title": "Lenco API",
    "version": "2.0"
  },
  "servers": [
    {
      "url": "https://api.lenco.co/access/v2"
    }
  ],
  "components": {
    "securitySchemes": {
      "sec0": {
        "type": "apiKey",
        "in": "header",
        "name": "Authorization",

```

```

        "x-bearer-format": "bearer",
        "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
    }
},
"security": [
    {
        "sec0": []
    }
],
"paths": {
    "/transfers/status/{reference}": {
        "get": {
            "summary": "/transfers/status/:reference",
            "description": "Retrieve information about a specific transfer using
the reference you used when initiating the transfer",
            "operationId": "get-transfer-by-reference",
            "parameters": [
                {
                    "name": "reference",
                    "in": "path",
                    "description": "The reference used when initiating the transfer",
                    "schema": {
                        "type": "string"
                    },
                    "required": true
                }
            ],
            "responses": {
                "200": {
                    "description": "200",
                    "content": {
                        "application/json": {
                            "examples": {
                                "Result": {
                                    "value": "{\n    \"status\": true,\n    \"message\":
\\\"\\\", \n    \"data\": {\n        \"id\": \"9525b4c6-502b-45be-90e1-
81eb81a3f424\", \n        \"amount\": \"20.00\", \n        \"fee\":
\\\"8.50\", \n        \"currency\": \"ZMW\", \n        \"narration\":
\\\"Transfer\", \n        \"initiatedAt\": \"2024-01-
01T00:00:00.447Z\", \n        \"completedAt\": \"2024-01-
01T00:00:01.237Z\", \n        \"accountId\": \"b176cda5-7d97-4a3f-b4dd-
ab0234e9e08c\", \n        \"creditAccount\": {\n            \"type\": \"bank-
account\", \n            \"accountName\": \"Beata
Jean\", \n            \"accountNumber\":
\\\"9130000000000\", \n            \"bank\": {\n                \"id\":
\\\"002\", \n                \"name\": \"Absa
Bank\", \n                \"country\":

```

```

\ "zm\ "\n          }\n          },\n          \ "status\ ":
\ "successful\ ",\n          \ "reasonForFailure\ ": null,\n          \ "reference\ ":
\ "ref-3\ ",\n          \ "lencoReference\ ": \ "240010002\ ",\n          \ "extraData\ ":
{\n          \ "nipSessionId\ ": null\n          },\n          \ "source\ ":
\ "api\ "\n      }\n}"
    }
  },
  "schema": {
    "type": "object",
    "properties": {
      "status": {
        "type": "boolean",
        "example": true,
        "default": true
      },
      "message": {
        "type": "string",
        "example": ""
      },
      "data": {
        "type": "object",
        "properties": {
          "id": {
            "type": "string",
            "example": "9525b4c6-502b-45be-90e1-81eb81a3f424"
          },
          "amount": {
            "type": "string",
            "example": "20.00"
          },
          "fee": {
            "type": "string",
            "example": "8.50"
          },
          "currency": {
            "type": "string",
            "example": "ZMW"
          },
          "narration": {
            "type": "string",
            "example": "Transfer"
          },
          "initiatedAt": {
            "type": "string",
            "example": "2024-01-01T00:00:00.447Z"
          },
          "completedAt": {
            "type": "string",

```

```
    "example": "2024-01-01T00:00:01.237Z"
  },
  "accountId": {
    "type": "string",
    "example": "b176cda5-7d97-4a3f-b4dd-ab0234e9e08c"
  },
  "creditAccount": {
    "type": "object",
    "properties": {
      "type": {
        "type": "string",
        "example": "bank-account"
      },
      "accountName": {
        "type": "string",
        "example": "Beata Jean"
      },
      "accountNumber": {
        "type": "string",
        "example": "9130000000000"
      }
    },
    "bank": {
      "type": "object",
      "properties": {
        "id": {
          "type": "string",
          "example": "002"
        },
        "name": {
          "type": "string",
          "example": "Absa Bank"
        },
        "country": {
          "type": "string",
          "example": "zm"
        }
      }
    }
  },
  "status": {
    "type": "string",
    "example": "successful"
  },
  "reasonForFailure": {},
  "reference": {
    "type": "string",
    "example": "ref-3"
  }
}
```

```

    },
    "lencoReference": {
      "type": "string",
      "example": "240010002"
    },
    },
    "extraData": {
      "type": "object",
      "properties": {
        "nipSessionId": {}
      }
    },
    },
    "source": {
      "type": "string",
      "example": "api"
    }
  }
}
}
}
}
},
"404": {
  "description": "404",
  "content": {
    "application/json": {
      "examples": {
        "Result": {
          "value": "{\n  \"status\": false,\n  \"message\":\n\"Transfer was not found\", \n  \"data\": null\n}"
        }
      }
    },
    "schema": {
      "type": "object",
      "properties": {
        "status": {
          "type": "boolean",
          "example": false,
          "default": true
        },
        "message": {
          "type": "string",
          "example": "Transfer was not found"
        },
        "data": {}
      }
    }
  }
}
}

```



```

    }
  }
},
"deprecated": false
}
}
},
"x-readme": {
  "headers": [],
  "explorer-enabled": false,
  "proxy-enabled": true
},
"x-readme-fauxas": true,
"_id": "65f06b6583c5de0051b8aa08:65f19bc16f0ae20079796bbc"
}
...

```

7 initiate-transfer-to-bank-account.md

```
# /transfers/bank-account
```

Initiate transfer to a bank account

Response Schema:

```

```json
{
 "status": boolean,
 "message": string,
 "data": {
 "id": string,
 "amount": string,
 "fee": string,
 "currency": string,
 "narration": string,
 "initiatedAt": date-time,
 "completedAt": date-time | null,
 "accountId": string,
 "creditAccount": {
 "type": "bank-account",
 "accountName": string,
 "accountNumber": string,
 "bank": {
 "id": string,
 "name": string,
 "country": string
 }
 }
 }
},

```

```

 "status": "pending" / "successful" / "failed",
 "reasonForFailure": string / null,
 "reference": string / null,
 "lencoReference": string,
 "extraData": {
 "nipSessionId": string / null,
 },
 "source": string
 }
}
```

# OpenAPI definition

```json
{
 "openapi": "3.1.0",
 "info": {
 "title": "Lenco API",
 "version": "2.0"
 },
 "servers": [
 {
 "url": "https://api.lenco.co/access/v2"
 }
],
 "components": {
 "securitySchemes": {
 "sec0": {
 "type": "apiKey",
 "in": "header",
 "name": "Authorization",
 "x-bearer-format": "bearer",
 "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
 }
 }
 },
 "security": [
 {
 "sec0": []
 }
],
 "paths": {
 "/transfers/bank-account": {
 "post": {
 "summary": "/transfers/bank-account",
 "description": "Initiate transfer to a bank account",
 "operationId": "initiate-transfer-to-bank-account",

```

```

"requestBody": {
 "content": {
 "application/json": {
 "schema": {
 "type": "object",
 "required": [
 "accountId",
 "amount",
 "reference"
],
 "properties": {
 "accountId": {
 "type": "string",
 "description": "Your 36-character account uuid to debit"
 },
 "amount": {
 "type": "number",
 "format": "double"
 },
 "narration": {
 "type": "string",
 "description": "Optional"
 },
 "reference": {
 "type": "string",
 "description": "Unique client reference. Only `~`, `~.`,
`_` and alphanumeric characters allowed"
 },
 "transferRecipientId": {
 "type": "string",
 "description": "Optional. 36-character transfer recipient
uuid"
 },
 "accountNumber": {
 "type": "string",
 "description": "Optional. If you do not have the
transferRecipientId, use this and bankId"
 },
 "bankId": {
 "type": "string",
 "description": "Optional. If you do not have the
transferRecipientId, use this and accountNumber"
 },
 "country": {
 "type": "string",
 "description": "Optional. i.e. `ng`, `zm`"
 }
 }
 }
 }
 }
}

```

```

 }
 }
},
"responses": {
 "200": {
 "description": "200",
 "content": {
 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": true,\n \"message\":\n\", \n \"data\": {\n \"id\": \"9525b4c6-502b-45be-90e1-81eb81a3f424\", \n \"amount\": \"20.00\", \n \"fee\": \"8.50\", \n \"currency\": \"ZMW\", \n \"narration\": \"Transfer\", \n \"initiatedAt\": \"2024-01-01T00:00:00.447Z\", \n \"completedAt\": \"2024-01-01T00:00:01.237Z\", \n \"accountId\": \"b176cda5-7d97-4a3f-b4dd-ab0234e9e08c\", \n \"creditAccount\": {\n \"type\": \"bank-account\", \n \"accountName\": \"Beata Jean\", \n \"accountNumber\": \"9130000000000\", \n \"bank\": {\n \"id\": \"002\", \n \"name\": \"Absa Bank\", \n \"country\": \"zm\" \n }, \n \"status\": \"successful\", \n \"reasonForFailure\": null, \n \"reference\": \"ref-3\", \n \"lencoReference\": \"240010002\", \n \"extraData\": {\n \"nipSessionId\": null \n }, \n \"source\": \"api\" \n } \n } \n},\n \"schema\": {\n \"type\": \"object\", \n \"properties\": {\n \"status\": {\n \"type\": \"boolean\", \n \"example\": true, \n \"default\": true \n }, \n \"message\": {\n \"type\": \"string\", \n \"example\": \"\" \n }, \n \"data\": {\n \"type\": \"object\", \n \"properties\": {\n \"id\": {\n \"type\": \"string\",

```

```
 "example": "9525b4c6-502b-45be-90e1-81eb81a3f424"
 },
 "amount": {
 "type": "string",
 "example": "20.00"
 },
 "fee": {
 "type": "string",
 "example": "8.50"
 },
 "currency": {
 "type": "string",
 "example": "ZMW"
 },
 "narration": {
 "type": "string",
 "example": "Transfer"
 },
 "initiatedAt": {
 "type": "string",
 "example": "2024-01-01T00:00:00.447Z"
 },
 "completedAt": {
 "type": "string",
 "example": "2024-01-01T00:00:01.237Z"
 },
 "accountId": {
 "type": "string",
 "example": "b176cda5-7d97-4a3f-b4dd-ab0234e9e08c"
 },
 "creditAccount": {
 "type": "object",
 "properties": {
 "type": {
 "type": "string",
 "example": "bank-account"
 },
 "accountName": {
 "type": "string",
 "example": "Beata Jean"
 },
 "accountNumber": {
 "type": "string",
 "example": "9130000000000"
 }
 },
 "bank": {
 "type": "object",
 "properties": {
```

```

 "id": {
 "type": "string",
 "example": "002"
 },
 "name": {
 "type": "string",
 "example": "Absa Bank"
 },
 "country": {
 "type": "string",
 "example": "zm"
 }
 }
 }
 },
 "status": {
 "type": "string",
 "example": "successful"
 },
 "reasonForFailure": {},
 "reference": {
 "type": "string",
 "example": "ref-3"
 },
 "lencoReference": {
 "type": "string",
 "example": "240010002"
 },
 "extraData": {
 "type": "object",
 "properties": {
 "nipSessionId": {}
 }
 },
 "source": {
 "type": "string",
 "example": "api"
 }
}
}
}
}
}
},
"400": {
 "description": "400",

```

```

 "content": {
 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": false,\n \"message\":\nDuplicate reference\",\n \"data\": null\n}"
 }
 },
 "schema": {
 "type": "object",
 "properties": {
 "status": {
 "type": "boolean",
 "example": false,
 "default": true
 },
 "message": {
 "type": "string",
 "example": "Duplicate reference"
 },
 "data": {}
 }
 }
 }
 },
 "deprecated": false
 },
 "x-readme": {
 "headers": [],
 "explorer-enabled": false,
 "proxy-enabled": true
 },
 "x-readme-fauxas": true,
 "_id": "65f06b6583c5de0051b8aa08:65f19be77bee5a00696b9fb2"
 }
 }
}

```

## 8 get-accounts.md

# /accounts

Retrieve information about your bank accounts

Response schema:

```

```json
{
  "status": boolean,
  "message": string,
  "data": [
    {
      "id": string,
      "details": {
        "type": string,
        "accountName": string,
        "tillNumber": string
      },
      "type": string,
      "status": string,
      "createdAt": date-time,
      "currency": string,
      "availableBalance": string | null,
      "ledgerBalance": string | null
    }
  ],
  "meta": {
    "total": number,
    "pageCount": number,
    "perPage": number,
    "currentPage": number
  }
}
```

```

```

>  date-time
>
> All date-time fields are expressed in ISO8601 UTC times.

```

## # OpenAPI definition

```

```json
{
  "openapi": "3.1.0",
  "info": {
    "title": "Lenco API",
    "version": "2.0"
  },
  "servers": [
    {
      "url": "https://api.lenco.co/access/v2"
    }
  ],

```



```

"components": {
  "securitySchemes": {
    "sec0": {
      "type": "apiKey",
      "in": "header",
      "name": "Authorization",
      "x-bearer-format": "bearer",
      "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
    }
  }
},
"security": [
  {
    "sec0": []
  }
],
"paths": {
  "/accounts": {
    "get": {
      "summary": "/accounts",
      "description": "Retrieve information about your bank accounts",
      "operationId": "get-accounts",
      "parameters": [
        {
          "name": "page",
          "in": "query",
          "description": "If not specified, it defaults to 1",
          "schema": {
            "type": "integer",
            "format": "int32",
            "default": 1
          }
        }
      ]
    },
    "responses": {
      "200": {
        "description": "200",
        "content": {
          "application/json": {
            "examples": {
              "Result": {
                "value": "{\n  \"status\": true,\n  \"message\":\n    \"\", \n  \"data\": [\n    {\n      \"id\": \"b176cda5-7d97-4a3f-b4dd-ab0234e9e08c\", \n      \"details\": {\n        \"type\":\n          \"lenco-merchant\", \n        \"accountName\": \"Account\nName\", \n        \"tillNumber\":\n          \"0000001\" \n      }, \n      \"type\": \"Lenco\nMerchant\", \n      \"status\": \"active\", \n      \"createdAt\":

```

```

\ "2024-01-01T00:00:00.000Z\ ", \n          \ "currency\ ":
\ "ZMW\ ", \n          \ "availableBalance\ ":
\ "0.00\ ", \n          \ "ledgerBalance\ ":
\ "0.00\ "\n          } \n    ], \n    \ "meta\ ": { \n          \ "total\ ":
1, \n          \ "pageCount\ ": 1, \n          \ "perPage\ ":
100, \n          \ "currentPage\ ": 1 \n          } \n }"
    }
  },
  "schema": {
    "type": "object",
    "properties": {
      "status": {
        "type": "boolean",
        "example": true,
        "default": true
      },
      "message": {
        "type": "string",
        "example": ""
      },
      "data": {
        "type": "array",
        "items": {
          "type": "object",
          "properties": {
            "id": {
              "type": "string",
              "example": "b176cda5-7d97-4a3f-b4dd-ab0234e9e08c"
            },
            "details": {
              "type": "object",
              "properties": {
                "type": {
                  "type": "string",
                  "example": "lenco-merchant"
                },
                "accountName": {
                  "type": "string",
                  "example": "Account Name"
                },
                "tillNumber": {
                  "type": "string",
                  "example": "0000001"
                }
              }
            }
          }
        },
        "type": {
          "type": "string",

```

```
        "example": "Lenco Merchant"
    },
    "status": {
        "type": "string",
        "example": "active"
    },
    "createdAt": {
        "type": "string",
        "example": "2024-01-01T00:00:00.000Z"
    },
    "currency": {
        "type": "string",
        "example": "ZMW"
    },
    "availableBalance": {
        "type": "string",
        "example": "0.00"
    },
    "ledgerBalance": {
        "type": "string",
        "example": "0.00"
    }
}
},
"meta": {
    "type": "object",
    "properties": {
        "total": {
            "type": "integer",
            "example": 1,
            "default": 0
        },
        "pageCount": {
            "type": "integer",
            "example": 1,
            "default": 0
        },
        "perPage": {
            "type": "integer",
            "example": 100,
            "default": 0
        },
        "currentPage": {
            "type": "integer",
            "example": 1,
            "default": 0
        }
    }
}
```

```

    }
  }
}
}
}
},
  "deprecated": false
}
}
},
"x-readme": {
  "headers": [],
  "explorer-enabled": false,
  "proxy-enabled": true
},
"x-readme-fauxas": true,
"_id": "65f06b6583c5de0051b8aa08:65f06b6583c5de0051b8aa0c"
}
...

```

9 accept-payments.md

Accept Payments

Lenco provides a simple and convenient payment flow for web with the popup widget. It can be integrated in a few easy steps.

Step 1: Collect customer information

To begin, you need to pass information such as email, amount, reference, etc.\ Here is the full list of parameters you can pass:

```

[block:parameters]
{
  "data": {
    "h-0": "Param",
    "h-1": "Required?",
    "h-2": "Description",
    "0-0": "key",
    "0-1": "Yes",
    "0-2": "Your public key from Lenco",
    "1-0": "email",
    "1-1": "Yes",
    "1-2": "Email address of customer",
    "2-0": "reference",
    "2-1": "Yes",

```

```
"2-2": "Unique case sensitive reference. Only `-, `., `_, and alphanumeric characters allowed",
"3-0": "amount",
"3-1": "Yes",
"3-2": "Amount the customer is to pay. This can include decimals (i.e. 10.75)",
"4-0": "currency",
"4-1": "No",
"4-2": "ISO 3-Letter Currency Code e.g. `ZMW`, `USD`",
"5-0": "label",
"5-1": "No",
"5-2": "Text to show on the widget. This could be the name of the checkout form.",
"6-0": "bearer",
"6-1": "No",
"6-2": "Decide who will bear the fee. Either `merchant` (you), or `customer` (your customer). \nNote: This will only be used if not already set in your dashboard.",
"7-0": "channels",
"7-1": "No",
"7-2": "An array of payment channels to control what is made available to the customer to make a payment with. \nAvailable channels include: [`card`, `mobile-money`]",
"8-0": "customer",
"8-1": "No",
"8-2": "This field holds the customer details",
"9-0": "customer.firstName",
"9-1": "No",
"9-2": "The first name of the customer",
"10-0": "customer.lastName",
"10-1": "No",
"10-2": "The last name of the customer",
"11-0": "customer.phone",
"11-1": "No",
"11-2": "The phone number of the customer",
"12-0": "billing",
"12-1": "No",
"12-2": "This field holds the customer's billing address",
"13-0": "billing.streetAddress",
"13-1": "No",
"13-2": "The street address",
"14-0": "billing.city",
"14-1": "No",
"14-2": "The city ",
"15-0": "billing.state",
"15-1": "No",
"15-2": "The state or province. \nIf a country does not have states or provinces, this can be left blank. \n \nNote: For US states and Canada
```

provinces, this should be the 2-letter code for the state / province. i.e. California should be `CA`. \n \nYou can find the list of US State and Canada Province codes

[here](https://www.ups.com/worldshiphelp/WSA/ENU/AppHelp/mergedProjects/CORE/Codes/State_Province_Codes.htm)",

"16-0": "billing.postalCode",

"16-1": "No",

"16-2": "The postal code",

"17-0": "billing.country",

"17-1": "No",

"17-2": "2-letter code i.e. United states should be `US`. \nYou can find the list of country codes [here](https://www.iban.com/country-codes)",

"18-0": "onSuccess",

"18-1": "No",

"18-2": "Javascript function that runs when payment is successful. This should ideally be a script that uses the verify endpoint to check the status of the payment.",

"19-0": "onClose",

"19-1": "No",

"19-2": "Javascript function that is called if the customer closes the payment window instead of making a payment.",

"20-0": "onConfirmationPending",

"20-1": "No",

"20-2": "Javascript function that is called if the customer closes the payment window before we verify their payment."

},

"cols": 3,

"rows": 21,

"align": [

"left",

"left",

"left"

]

}

[/block]

Step 2: Initiate the Payment

When you have all the details needed to initiate the payment, the next step is to pass them to Lenco to display the popup widget.

```
```html
```

```
<script src="https://pay.lenco.co/js/v1/inline.js"></script>
```

```
<script>
```

```
function getPaidWithLenco() {
```

```

LencoPay.getPaid({
 key: 'YOUR_PUBLIC_KEY', // your Lenco public key
 reference: 'ref-' + Date.now(), // a unique reference you generated
 email: 'customer@email.com', // the customer's email address
 amount: 1000, // the amount the customer is to pay
 currency: "ZMW",
 channels: ["card", "mobile-money"],
 customer: {
 firstName: "John",
 lastName: "Doe",
 phone: "0971111111",
 },
 onSuccess: function (response) {
 //this happens after the payment is completed successfully
 const reference = response.reference;
 alert('Payment complete! Reference: ' + reference);
 // Make an AJAX call to your server with the reference to verify the
 payment
 },
 onClose: function () {
 alert('Payment was not completed, window closed.');
```

```

 },
 onConfirmationPending: function () {
 alert('Your purchase will be completed when the payment is confirmed');
```

```

 },
});
}
</script>
...

```

For the sandbox environment, use  
[`https://pay.sandbox.lenco.co/js/v1/inline.js`](https://pay.sandbox.lenco.co/js/v1/inline.js) as the source for the lenco  
 widget script.

### **\*\*Important Notes:\*\***

1. The ``key`` field takes your Lenco **\*\*public\*\*** key.
2. The ``amount`` field should not be converted to the lowest currency unit. Rather you can pass in a number with decimal places i.e. 10.75
3. It is ideal to generate a unique reference from your system for every payment to avoid duplicate attempts.
4. The ``onSuccess`` callback function is called when payment has been completed successfully. See the next section for how to handle the callback.
5. The ``onClose`` callback function is called if the user closes the widget without completing payment.
6. The ``onConfirmationPending`` callback function is called if the customer closes the payment window before we verify their payment.

<br />

### ### Step 3: Handle the `onSuccess` callback method

The `onSuccess` callback function is fired when the payment is successful. This is where you include any action you want to perform when the payment is successful.

The recommended next step here is to verify the payment as detailed in step 4.

>   
>  
> **\*\*Note\*\***\n> To verify the payment, you have to set up a route or page on your server that you pass the reference to. Then from your server, you call the verify endpoint to confirm the status of the payment, and the response is returned to your frontend.

There are 2 ways you can call your server from the callback function

1. Make an AJAX request to the endpoint on your server that handles the payment verification

```
```javascript
onSuccess: function(response){
  $.ajax({
    url: 'https://www.yoururl.com/verify_payment?reference=' +
response.reference,
    method: 'get',
    success: function (response) {
      // the payment status is in response.data.status
    }
  });
}
```
```

2. Redirect to the verification endpoint URL on your server.

```
```javascript
onSuccess: function(response) {
  window.location = "https://www.yoururl.com/verify_payment.php?reference=" +
response.reference;
}
// On the redirected page, you can call Lenco's API to verify the payment.
```
```

> !



```
>
> **Warning**\
> Never call the Lenco API directly from your frontend to avoid exposing your
api secret key on the frontend. All requests to the Lenco API should be
initiated from your server, and your frontend gets the response from your
server.
```

```


```

### ### Step 4: Verify the Payment

You do this by making a GET request to  
`https://api.lenco.co/access/v2/collections/status/:reference` from your  
server using your reference. You can find more information about this endpoint  
[here](https://lenco-api.readme.io/v2.0/reference/get-collection-by-  
reference).

```
```curl
# Sample Request

curl https://api.lenco.co/access/v2/collections/status/ref-1
-H "Authorization: Bearer API_SECRET_KEY"
-X GET
```
```

```
```json
// Sample Response

{
  "status": true,
  "message": "",
  "data": {
    "id": "d7bd9ccb-0737-4e72-a387-d00454341f21",
    "initiatedAt": "2024-03-12T07:06:11.562Z",
    "completedAt": "2024-03-12T07:14:10.412Z",
    "amount": "10.00",
    "fee": "0.25",
    "bearer": "merchant",
    "currency": "ZMW",
    "reference": "ref-1",
    "lencoReference": "240720004",
    "type": "mobile-money",
    "status": "successful",
    "source": "api",
    "reasonForFailure": null,
    "settlementStatus": "settled",
    "settlement": {
      "id": "c04583d7-d026-4dfa-b8b5-e96f17f93bb8",
```

```

    "amountSettled": "9.75",
    "currency": "ZMW",
    "createdAt": "2024-03-12T07:14:10.439Z",
    "settledAt": "2024-03-12T07:14:10.496Z",
    "status": "settled",
    "type": "instant",
    "accountId": "68f11209-451f-4a15-bfcd-d916eb8b09f4"
  },
  "mobileMoneyDetails": {
    "country": "zm",
    "phone": "0977433571",
    "operator": "airtel",
    "accountName": "Beata Jean",
    "operatorTransactionId": "MP240312.0000.A00001"
  },
  "bankAccountDetails": null,
  "cardDetails": null
}
}
...

```


Step 5: Handle webhook

When a payment is successful, Lenco sends a `collection.successful` webhook event to your webhook URL. You can [learn more here](https://lenco-api.readme.io/v2.0/reference/webhooks).

10 test-cards-and-accounts.md

Test Cards and Accounts

Mobile Money Test Accounts

Here are some mobile money accounts to test collections in the sandbox environment

Phone	Operator	Response	Error
:-----	:-----	:-----	:-----
0961111111	mtn	Successful	
0962222222	mtn	Failed	Not enough funds
0963333333	mtn	Failed	Withdrawal amount limit exceeded
0964444444	mtn	Failed	Transaction unauthorized
0965555555	mtn	Failed	Transaction unauthorized
0966666666	mtn	Failed	Transaction Timed Out
0971111111	airtel (zm)	Successful	
0972222222	airtel (zm)	Failed	Incorrect Pin

0973333333	airtel (zm)	Failed	Invalid Amount	
0974444444	airtel (zm)	Failed	Payment invalid	
0975555555	airtel (zm)	Failed	Not enough funds	
0976666666	airtel (zm)	Failed	Failed	
0977777777	airtel (zm)	Failed	Transaction Timed Out	
0978888888	airtel (zm)	Failed	Failed	
0881111111	tnm	Successful		
0883333333	tnm	Failed	Not enough funds	
0885555555	tnm	Failed	Transaction unauthorized	
0991111111	airtel (mw)	Successful		
0992222222	airtel (mw)	Failed	Not enough funds	
0984444444	airtel (mw)	Failed	Transaction unauthorized	

Test Cards

Here are some cards you can use in the sandbox environment

Type	Number	CVV	
Expiry			
:-----	:-----	:-----	:-----

Visa	4622 9431 2701 3705	838	Any date in the future
Visa	4622 9431 2701 3747	370	Any date in the future
Mastercard	5555 5555 5555 4444	Any 3-digit combination	Any date in the future

11 get-account-by-id.md

/accounts/:id

Retrieve information about a specific bank account

Response schema:

```
```json
{
 "status": boolean,
 "message": string,
 "data": {
 "id": string,
 "details": {
 "type": string,
 "accountName": string,
 "tillNumber": string
 }
 }
}
```

```

 },
 "type": string,
 "status": string,
 "createdAt": date-time,
 "currency": string,
 "availableBalance": string | null,
 "ledgerBalance": string | null
 }
}
...

OpenAPI definition

```json
{
  "openapi": "3.1.0",
  "info": {
    "title": "Lenco API",
    "version": "2.0"
  },
  "servers": [
    {
      "url": "https://api.lenco.co/access/v2"
    }
  ],
  "components": {
    "securitySchemes": {
      "sec0": {
        "type": "apiKey",
        "in": "header",
        "name": "Authorization",
        "x-bearer-format": "bearer",
        "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
      }
    }
  },
  "security": [
    {
      "sec0": []
    }
  ],
  "paths": {
    "/accounts/{id}": {
      "get": {
        "summary": "/accounts/:id",
        "description": "Retrieve information about a specific bank account",
        "operationId": "get-account-by-id",
        "parameters": [

```

```

    {
      "name": "id",
      "in": "path",
      "description": "Your 36-character account uuid.",
      "schema": {
        "type": "string"
      },
      "required": true
    }
  ],
  "responses": {
    "200": {
      "description": "200",
      "content": {
        "application/json": {
          "examples": {
            "Result": {
              "value": "{\n  \"status\": true,\n  \"message\":  

\\\"\", \n  \"data\": {\n    \"id\": \"b176cda5-7d97-4a3f-b4dd-  

ab0234e9e08c\", \n    \"details\": {\n      \"type\": \"lenco-  

merchant\", \n      \"accountName\": \"Account  

Name\", \n      \"tillNumber\":  

\\\"0000001\\\" \n    }, \n    \"type\": \"Lenco  

Merchant\", \n    \"status\": \"active\", \n    \"createdAt\": \"2024-  

01-01T00:00:00.000Z\", \n    \"currency\":  

\\\"ZMW\", \n    \"availableBalance\": \"0.00\", \n    \"ledgerBalance\":  

\\\"0.00\" \n  } \n}"
            }
          },
          "schema": {
            "type": "object",
            "properties": {
              "status": {
                "type": "boolean",
                "example": true,
                "default": true
              },
              "message": {
                "type": "string",
                "example": ""
              },
              "data": {
                "type": "object",
                "properties": {
                  "id": {
                    "type": "string",
                    "example": "b176cda5-7d97-4a3f-b4dd-ab0234e9e08c"
                  }
                }
              }
            }
          }
        }
      }
    }
  }
}

```

```

        "details": {
          "type": "object",
          "properties": {
            "type": {
              "type": "string",
              "example": "lenco-merchant"
            },
            "accountName": {
              "type": "string",
              "example": "Account Name"
            },
            "tillNumber": {
              "type": "string",
              "example": "0000001"
            }
          }
        },
        "type": {
          "type": "string",
          "example": "Lenco Merchant"
        },
        "status": {
          "type": "string",
          "example": "active"
        },
        "createdAt": {
          "type": "string",
          "example": "2024-01-01T00:00:00.000Z"
        },
        "currency": {
          "type": "string",
          "example": "ZMW"
        },
        "availableBalance": {
          "type": "string",
          "example": "0.00"
        },
        "ledgerBalance": {
          "type": "string",
          "example": "0.00"
        }
      }
    }
  }
},

```

```

    "400": {
      "description": "400",
      "content": {
        "application/json": {
          "examples": {
            "Result": {
              "value": "{\n  \"status\": false,\n  \"message\":\nAccount was not found or api key does not have access to the\naccount\", \n  \"data\": []\n}"
            }
          },
          "schema": {
            "type": "object",
            "properties": {
              "status": {
                "type": "boolean",
                "example": false,
                "default": true
              },
              "message": {
                "type": "string",
                "example": "Account was not found or api key does not\nhave access to the account"
              },
              "data": {
                "type": "array",
                "items": {
                  "type": "object",
                  "properties": {}
                }
              }
            }
          }
        }
      },
      "deprecated": false
    }
  },
  "x-readme": {
    "headers": [],
    "explorer-enabled": false,
    "proxy-enabled": true
  },
  "x-readme-fauxas": true,
  "_id": "65f06b6583c5de0051b8aa08:65f06b6583c5de0051b8aa0d"

```

```
}  
---
```

12 get-account-balance.md

```
# /accounts/:id/balance
```

Retrieve account balance of a specific bank account

Response schema:

```
```json  
{
 "status": boolean,
 "message": string,
 "data": {
 "availableBalance": string,
 "ledgerBalance": string,
 "currency": string,
 }
}
```
```

```
# OpenAPI definition
```

```
```json  
{
 "openapi": "3.1.0",
 "info": {
 "title": "Lenco API",
 "version": "2.0"
 },
 "servers": [
 {
 "url": "https://api.lenco.co/access/v2"
 }
],
 "components": {
 "securitySchemes": {
 "sec0": {
 "type": "apiKey",
 "in": "header",
 "name": "Authorization",
 "x-bearer-format": "bearer",
 "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
 }
 }
 }
},
```
```



```

"security": [
  {
    "sec0": []
  }
],
"paths": {
  "/accounts/{id}/balance": {
    "get": {
      "summary": "/accounts/:id/balance",
      "description": "Retrieve account balance of a specific bank account",
      "operationId": "get-account-balance",
      "parameters": [
        {
          "name": "id",
          "in": "path",
          "description": "Your 36-character account uuid.",
          "schema": {
            "type": "string"
          },
          "required": true
        }
      ],
      "responses": {
        "200": {
          "description": "200",
          "content": {
            "application/json": {
              "examples": {
                "Result": {
                  "value": "{\n  \"status\": true,\n  \"message\":  
\\\"\\\", \n  \"data\": {\n    \"currency\":  
\\\"ZMW\\\", \n    \"availableBalance\": \"0.00\\\", \n    \"ledgerBalance\":  
\\\"0.00\\\" \n  } \n}"
                }
              }
            },
            "schema": {
              "type": "object",
              "properties": {
                "status": {
                  "type": "boolean",
                  "example": true,
                  "default": true
                },
                "message": {
                  "type": "string",
                  "example": ""
                },
                "data": {

```

```

        "type": "object",
        "properties": {
          "currency": {
            "type": "string",
            "example": "ZMW"
          },
          "availableBalance": {
            "type": "string",
            "example": "0.00"
          },
          "ledgerBalance": {
            "type": "string",
            "example": "0.00"
          }
        }
      },
      "400": {
        "description": "400",
        "content": {
          "application/json": {
            "examples": {
              "Result": {
                "value": "{\n  \"status\": false,\n  \"message\": \"Account was not found or api key does not have access to the account\", \n  \"data\": []\n}"
              }
            }
          },
          "schema": {
            "type": "object",
            "properties": {
              "status": {
                "type": "boolean",
                "example": false,
                "default": true
              }
            },
            "message": {
              "type": "string",
              "example": "Account was not found or api key does not have access to the account"
            },
            "data": {
              "type": "array",
              "items": {

```

```

        "type": "object",
        "properties": {}
      }
    }
  }
}
},
"deprecated": false
}
}
},
"x-readme": {
  "headers": [],
  "explorer-enabled": false,
  "proxy-enabled": true
},
"x-readme-fauxas": true,
"_id": "65f06b6583c5de0051b8aa08:65f06b6583c5de0051b8aa0e"
}
...

```

13 get-banks.md

```

# /banks

Get list of banks and financial institutions

Response schema:

```json
{
 "status": boolean,
 "message": string,
 "data": [
 {
 "id": string,
 "name": string,
 "country": string
 }
]
}
...

OpenAPI definition

```

```
```json
{
  "openapi": "3.1.0",
  "info": {
    "title": "Lenco API",
    "version": "2.0"
  },
  "servers": [
    {
      "url": "https://api.lenco.co/access/v2"
    }
  ],
  "components": {
    "securitySchemes": {
      "sec0": {
        "type": "apiKey",
        "in": "header",
        "name": "Authorization",
        "x-bearer-format": "bearer",
        "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
      }
    }
  },
  "security": [
    {
      "sec0": []
    }
  ],
  "paths": {
    "/banks": {
      "get": {
        "summary": "/banks",
        "description": "Get list of banks and financial institutions",
        "operationId": "get-banks",
        "parameters": [
          {
            "name": "country",
            "in": "query",
            "description": "i.e. ng, zm",
            "schema": {
              "type": "string"
            }
          }
        ]
      },
      "responses": {
        "200": {
          "description": "200",
          "content": {

```

```

        "application/json": {
            "examples": {
                "Result": {
                    "value": "{\n    \"status\": true,\n    \"message\":\n    \"\", \n    \"data\": [\n        {\n            \"id\":\n            \"002\", \n            \"name\": \"Absa Bank\", \n            \"country\":\n            \"zm\"\n        }\n    ]\n}"
                }
            },
            "schema": {
                "type": "object",
                "properties": {
                    "status": {
                        "type": "boolean",
                        "example": true,
                        "default": true
                    },
                    "message": {
                        "type": "string",
                        "example": ""
                    },
                    "data": {
                        "type": "array",
                        "items": {
                            "type": "object",
                            "properties": {
                                "id": {
                                    "type": "string",
                                    "example": "002"
                                },
                                "name": {
                                    "type": "string",
                                    "example": "Absa Bank"
                                },
                                "country": {
                                    "type": "string",
                                    "example": "zm"
                                }
                            }
                        }
                    }
                }
            },
            "deprecated": false
        }
    }
}

```

```

    }
  },
  "x-readme": {
    "headers": [],
    "explorer-enabled": false,
    "proxy-enabled": true
  },
  "x-readme-fauxas": true,
  "_id": "65f06b6583c5de0051b8aa08:65f06b6583c5de0051b8aa14"
}
...

```

14 resolve-bank-account.md

```
# /resolve/bank-account
```

Verify/resolve account details

Response Schema:

```

```json
{
 "status": boolean,
 "message": string,
 "data": {
 "type": "bank-account",
 "accountName": string,
 "accountNumber": string,
 "bank": {
 "id": string,
 "name": string,
 "country": string
 }
 }
}
...

```

```
OpenAPI definition
```

```

```json
{
  "openapi": "3.1.0",
  "info": {
    "title": "Lenco API",
    "version": "2.0"
  },
  "servers": [

```

```

{
  "url": "https://api.lenco.co/access/v2"
}
],
"components": {
  "securitySchemes": {
    "sec0": {
      "type": "apiKey",
      "in": "header",
      "name": "Authorization",
      "x-bearer-format": "bearer",
      "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
    }
  }
},
"security": [
  {
    "sec0": []
  }
],
"paths": {
  "/resolve/bank-account": {
    "post": {
      "summary": "/resolve/bank-account",
      "description": "Verify/resolve account details",
      "operationId": "resolve-bank-account",
      "requestBody": {
        "content": {
          "application/json": {
            "schema": {
              "type": "object",
              "required": [
                "accountNumber",
                "bankId"
              ],
              "properties": {
                "accountNumber": {
                  "type": "string"
                },
                "bankId": {
                  "type": "string"
                },
                "country": {
                  "type": "string",
                  "description": "Optional. i.e `ng`, `zm`"
                }
              }
            }
          }
        }
      }
    }
  }
}

```

```

    }
  }
},
"responses": {
  "200": {
    "description": "200",
    "content": {
      "application/json": {
        "examples": {
          "Result": {
            "value": "{\n  \"status\": true,\n  \"message\":\n  \"\", \n  \"data\": {\n    \"type\": \"bank-\naccount\", \n    \"accountName\": \"Beata\nJean\", \n    \"accountNumber\": \"9130000000000\", \n    \"bank\":\n{\n  \"id\": \"002\", \n    \"name\": \"Absa\nBank\", \n    \"country\": \"zm\" \n  } \n } \n}"
          }
        },
        "schema": {
          "type": "object",
          "properties": {
            "status": {
              "type": "boolean",
              "example": true,
              "default": true
            },
            "message": {
              "type": "string",
              "example": ""
            },
            "data": {
              "type": "object",
              "properties": {
                "type": {
                  "type": "string",
                  "example": "bank-account"
                },
                "accountName": {
                  "type": "string",
                  "example": "Beata Jean"
                },
                "accountNumber": {
                  "type": "string",
                  "example": "9130000000000"
                },
                "bank": {
                  "type": "object",
                  "properties": {

```



```

        "id": {
            "type": "string",
            "example": "002"
        },
        "name": {
            "type": "string",
            "example": "Absa Bank"
        },
        "country": {
            "type": "string",
            "example": "zm"
        }
    }
}
}
}
}
}
},
"400": {
    "description": "400",
    "content": {
        "application/json": {
            "examples": {
                "Result": {
                    "value": "{\n    \"status\": false,\n    \"message\":\n\"Account details was not found\", \n    \"data\": null\n}"
                }
            }
        },
        "schema": {
            "type": "object",
            "properties": {
                "status": {
                    "type": "boolean",
                    "example": false,
                    "default": true
                },
                "message": {
                    "type": "string",
                    "example": "Account details was not found"
                },
                "data": {}
            }
        }
    }
}
}
}
}
}

```

```

    }
  },
  "deprecated": false
}
},
"x-readme": {
  "headers": [],
  "explorer-enabled": false,
  "proxy-enabled": true
},
"x-readme-fauxas": true,
"_id": "65f06b6583c5de0051b8aa08:65f06b6583c5de0051b8aa16"
}
...

```

15 resolve-mobile-money-account.md

/resolve/mobile-money

Response Schema:

```

```json
{
 "status": boolean,
 "message": string,
 "data": {
 "type": "mobile-money",
 "accountName": string,
 "phone": string,
 "operator": string,
 "country": string
 }
}
```

```

OpenAPI definition

```

```json
{
 "openapi": "3.1.0",
 "info": {
 "title": "Lenco API",
 "version": "2.0"
 },
 "servers": [
 {
 "url": "https://api.lenco.co/access/v2"
 }
]
}
```

```

```

    }
  ],
  "components": {
    "securitySchemes": {
      "sec0": {
        "type": "apiKey",
        "in": "header",
        "name": "Authorization",
        "x-bearer-format": "bearer",
        "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
      }
    }
  },
  "security": [
    {
      "sec0": []
    }
  ],
  "paths": {
    "/resolve/mobile-money": {
      "post": {
        "summary": "/resolve/mobile-money",
        "description": "",
        "operationId": "resolve-mobile-money-account",
        "requestBody": {
          "content": {
            "application/json": {
              "schema": {
                "type": "object",
                "required": [
                  "phone",
                  "operator"
                ],
                "properties": {
                  "phone": {
                    "type": "string"
                  },
                  "operator": {
                    "type": "string",
                    "description": "either `mtn`, `airtel`, or `zamtel`",
                    "enum": [
                      "airtel",
                      "mtn",
                      "zamtel"
                    ]
                  }
                }
              }
            }
          }
        },
        "country": {
          "type": "string",

```

```

        "description": "Optional. Currently supporting only `zm`",
        "enum": [
            "zm"
        ]
    },
    },
    "examples": {
        "Request Example": {
            "value": {
                "phone": "0961111111",
                "operator": "mtn",
                "country": "zm"
            }
        }
    },
    },
    "responses": {
        "200": {
            "description": "200",
            "content": {
                "application/json": {
                    "examples": {
                        "Result": {
                            "value": "{\n    \"status\": true,\n    \"message\":\n    \"\", \n    \"data\": {\n        \"type\": \"mobile-money\", \n        \"accountName\": \"Beata Jean\", \n        \"phone\":\n        \"0750000000\", \n        \"operator\": \"zamtel\", \n        \"country\":\n        \"zm\" \n    } \n}"
                        }
                    }
                },
                "schema": {
                    "type": "object",
                    "properties": {
                        "status": {
                            "type": "boolean",
                            "example": true,
                            "default": true
                        },
                        "message": {
                            "type": "string",
                            "example": ""
                        },
                        "data": {
                            "type": "object",
                            "properties": {

```

```

    "type": {
      "type": "string",
      "example": "mobile-money"
    },
    "accountName": {
      "type": "string",
      "example": "Beata Jean"
    },
    "phone": {
      "type": "string",
      "example": "0750000000"
    },
    "operator": {
      "type": "string",
      "example": "zamtel"
    },
    "country": {
      "type": "string",
      "example": "zm"
    }
  }
}
},
{
  "400": {
    "description": "400",
    "content": {
      "application/json": {
        "examples": {
          "Result": {
            "value": "{\n  \"status\": false,\n  \"message\": \"Account details was not found\", \n  \"data\": null\n}"
          }
        }
      }
    },
    "schema": {
      "type": "object",
      "properties": {
        "status": {
          "type": "boolean",
          "example": false,
          "default": true
        }
      },
      "message": {
        "type": "string",
        "example": "Account details was not found"
      }
    }
  }
}

```

```

    },
    "data": {}
  }
}
}
}
},
"deprecated": false
}
}
},
"x-readme": {
  "headers": [],
  "explorer-enabled": false,
  "proxy-enabled": true
},
"x-readme-fauxas": true,
"_id": "65f06b6583c5de0051b8aa08:65f19d984120a1001d1d60f4"
}
```

```

## 16 resolve-lenco-money-account.md

```
/resolve/lenco-money
```

Response Schema:

```

```json
{
  "status": boolean,
  "message": string,
  "data": {
    "type": "lenco-money",
    "accountName": string,
    "walletNumber": string
  }
}
```

```

```
OpenAPI definition
```

```

```json
{
  "openapi": "3.1.0",
  "info": {
    "title": "Lenco API",
    "version": "2.0"
  }
}
```

```

```
},
"servers": [
 {
 "url": "https://api.lenco.co/access/v2"
 }
],
"components": {
 "securitySchemes": {
 "sec0": {
 "type": "apiKey",
 "in": "header",
 "name": "Authorization",
 "x-bearer-format": "bearer",
 "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
 }
 }
},
"security": [
 {
 "sec0": []
 }
],
"paths": {
 "/resolve/lenco-money": {
 "post": {
 "summary": "/resolve/lenco-money",
 "description": "",
 "operationId": "resolve-lenco-money-account",
 "requestBody": {
 "content": {
 "application/json": {
 "schema": {
 "type": "object",
 "required": [
 "walletNumber"
],
 "properties": {
 "walletNumber": {
 "type": "string"
 }
 }
 }
 }
 }
 },
 "responses": {
 "200": {
 "description": "200",

```

```

 "content": {
 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": true,\n \"message\":
\\\"\\\", \n \"data\": {\n \"type\": \"lenco-
money\", \n \"accountName\": \"Beata Jean\", \n \"walletNumber\":
\\\"0000001\" \n } \n}"
 }
 },
 "schema": {
 "type": "object",
 "properties": {
 "status": {
 "type": "boolean",
 "example": true,
 "default": true
 },
 "message": {
 "type": "string",
 "example": ""
 },
 "data": {
 "type": "object",
 "properties": {
 "type": {
 "type": "string",
 "example": "lenco-money"
 },
 "accountName": {
 "type": "string",
 "example": "Beata Jean"
 },
 "walletNumber": {
 "type": "string",
 "example": "0000001"
 }
 }
 }
 }
 }
 }
 },
 "400": {
 "description": "400",
 "content": {
 "application/json": {

```



```

 "examples": {
 "Result": {
 "value": "{\n \"status\": false,\n \"message\":
\"Account details was not found\", \n \"data\": null\n}"
 }
 },
 "schema": {
 "type": "object",
 "properties": {
 "status": {
 "type": "boolean",
 "example": false,
 "default": true
 },
 "message": {
 "type": "string",
 "example": "Account details was not found"
 },
 "data": {}
 }
 }
 }
 },
 "deprecated": false
 }
},
"x-readme": {
 "headers": [],
 "explorer-enabled": false,
 "proxy-enabled": true
},
"x-readme-fauxas": true,
"_id": "65f06b6583c5de0051b8aa08:65f19da74120a1001d1d6100"
}
...

```

## 17 resolve-lenco-merchant-account.md

```
/resolve/lenco-merchant
```

Response Schema:

```

```json
{
  "status": boolean,

```

```

    "message": string,
    "data": {
        "type": "lenco-merchant",
        "accountName": string,
        "tillNumber": string
    }
}
...

# OpenAPI definition

```json
{
 "openapi": "3.1.0",
 "info": {
 "title": "Lenco API",
 "version": "2.0"
 },
 "servers": [
 {
 "url": "https://api.lenco.co/access/v2"
 }
],
 "components": {
 "securitySchemes": {
 "sec0": {
 "type": "apiKey",
 "in": "header",
 "name": "Authorization",
 "x-bearer-format": "bearer",
 "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
 }
 }
 },
 "security": [
 {
 "sec0": []
 }
],
 "paths": {
 "/resolve/lenco-merchant": {
 "post": {
 "summary": "/resolve/lenco-merchant",
 "description": "",
 "operationId": "resolve-lenco-merchant-account",
 "requestBody": {
 "content": {
 "application/json": {

```

```

 "schema": {
 "type": "object",
 "required": [
 "tillNumber"
],
 "properties": {
 "tillNumber": {
 "type": "string"
 }
 }
 }
 },
 "responses": {
 "200": {
 "description": "200",
 "content": {
 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": true,\n \"message\":

\\\"\", \n \"data\": {\n \"type\": \"lenco-

merchant\", \n \"accountName\": \"Account

Name\", \n \"tillNumber\": \"0000001\" \n } \n}"
 }
 }
 }
 },
 "schema": {
 "type": "object",
 "properties": {
 "status": {
 "type": "boolean",
 "example": true,
 "default": true
 },
 "message": {
 "type": "string",
 "example": ""
 }
 },
 "data": {
 "type": "object",
 "properties": {
 "type": {
 "type": "string",
 "example": "lenco-merchant"
 },
 "accountName": {
 "type": "string",

```

```

 "example": "Account Name"
 },
 "tillNumber": {
 "type": "string",
 "example": "0000001"
 }
 }
 },
 "400": {
 "description": "400",
 "content": {
 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": false,\n \"message\":\n \"Account details was not found\", \n \"data\": null\n}"
 }
 }
 },
 "schema": {
 "type": "object",
 "properties": {
 "status": {
 "type": "boolean",
 "example": false,
 "default": true
 },
 "message": {
 "type": "string",
 "example": "Account details was not found"
 },
 "data": {}
 }
 }
 }
 },
 "deprecated": false
}
},
"x-readme": {
 "headers": [],

```

```
 "explorer-enabled": false,
 "proxy-enabled": true
 },
 "x-readme-fauxas": true,
 "_id": "65f06b6583c5de0051b8aa08:65f19db57bee5a00696ba004"
}
...
```

get-transfer-recipients.md

## # /transfer-recipients

Retrieve information about all your transfer recipients

Response schema:

```
```json
{
  "status": boolean,
  "message": string,
  "data": [
    {
      "id": string,
      "currency": string,
      "type": string,
      "country": string,
      "details": {
        "type": string,
        "accountName": string,
        "accountNumber": string | null,
        "bank": {
          "id": string,
          "name": string,
          "country": string
        } | null,
        "phone": string | null,
        "operator": string | null,
        "walletNumber": string | null,
        "tillNumber": string | null
      }
    }
  ],
  "meta": {
    "total": number,
    "pageCount": number,
    "perPage": number,
    "currentPage": number
  }
}
```

```

}
```

OpenAPI definition

```json
{
  "openapi": "3.1.0",
  "info": {
    "title": "Lenco API",
    "version": "2.0"
  },
  "servers": [
    {
      "url": "https://api.lenco.co/access/v2"
    }
  ],
  "components": {
    "securitySchemes": {
      "sec0": {
        "type": "apiKey",
        "in": "header",
        "name": "Authorization",
        "x-bearer-format": "bearer",
        "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
      }
    }
  },
  "security": [
    {
      "sec0": []
    }
  ],
  "paths": {
    "/transfer-recipients": {
      "get": {
        "summary": "/transfer-recipients",
        "description": "Retrieve information about all your transfer recipients",
        "operationId": "get-transfer-recipients",
        "parameters": [
          {
            "name": "page",
            "in": "query",
            "description": "If not specified, it defaults to 1",
            "schema": {
              "type": "integer",
              "format": "int32",

```

```

        "default": 1
    },
    {
        "name": "type",
        "in": "query",
        "description": "either `mobile-money`, `bank-account`, `lenco-
money` or `lenco-merchant`",
        "schema": {
            "type": "string"
        }
    },
    {
        "name": "country",
        "in": "query",
        "description": "i.e. ng, zm",
        "schema": {
            "type": "string"
        }
    }
],
"responses": {
    "200": {
        "description": "200",
        "content": {
            "application/json": {
                "examples": {
                    "Result": {
                        "value": "{\n    \"status\": true,\n    \"message\":
\\\"\", \n    \"data\": [\n        {\n            \"id\": \"d6b6e00e-bdb6-43a6-
a561-85b61496198e\", \n            \"details\": {\n                \"type\":
\\\"mobile-money\", \n                \"accountName\": \"Beata
Jean\", \n                \"phone\":
\\\"0750000000\", \n                \"operator\":
\\\"zamtel\", \n                \"currency\":
\\\"ZMW\", \n                \"type\": \"mobile-money\", \n                \"country\":
\\\"zm\" \n            }, \n        }, \n    ], \n    \"meta\": {\n        \"total\":
1, \n        \"pageCount\": 1, \n        \"perPage\":
100, \n        \"currentPage\": 1 \n    } \n}"
                    }
                }
            }
        },
        "schema": {
            "type": "object",
            "properties": {
                "status": {
                    "type": "boolean",
                    "example": true,
                    "default": true
                }
            }
        }
    }
}

```

```
    },
    "message": {
      "type": "string",
      "example": ""
    },
    "data": {
      "type": "array",
      "items": {
        "type": "object",
        "properties": {
          "id": {
            "type": "string",
            "example": "d6b6e00e-bdb6-43a6-a561-85b61496198e"
          },
          "details": {
            "type": "object",
            "properties": {
              "type": {
                "type": "string",
                "example": "mobile-money"
              },
              "accountName": {
                "type": "string",
                "example": "Beata Jean"
              },
              "phone": {
                "type": "string",
                "example": "0750000000"
              },
              "operator": {
                "type": "string",
                "example": "zamtel"
              }
            }
          }
        }
      },
      "currency": {
        "type": "string",
        "example": "ZMW"
      },
      "type": {
        "type": "string",
        "example": "mobile-money"
      },
      "country": {
        "type": "string",
        "example": "zm"
      }
    }
  }
}
```



```

    }
  },
  "meta": {
    "type": "object",
    "properties": {
      "total": {
        "type": "integer",
        "example": 1,
        "default": 0
      },
      "pageCount": {
        "type": "integer",
        "example": 1,
        "default": 0
      },
      "perPage": {
        "type": "integer",
        "example": 100,
        "default": 0
      },
      "currentPage": {
        "type": "integer",
        "example": 1,
        "default": 0
      }
    }
  },
  "deprecated": false
},
"x-readme": {
  "headers": [],
  "explorer-enabled": false,
  "proxy-enabled": true
},
"x-readme-fauxas": true,
"_id": "65f06b6583c5de0051b8aa08:65f06b6583c5de0051b8aa10"
}

```

18 get-transfer-recipient-by-id.md

/transfer-recipients/:id

Retrieve information about a specific transfer recipient

Response schema:

```
```json
{
 "status": boolean,
 "message": string,
 "data": {
 "id": string,
 "currency": string,
 "type": string,
 "country": string,
 "details": {
 "type": string,
 "accountName": string,
 "accountNumber": string | null,
 "bank": {
 "id": string,
 "name": string,
 "country": string
 } | null,
 "phone": string | null,
 "operator": string | null,
 "walletNumber": string | null,
 "tillNumber": string | null
 }
 }
}
```
```

OpenAPI definition

```
```json
{
 "openapi": "3.1.0",
 "info": {
 "title": "Lenco API",
 "version": "2.0"
 },
 "servers": [
 {
 "url": "https://api.lenco.co/access/v2"
 }
],
}
```

```

"components": {
 "securitySchemes": {
 "sec0": {
 "type": "apiKey",
 "in": "header",
 "name": "Authorization",
 "x-bearer-format": "bearer",
 "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
 }
 }
},
"security": [
 {
 "sec0": []
 }
],
"paths": {
 "/transfer-recipients/{id}": {
 "get": {
 "summary": "/transfer-recipients/:id",
 "description": "Retrieve information about a specific transfer recipient",
 "operationId": "get-transfer-recipient-by-id",
 "parameters": [
 {
 "name": "id",
 "in": "path",
 "description": "Your 36-character recipient uuid.",
 "schema": {
 "type": "string"
 },
 "required": true
 }
],
 "responses": {
 "200": {
 "description": "200",
 "content": {
 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": true,\n \"message\": \"\", \n \"data\": {\n \"id\": \"d6b6e00e-bdb6-43a6-a561-85b61496198e\", \n \"details\": {\n \"type\": \"mobile-money\", \n \"accountName\": \"Beata Jean\", \n \"phone\": \"0750000000\", \n \"operator\": \"zamtel\", \n \"currency\": \"ZMW\", \n \"type\": \"mobile-money\", \n \"country\": \"zm\" \n } \n } \n}"

```

```
 }
 },
 "schema": {
 "type": "object",
 "properties": {
 "status": {
 "type": "boolean",
 "example": true,
 "default": true
 },
 "message": {
 "type": "string",
 "example": ""
 },
 "data": {
 "type": "object",
 "properties": {
 "id": {
 "type": "string",
 "example": "d6b6e00e-bdb6-43a6-a561-85b61496198e"
 },
 "details": {
 "type": "object",
 "properties": {
 "type": {
 "type": "string",
 "example": "mobile-money"
 },
 "accountName": {
 "type": "string",
 "example": "Beata Jean"
 },
 "phone": {
 "type": "string",
 "example": "0750000000"
 },
 "operator": {
 "type": "string",
 "example": "zamtel"
 }
 }
 },
 "currency": {
 "type": "string",
 "example": "ZMW"
 },
 "type": {
 "type": "string",
```

```

 "example": "mobile-money"
 },
 "country": {
 "type": "string",
 "example": "zm"
 }
 }
 },
 "400": {
 "description": "400",
 "content": {
 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": false,\n \"message\":\n\"Transfer Recipient was not found\", \n \"data\": null\n}"
 }
 }
 },
 "schema": {
 "type": "object",
 "properties": {
 "status": {
 "type": "boolean",
 "example": false,
 "default": true
 },
 "message": {
 "type": "string",
 "example": "Transfer Recipient was not found"
 },
 "data": {}
 }
 }
 }
 },
 "deprecated": false
}
},
"x-readme": {
 "headers": [],

```

```

 "explorer-enabled": false,
 "proxy-enabled": true
 },
 "x-readme-fauxas": true,
 "_id": "65f06b6583c5de0051b8aa08:65f06b6583c5de0051b8aa11"
}
...

```

## 19 create-transfer-recipient-as-bank-account.md

```
/transfer-recipients/bank-account
```

Create transfer recipient as a bank account

Response schema:

```

```json
{
  "status": boolean,
  "message": string,
  "data": {
    "id": string,
    "currency": string,
    "type": "string",
    "country": string,
    "details": {
      "type": "bank-account",
      "accountName": string,
      "accountNumber": string,
      "bank": {
        "id": string,
        "name": string,
        "country": string
      }
    }
  }
}
```

```

```
OpenAPI definition
```

```

```json
{
  "openapi": "3.1.0",
  "info": {
    "title": "Lenco API",
    "version": "2.0"
  },

```

```
"servers": [
  {
    "url": "https://api.lenco.co/access/v2"
  }
],
"components": {
  "securitySchemes": {
    "sec0": {
      "type": "apiKey",
      "in": "header",
      "name": "Authorization",
      "x-bearer-format": "bearer",
      "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
    }
  }
},
"security": [
  {
    "sec0": []
  }
],
"paths": {
  "/transfer-recipients/bank-account": {
    "post": {
      "summary": "/transfer-recipients/bank-account",
      "description": "Create transfer recipient as a bank account",
      "operationId": "create-transfer-recipient-as-bank-account",
      "requestBody": {
        "content": {
          "application/json": {
            "schema": {
              "type": "object",
              "required": [
                "accountNumber",
                "bankId"
              ],
              "properties": {
                "accountNumber": {
                  "type": "string"
                },
                "bankId": {
                  "type": "string"
                },
                "country": {
                  "type": "string",
                  "description": "Optional"
                }
              }
            }
          }
        }
      }
    }
  }
}
```

```

    }
  }
},
"responses": {
  "200": {
    "description": "200",
    "content": {
      "application/json": {
        "examples": {
          "Result": {
            "value": "{\n  \"status\": true,\n  \"message\":\n  \"\",\n  \"data\": {\n    \"id\": \"d4f71d4a-eda4-4237-9976-5cbdc8a54cf3\",\n    \"details\": {\n      \"type\": \"bank-account\",\n      \"accountName\": \"Beata Jean\",\n      \"accountNumber\": \"9130000000000000\",\n      \"bank\": {\n        \"id\": \"002\",\n        \"name\": \"Absa Bank\",\n        \"country\": \"zm\"\n      },\n      \"currency\": \"ZMW\",\n      \"type\": \"bank-account\",\n      \"country\": \"zm\"\n    }\n  }"
          }
        }
      },
    },
    "schema": {
      "type": "object",
      "properties": {
        "status": {
          "type": "boolean",
          "example": true,
          "default": true
        },
        "message": {
          "type": "string",
          "example": ""
        },
        "data": {
          "type": "object",
          "properties": {
            "id": {
              "type": "string",
              "example": "d4f71d4a-eda4-4237-9976-5cbdc8a54cf3"
            },
            "details": {
              "type": "object",
              "properties": {
                "type": {
                  "type": "string",

```



```

    "400": {
      "description": "400",
      "content": {
        "application/json": {
          "examples": {
            "Result": {
              "value": "{\n  \"status\": false,\n  \"message\":\n\"Account Details could not be verified\",\n  \"data\": null\n}"
            }
          },
          "schema": {
            "type": "object",
            "properties": {
              "status": {
                "type": "boolean",
                "example": false,
                "default": true
              },
              "message": {
                "type": "string",
                "example": "Account Details could not be verified"
              },
              "data": {}
            }
          }
        }
      },
      "deprecated": false
    },
    "x-readme": {
      "headers": [],
      "explorer-enabled": false,
      "proxy-enabled": true
    },
    "x-readme-fauxas": true,
    "_id": "65f06b6583c5de0051b8aa08:65f06b6583c5de0051b8aa12"
  },
  ...

```

20 create-transfer-recipient-as-mobile-money.md

```
# /transfer-recipients/mobile-money
```

Create transfer recipient as a mobile money

Response schema:

```
```json
{
 "status": boolean,
 "message": string,
 "data": {
 "id": string,
 "currency": string,
 "type": "string",
 "country": string,
 "details": {
 "type": "mobile-money",
 "accountName": string,
 "phone": string,
 "operator": string
 }
 }
}
```
```

OpenAPI definition

```
```json
{
 "openapi": "3.1.0",
 "info": {
 "title": "Lenco API",
 "version": "2.0"
 },
 "servers": [
 {
 "url": "https://api.lenco.co/access/v2"
 }
],
 "components": {
 "securitySchemes": {
 "sec0": {
 "type": "apiKey",
 "in": "header",
 "name": "Authorization",
 "x-bearer-format": "bearer",
 "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
 }
 }
 },
 "security": [

```

```

{
 "sec0": []
}
],
"paths": {
 "/transfer-recipients/mobile-money": {
 "post": {
 "summary": "/transfer-recipients/mobile-money",
 "description": "Create transfer recipient as a mobile money",
 "operationId": "create-transfer-recipient-as-mobile-money",
 "requestBody": {
 "content": {
 "application/json": {
 "schema": {
 "type": "object",
 "required": [
 "phone",
 "operator"
],
 "properties": {
 "phone": {
 "type": "string"
 },
 "operator": {
 "type": "string",
 "description": "either `airtel`, `mtn`, or `zamtel`",
 "enum": [
 "airtel",
 "mtn",
 "zamtel"
]
 },
 "country": {
 "type": "string",
 "description": "Optional. Currently supporting only `zm`",
 "enum": [
 "zm"
]
 }
 }
 }
 }
 }
 },
 "responses": {
 "200": {
 "description": "200",
 "content": {

```

```

 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": true,\n \"message\":
\\\"\\\", \n \"data\": {\n \"id\": \"d6b6e00e-bdb6-43a6-a561-
85b61496198e\", \n \"details\": {\n \"type\": \"mobile-
money\", \n \"accountName\": \"Beata Jean\", \n \"phone\":
\\\"0750000000\", \n \"operator\":
\\\"zamtel\" \n }, \n \"currency\": \"ZMW\", \n \"type\":
\\\"mobile-money\", \n \"country\": \"zm\" \n } \n}"
 }
 },
 "schema": {
 "type": "object",
 "properties": {
 "status": {
 "type": "boolean",
 "example": true,
 "default": true
 },
 "message": {
 "type": "string",
 "example": ""
 },
 "data": {
 "type": "object",
 "properties": {
 "id": {
 "type": "string",
 "example": "d6b6e00e-bdb6-43a6-a561-85b61496198e"
 },
 "details": {
 "type": "object",
 "properties": {
 "type": {
 "type": "string",
 "example": "mobile-money"
 },
 "accountName": {
 "type": "string",
 "example": "Beata Jean"
 },
 "phone": {
 "type": "string",
 "example": "0750000000"
 },
 "operator": {
 "type": "string",

```

```

 "example": "zamtel"
 }
 },
 "currency": {
 "type": "string",
 "example": "ZMW"
 },
 "type": {
 "type": "string",
 "example": "mobile-money"
 },
 "country": {
 "type": "string",
 "example": "zm"
 }
 }
}
},
"400": {
 "description": "400",
 "content": {
 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": false,\n \"message\":\n\"Account Details could not be verified\",\n \"data\": null\n}"
 }
 }
 },
 "schema": {
 "type": "object",
 "properties": {
 "status": {
 "type": "boolean",
 "example": false,
 "default": true
 },
 "message": {
 "type": "string",
 "example": "Account Details could not be verified"
 },
 "data": {}
 }
 }
 }
}

```

```

 }
 }
 },
 "deprecated": false
 }
}
},
"x-readme": {
 "headers": [],
 "explorer-enabled": false,
 "proxy-enabled": true
},
"x-readme-fauxas": true,
"_id": "65f06b6583c5de0051b8aa08:65f17924e7695d001ef86449"
}
...

```

## 21 create-transfer-recipient-as-lenco-money.md

```
/transfer-recipients/lenco-money
```

Create transfer recipient as a bank account

Response schema:

```

```json
{
  "status": boolean,
  "message": string,
  "data": {
    "id": string,
    "currency": string,
    "type": "string",
    "country": string,
    "details": {
      "type": "lenco-money",
      "accountName": string,
      "walletNumber": string
    }
  }
}
```

```

```
OpenAPI definition
```

```

```json
{

```

```
"openapi": "3.1.0",
"info": {
  "title": "Lenco API",
  "version": "2.0"
},
"servers": [
  {
    "url": "https://api.lenco.co/access/v2"
  }
],
"components": {
  "securitySchemes": {
    "sec0": {
      "type": "apiKey",
      "in": "header",
      "name": "Authorization",
      "x-bearer-format": "bearer",
      "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
    }
  }
},
"security": [
  {
    "sec0": []
  }
],
"paths": {
  "/transfer-recipients/lenco-money": {
    "post": {
      "summary": "/transfer-recipients/lenco-money",
      "description": "Create transfer recipient as a bank account",
      "operationId": "create-transfer-recipient-as-lenco-money",
      "requestBody": {
        "content": {
          "application/json": {
            "schema": {
              "type": "object",
              "required": [
                "walletNumber"
              ],
              "properties": {
                "walletNumber": {
                  "type": "string"
                }
              }
            }
          }
        }
      }
    }
  }
}
```



```

    },
    "responses": {
      "200": {
        "description": "200",
        "content": {
          "application/json": {
            "examples": {
              "Result": {
                "value": "{\n  \"status\": true,\n  \"message\":  

  \"\", \n  \"data\": {\n    \"id\": \"d4f71d4a-eda4-4237-9976-  

  5cbdc8a54cf3\", \n    \"details\": {\n      \"type\": \"lenco-  

  money\", \n      \"accountName\": \"Beata  

  Jean\", \n      \"walletNumber\":  

  \"0000001\", \n    }, \n    \"currency\": \"ZMW\", \n    \"type\":  

  \"lenco-money\", \n    \"country\": \"zm\" \n  } \n}"
              }
            }
          }
        },
        "400": {
          "description": "400",
          "content": {
            "application/json": {
              "examples": {
                "Result": {
                  "value": "{\n  \"status\": false, \n  \"message\":  

  \"Account Details could not be verified\", \n  \"data\": null \n}"
                }
              }
            }
          },
          "schema": {
            "type": "object",
            "properties": {
              "status": {
                "type": "boolean",
                "example": false,
                "default": true
              },
              "message": {
                "type": "string",
                "example": "Account Details could not be verified"
              },
              "data": {}
            }
          }
        }
      }
    }
  }
}

```

```

    },
    "deprecated": false
  }
},
"x-readme": {
  "headers": [],
  "explorer-enabled": false,
  "proxy-enabled": true
},
"x-readme-fauxas": true,
"_id": "65f06b6583c5de0051b8aa08:65f17927342f24003acc1fbb"
}
...

```

create-transfer-recipient-as-lenco-merchant.md

```

# /transfer-recipients/lenco-merchant

Create transfer recipient as a bank account

```

Response schema:

```

```json
{
 "status": boolean,
 "message": string,
 "data": {
 "id": string,
 "currency": string,
 "type": "string",
 "country": string,
 "details": {
 "type": "lenco-merchant",
 "accountName": string,
 "tillNumber": string
 }
 }
}
```

```

OpenAPI definition

```

```json
{
 "openapi": "3.1.0",
 "info": {
 "title": "Lenco API",

```

```
 "version": "2.0"
 },
 "servers": [
 {
 "url": "https://api.lenco.co/access/v2"
 }
],
 "components": {
 "securitySchemes": {
 "sec0": {
 "type": "apiKey",
 "in": "header",
 "name": "Authorization",
 "x-bearer-format": "bearer",
 "x-default": "xo+CAiijrIy9XvZCYyhjrv0fpSAL6CfU8CgA+up1NXqK"
 }
 }
 },
 "security": [
 {
 "sec0": []
 }
],
 "paths": {
 "/transfer-recipients/lenco-merchant": {
 "post": {
 "summary": "/transfer-recipients/lenco-merchant",
 "description": "Create transfer recipient as a bank account",
 "operationId": "create-transfer-recipient-as-lenco-merchant",
 "requestBody": {
 "content": {
 "application/json": {
 "schema": {
 "type": "object",
 "required": [
 "tillNumber"
],
 "properties": {
 "tillNumber": {
 "type": "string"
 }
 }
 }
 }
 }
 },
 "responses": {
 "200": {
```

```

 "description": "200",
 "content": {
 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": true,\n \"message\":

\\\"\", \n \"data\": {\n \"id\": \"d4f71d4a-eda4-4237-9976-

5cbdc8a54cf3\", \n \"details\": {\n \"type\": \"lenco-

merchant\", \n \"accountName\": \"Account

Name\", \n \"tillNumber\":

\\\"0000001\", \n }, \n \"currency\": \"ZMW\", \n \"type\":

\\\"lenco-merchant\", \n \"country\": \"zm\" \n } \n}"
 }
 }
 }
 },
 "400": {
 "description": "400",
 "content": {
 "application/json": {
 "examples": {
 "Result": {
 "value": "{\n \"status\": false, \n \"message\":

\\\"Account Details could not be verified\", \n \"data\": null \n}"
 }
 }
 },
 "schema": {
 "type": "object",
 "properties": {
 "status": {
 "type": "boolean",
 "example": false,
 "default": true
 },
 "message": {
 "type": "string",
 "example": "Account Details could not be verified"
 },
 "data": {}
 }
 }
 }
 },
 "deprecated": false
 }
}

```

```
 }
 },
 "x-readme": {
 "headers": [],
 "explorer-enabled": false,
 "proxy-enabled": true
 },
 "x-readme-fauxas": true,
 "_id": "65f06b6583c5de0051b8aa08:65f17929b650d0003440d860"
}
...
```