In [87]:

```
import numpy as np
import pandas as pd
from scipy import stats as sts
import matplotlib.pyplot as plt
import math
import seaborn as sbn
from sklearn import metrics as mts
from sklearn.datasets import load_iris
%pylab inline
```

Populating the interactive namespace from numpy and matplotlib

```
/home/dima/anaconda3/lib/python3.6/site-packages/IPython/core/magic s/pylab.py:161: UserWarning: pylab import has clobbered these variab les: ['grid', 'colors', 'draw'] `%matplotlib` prevents importing * from pylab and numpy "\n`%matplotlib` prevents importing * from pylab and numpy"
```

In [88]:

```
data = load_iris()
X = data['data'] # выборка
y = data['target'] # номера компонент смеси
```

In [98]:


```
# для каждого из классов оценим параметры распределения sample0 = X[y == 0] sample1 = X[y == 1] sample2 = X[y == 2] mean0 = np.mean(sample0, axis = 0) mean1 = np.mean(sample1, axis = 0) mean2 = np.mean(sample2, axis = 0) cov0 = np.cov(sample0.T) cov1 = np.cov(sample1.T) cov2 = np.cov(sample2.T) Gauss0 = sts.multivariate_normal(mean=mean0, cov=cov0) Gauss1 = sts.multivariate_normal(mean=mean1, cov=cov1) Gauss2 = sts.multivariate_normal(mean=mean2, cov=cov2)
```

In [90]:

```
df = pd.DataFrame(X)
df['target'] = y
sbn.pairplot(df, hue = 'target')
```

Out[90]:

<seaborn.axisgrid.PairGrid at 0x7fbc3efc01d0>




In [91]:


In [92]:


```
I = np.array([0, 1])
gauss0TwoDim = sts.multivariate_normal(*getVectorDensity(mean0, cov0, *I))
gauss1TwoDim = sts.multivariate_normal(*getVectorDensity(mean1, cov1, *I))
gauss2TwoDim = sts.multivariate_normal(*getVectorDensity(mean2, cov2, *I))
```

In [93]:

```
grid = np.mgrid[3.6:8.5:1e-2, 1.5:4.7:1e-2]
pos = np.empty(grid[0].shape + (2,))
pos[:, :, 0] = grid[0]; pos[:, :, 1] = grid[1]
density0 = 1/2 * (gauss1TwoDim.pdf(pos) + gauss2TwoDim.pdf(pos))
density1 = 1/2 * (gauss0TwoDim.pdf(pos) + gauss2TwoDim.pdf(pos))
density2 = 1/2 * (gauss0TwoDim.pdf(pos) + gauss1TwoDim.pdf(pos))
plt.figure(figsize=(15, 20))
boards = ([0.02, 0.1, 0.2, 0.3, 0.6, 0.8],
          [0.02, 0.1, 0.2, 0.3, 0.4, 0.6, 0.8],
          [0.02, 0.1, 0.2, 0.35, 0.55, 0.8])
for i, zip_ in enumerate(zip([density0, density1, density2], boards)):
    density, board = zip_
    plt.subplot(3, 1, i + 1)
    plt.pcolormesh(grid[0], grid[1], density, cmap='Oranges')
    plt.contour(grid[0], grid[1], density, board)
plt.show()
```







In [94]:

 $argmax_k = lambda x: np.argmax(np.array([Gauss0.pdf(x), Gauss1.pdf(x), Gauss2.pdf(x)]))$

In [95]:


y_pred = np.array(list(map(lambda x: argmax_k(x), X)))
mts.accuracy_score(y_pred, y)


Out[95]:


0.979999999999998

In [96]:

In [97]:







In []: