

# Giving a Voice to Your Graph: Representing Structured Data for LLMs



**Bryan Perozzi**  
Google Research

6/17/24




[Workshop on Scene Graphs and Graph Representation Learning](#) (CVPR)

# GNN Team

The GNN Team's mission is to make it easy to use graph structured data inside neural networks.

In service of this goal, we produce:

- **Research** in the area (ICML, NeurIPS, KDD, etc)
- **Library** to express these models (TF-GNN)
- **Infra** for training & deploying GNNs
- **Models** for custom applications



# Motivation



We have a powerful new tool (GenAI models), that allows us incredible new capabilities in language, vision, video, and more. However, there are weaknesses stopping us from applying this tool everywhere.

- LLMs make stuff up (***hallucinations***)
- LLMs have stale pretraining (***freshness***)
- There's a desire for *private* LLMs that can use personal data without leaking it (***privacy***)
- Training and inference is expensive (***cost***)

# How can Graphs help?


Graphs are tools for modeling the fundamental structure of data. They allow us to

- **Represent knowledge** in human-accessible formats (knowledge graphs, relational databases, etc)
  - Grounding
  - Structured Data in prompt
  - Private information in prompt
- Use sparsity for efficient algorithms and hierarchical decompositions (**efficiency**)
  - Graph models vs Transformers
    - Graphs: more parameter efficient
    - Graphs: higher sample efficiency




# How can we best get graph structure into GenAI models?

## Idea 1: Graphs as Text



## Idea 2: Graphs as Embedding




# Question 1: How to best encode graphs as Text?

In this work, we seek to find the best way to encode graphs as text for “black box” use in LLMs.


Why **text**? → Dominant LLM interface

What’s novel here?

- ❖ Exploration of graph prompting
- ❖ Evaluation of graph encoding
- ❖ Analysis of the effect of graph structure




# Overview of Framework



**Goal:** We seek to find a *graph encoder* and *prompt question* that can maximize the score of the correct answers over the training dataset.

# What's in a node id?

**Q: What if we used Fantasy Characters?**



**GOT:** G describes a friendship graph among Ned, Cat, Daenerys, Jon, Bran, Sansa, Arya, Cersei, and Jaime.

In this friendship graph: Ned and Cat are friends, Ned and Daenerys are friends, Cat and Daenerys are friends, Daenerys and Jon are friends, Daenerys and Bran are friends, Daenerys and Sansa are friends, Daenerys and Cersei are friends, Jon and Jaime are friends, Sansa and Arya are friends, Arya and Cersei are friends, Cersei and Jaime are friends.

(More encoder descriptions in paper)



# Graph Encoding Choice Matters

graph encoding	ZERO-SHOT
Adjacency	4.83
Incident	6.16
Co-authorship	6.08
Friendship	5.16
SP	5.16
GOT	4.33
Social Network	4.58
Politician	<b>3.50</b>
Expert	5.16

Table 5: Ranking of graph encodings from experiment in Section 3.1 (lower better).


# Graph Encoding Choice Matters

graph encoding	ZERO-SHOT	ZERO-COT	FEW-SHOT	COT	COT-BAG
Adjacency	4.83	3.25	2.16	3.00	1.83
Incident	6.16	<b>2.58</b>	<b>2.00</b>	<b>2.33</b>	<b>1.33</b>
Co-authorship	6.08	6.33	5.58	6.75	8.83
Friendship	5.16	6.41	6.25	4.66	6.00
SP	5.16	4.50	5.25	5.75	4.66
GOT	4.33	4.08	5.83	5.00	6.25
Social Network	4.58	6.50	5.83	6.16	6.41
Politician	<b>3.50</b>	6.33	6.25	5.58	4.00
Expert	5.16	5.00	5.83	5.75	5.66

Table 5: Ranking of graph encodings from experiment in Section 3.1 (lower better).


# “Talk like a Graph” Leaderboard

Sept 20th, 2023



# “Talk like a Graph” Leaderboard

May 8th, 2024



# Question 2: How to Best Encode Data for LLMs?

In this work, we seek to find the best way to encode data for LLMs.

Why **graphs**? → Can encode anything, e.g.


- complex interactions
- multi-scale effects
- multi-modal data

Why **not text**? → Talk like a Graph showed some limitations of text encoding.

What's novel here?

- ❖ GraphToken → Fundamentally new way of learning graph embeddings
- ❖ GNN Soft Prompting Functions
- ❖ Generalization experiments of GraphToken


“Talk like a Graph” ⇒ “GraphToken”



LET YOUR GRAPH DO THE TALKING: ENCODING STRUCTURED DATA FOR LLMs

<https://arxiv.org/pdf/2402.05862.pdf>

# GraphToken: *Graphs that Talk*




**Goal:** We seek a GNN encoding function that can project structured data into the token space of a frozen model.

LET YOUR GRAPH DO THE TALKING: ENCODING STRUCTURED DATA FOR LLMs

<https://arxiv.org/pdf/2402.05862.pdf>


# GraphToken Results



# What else is at the intersection of Graphs and LLMs?


## Idea 3: Theory - Graph capabilities of Transformers

GNNs




VS

Transformers



## Idea 4: Using Graphs to generate unseen synthetic data patterns






# Question 3: What can we say about Graph Algorithms in Transformers?

Our new work explores the theoretical underpinnings of graph algorithms in Transformers!

We analyze the “token only”  
(no text representation) →



---


## Understanding Transformer Reasoning Capabilities via Graph Algorithms

---

Clayton Sanford<sup>1,2\*</sup>, Bahare Fatemi<sup>1</sup>, Ethan Hall<sup>3</sup>, Anton Tsitsulin<sup>1</sup>,  
Mehran Kazemi<sup>4</sup>, Jonathan Halcrow<sup>1</sup>, Bryan Perozzi<sup>1</sup>, and Vahab Mirrokni<sup>1</sup>

<sup>1</sup>Google Research, <sup>2</sup>Columbia University, <sup>3</sup>Google, <sup>4</sup>Google DeepMind

# Hierarchy of Graph Algorithms



(a) The complexity hierarchy

Task class	Example tasks	Complexity
Retrieval ( <a href="#">§3.3</a> ) $L = 1$ $m = O(\log N)$	Node count Edge count Edge existence Node degree	D1 D1 D1 D1
Parallelizable ( <a href="#">§3.1</a> ) $L = O(\log N)$ $m = O(N^\epsilon)$	Connectivity Cycle check Bipartiteness	LD $\text{LDP} \cap \text{LDW}$ $\text{LDP} \cap \text{LDW}$
Search ( <a href="#">§3.2</a> ) $L = O(\log N)$ $m = O(N^{1/2+\epsilon})$	Shortest path Diameter	LDW LDW

(b) Example tasks and their complexity.

Figure 2: A summary of the theoretical hierarchy of Section 3 that visualizes which type of graph reasoning tasks can be solved in which transformer scaling regime (Depth1 (D1), LogDepth (LD), LogDepthWide (LDW) and LogDepthPause (LDP)).

# Experimental Results

- Transformers excel at global tasks
  - a. Shortest path, connectedness, etc
  - b. “Pure GNNs” may have capacity problems with tasks that require
- GNN’s graph bias does help them learn with less data, but
  - a. With more data, Transformers can be very competitive

note: ~100k  
params

Model	Node Degree		Cycle Check	
	1K		1K	
GCN [42]	9.8		83.2	
MPNN [26]	99.4		99.0	
GIN [82]	36.2		98.8	
60M transformer	31.6		97.1	

**GNN winning on local tasks**

Model	# of training samples	
	1K	
GCN [42]	50.2	
MPNN [26]	66.8	
GIN [82]	54.0	
60M transformer	57.4	

**Shortest path results**

# Experimental Results

- Transformers excel at global tasks
  - Shortest path, connectedness, etc
  - “Pure GNNs” may have capacity problems with tasks that require
- GNN’s graph bias does help them learn with less data, but
  - With more data, Transformers can be very competitive

note: ~100k  
params

Model	Node Degree		Cycle Check	
	1K	100K	1K	100K
GCN [42]	9.8	9.4	83.2	83.2
MPNN [26]	99.4	<b>99.8</b>	99.0	<b>100.0</b>
GIN [82]	36.2	37.8	98.8	83.2
60M transformer	31.6	91.7	97.1	98.0

## GNN winning on local tasks

Model	# of training samples	
	1K	100K
GCN [42]	50.2	55.0
MPNN [26]	66.8	72.6
GIN [82]	54.0	58.6
60M transformer	57.4	<b>97.1</b>

## Shortest path results

# Idea 4: Graphs for synthetic data generation

Synthetic data generation is becoming more popular for evaluating LLMs.

- Why?
  - Synthetic data is harder to memorize
  - Synthetic data can disentangle “reasoning” from memorized facts (“parametric knowledge”)
- Graphs can help here!

## Test of Time: A Benchmark for Evaluating LLMs on Temporal Reasoning

Bahare Fatemi<sup>1</sup>, Mehran Kazemi<sup>2\*</sup>, Anton Tsitsulin<sup>1</sup>, Karishma Malkan<sup>2</sup>, Jinyeong Yim<sup>3</sup>, John Palowitch<sup>2</sup>, Sungyong Seo<sup>3</sup>, Jonathan Halcrow<sup>1</sup>, and Bryan Perozzi<sup>1</sup>

<sup>1</sup>Google Research, <sup>2</sup>Google DeepMind, <sup>3</sup>Google

**Prompt:** Below are the list of head coaches for Chelsea FC. Who was the coach before Pochettino?  
Pochettino: July 2023 to May 2024  
Potter: September 2022 to April 2023  
Tuchel: January 2021 to September 2022  
Lampard: July 2019 to January 2021 and April 2023 to June 2023  
Sarri: July 2018 to June 2019

**Model Response:** The coach before Pochettino was **Frank Lampard** during his second stint with the club from April 2023 to June 2023.


Grounded prompt (answered correctly)

**Prompt:** Below are the list of head coaches for a club. Who was the coach before E5?  
E5: July 2023 to May 2024  
E4: September 2022 to April 2023  
E3: January 2021 to September 2022  
E2: July 2019 to January 2021 and April 2023 to June 2023  
E1: July 2018 to June 2019

**Model Response:** E4 was the coach before E5.

Abstract prompt (answered incorrectly)

# Turning Random Graphs into Random KGs



# Illustrating different synthetic temporal datasets




Figure 5: A visualization of a representative graph from each graph generator: Erdős-Rényi (ER), Scale-Free Networks (SFN), Barabási-Albert (BA), Stochastic Block Model (SBM), star-graph, and complete-graph.

# Conclusions

1. Adding graph information can help frozen LLMs solve graph tasks.
2. The way you represent your structured data matters!
3. Transformers are less sample efficient than GNNs, but with enough training data they do get a lot better.
4. Graphs are useful for synthetic data generation for LLMs too.
5. ... many more details in the respective papers



**Understanding Transformer Reasoning Capabilities  
via Graph Algorithms**

Sanford, Fatemi, Hall, Tsitsulin, Kazemi, Halcrow,  
Perozzi, Mirrokni

<https://arxiv.org/pdf/2405.18512>

**Test of Time: A Benchmark for Evaluating LLMs on  
Temporal Reasoning**

Fatemi, Kazemi, Tsitsulin, Malkan, Yim,  
Palowitch, Seo, Halcrow, Perozzi

<https://arxiv.org/abs/2406.09170>

# Thanks!

Bryan Perozzi

LinkedIn:



Twitter:

[@phanein](https://twitter.com/phanein)

TALK LIKE A GRAPH: ENCODING GRAPHS  
FOR LARGE LANGUAGE MODELS (ICLR'24)

Fatemi, Halcrow, Perozzi

<https://arxiv.org/pdf/2310.04560.pdf>

LET YOUR GRAPH DO THE TALKING:  
ENCODING STRUCTURED DATA FOR LLMs

Perozzi, Fatemi, Zelle, Tsitsulin, Kazemi, Al-Rfou, Halcrow

<https://arxiv.org/pdf/2402.05862.pdf>