

Terminal

Win-1 x Win-2 x Win-3 x

```
c:\WINDOWS\system32\cmd.exe
Approximate round trip times in milli-seconds:
  Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\Documents and Settings\user>ping 172.36.0.10

Pinging 172.36.0.10 with 32 bytes of data:

Reply from 172.36.0.10: bytes=32 time=5ms TTL=124
Reply from 172.36.0.10: bytes=32 time=3ms TTL=124
Reply from 172.36.0.10: bytes=32 time=2ms TTL=124
Reply from 172.36.0.10: bytes=32 time=2ms TTL=124

Ping statistics for 172.36.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 5ms, Average = 3ms

C:\Documents and Settings\user>ping 223.0.50.10

Pinging 223.0.50.10 with 32 bytes of data:

Reply from 223.0.50.10: bytes=32 time=3ms TTL=125
Reply from 223.0.50.10: bytes=32 time=2ms TTL=125
Reply from 223.0.50.10: bytes=32 time=1ms TTL=125
Reply from 223.0.50.10: bytes=32 time=2ms TTL=125

Ping statistics for 223.0.50.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 3ms, Average = 2ms
```

Terminal

Win-1 x Win-2 x Win-3 x

My Documents

My Computer

My Network Places

Recycle Bin

Internet Explorer

Cisco ASDM-1...

Old Java ASDM

PUTTY

ifpd32

```
C:\WINDOWS\system32\cmd.exe
Microsoft Windows XP [Version 5.1.2600.1]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\User>ping 192.50.20.100

Pinging 192.50.20.100 with 32 bytes of data:

Reply from 192.50.20.100: bytes=32 time=3ms TTL=125
Reply from 192.50.20.100: bytes=32 time=2ms TTL=125
Reply from 192.50.20.100: bytes=32 time=2ms TTL=125
Reply from 192.50.20.100: bytes=32 time=2ms TTL=125

Ping statistics for 192.50.20.100:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 3ms, Average = 2ms

C:\Documents and Settings\User>ping 172.36.0.10

Pinging 172.36.0.10 with 32 bytes of data:

Reply from 172.36.0.10: bytes=32 time=3ms TTL=124
Reply from 172.36.0.10: bytes=32 time=3ms TTL=124
Reply from 172.36.0.10: bytes=32 time=3ms TTL=124
Reply from 172.36.0.10: bytes=32 time=3ms TTL=124

Ping statistics for 172.36.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 3ms, Maximum = 3ms, Average = 3ms

C:\Documents and Settings\User>
```

Start

C:\WINDOWS\system...

11:00 AM

```
C:\WINDOWS\system32\cmd.exe
Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ping 192.50.20.100

Pinging 192.50.20.100 with 32 bytes of data:

Reply from 192.50.20.100: bytes=32 time=2ms TTL=124
Reply from 192.50.20.100: bytes=32 time=4ms TTL=124
Reply from 192.50.20.100: bytes=32 time=2ms TTL=124
Reply from 192.50.20.100: bytes=32 time=2ms TTL=124

Ping statistics for 192.50.20.100:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 4ms, Average = 2ms

C:\Documents and Settings\user>ping 223.0.50.10

Pinging 223.0.50.10 with 32 bytes of data:

Reply from 223.0.50.10: bytes=32 time=1ms TTL=124
Reply from 223.0.50.10: bytes=32 time=2ms TTL=124
Reply from 223.0.50.10: bytes=32 time=3ms TTL=124
Reply from 223.0.50.10: bytes=32 time=2ms TTL=124

Ping statistics for 223.0.50.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 3ms, Average = 2ms

C:\Documents and Settings\user>
```

Old Java ASDM

Putty

Hpdi32

Terminal

R1 x

R1#SH IP ROUTE

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

12.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 12.0.0.0/8 is directly connected, Ethernet0/1
L 12.0.0.1/32 is directly connected, Ethernet0/1
S 172.36.0.0/16 [1/0] via 12.0.0.2
192.50.20.0/24 is variably subnetted, 2 subnets, 2 masks
C 192.50.20.0/24 is directly connected, Ethernet0/0
L 192.50.20.1/32 is directly connected, Ethernet0/0
S 223.0.50.0/24 [1/0] via 12.0.0.2

R1#

Terminal

R1 x R2 x

ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

12.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 12.0.0.0/8 is directly connected, Ethernet0/0
L 12.0.0.2/32 is directly connected, Ethernet0/0
23.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 23.0.0.0/8 is directly connected, Ethernet0/2
L 23.0.0.1/32 is directly connected, Ethernet0/2
24.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 24.0.0.0/8 is directly connected, Ethernet0/3
L 24.0.0.1/32 is directly connected, Ethernet0/3
26.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 26.0.0.0/8 is directly connected, Ethernet0/1
L 26.0.0.1/32 is directly connected, Ethernet0/1
S 172.36.0.0/16 [1/0] via 23.0.0.2
S 192.50.20.0/24 [1/0] via 12.0.0.1
S 223.0.50.0/24 [1/0] via 26.0.0.2

R2#

Terminal

R1 x R2 x R3 x

R3#sh ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

23.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 23.0.0.0/8 is directly connected, Ethernet0/0
L 23.0.0.2/32 is directly connected, Ethernet0/0
32.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 32.0.0.0/8 is directly connected, Ethernet0/1
L 32.0.0.1/32 is directly connected, Ethernet0/1
S 172.36.0.0/16 [1/0] via 32.0.0.2
S 192.50.20.0/24 [1/0] via 23.0.0.1
S 223.0.50.0/24 [1/0] via 23.0.0.1

R3#

Terminal

R1 x R2 x R3 x R4 x

R4#sh ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

24.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 24.0.0.0/8 is directly connected, Ethernet0/0
L 24.0.0.2/32 is directly connected, Ethernet0/0
45.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C 45.0.0.0/8 is directly connected, Ethernet0/1
L 45.0.0.1/32 is directly connected, Ethernet0/1
S 172.36.0.0/16 [1/0] via 45.0.0.2
S 192.50.20.0/24 [1/0] via 24.0.0.1
S 223.0.50.0/24 [1/0] via 24.0.0.1

R4#

Terminal

R5 x

i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

32.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 32.0.0.0/8 is directly connected, Ethernet0/1

L 32.0.0.2/32 is directly connected, Ethernet0/1

45.0.0.0/8 is variably subnetted, 2 subnets, 2 masks

C 45.0.0.0/16 is directly connected, Ethernet0/2

L 45.0.0.2/32 is directly connected, Ethernet0/2

172.36.0.0/16 is variably subnetted, 2 subnets, 2 masks

C 172.36.0.0/16 is directly connected, Ethernet0/0

L 172.36.0.1/32 is directly connected, Ethernet0/0

S 192.50.20.0/24 [1/0] via 45.0.0.1

[1/0] via 32.0.0.1

S 223.0.50.0/24 [1/0] via 45.0.0.1

[1/0] via 32.0.0.1

R5#

R5#


```
R6#SH IP ROUTE
```

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2  
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2  
ia - IS-IS inter area, * - candidate default, U - per-user static route  
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP  
a - application route  
+ - replicated route, % - next hop override, p - overrides from PfR
```

```
Gateway of last resort is not set
```

```
26.0.0.0/8 is variably subnetted, 2 subnets, 2 masks  
C    26.0.0.0/8 is directly connected, Ethernet0/1  
L    26.0.0.2/32 is directly connected, Ethernet0/1  
S    172.36.0.0/16 [1/0] via 26.0.0.1  
S    192.50.20.0/24 [1/0] via 26.0.0.1  
223.0.50.0/24 is variably subnetted, 2 subnets, 2 masks  
C    223.0.50.0/24 is directly connected, Ethernet0/0  
L    223.0.50.1/32 is directly connected, Ethernet0/0
```

```
R6#
```