

ARQA TECHNOLOGIES

FIX adapter program interface

FIX Protocol Description

Version 4.2

quik



Contents

1. Supported messages 6
   1.1 Session level 6
   1.2 Application level 6
2. Messages format 7
   2.1 Header/Trailer 8
      2.1.1 Header 8
      2.1.2 Trailer 9
   2.2 Heart Beat 9
   2.3 Logon 9
   2.4 Logout 10
   2.5 Test Request 10
   2.6 Resend Request 10
   2.7 Reject 11
   2.8 Sequence Reset 11
   2.9 New Order Single 11
      2.9.1 Submit common orders (all types of orders except for algo and OMS) ... 11
      2.9.2 Submit stop orders 15
      2.9.3 Submit negotiated order 18
      2.9.4 Submit OMS-order 20
      2.9.5 Submit ICEBERG Algo order 22
      2.9.6 Submit TWAP Algo orders 24
      2.9.7 Submit VWAP Algo orders 26
      2.9.8 Submit STOP Algo order 28
      2.9.9 Submit GTD Algo order 31
      2.9.10 Transferring risks 32
   2.10 NewOrderMultileg 33

2.10.1 Submit order for the exchange of National settlement depositary pays 33
2.11 Order Cancel Request 34
2.12 Order Cancel Replace Request 35
2.12.1 Replacing common orders 35
2.12.2 Replacing stop orders 38
2.12.3 Replacing algo orders of ICEBERG type 40
2.12.4 Replacing OMS orders 42
2.13 Order Mass Cancel Request 43
2.14 Execution Report 44
2.14.1 Common orders 44
2.14.2 Negotiated orders 55
2.14.3 Stop orders 62
2.14.4 OMS orders 72
2.14.5 Algo orders of ICEBERG type 77
2.14.6 Algo orders of TWAP type 85
2.14.7 Algo orders of VWAP type 94
2.14.8 Algo orders of STOP type 102
2.14.9 Algo orders of GTD type 111
2.14.10 Transferring risks 119
2.14.11 Orders of National settlement depositary pays change 121
2.15 Trade Capture Report 124
2.15.1 OTC trade entry 124
2.15.2 Cancellation of OTC trade of current session (incoming message) 125
2.15.3 Trade reporting (outgoing message) 126
2.16 Trade Capture Report Ask 127
2.17 Trade Capture Report Request 128
2.18 Order Cancel Reject 128
2.19 Market Data Request 129

2.20 Market Data Request Reject 131
2.21 Market Data Incremental Refresh 131
2.22 Market Data – Snap Shot / Full Refresh 133
2.23 Security Definition Request 136
2.24 Security Definition 136
2.25 Order Status Request 140
2.26 Order Mass Status Request 140
2.27 Security Status Request 141
2.28 Security Status 141
2.29 User Request 143
2.30 User Response 143
2.31 Request for Positions 144
2.32 Request for Positions Ack 145
2.33 Position Report 145
2.34 Quote Request 148
2.35 Quote Request Reject 149
2.36 Quote 149
2.37 Quote Cancel 150
2.38 Quote Status Report 150
2.39 Indication of Interest (IOI) 151
2.40 Quote Acknowledgment 152
2.40.1 Client notification about request rejection 152
2.40.2 Client request to terminate a translation of quotes 152
2.41 QUIK Session Change Request 153
2.42 QUIK Session Change Response 153
2.43 POS Order Allocation Request 154
2.44 POS Security Allocation Request 154
2.45 POS Allocation Response 155
3. Correspondences of OMS order client statuses 155

4. Diagnostics of request rejection 156
4.1 New Order Single 156
4.2 Order Cancel Request 158
4.3 Order Cancel Replace Request.....159
5. APPENDIX 162
5.1 The format of filling the order cancel / replace request.....162
5.2 <Instrument> component block.....163

You may email your comments on this Manual to: quiksupport@arqatech.com

1. Supported messages

1.1 Session level

Message	Message type
Heart Beat	0
Logon	A
Logout	5
Test Request	1
Resend Request	2
Reject	3
Sequence Reset	4

1.2 Application level

Message	Message type
New Order Single	D
Order Cancel Request	F
Execution Report	8
Trade Capture Report	AE
Trade Capture Report Ask	AR
Trade Capture Report Request	AD
Order Cancel Reject	9
Order Cancel Replace Request	G
Order Mass Cancel Request	Q
Market Data Request	V
Market Data Request Reject	Y
Market Data Incremental Refresh	X
Market Data – Snap Shot / Full Refresh	W
Security Definition Request	c

Message	Message type
Security Definition	D
Order Status Request	H
Order Mass Status Request	AF
Security Status Request	E
Security Status	F
User Request	BE
User Response	BF
Request For Positions	AN
Request For Positions Ack	AO
Position Report	AP
Quote Request	R
Quote Request Reject	AG
Quote	S
Quote Cancel	Z
Quote Status Report	Al
Indication of Interest	6
QuoteAcknowledgment	b
QUIK Session Change Request	UQSCRQ
QUIK Session Change Response	UQSCRS
POS Order Allocation Request	UPOARQ
POS Security Allocation Request	UPSARQ
POS Allocation Response	UPARS

2. Messages format

1. **Tags which are necessary to be filled are ticked by '*'.**
2. **Tags which are the first elements of a group are ticked by '**'.**
3. **Tags included to a group are ticked by '→'.**

2.1 Header/Trailer

2.1.1 Header

Supported tags:

Field name	Tag	Comments
BeginString*	8	Valid values: _ FIX.4.2 – for protocol version 4.2; _ FIX.4.4 – for protocol version 4.4; _ FIXT.1.1 – for protocol version 5.0
BodyLength*	9	
MsgType*	35	
SenderCompID*	49	For example: CLIENT
TargetCompID*	56	For example: QUIK
OnBehalfOfCompID	115	
DeliverToCompID	128	
MsgSeqNum*	34	
PossDupFlag	43	
PossResend	97	
SendingTime	52	For example: 20070830-09:38:26
OrigSendingTime	122	For example: 20070830-09:38:26
ApplVerID	1128	Valid values: _ 4 – for protocol version 4.2; _ 6 – for protocol version 4.4; _ 7 – for protocol version 5.0; _ 9 – for protocol vercion 5.0SP2
SenderSubID	50	
TargetSubID	57	
DeliverToSubID	129	
OnBehalfOfSubID	116	

2.1.2 Trailer

Supported tags:

Field name	Tag	Comments
CheckSum*	10	Message checksum

2.2 Heart Beat

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: 0
TestReqID	112	Identifier included in Test Request message to be returned in resulting Heartbeat

2.3 Logon

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: A
EncryptMethod	98	Valid value: 0 (always unencrypted)
HearBitInt*	108	Seconds
ResetSeqNumFlag	141	Reset session count to 1, clearing the storage of sent messages
DefaultApplVerID	1137	FIX protocol version. Valid values: _ 4 – for protocol version 4.2; _ 5 – for protocol version 4.3; _ 6 – for protocol version 4.4; _ 7 – for protocol version 5.0; _ 9 – for protocol vercion 5.0SP2. Required field for protocol version 5.0 or newer

2.4 Logout

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: 5
Text	58	Reason for closing FIX session
SessionStatus***	1409	Reason for loss of connection to the QUIK server. Valid values: _ 100 – Interface is not connected to the QUIK server

*** – tag is available only if there is a permission in the scheme.

2.5 Test Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: 1
TestReqID	112	

2.6 Resend Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: 2
BeginSeqNo*	7	
EndSeqNo	16	All messages are sent if EndSeqNo = 0 or blank

2.7 Reject

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: 3
Text	58	Free format text string if the trade system answer / clients comment
SessionRejectReason	373	Code to identify reason for a session-level Reject message. Supported only for protocol version 5.0
RefTagID	371	The tag number of the FIX field being referenced. Supported only for protocol version 5.0
RefSeqNum	45	Number of rejected message
RefMsgType	372	Type of rejected message

2.8 Sequence Reset

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: 4
GapFillFlag	123	Valid value: Y
NewSeqNo	36	When sending a message by Interface: the number of the next message, which will be sent by the Interface. When receiving a message by Interface: number of the following message that will be sent by the client. The number value must be higher than number of the previous message

2.9 New Order Single

2.9.1 Submit common orders (all types of orders except for algo and OMS)

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: D
ClOrdID*	11	Unique identifier for Order

Field name	Tag	Comments
HandlInst*	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side*	54	Valid values: _ 1 – Buy; _ 2 – Sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed
SecurityType	167	Instrument type. Valid values: _ FXSPOT; _ FXFWD; _ FXNDF; _ FXFLEXFWD
StartDate	5142	FXFLEXFWD (Flexible Forward) contract start date in the format <YYYYMMDD>
OrdType*	40	Valid values: _ 1 – Market; _ 2 – Limit; _ 5 – Market On Close; _ B – limit On Close; _ H – Forex Previously Quoted; _ q – Quote
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Price*	44	Price
Currency	15	Identifies currency used for price
OrderQty*	38	Tag may include: _ Order quantity. The Interface checks if the value is divisible into lots and convert items into lots; _ Total quantity (for Iceberg orders)
CouponRate	223	Coupon rate
Text	58	Clients comment
TimeInForce***	59	Valid values:

Field name	Tag	Comments
		_ 0 – Day; _ 1 – Good Till Cancel; _ 2 – At The Opening; _ 3 – Immediate Or Cancel; _ 4 – Fill Or Kill; _ 6 – Good Till Date; _ 7 – At The Close; _ X – Extended Hours; _ z – Book or Cancel
ExpiryTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
ClientID	109	Clients ID. For details on clients ID identification see Administrator's manual, 2.11
NoPartyIDs	453	Number of PartyID groups
→PartyID **	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code; _ 11 – client code; _ 12 – MiFID2 executing trader short code; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
OrderRestrictions****	529	Market maker order attribute. [FIX4.4+] Valid value: _ 5 – Acting as Market Maker or Specialist in the security
FirmId	5018	Firm code on behalf of which a makler order is submitted. If this tag has a non-empty value, a makler transaction is used instead of a usual one to submit an order (Special operations permission by a class in which an order is submitted has to be assigned to a technological user)

Field name	Tag	Comments
MaxFloor	111	Displayed quantity (for market Iceberg orders)
SettlDate	64	Settlement date in <YYYYMMDD> format
PegOffsetValue	211	Protective spread. Value by default: 0. The tag is used for stop orders of Take profit type
PegOffsetType	836	Item of protective spread. Valid values: _ 0 (by default) – price currency; _ 1 – percent. The tag is used for stop orders of Take profit type
DiscretionOffsetValue	389	Valid values: _ shift from the minimum price – for buying; _ shift from the maximum price – for selling. Value by default: 0. The tag is used for stop orders of Take profit type
DiscretionOffsetType	842	Shift item. Valid values: _ 0 (by default) – price currency; _ 1 – percent. The tag is used for stop orders of Take profit type
QuoteID	117	Order identifier from Quote
CashOrderQty	152	Order volume in cash
MarketLot	6200	Lot size of instrument
OrderOrigination	1724	Value: 5 – DEA
SettlType	63	Settlement code in QUIK system format
ReOffer	5092	Attribute of approval to any rate when submitting orders for offering. Valid values: _ N – no; _ Y – yes
VenueClassCode	5143	Exchange class. Required tag when placing an OMSFX class order
DealerBook	5144	Dealer book
FundsFlow	5145	Funds flow. Value in representation format of the OMSFX system, for example: “1st-1st”, “3rd-unknown”
DealerPrice	5146	Dealer price
ClientPriceEntryMode	5147	Price input mode by client. Valid values: _ A – Auto; _ M – Manual;

Field name	Tag	Comments
		_ S – Spread
ClientSpread	5148	Spread on client price
ExtRef	5081	External reference

*** – only value 0 or <empty> (considered as 0) is available if value B or 5 is specified in tag [40].

**** – [FIX <N>] – the tag is only available for the FIX protocol version <N> or newer (if the version is specified) or if it is allowed in the scheme.

2.9.2 Submit stop orders

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: D
ClOrdID*	11	Unique identifier for Order
HandlInst*	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side*	54	Valid values: _ 1 – buy; _ 2 – sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed
OrdType*	40	Type of an order. Valid values: _ 3 – Stop / Stop Loss; _ 4 – Stop Limit; _ T – Stop / Take-profit; _ b – Stop Limit With linked order; _ a – Stop price of another instrument; _ t – Take profit and stop limit
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10

Field name	Tag	Comments
Price	44	Price. If the tag is absent then the At market price attribute for stop limit is transmitted
Currency	15	Instrument currency
OrderQty*	38	Order quantity. The Interface checks if the value is divisible into lots and convert items into lots
Text	58	Clients comment
TimeInForce	59	Valid values: _ 0 – Day; _ 1 – Good Till Cancel; _ 6 – Good Till Date
StopPx	99	Stop price (for Stop-limit, Take profit orders, Stop Limit With linked order, Stop price of another instrument, Take profit and stop limit)
RefOrderPrice	5075	Price of linked order. It is used for stop orders of Stop Limit With linked order type
CancelStopIfRefOrderPartiallyFilled	5076	Value: Y – cancel stop order when partially executed linked order. It is used for stop orders of Stop Limit With linked order type
StopPxCondition	5077	Type of stop price condition. It is used for stop orders of Stop price of another instrument type. Valid values: _ G – Greater than or equal to; _ L – Less than or equal to
RefSecurityID	5078	Code of instrument of stop price. It is used for stop orders of Stop price of another instrument type
RefExDestination	5079	Code of class or stop price instrument market. It is used for stop orders of Stop price of another instrument type. If no value is specified, the code of class or stop price instrument market is inherited from ExDestination
TakeProfitPx	5080	Take-profit price. It is used for stop orders of Take profit and stop limit type
ExpiryTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD> format. For the Take Profit and Stop Limit orders the format is the following <YYYYMMDD-HH:MM:SS>
ClientID	109	Client's ID. For details on clients ID identification see Administrator's manual, 2.11
NoPartyIDs	453	Number of PartyID groups

Field name	Tag	Comments
→ PartyID**	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code; _ 11 – client code; _ 12 – MiFID2 executing trader short code; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
PegOffsetValue	211	Protective spread. Value by default: 0. The tag is used for stop orders of Take profit and Take profit and stop limit types. If the tag is absent, then the At market price attribute is transmitted for take profit
PegOffsetType	836	Item of protective spread. Valid values: _ 0 (by default) – price currency; _ 1 – percent The tag is used for stop orders of Take profit and Take profit and stop limit types
DiscretionOffsetValue	389	Valid values: _ shift from the minimum price – for buying; _ shift from the maximum price – for selling. Value by default: 0. The tag is used for stop orders of Take profit and Take profit and stop limit types
DiscretionOffsetType	842	Shift item. Valid values: _ 0 (by default) – price currency; _ 1 – percent The tag is used for stop orders of Take profit and Take profit and stop limit types
FirmID	5018	Firm code on behalf of which a makler order is submitted. If this tag has a non-empty value, a makler transaction is used

Field name	Tag	Comments
		instead of a usual one to submit an order (Special operations permission by a class in which an order is submitted has to be assigned to a technological user)
MarketLot	6200	Lot size of instrument
StartTime	5083	Stop order start time in the UTCTimeOnly format (<HH:MM:SS>). Must be filled in pair with [5084] EndTime
EndTime	5084	Stop order end time in the UTCTimeOnly format (<HH:MM:SS>). Must be filled in pair with [5083] StartTime

2.9.3 Submit negotiated order

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: D
ClOrdID*	11	Unique identifier for Order
HandlInst*	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side*	54	Valid values: _ 1 – buy; _ 2 – sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed
SettlmntTyp	63	Settlement code in QUIK system format
OrdType*	40	Order type. Value: _ R – Negotiated order; _ M – REPO-M order
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Price*	44	Price

Field name	Tag	Comments
Currency	15	Instrument currency
OrderQty*	38	Order quantity. The Interface checks if the value is divisible into lots and convert items into lots
Text	58	Clients comment
TimeInForce	59	Value: 0 – Day
ContraBroker	375	Contra brokers code (only for two-sided orders [40=R])
ComplianceID	376	Reference (only for two-sided orders [40=R])
ClientID	109	Clients ID. For details on clients ID identification see Administrator's manual, 2.11
CashOrderQty	152	Negotiated order volume in monetary unit
NoPartyIDs	453	Number of PartyID groups
→ PartyID**	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code; _ 11 – client code; _ 12 – MiFID2 executing trader short code; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
MarketLot	6200	Lot size of instrument
RefundRate	5141	Compensation in percentages
SettlCurrency	120	Settlement currency
ExtRef	5081	External reference
RepoRate	5006	REPO rate

Field name	Tag	Comments
RepoTerm	5012	REPO term
RepoStartDiscount	5019	REPO start discount, %
RepoLowerDiscount	5020	REPO lower discount, %
RepoUpperDiscount	5021	REPO upper discount, %
FirmId	5018	Firm code on behalf of which a negotiated makler order is submitted. If this tag has a non-empty value, a makler transaction is used instead of a usual one to submit a negotiated order which requires the **Special operations** permission for the order submission class

2.9.4 Submit OMS-order

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: D
ClOrdID*	11	Unique identifier for Order
HandlInst*	21	Value: 3 – Manual order
Side*	54	Valid values: _ 1 – buy; _ 2 – sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Price*	44	Price
Currency	15	Identifies currency used for price
OrderQty*	38	Order quantity. The Interface checks if the value is divisible into lots and convert items into lots
Account	1	Trading account. For details on trading account identification, see Administrator's manual, 2.10
ClientID	109	Clients identifier. For details on clients ID identification, see Administrator's manual, 2.11

Field name	Tag	Comments
OrdType*	40	Type of an order. Valid values: _ 1 – Market; _ 2 – Limit; _ 5 – Market On Close; _ B – Limit On Close When the values 5 or B are specified, the tag [59] TimeInForce must be absent or have value 0
TimeInForce	59	Validity term of order. Valid values: _ 0 – Day; _ 1 – Good Till Cancel; _ 2 – At The Opening; _ 6 – Good Till Date; _ 7 – At The Close
ExpiryTime	126	Date and term of order's validity period in format <YYYYMMDD-HH:MM:SS>. Used only for orders with time in force Good Till Date
SettlType	63	Settlement code in QUIK system format
SettlCurrency	120	Settlement currency
Commission	12	Commission amount
CommType	13	Type of commission. Valid values: _ 1 – Per Unit; _ 2 – Percent; _ 3 – Absolute; _ 7 – Base points Value transmission depends on the CommissionReporting setting in [OMS] section (see Administrator's manual, sub-section 2.2.29)
SalesInvolved	7672	Attribute of Sales participation: _ 1 – Sales participates; _ 2 – Sales does not participate
Memo	5149	Comment to OMS order
SecurityExchange	207	Reference field, returns to client in response messages ExecutionReport. When running in OMS / DMA mode, the value is interpreted by the OMS module as the code of the execution platform
FutSettDate	64	Settlement date
PaymentDate	504	Payment date
DeliveryType	919	Delivery type
CstmOrdType	5057	Extended type of order
OMSFreeText1	5061	A free text of the length up to 64 symbols

Field name	Tag	Comments
OMSFreeText2	5062	
OMSFreeText3	5063	
OMSFreeText4	5064	
OMSFreeText5	5065	
NETPriceIndicator	5074	Attribute of entering a NET price. Valid values: _ 0 (or empty) – Gross price is specified; _ 1 – Net price is specified
Strategy	6258	External algorithm name. For a list of supported algorithms and their parameters, contact QUIK support technical service
Counterparty	375	Counterparty
TradingBook	5094	Trading book
GiveUpBroker	5107	GiveUp broker
OrderRecvDateTime	5112	Date and time in format GMT <YYYYMMDD-HH:MM:SS> when an instruction was sent
TradingCode	5133	Client's trading code

2.9.5 Submit ICEBERG Algo order

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: D
ClOrdID*	11	Unique identifier for Order
HandlInst*	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side*	54	Valid values: _ 1 – buy; _ 2 – sell
OrdType*	40	Type of an order. Valid values: _ 1 – Market;

Field name	Tag	Comments
		_ 2 – Limit
Account	1	Trading account. For details on trading account identification see Administrator's manual for FIX adapter Program Interface, 2.10
Price*	44	Price
Currency	15	Identifies currency used for price
OrderQty*	38	Tag might include: _ Order quantity. The Interface checks if the value is divisible into lots and convert items into lots; _ Summary quantity (for Iceberg orders)
Text	58	Clients comment
TimeInForce	59	Valid values: _ 0 – Day; _ 1 – Good Till Cancel; _ 6 – Good Till Date
ExpiryTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
ClientID	109	Clients ID. For details on clients ID identification see Administrator's manual, 2.11
NoPartyIDs	453	Number of PartyID groups
→ PartyID**	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code; _ 11 – client code; _ 12 – MiFID2 executing trader short code; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity;

Field name	Tag	Comments
		_ 24 – Natural person
RefreshQty	6251	Visible quantity in algo orders (for Iceberg orders, sent via algorithmic trading module)
Strategy	6258	Algorithm name. Valid values: _ Iceberg – Iceberg algo order
ExecutionStyle	6261	Aggressiveness (for Iceberg algo orders). Valid values: _ 0 – standard mode; _ 1 – Quotes table analysis; _ 2 – Level II quotes table analysis
AlgField1	6271	Flag of related order being cancelled (for Iceberg algo orders). Valid values: _ 0 – yes; _ 1 – no
SettlDate	64	Settlement date in <YYYYMMDD> format
UseWorkInterval	6280	Indicates whether the activity interval is used. Valid values: _ 0 – not used; _ 1 – used
StartTime	6254	Start time. Time format is determined by the AlgoTimeFormat setting of section [General] in the QuikFix.ini configuration file (for details, see the Administrator's manual)
EndTime	6255	End time. Time format is determined by the AlgoTimeFormat setting of section [General] in the QuikFix.ini configuration file (for details, see the Administrator's manual)

2.9.6 Submit TWAP Algo orders

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: D
ClOrdID*	11	Unique identifier for Order
HandlInst*	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention

Field name	Tag	Comments
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side*	54	Valid values: _ 1 – buy; _ 2 – sell
OrdType*	40	Type of an order. Valid values: _ 1 – Market; _ 2 – Limit
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Currency	15	Identifies currency used for price
OrderQty*	38	Order quantity. QUIK FIX checks if the value is divisible into lots and convert items into lots
Text	58	Clients comment
TimeInForce	59	Valid value: 0 – Day
ClientID	109	Clients ID. For details on clients ID identification see Administrator's manual, 2.11
CashOrderQty	152	Algo order volume
NoPartyIDs	453	Number of PartyID groups
→ PartyID**	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code; _ 11 – client code; _ 12 – MiFID2 executing trader short code; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity;

Field name	Tag	Comments
		_ 24 – Natural person
StartTime	6254	Start. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
EndTime	6255	End time. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
Duration	6256	Number of portions
Strategy	6258	Algorithm name. Value: TWAP – TWAP algo order
ToleranceLimit1	6264	Deviation of price in percent
AlgField3	6273	Start time type. Valid values: _ 0 – current time; _ 1 – time set by user
SettlDate	64	Settlement date in <YYYYMMDD> format
AlgField11	6320	Attribute of time profile use. Valid values: _ 0 – time profile is not used; _ 1 – time profile is not used
Price	44	Price
IterationTime	6259	Iteration time
IterationSetMode	6260	Iteration set mode. Valid values: _ 1 – Iteration Time; _ 0 – Iterations Number

2.9.7 Submit VWAP Algo orders

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: D
ClOrdID*	11	Unique identifier for Order
HandlInst*	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention

Field name	Tag	Comments
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side*	54	Valid values: _ 1 – buy; _ 2 – sell
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Price*	44	Price
Currency	15	Identifies currency used for price
OrderQty*	38	Order quantity. QUIK FIX checks if the value is divisible into lots and convert items into lots
Text	58	Clients comment
TimeInForce	59	Valid value: 0 – Day
ClientID	109	Clients ID. For details on clients ID identification see Administrator's manual, 2.11
NoPartyIDs	453	Number of PartyID groups
→ PartyID**	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code; _ 11 – client code; _ 12 – MiFID2 executing trader short code; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person

Field name	Tag	Comments
StartTime	6254	Start time. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
EndTime	6255	End time. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
Duration	6256	Number of portions
Strategy	6258	Algorithm name. Value: TWAP – TWAP algo order;
ToleranceLimit2	6265	Maximum permissible deviation from the volume weighted average price in percent
AlgField4	6274	Flag of execution of the portion (in percent) value estimated by market price. Valid values: _ 0 – no; _ 1 – yes
AlgField5	6275	Portion size in percent of value estimated by market price
CashOrderQty	152	Algo order volume
AlgField11	6281	Working in a price range. Valid values: _ 0 – no; _ 1 – yes
SettlDate	64	Settlement date in <YYYYMMDD> format
AlgField11	6320	Attribute of time profile use. Valid values: _ 0 – time profile is not used; _ 1 – time profile is not used
AlgoTag1	6088	Minimum price
AlgoTag2	6089	Maximum price

2.9.8 Submit STOP Algo order

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: D
ClOrdID*	11	Unique identifier for Order
HandlInst*	21	Valid values:

Field name	Tag	Comments
		_ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
OrdType*	40	Type of an order. Valid values: _ 1 – Market; _ 2 – Limit
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Currency	15	Identifies currency used for price
Text	58	Clients comment
TimeInForce	59	Valid values: _ 0 – Day; _ 1 – Good Till Cancel; _ 6 – Good Till Date
StopPx	99	Stop price (for Stop limit and Take profit orders)
ExpiryTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
ClientID	109	Clients ID. For details on clients ID identification see Administrator's manual, 2.11
NoPartyIDs	453	Number of PartyID groups
→PartyID**	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code; _ 11 – client code; _ 12 – MiFID2 executing trader short code; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker

Field name	Tag	Comments
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
StartTime	6254	Time of activity start
EndTime	6255	Time of activity end
Strategy	6258	Name of algorithm. Value: STOP – STOP algo order
AlgField9	6279	Attribute of cancelling client orders. Valid values: _ 0 – do not cancel; _ 1 – cancel
UseWorkInterval	6280	Attribute of using the activity interval Valid values: _ 0 – do not use; _ 1 – use
AlgField12	6282	Take profit in percent
AlgoParameter1	6315	Stop-limit in percent
AlgoParameter2	6316	Protective spread in percent
AlgoParameter3	6317	Take profit
AlgoParameter4	6318	Type of take profit specifying. Valid values: _ 0 – percent; _ 1 – price currency; _ 2 – not set
AlgoParameter5	6319	Type of stop-limit specifying. Valid values: _ 0 – percent; _ 1 – price currency; _ 2 – not set
SettlDate	64	Settlement date in <YYYYMMDD> format
PegOffsetValue	211	Protective spread. Value by default: 0. The tag is used for stop orders of Take profit type
PegOffsetType	836	Unit of measuring protective spread. Valid values: _ 0 (by default) – price currency; _ 1 – percent

2.9.9 Submit GTD Algo order

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: D
ClOrdID*	11	Unique identifier for Order
HandlInst*	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side*	54	Valid values: _ 1 – buy; _ 2 – sell
OrdType*	40	Type of an order. Valid values: _ 1 – Market; _ 2 – Limit
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Price*	44	Price
Currency	15	Identifies currency used for price
OrderQty*	38	Order quantity. QUIK FIX checks if the value is divisible into lots and convert items into lots
Text	58	Clients comment
TimeInForce	59	Valid values: _ 1 – Good Till Cancel; _ 6 – Good Till Date
ExpiryTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
ClientID	109	Clients ID. For details on clients ID identification see Administrator's manual, 2.11
NoPartyIDs	453	Number of PartyID groups
→ PartyID**	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code; _ 11 – client code; _ 12 – MiFID2 executing trader short code;

Field name	Tag	Comments
		_ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
StartTime	6254	Time of activity start
EndTime	6255	Time of activity end
Strategy	6258	Name of algorithm. Value: GTD – GTD algo order
SettlDate	64	Settlement date in <YYYYMMDD> format
UseWorkInterval	6280	Attribute of activity interval use. Valid values: _ 0 – activity interval is not used; _ 1 – activity interval is used

2.9.10 Transferring risks

Supported tags:

Field name	Tag	Comments
MsgType*	35	Type of message. Value: D
ClOrdID	11	Unique identifier for Order
HandlInst	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
Account	1	Trading account
Side	54	Valid values: _ 1 – buy;

Field name	Tag	Comments
		_ 2 – sell
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
OrderQty	38	Order volume. The value is converted in lots depending on settings

2.10 NewOrderMultileg

2.10.1 Submit order for the exchange of National settlement depositary pays

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AB
ClOrdID*	11	Client's order identifier
Account	1	Trading account code
ClientID	109	Client code
Side*	54	Valid value: B – As Defined
OrdType*	40	Valid value: 1 – Market
OrderQty*	38	The number of the instruments in sell
Text	58	Comment
TimeInForce*	59	Valid value: 1 – Good Till Cancel
ExDestination	100	Class code or market code
NoLegs*	555	Valid value: 2
→LegSecurityID*	602	Identifier of instrument of leg
→LegSecurityIDSource*	603	The type of leg instrument identifier specified in [602] LegSecurityID. Valid values: _ 1 – CUSIP; _ 2 – SEDOL; _ 4 – ISIN-number; _ 5 – RIC code; _ 6 – ISO code; _ 8 – exchange code;

Field name	Tag	Comments
		_ 100 – short name
→LegSide*	624	Direction of a leg instrument trade. Valid values: _ 1 – Buy; _ 2 – Sell

2.11 Order Cancel Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: F
OrigClOrdID	41	Previous value of ClOrdID
OrderID	37	Unique order identifier. Is generated by the Interface (for format see 5.1). It is used for searching an order, if a cancelling / replacing order is not found by OrigClOrdID. It can be used for cancellation / withdrawal order sent via another Interface
ClOrdID*	11	Unique identifier for Order
Side	54	Valid values: _ 1 – buy; _ 2 – sell. The tag is required when canceling an order placed via this instance of the Interface
TransactTime	60	GMT in <YYYYMMDD-HH:MM:SS.sss> format. For example: 20070830-09:38:26.116
OrdType	40	Valid values: _ 1 – Market; _ 2 – Limit; _ 3 – Stop limit at market price; _ 4 – Stop Limit; _ 5 – Market On Close; _ a – Stop price on another instrument; _ b – Stop limit with linked order; _ t – Take profit and Stop limit; _ B – Limit On Close; _ R – Negotiated order; _ T – Stop / Take-profit

Field name	Tag	Comments
OrderQty	38	Order quantity. The tag is required when canceling an order placed via this instance of the Interface
CashOrderQty	152	Algo order volume

2.12 Order Cancel Replace Request

2.12.1 Replacing common orders

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: G
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
ClOrdId*	11	Unique identifier for Order
Currency	15	Identifies currency used for price
HandleInst*	21	Value: 1
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
OrderQty*	38	The tag may include: _ Order quantity. QUIK FIX checks if the value is divisible into lots and convert items into lots; _ Summary quantity
OrdType*	40	Valid values: _ 1 – Market; _ 2 – Limit; _ B – Limit On Close; _ 5 – Market On Close
OrigClOrderID*	41	ClOrdID of replaced order
OrderID	37	Unique order identifier. Is generated by the Interface (for format see 5.1). It is used for searching an order, if a cancelling / replacing order is not found by OrigClOrdID. It can be used for cancellation / withdrawal order sent via another Interface

Field name	Tag	Comments
Price*	44	Price
Side*	54	Valid values: _ 1 – buy; _ 2 – sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed
Text	58	Text response of trading system/Clients comment
TimeInForce	59	Valid values: _ 0 – Day; _ 1 – Good Till Cancel; _ 2 – At The Opening; _ 3 – Immediate Or Cancel; _ 4 – Fill Or Kill; _ 6 – Good Till Date; _ 7 – At The Close; _ X – Extended Hours; _ z – Book or Cancel
TransactTime	60	GMT in <YYYYMMDD-HH:MM:SS.sss> format. For example: 20070830-09:38:26.116
ClientID	109	Clients ID. For details on clients ID identification see Administrator's manual, 2.11
FirmId	5018	Dealers identifier in transaction
MaxFloor	111	Displayed quantity. A nonnull value in the tag is the attribute of Iceberg algo order
ExpireTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
SettlDate	64	Settlement date in <YYYYMMDD> format
CashOrderQty	152	Order value in cash
ReplaceMode	6001	Replacing mode of exchange order. Possible values: _ 1 – direct replacement (if available); _ 0 – emulation of replacement through removal/submission.
NoPartyIDs	453	Number of PartyID groups
→ PartyID**	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code; _ 11 – client code; _ 12 – MiFID2 executing trader short code;

Field name	Tag	Comments
		_ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
OrderOrigination	1724	Value: 5 – DEA
SettlType	63	Settlement code in QUIK system format
ExtRef	5081	External reference

Replacing of previously submitted order using Order Cancel Replace Request message can be performed in two modes:

1. Direct order replacement with a single transaction (tag [6001] ReplaceMode equal to one), is available if such transaction is supported by the Interface. The number, specified by the client in order to replace, is transmitted without changes to transaction.
2. Replacement of order in two stages ([6001] ReplaceMode equal to zero):
   - An existing order is dropped;
   - The order with new parameters is put. The quantity of the new order is calculated according to the formula:

     Qty = Qty1 – Qty2

     Where:

     - Qty – quantity of the order being put to the TS;
     - Qty1 – quantity in tag OrderQty [038] in the received message Order Cancel Replace Request;
     - Qty2 – executed part of the dropped order quantity.

   The formula is true in case of replacing an active or executed order.

   The attempt to replace a dropped order leads to the inquiry rejecting.

2.12.2 Replacing stop orders

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: G
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
ClOrdId*	11	Unique identifier for Order
Currency	15	Instrument currency
HandleInst*	21	Value: 1
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
OrderQty*	38	Tag may include: _ Order quantity. The Interface checks if the value is divisible into lots and convert items into lots; _ Total quantity
OrdType*	40	Valid values: _ 3 – Stop / Stop Loss; _ 4 – Stop Limit; _ T – Stop / Take-profit
OrigClOrderID*	41	ClOrdID of replaced order
OrderID	37	Unique order identifier. It ss generated by the Interface (for format see 5.1). It is used for searching an order, if a cancelling / replacing order is not found by OrigClOrdID. It can be used for cancellation / withdrawal order sent via another Interface
Price*	44	Price
Side*	54	Valid values: _ 1 – buy; _ 2 – sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed
Text	58	Text client from the trading system/ Clients comment
TimeInForce	59	Valid values:

Field name	Tag	Comments
		_ 0 – Day; _ 1 – Good Till Cancel; _ 6 – Good Till Date
TransactTime	60	Date of transaction in <YYYYMMDD-HH:MM:SS.sss> format
StopPx	99	Stop price (for Stop limit and Take profit orders)
ClientID	109	Clients ID. For details on clients ID identification see Administrator's manual, 2.11
FirmId	5018	Dealers identifier in transaction
RefreshQty	6251	Visible quantity (for Iceberg orders sent via algorithmic trading module)
ExecutionStyle	6261	Aggressiveness (for Iceberg algo orders). Valid values: _ 0 – standard mode; _ 1 – Quotes table analysis; _ 2 – Level II quotes table analysis
ExpireTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
SettlDate	64	Settlement date in <YYYYMMDD> format
PegOffsetValue	211	Protective spread. Value by default: 0. The tag is used for stop orders of Take profit type
PegOffsetType	836	Item of protective spread. Valid values: _ 0 (by default) – price currency; _ 1 – percent. The tag is used for stop orders of Take profit type
DiscretionOffsetValue	389	Valid values: _ shift from the minimum price – for buying; _ shift from the maximum price – for selling. Value by default: 0. The tag is used for stop orders of Take profit type
DiscretionOffsetType	842	Shift item. Valid values: _ 0 (by default) – price currency; _ 1 – percent. The tag is used for stop orders of Take profit type
Strategy*	6258	Algorithm name. Valid values: Iceberg – Iceberg algo order
MarketLot	6200	Lot size of instrument
NoPartyIDs	453	Number of PartyID groups
→PartyID**	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code;

Field name	Tag	Comments
		_ 11 – client code; _ 12 – MiFID2 executing trader short code; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person

On stop order replacing if it had not been activated by the moment when request was received than it is cancelled and a new stop order is entered. If stop order had been activated and the order was entered to the TS by the moment when request was received than stop order is not replaced but market order is replaced, which was created by it. At this value of stop price is ignored.

2.12.3 Replacing algo orders of ICEBERG type

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: G
ClOrdId*	11	Unique identifier for Order
HandleInst*	21	Value: 1
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
OrderQty*	38	Total quantity in order

Field name	Tag	Comments
OrigClOrderID*	41	ClOrdID of replaced order
OrderID	37	Unique order identifier. It is generated by the Interface (for format see 5.1). It is used for searching an order, if a cancelling / replacing order is not found by OrigClOrdID. It can be used for cancellation / withdrawal order sent via another Interface
Price*	44	Price
Side	54	Valid values: _ 1 – buy; _ 2 – sell
RefreshQty	6251	Visible quantity (for Iceberg orders sent via algorithmic trading module)
ExecutionStyle	6261	Aggressiveness (for Iceberg algo orders). Valid values: _ 0 – standard mode; _ 1 – Quotes table analysis; _ 2 – Level II quotes table analysis
SettlDate	64	Settlement date in <YYYYMMDD> format
Strategy*	6258	Algorithm name. Valid value: Iceberg – Iceberg algo order
MarketLot	6200	Lot size of instrument
NoPartyIDs	453	Number of PartyID groups
→ PartyID**	448	Valid values depending on the value of PartyRole: _ 3 – MiFID2 client short code; _ 11 – client code; _ 12 – MiFID2 executing trader short code; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity;

Field name	Tag	Comments
		_ 24 – Natural person

> **Unlike replacing standard order, after replacing Iceberg algo order its number in QUIK is not changed, i.e. the current order is modified.**

2.12.4 Replacing OMS orders

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: G
ClOrdId*	11	Client identifier of replacement request
OrigClOrderID*	41	Client identifier of replaced order
OrderID	37	Unique order identifier. Its s generated by the Interface (for format see 5.1). It is used for searching an order, if a cancelling / replacing order is not found by OrigClOrdID. It can be used for cancellation / withdrawal order sent via another Interface
HandleInst*	21	Value: 3 – Manual order
Side*	54	Valid values: _ 1 – buy; _ 2 – sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed)
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Price*	44	Price
Currency	15	Price currency
OrderQty*	38	Quantity
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
ClientID	109	Client identifier
OrdType*	40	Order type

Field name	Tag	Comments
TimeInForce	59	Order's validity period
ExpireTime	126	Date and time of the order's validity period in <YYYYMMDD-HH:MM:SS> format. Only for orders with time in force Good Till Date
SettlType	63	Settlement code in QUIK system format
Memo	5149	Comment to OMS order
SecurityExchange	207	Reference field, returns to client in response messages ExecutionReport
FutSettDate	64	Settlement date
PaymentDate	504	Payment date
DeliveryType	919	Delivery type
CstmOrdType	5057	Extended type of order
Side	54	Direction
Currency	15	Price currency of OMS order
SettlCurrency	120	Settlement currency of OMS order
TradingCode	5133	Client's trading code

2.13 Order Mass Cancel Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: q
ClOrdId	11	Identifier of request for canseling
MassCancelRequestType	530	Valid values: _ 1 – Cancel orders for a security; _ 7 – Cancel all orders
<Instrument>		Set of the fields that describing the instrument. For a detailed description of the <Instrument> component block, see 5.2. Required to fill in when MassCancelRequestType=1
Side	54	Valid values: _ 1 – Buy; _ 2 – Sell

2.14 Execution Report

2.14.1 Common orders

Supported tags:

Field name	Tag	Comments
MsgType	35	Message type. Valid value: 8
HandlInst	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
OrdStatus	39	Order status. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 4 – Canceled; _ 5 – Replaced; _ 6 – Pending Cancel; _ 8 – Rejected; _ 9 – Suspended; _ E – Pending Replace; _ A – Pending New
ExecType	150	Execution report type. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 4 – Canceled; _ 5 – Replace; _ 6 – Pending Cancel; _ 8 – Rejected; _ 9 – Suspended; _ A – Pending New; _ E – Pending Replace; _ F – Trade – partial fill or fill (in protocol version 5.0 while reporting partially or fully executed orders); _ I – Order Status (in protocol version 5.0 for reports sent in response to the OrderStatusRequest and OrderMassStatusRequest messages); _ D – Restated; _ L – Triggered or Activated by System
OrderQty	38	Total quantity in an order
CumQty	14	Executed quantity of an order

Field name	Tag	Comments
LastQty	32	Quantity of a current order execution
LeavesQty	151	Quantity remained in an order
ClOrdID	11	Unique identifier for Order from client request
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2. For FX fixing trades, if MLegFillReportingMode.CcyFixing=0 – an instrument of the first leg trade
Side	54	Valid values: _ 1 – buy; _ 2 – sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed. For SWAP trades if MLegFillReportingMode.Swap=0 – direction of the second leg trade
OrdType	40	Type of order. Valid values: _ 1 – Market; _ 2 – Limit; _ 5 – Market On Close; _ B – Limit On Close; _ H – Forex Previously Quoted; _ q – Quote
AvgPx	6	Average price of a fill. For SWAP, REPO with CCP, futures spread and FX fixing trades if MLegFillReportingMode.Swap=0, MLegFillReportingMode.RepoCpty=0, MLegFillReportingMode.FutSpread=0, MLegFillReportingMode.CcyFixing=0 – price of the first leg trade
ExecRefID	19	Identifier of cancelled execution
ExecTransType	20	Valid values: _ 0 – New; _ 1 – Trade Cancel; _ 3 – Status, for reports sent in response to OrderMassStatusRequest message
OrderID	37	Unique identifier for order. Generated by the Interface (for format see 5.1)
ExecID	17	Unique identifier for trade. Generated by the Interface (for format see 5.1). Value 0 is valid for reports sent in response to the OrderStatusRequest and OrderMassStatusRequest messages

Field name	Tag	Comments
SecondaryExecID	527	Exchange trade identifier in the format <[Class code]-[Trade number]-[B/S]>. It is transmitted if execution is reported in the context of a class other than the exchange trade class
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]
Price	44	Order price. For SWAP, REPO with CCP, futures spread and FX fixing trades if MLegFillReportingMode.Swap=0, MLegFillReportingMode.RepoCpty=0, MLegFillReportingMode.FutSpread=0, MLegFillReportingMode.CcyFixing=0 – price of the first leg trade
LastPx	31	Trade price. For SWAP, REPO with CCP, futures spread and FX fixing trades if MLegFillReportingMode.Swap=0, MLegFillReportingMode.RepoCpty=0, MLegFillReportingMode.FutSpread=0, MLegFillReportingMode.CcyFixing=0 – price of the first leg trade
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Currency	15	Valid values: _ For the **Currency** type classes – order quantity currency; _ For the **Futures** and **Options** type classes – price step currency (if not specified, then the nominal currency); _ For other type classes – price currency (if any); otherwise face value currency
AdditionalTermBondCurrency *****	40006	Bond face value currency [XML]
ClientID	109	Clients ID. For details on client identification see Administrator's manual, 2.11
Text	58	Text reply of the trading system / client comment. For cross trades – text of the diagnostic message
UserText	9906	Users comment
ExecBroker	76	Broker identifier
TradeNum	5001	Valid values: _ Trade number (number of the first leg trade – for FX fixing trades if MLegFillReportingMode.CcyFixing=0); _ Number of an order submitted based on a stop order; _ Number of an order that replaced this order (if OrdStatus=Replaced)

Field name	Tag	Comments
TransactTime	60	Date and time of transaction / non-trade instruction execution in <YYYYMMDD-HH:MM:SS.sss> format
TradeDate	75	Valid values: _ Trade date; _ Settlement date, for trades at FORTS
OrderNum	5002	Order number
AccruedCoupon	5003	Accrued coupon interest
ExValue	5004	Trade volume. For FX fixing trades if MLegFillReportingMode.CcyFixing=0 – volume of the first leg trade
GrossTradeAmt	381	Trade volume. For FX fixing trades if MLegFillReportingMode.CcyFixing=0 – volume of the first leg trade
DealSettlementCode	63	Settlement code of a trade in QUIK format. For FX fixing trades if MLegFillReportingMode.CcyFixing=0 – settlement code of the first leg trade
Commission	12	Trading system commission. For SWAP, futures spread and FX fixing trades if MLegFillReportingMode.Swap=0, MLegFillReportingMode.FutSpread=0, MLegFillReportingMode.CcyFixing=0 – trading system commission for the first leg trade
ClearingCommission	5008	Clearing commission. For SWAP, futures spread and FX fixing trades if MLegFillReportingMode.Swap=0, MLegFillReportingMode.FutSpread=0, MLegFillReportingMode.CcyFixing=0 – clearing commission for the first leg trade
TradingCommission	5009	Commission for trading organization. For SWAP, futures spread and FX fixing trades if MLegFillReportingMode.Swap=0, MLegFillReportingMode.FutSpread=0, MLegFillReportingMode.CcyFixing=0 – commission for trading organization for the first leg trade
ServiceCommission	5010	Commission to the service center. For SWAP, futures spread and FX fixing trades if MLegFillReportingMode.Swap=0, MLegFillReportingMode.FutSpread=0, MLegFillReportingMode.CcyFixing=0 – commission to the service center for the first leg trade
RepoValue / NearTradeValue	5011	For NDM and REPO with CCP – repo amount. For SWAP, futures spread and FX fixing trades if MLegFillReportingMode.Swap=0,

Field name	Tag	Comments
		MLegFillReportingMode.FutSpread=0, MLegFillReportingMode.CcyFixing=0 – volume of the first leg trade
TradeType	5014	Valid values: _ R – Repo; _ N – NDM; _ P – Initial placement; _ T – Standard transaction
CommType	13	Valid value: 3 (absolute)
TimeInForce	59	Valid values: _ 0 – Day; _ 1 – Good Till Cancel; _ 2 – At The Opening; _ 3 – Immediate Or Cancel; _ 4 – Fill Or Kill; _ 6 – Good Till Date; _ 7 – At The Close; _ X – Extended Hours; _ z – Book or Cancel. For market on close auction orders: 0
ExpireTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
FutSettDate	64	Date of trade settlements. For SWAP and FX fixing trades if MLegFillReportingMode.Swap=0 and MLegFillReportingMode.RepoCpty=0 – date of trade settlements for the first leg trade
SecurityExchange	207	Exchange identifier
OrderCapacity	528	Valid values: _ A – Any other trading capacity (AOTC); _ P – Dealing on own account (DEAL); _ R – Matched Principal (MTCH); _ G – Proprietary; _ I – Individual; _ W – Agent for Other Member; _ M – Mixed capacity
TraderID	10039	Login in the TS of the user under which the QUIK gateway connects to the TS
SettlCurrency	120	Trade / order settlement currency
UserID	5015	ID of the QUIK user that submitted the order
StationID	5016	Traders workstation ID

Field name	Tag	Comments
TradeTimeGMT	5017	Shift of the Interface local time relative to GMT
FirmId	5018	Transaction firm ID
RepoStartDiscount	5019	Start discount (in percent)
RepoLowerDiscount	5020	Lower discount (in percent)
RepoUpperDiscount	5021	Upper discount (in percent)
MaturityMonthYear	200	Month and Year of redemption in <YYYYMM> format for reports on execution of futures
MaturityDay	205	Day of redemption date in DD format for reports on execution of futures
ExchangeOrderID	5066	Exchange number of an order
ExchangeTradeID	5022	Exchange number of a trade
MaxFloor	111	Displayed quantity (for exchange order of Icebrg type)
NoPartyIDs	453	Number of PartyID groups
→ PartyID **	448	Valid values depending on the value of PartyRole: _ 1 – Firm code; _ 3 – MiFID2 client short code; _ 11 – Value which was specified in new order; _ 12 – MiFID2 executing trader short code; _ 13 – firm code in an order; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 1 – Executing Firm; _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 13 – Order Origination Firm; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person

Field name	Tag	Comments
LastSpotRate	194	Parent trade price. Transmitted only for SWAP and futures spread trades if MLegFillReportingMode.Swap=0 and MLegFillReportingMode.FutSpread=0
TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
OrderQty2	192	Quantity of the second leg trade. Transmitted only for SWAP and futures spread trades if MLegFillReportingMode.Swap=0 and MLegFillReportingMode.FutSpread=0
SettlDate2	193	Settlement date of the second leg trade. Transmitted only for SWAP and REPO with CCP trades if MLegFillReportingMode.Swap=0 and MLegFillReportingMode.RepoCpty=0
Price2	640	Price of the second leg trade. Transmitted only for SWAP and futures spread trades if MLegFillReportingMode.Swap=0 and MLegFillReportingMode.FutSpread=0
SettlCurrAmt	119	Value of trade in settlement currency
SettlCurrFxRate	155	For trades passed through FXConverter: FX trade price. For other trades: trade cross rate (if transmitted by a corresponding Trading interface)
SettlCurrFxRateSide	5058	Side of the cross rate specified in SettlCurrFxRate [155] in format <currency 1>/<currency 2>
FxConvAvgPxInSettlCurr	5051	Weighted average price of order execution in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvLastPxInSettleCurr	5052	Trade price in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvPriceInSettleCurr	5053	Order price in the settlement currency (the tag is transmitted for trades after currency conversion made with the help of the FxConvertor module)
CumSettlCurAmt	5031	The total volume of the partial execution of the order in the destination currency of FXConverter module if the order is executed by several trades
AvgSettlCurFxRate	5032	The average value of the conversion rate from trades in the destination currency of FXConverter module if the order is executed by several trades
MassStatusReqID	584	Client identifier of the OrderMassStatusRequest message

Field name	Tag	Comments
LastRptRequested	912	Attribute of the last report in the set of messages (Y) sent in response to the OrderMassStatusRequest message
CheckLotFlag	6201	Quantity is presented in lots or pieces. Valid values: _ 0 – disabled; _ 1 – enabled; _ 2 – enabled, check of the instrument lot size is enabled; _ 3 – disabled, check of the instrument lot size is enabled
OrderStatusReqID	790	Client identifier of the status request
OrigClOrdID	41	Client identifier of the order to be cancelled/replaced
RequestID	5060	Client transaction ID in the QUIK server
LastLiquidityInd	851	Attribute of active/passive trade. Valid values: _ 1 – Added Liquidity; _ 2 – Removed Liquidity; _ 3 – Liquidity Routed Out; _ 4 – Auction
MaturityDate	541	Instrument execution date
CashOrderQty	152	Value of order in monetary unit
NetTradePrice	5059	REPO repurchase amount
PossResend	97	Value: Y – on reporting trades by orders cancelled or replaced by OrderID
OrderOrigination	1724	Value: 5 – DEA
OrderRejectReason*****	5093	Order rejection reason [XML]
LastCapacity	29	Valid values: _ 1 – Agent; _ 2 – Cross as agent; _ 3 – Cross as principal; _ 4 – Principal; _ 5 – Riskless principal
LastMarket	30	Execution market
NoTrdRegPublications	2668	Quantity of TrdRegPublication groups
→TrdRegPublicationType	2669	Value: 0 – Pre-trade transparency waiver
→TrdRegPublicationReason	2670	Valid values: _ 0 – NLIQ;

Field name	Tag	Comments
		_ 1 – OLIQ; _ 2 – PRIC; _ 3 – RFPT; _ 4 – ILQD; _ 5 – SIZE
NoOtcPostTradeIndicators	5067	Quantity of TrdRegPublication groups
→OtcPostTradeIndicator	5068	Valid values: _ BENC – Benchmark; _ ACTX – Agency cross; _ LRGS – Large in scale; _ ILQD – Illiquid instrument; _ SIZE – Above specified size; _ CANC – Cancellations; _ AMND – Amendments; _ SDIV – Special dividend; _ RPRI – Price improvement; _ DUPL – Duplicative; _ TNCP – Not contributing to the price discovery process; _ TPAC – Package; _ XFPH – Exchange for Physical
MarketSegmentSymbol	7177	Product ISIN (is transmitted with Eurex orders / trades)
ExecRestatementReason****	378	Valid values: _ 4 – Broker Option; _ 6 – Cancel on Trading Halt [FIX 4.4]; _ 101 – Assign UIDs [XML+]; _ 102 – Assign broker commission [XML+]
NoCommissions****	2639	Number of CommissionDataGrp groups [FIX 5.0 SP2]
→CommissionAmount****	2640	Commission value. For SWAP, futures spread and FX fixing trades if MLegFillReportingMode.Swap=0, MLegFillReportingMode.FutSpread=0, MLegFillReportingMode.CcyFixing=0 – commission for the first leg trade [FIX 5.0 SP2]
→CommissionAmountType****	2641	Commission type. Value: 2 – Broker [FIX 5.0 SP2]
NoOrders*****	73	Number of RelatedOrderGrp groups [XML]
→RelatedOrderID*****	2887	Identifier of a related order in format <[Registration session date]-[Class code]-[Order number]>.

Field name	Tag	Comments
		For offering orders – identifier of an exchange order submitted by the Bookbuilding module to the TS [XML]
→RelatedOrderIDSource *****	2888	Identifier source. Value is 1 – Order identifier [XML]
→RelatedOrderQty*****	2889	For offering orders – quantity in an exchange order in pieces [XML]
SpbOutOfBookIndicator *****	5111	Value is Y – an order is placed in an external liquidity pool (SPB) [XML]
NoLegs****	555	Number of trade legs (number of LegExecGrp groups). This group is transmitted only for SWAP, REPO with CCP, futures spread and FX fixing trades if MLegFillReportingMode.Swap=1, MLegFillReportingMode.RepoCpty=1, MLegFillReportingMode.FutSpread=1, MLegFillReportingMode.CcyFixing=1 [FIX 4.4+]
→LegSymbol****	600	Short name of a leg instrument [FIX 4.4+]
→LegSecurityID****	602	Identifier of a leg instrument [FIX 4.4+]
→LegSecurityIDSource****	603	Type of of a leg instrument identifier specified in LegSecurityID [602]. [FIX 4.4+]
→LegNumber *****	1152	Leg number [XML]
→LegSide****	624	Trade side of a leg instrument. [FIX 4.4+]. Valid values: _ 1 – Buy; _ 2 – Sell
→LegPrice****	566	Leg order price. Transmitted if order number of a leg trade differs from order number of a parent trade [FIX 4.4+]
→LegOrderQty****	685	Leg order quantity. Transmitted if order number of a leg trade differs from order number of a parent trade [FIX 4.4+]
→LegSettlType****	587	Settlement code of a leg trade [FIX 4.4+]
→LegSettlDate****	588	Settlement date of a leg trade [FIX 4.4+]
→LegLastPx****	637	Leg trade price [FIX 4.4+]
→LegGrossTradeAmt****	1075	Leg trade volume [FIX 4.4+]
→LegLastQty****	1418	Leg trade quantity [FIX 5.0+]

Field name	Tag	Comments
→LegCommission *****	5125	Trading system commission for a leg trade [XML]
→LegClearingCommission *****	5126	Clearing commission for a leg trade [XML]
→LegTradingCommission *****	5127	Commission for trading organization for a leg trade [XML]
→LegServiceCommission *****	5128	Commission to the service center for a leg trade [XML]
→LegBrokerCommission *****	5129	Brokerage commission for a leg trade [XML]
→LegTradeNumber *****	5130	Leg trade number in QUIK [XML]
→LegOrderNumber *****	5131	Leg order number in QUIK. Transmitted if order number of a leg trade differs from order number of a parent trade [XML]
BenchmarkCurveName ****	221	Indicator name [FIX 4.4+]
QtyType ****	854	Type of quantity setting. Transmitted only for derivatives. [FIX 4.4+]. Valid values: _ 1 – Contracts (for futures and options)
ContractMultiplier ****	231	Multiplier to convert the number of contracts to the number of units of the underlying asset. Transmitted only for derivatives [FIX 4.2+]
ExtRef*****	5081	External reference [XML+]
OrderRestrictions****	529	Market maker order attribute. [FIX4.4+]. Valid value: _ 5 – Acting as Market Maker or Specialist in the security
LinkedTradeNumber*****	5150	Linked trade number [XML+]
OrdRejReason****	103	Error code for order rejection [FIX4.2+]
OrdRejSource*****	5152	Source of the error which code is specified in the tag OrdRejReason [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway
ComplianceText*****	2404	Text from reply to order registration transaction [XML+]

**** [FIX <N>] – tag is available for the FIX protocol version <N> or newer (if the version is specified) or if it is allowed in the scheme.

***** – tag is available if it is allowed in the scheme.

2.14.2 Negotiated orders

Supported tags:

Field name	Tag	Comments
MsgType	35	Message type. Valid value: 8
HandlInst	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
OrdStatus	39	Order status. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replaced; _ 6 – Pending Cancel; _ 8 – Rejected; _ E – Pending Replace; _ A – Pending New
ExecType	150	Execution report type. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replace; _ 6 – Pending Cancel; _ 8 – Rejected; _ A – Pending New; _ C – Expired (for OMS orders); _ D – Restated (for OMS orders); _ E – Pending Replace; _ F – Trade – partial fill or fill (in protocol version 5.0 while reporting partially or fully executed orders); _ I – Order Status (in protocol version 5.0 for reports sent in response

Field name	Tag	Comments
		to OrderStatusRequest and OrderMassStatusRequest messages)
OrderQty	38	Total quantity in an order
CumQty	14	Executed quantity of an order
LastQty	32	Quantity of a current order execution
LeavesQty	151	Quantity remained in an order
ClOrdID	11	Unique identifier for Order from clients request
Symbol	55	Ticker symbol. Common, human understood representation of the security
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side	54	Valid values: _ 1 – buy; _ 2 – sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed. For calendar spread trades: direction of the parent trade
OrdType	40	Type of order. Valid values: _ R – Negotiated order; _ M – REPO-M order
AvgPx	6	Calculated average price of all fills on this order. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
ExecTransType	20	Value: 0 – New. Contains the value 3 for reports sent in response to OrderMassStatusRequest message
OrderID	37	Unique identifier for order. Generated by the Interface (for format see 5.1)
ExecID	17	Unique identifier for trade. Generated by the Interface (for format see 5.1). Value 0 is valid for reports sent in response to OrderStatusRequest and OrderMassStatusRequest messages
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]

Field name	Tag	Comments
Price	44	Order price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part. Value for STOP algo orders: 0
LastPx	31	Trade price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Currency	15	Valid values: _ For the Currency type classes – order quantity currency; _ For the **Futures** and **Options** type classes – the Price step currency (if not specified, then the nominal currency); _ For other type classes – price currency (if any); otherwise face value currency
AdditionalTermBondCurrency ****	40006	Bond face value currency [XML]
ClientID	109	Clients ID. For details on clients identification see Administrator's manual, 2.11
Text	58	Text reply of the trading system / clients comment. For cross trades – text of the diagnostic message
UserText	9906	Users comment
ExecBroker	76	Broker identifier
TradeNum	5001	Valid values: _ Trade number; _ Number of new order, created by stop order; _ Number of new order, if OrdStatus=Replaced
TransactTime	60	Date and time of transaction / non-trade instruction execution in <YYYYMMDD-HH:MM:SS.sss> format
TradeDate	75	Valid values: _ Trade date; _ Settlement date, for trades at FORTS
OrderNum	5002	Valid values: _ Order / non-trade instruction number; _ Number of replaced (old) order (if OrdStatus=Replaced)
AccruedCoupon	5003	Accrued coupon interest

Field name	Tag	Comments
ExValue	5004	Transaction value
DealSettlementCode	63	Settlement code in QUIK system format
Commission	12	Commission
RepoRate	5006	REPO rate
Price2	5007	Buyback price for the second REPO part
ClearingCommission	5008	Valid values: _ Depository commission (for non-trade instructions); _ Commission for clearing
TradingCommission	5009	Commission for organization of trading session
ServiceCommission	5010	Valid values: _ Commission for cash issue (for non-tradeinstructions); _ Commission to service center
RepoValue / NearTradeValue	5011	REPO value on current date / Value of the first part of SWAP trade For calendar spread trades: volume of the first trade part
RepoTerm	5012	REPO term
Repo2Value	5013	Volume of REPO buyback trade
TradeType	5014	Valid values: _ R – Repo; _ N – NDM; _ P – Initial placement; _ T – Standard transaction
CommType	13	Valid value: 3 (absolute)
TimeInForce	59	Valid value: 0 – Day
ExpireTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
FutSettDate	64	Time of execution. For trades in REPO with CCP mode: price of the first trade part
SecurityExchange	207	Exchange identifier
SecurityType	167	Instrument type
TraderID	10039	Login in the TS of the user under which the QUIK gateway connects to the TS

Field name	Tag	Comments
SettlCurrency	120	Trade / order settlement currency
UserID	5015	ID of the QUIK user that submitted the order
StationID	5016	Traders workstation ID
TradeTimeGMT	5017	Shift of the Interface local time relative to GMT
FirmId	5018	Transaction firm ID
ContraBroker	375	Contra brokers code (only for two-sided orders [40=R])
ComplianceID	376	Reference (only for two-sided orders [40=R])
RepoStartDiscount	5019	Start discount (in percent)
RepoLowerDiscount	5020	Lower discount (in percent)
RepoUpperDiscount	5021	Upper discount (in percent)
MaturityMonthYear	200	Month and Year of redemtion in <YYYYMM> format for reports on execution of futures
MaturityDay	205	Day of redemtion date in DD format for reports on execution of futures
ExchangeOrderID	5066	Exchange number of an order
ExchangeTradeID	5022	Exchange number of a trade
RepoActivationDate	5023	Activation date of the negotiated REPO order
NoPartyIDs	453	Number of PartyID groups
→ PartyID **	448	Valid values depending on the PartyRole value: _ 1 – firm code; _ 3 – MiFID2 client short code; _ 11 – value specified when submitting an order; _ 12 – MiFID2 executing trader short code; _ 13 – firm code in an order; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 1 – Executing Firm; _ 3 – ClientID;

Field name	Tag	Comments
		_ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 13 – Order Origination Firm; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
LastSpotRate	194	Conversion cross-rate. For calendar spread trades: price of a parent trade
TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
OrderQty2	192	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlDate2	193	For SWAP-trades: settlement date of a Far trade. For REPO with CCP trades: settlement date of the second trade part
Price2	640	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
MassStatusReqID	584	Client identifier of the OrderMassStatusRequest message
LastRptRequested	912	Attribute of the last report in the set of messages (Y) sent in response to the OrderMassStatusRequest message
CheckLotFlag	6201	Quantity is presented in lots or pieces. Valid values: _ 0 – disabled; _ 1 – enabled; _ 2 – enabled, check of the instrument lot size is enabled; _ 3 – disabled, check of the instrument lot size is enabled
OrderStatusReqID	790	Client identifier of the status request
OrigClOrdID	41	Client identifier of the order to be cancelled/replaced
RequestID	5060	Client transaction ID in the QUIK server
LastLiquidityInd	851	Attribute of active/passive trade. Valid values: _ 1 – Added Liquidity; _ 2 – Removed Liquidity; _ 3 – Liquidity Routed Out; _ 4 – Auction

Field name	Tag	Comments
MaturityDate	541	Instrument execution date
CashOrderQty	152	Value of order in monetary unit
PossResend	97	Value: Y – on reporting trades by orders cancelled or replaced by OrderID
LastCapacity	29	Valid values: _ 1 – Agent; _ 2 – Cross as agent; _ 3 – Cross as principal; _ 4 – Principal; _ 5 – Riskless principal
LastMarket	30	Execution market
NoTrdRegPublications	2668	Quantity of TrdRegPublication groups
→TrdRegPublicationType	2669	Value: 0 – Pre-trade transparency waiver
→TrdRegPublicationReason	2670	Valid values: _ 0 – NLIQ; _ 1 – OLIQ; _ 2 – PRIC; _ 3 – RFPT; _ 4 – ILQD; _ 5 – SIZE
NoOtcPostTradeIndicators	5067	Quantity of TrdRegPublication groups
→OtcPostTradeIndicator	5068	Valid values: _ BENC – Benchmark; _ ACTX – Agency cross; _ LRGS – Large in scale; _ ILQD – Illiquid instrument; _ SIZE – Above specified size; _ CANC – Cancellations; _ AMND – Amendments; _ SDIV – Special dividend; _ RPRI – Price improvement; _ DUPL – Duplicative; _ TNCP – Not contributing to the price discovery process; _ TPAC – Package; _ XFPH – Exchange for Physical
NoCommissions***	2639	Number of CommissionDataGrp groups [FIX 5.0 SP2]
→CommissionAmount***	2640	Commission value [FIX 5.0 SP2]

Field name	Tag	Comments
→CommissionAmountType***	2641	Commission type. Value: 2 – Broker [FIX 5.0 SP2]
BenchmarkCurveName ***	221	Indicator name [FIX 4.4+]
LinkedTradeNumber****	5150	Linked trade number [XML+]
ExtRef****	5081	External reference [XML+]
OrdRejReason***	103	Error code for order rejection [FIX4.2+]
OrdRejSource****	5152	Source of the error which code is specified in the tag OrdRejReason [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway
ExecRestatementReason	378	Valid values: _ 4 – Broker Option; _ 6 – Cancel on Trading halt; _ 101 – Assign UIDs [XML+]; _ 102 – Assign broker commission [XML+]
ComplianceText*****	2404	Text from reply to order registration transaction [XML+]

*** [FIX <N>] – tag is available for the FIX protocol version <N> or newer or if it is allowed in the scheme.

**** – tag is available if it is allowed in the scheme.

2.14.3 Stop orders

Supported tags:

Field name	Tag	Comments
MsgType	35	Message type. Valid value: 8
HandlInst	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
OrdStatus	39	Order status. Valid values: _ 0 – New; _ 1 – Partially Fill;

Field name	Tag	Comments
		_ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replaced; _ 6 – Pending Cancel; _ 8 – Rejected; _ E – Pending Replace; _ A – Pending New
ExecType	150	Execution report type. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replace; _ 6 – Pending Cancel; _ 8 – Rejected; _ A – Pending New; _ C – Expired (for OMS orders); _ D – Restated (for OMS orders); _ E – Pending Replace; _ F – Trade – partial fill or fill (in protocol version 5.0 while reporting partially or fully executed orders); _ I – Order Status (in protocol version 5.0 for reports sent in response to the OrderStatusRequest and OrderMassStatusRequest messages); _ L – Triggered or Activated by System; _ D – Restated
ExecRestatementReason	378	Valid values: _ 4 – Broker Option; _ 6 – Cancel on Trading halt; _ 100 – number of linked order is assigned; _ 101 – Assign UIDs [XML+]; _ 102 – Assign broker commission [XML+]. It is transmitted for stop orders of Stop Limit With linked order type
OrderQty	38	Total quantity in an order
CumQty	14	Executed quantity of an order
LastQty	32	Quantity of a current order execution
LeavesQty	151	Quantity remained in an order
ClOrdID	11	Unique identifier for Order from client's request

Field name	Tag	Comments
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side	54	Valid values: _ 1 – buy; _ 2 – sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed. For calendar spread trades: direction of the parent trade
OrdType	40	Type of order. Valid values: _ 3 – Stop / Stop Loss; _ 4 – Stop Limit; _ T – Stop / Take-profit; _ b – Stop Limit With linked order; _ a – Stop price of another instrument; _ t – Take profit and stop limit
AvgPx	6	Calculated average price of all fills on this order. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
ExecTransType	20	Valid value: 0 – New. Contains the value 3 for reports sent in response to OrderMassStatusRequest message
OrderID	37	Unique identifier for order / linked stop order. Generated by the Interface (for format see 5.1)
RefOrderID	1080	Unique identifier for stop order / linked order. Format: <[Stop order / linked order registration date]-[Class code]-[Stop order / linked order number]>, where: _ [Stop order / linked order registration date] is the date of Stop order / linked order registration in the current session, even if the local time zone of the computer, on which the Interface is installed, shifted to the next date on order registration. The format of the date is <YYMMDD>
ExecID	17	Unique identifier for trade. Generated by the Interface (for format see 5.1). Value 0 is valid for reports sent in response to OrderStatusRequest and OrderMassStatusRequest messages
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]

Field name	Tag	Comments
Price	44	Order price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part. Value for STOP algo orders: 0
LastPx	31	Trade price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Currency	15	Valid values: _ For the Currency type classes – order quantity currency; _ For the **Futures** and **Options** type classes – Price step currency (if not specified, then the nominal currency); _ For other type classes – price currency (if any); otherwise face value currency
AdditionalTermBondCurrency *****	40006	Bond face value currency [XML]
ClientID	109	Clients ID. For details on clients identification see Administrator's manual, 2.11
Text	58	Text reply of the trading system / clients comment. For cross trades – text of the diagnostic message
UserText	9906	Users comment
ExecBroker	76	Broker identifier
TradeNum	5001	Valid values: _ Trade number; _ Number of new order, created by stop order if ExecType="Triggered or Activated by System"; _ Number of new order, if OrdStatus=Replaced
WorkingIndicator	636	Used for Stop orders. Valid values: _ Y – the order is in trade (in fact it means that the condition of stop order arrived and the order was successfully sent to the trading system or executed); _ N – the order is accepted, but is not in trade yet
StopPx	99	Stop price (for Stop limit and Take profit orders)
TransactTime	60	Date and time of transaction / non-trade instruction execution in <YYYYMMDD-HH:MM:SS.sss> format

Field name	Tag	Comments
TradeDate	75	Valid values: _ Trade date; _ Settlement date, for trades at FORTS
OrderNum	5002	Valid values: _ Stop order / order number, that was submitted on the basis of the stop-order; _ Number of replaced (old) order (if OrdStatus=Replaced)
AccruedCoupon	5003	Accrued coupon interest
ExValue	5004	Transaction value
DealSettlementCode	63	Settlement code in QUIK system format
Commission	12	Commission
ClearingCommission	5008	Valid values: _ Depository commission (for non-trade instructions); _ Commission for clearing
TradingCommission	5009	Commission for organization of trading session
ServiceCommission	5010	Valid values: _ Commission for cash issue (for non-trade instructions); _ Commission to service center
RepoValue / NearTradeValue	5011	REPO value on current date / Value of the first part of SWAP trade For calendar spread trades: volume of the first trade part
TradeType	5014	Valid values: _ R – Repo; _ N – NDM; _ P – Initial placement; _ T – Standard transaction
CommType	13	Valid value: 3 (absolute)
TimeInForce	59	Valid values: _ 0 – Day; _ 1 – Good Till Cancel; _ 6 – Good Till Date For market on close auction orders: 0
ExpireTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format

Field name	Tag	Comments
FutSettDate	64	Time of execution. For trades in REPO with CCP mode: price of the first trade part
SecurityExchange	207	Exchange identifier
SecurityType	167	Instrument type
OrderCapacity	528	Valid values: _ A – Any other trading capacity (AOTC); _ P – Dealing on own account (DEAL); _ R – Matched Principal (MTCH); _ G – Proprietary; _ I – Individual; _ W – Agent for Other Member; _ M – Mixed capacity
TraderID	10039	Login in the TS of the user under which the QUIK gateway connects to the TS
SettlCurrency	120	Trade / order settlement currency
UserID	5015	ID of the QUIK user that submitted the order
StationID	5016	Traders workstation ID
TradeTimeGMT	5017	Shift of the Interface local time relative to GMT
FirmId	5018	Transaction firm ID
RepoStartDiscount	5019	Start discount (in percent)
RepoLowerDiscount	5020	Lower discount (in percent)
RepoUpperDiscount	5021	Upper discount (in percent)
MaturityMonthYear	200	Month and Year of redemtion in <YYYYMM> format for reports on execution of futures
MaturityDay	205	Day of redemtion date in DD format for reports on execution of futures
ExchangeOrderID	5066	Exchange number of an order
ExchangeTradeID	5022	Exchange number of a trade
NoPartyIDs	453	Number of PartyID groups
→ PartyID **	448	Valid values depending on the PartyRole value: _ 1 – firm code _ 3 – MiFID2 client short code; _ 11 – value specified when submitting an order; _ 12 – MiFID2 executing trader short code;

Field name	Tag	Comments
		_ 13 – firm code in an order; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 1 – Executing Firm; _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 13 – Order Origination Firm; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
LastSpotRate	194	Conversion cross-rate. For calendar spread trades: price of a parent trade
TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
OrderQty2	192	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlDate2	193	For SWAP-trades: settlement date of a Far trade. For REPO with CCP trades: settlement date of the second trade part
Price2	640	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlCurrAmt	119	Value of trade in the settlement currency
SettlCurrFxRate	155	For trades passed through FXConverter: FX trade price. For other trades: trade cross rate (if transmitted by a corresponding Trading interface)
SettlCurrFxRateSide	5058	Side of the cross rate specified in SettlCurrFxRate [155] in format <currency 1>/<currency 2>

Field name	Tag	Comments
PegOffsetValue	211	Protective spread. Value by default: 0. The tag is used for stop orders of Take profit type
PegOffsetType	836	Item of protective spread. Valid values: _ 0 (by default) – price currency; _ 1 – percent. The tag is used for stop orders of Take profit type
DiscretionOffsetValue	389	Valid values: _ shift from the minimum price – for buying; _ shift from the maximum price – for selling. Value by default: 0. The tag is used for stop orders of Take profit type
DiscretionOffsetType	842	Shift item. Valid values: _ 0 (by default) – price currency; _ 1 – percent. The tag is used for stop orders of Take profit type
FxConvAvgPxInSettlCurr	5051	Weighted average price of order execution in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvLastPxInSettleCurr	5052	Trade price in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvPriceInSettleCurr	5053	Order price in the settlement currency (the tag is transmitted for trades after currency conversion made with the help of the FxConvertor module)
CumSettlCurAmt	5031	The total volume of the partial execution of the order in the destination currency of FXConverter module if the order is executed by several trades
AvgSettlCurFxRate	5032	The average value of the conversion rate from trades in the destination currency of FXConverter module if the order is executed by several trades
MassStatusReqID	584	Client identifier of the OrderMassStatusRequest message
LastRptRequested	912	Attribute of the last report in the set of messages (Y) sent in response to the OrderMassStatusRequest message
CheckLotFlag	6201	Quantity is presented in lots or pieces. Valid values: _ 0 – disabled; _ 1 – enabled; _ 2 – enabled, check of the instrument lot size is enabled;

Field name	Tag	Comments
		_ 3 – disabled, check of the instrument lot size is enabled
OrderStatusReqID	790	Client identifier of the status request
OrderRejectReason*****	5093	Order rejection reason [XML]
OrigClOrdID	41	Client identifier of the order to be cancelled/replaced
RequestID	5060	Client transaction ID in the QUIK server
LastLiquidityInd	851	Attribute of active/passive trade. Valid values: _ 1 – Added Liquidity; _ 2 – Removed Liquidity; _ 3 – Liquidity Routed Out; _ 4 – Auction
MaturityDate	541	Instrument execution date
CashOrderQty	152	Volume of order in monetary unit
PossResend	97	Value: Y – on reporting trades by orders cancelled or replaced by OrderID
LastCapacity	29	Valid values: _ 1 – Agent; _ 2 – Cross as agent; _ 3 – Cross as principal; _ 4 – Principal; _ 5 – Riskless principal
LastMarket	30	Execution market
NoTrdRegPublications	2668	Quantity of TrdRegPublication groups
→TrdRegPublicationType	2669	Value: 0 – Pre-trade transparency waiver
→TrdRegPublicationReason	2670	Valid values: _ 0 – NLIQ; _ 1 – OLIQ; _ 2 – PRIC; _ 3 – RFPT; _ 4 – ILQD; _ 5 – SIZE
NoOtcPostTradeIndicators	5067	Quantity of TrdRegPublication groups
→OtcPostTradeIndicator	5068	Valid values: _ BENC – Benchmark; _ ACTX – Agency cross; _ LRGS – Large in scale;

Field name	Tag	Comments
		_ ILQD – Illiquid instrument; _ SIZE – Above specified size; _ CANC – Cancellations; _ AMND – Amendments; _ SDIV – Special dividend; _ RPRI – Price improvement; _ DUPL – Duplicative; _ TNCP – Not contributing to the price discovery process; _ TPAC – Package; _ XFPH – Exchange for Physical
NoCommissions****	2639	Number of CommissionDataGrp groups [FIX 5.0 SP2]
→CommissionAmount****	2640	Commission value [FIX 5.0 SP2]
→CommissionAmountType****	2641	Commission type. Value: 2 – Broker [FIX 5.0 SP2]
OrderRestrictions****	529	Market maker order attribute. [FIX4.4+]. Valid value: _ 5 – Acting as Market Maker or Specialist in the security
LinkedTradeNumber*****	5150	Linked trade number [XML+]
OrdRejReason****	103	Error code for order rejection [FIX4.2+]
OrdRejSource*****	5152	Source of the error which code is specified in the tag OrdRejReason [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway
TakeProfitPx*****	5080	Take profit price. It is used for stop orders of Take profit and stop limit type [XML+]
ComplianceText*****	2404	Text from reply to order registration transaction [XML+]

**** [FIX <N>] – the tag is available for the FIX protocol version <N> or newer or if it is allowed in the scheme.

***** – the tag is available if it is allowed in the scheme.

2.14.4 OMS orders

Supported tags:

Field name	Tag	Comments
MsgType	35	Message type. Valid value: 8
ClOrdID	11	Client identifier for Order. Client identifier ofrequest to cancel/replace order
HandlInst	21	Value: 3 – Manual order
OrigClOrdID	41	Client identifier of the order to be cancelled/replaced
OrderID	37	Onique identifier of OMS order in format <[Class code]-[Order number]> (for format see 5.1)
SecondaryOrderID	198	Revision of OMS order. The maximum permissible length of the identifier is 10 characters
ExecID	17	Unique identifier. It is generated by the Interface (for format see 5.1)
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]
ExecRefID	19	Identifier of cancelled/replaced execution
SecondaryExecID	527	Identifier of an exchange/OTC trade in format <[Class code]-[Trade number]-[B/S]>
ExecRestatementReason	378	Valid value: 4 – Broker option
OrdStatus	39	Order status. Valid values: _ 0 – New; _ 1 – Partially Filled; _ 2 – Filled; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replaced; _ 6 – Pending Cancel; _ 8 – Rejected; _ A – Pending New; _ C – Expired; _ E – Pending Replace
ExecType	150	Execution report type. Valid values: _ 0 – New; _ 1 – Partially Filled; _ 2 – Filled; _ 3 – Done For Day; _ 4 – Cancel; _ 5 – Replace; _ 6 – Pending Cancel;

Field name	Tag	Comments
		_ 8 – Rejected; _ A – Pending New; _ C – Expired; _ D – Restate; _ E – Pending Replace
ExecTransType	20	Valid values: _ 0 – New; _ 1 – Trade Cancel; _ 2 – Trade Correct; _ 3 – Status
Side	54	Valid values: _ 1 – buy; _ 2 – sell; _ 5 – Sell short; _ 6 – Sell short exempt; _ H – Sell undisclosed
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
OrdType	40	Type of order. Valid values: _ 1 – Market; _ 2 – Limit; _ 5 – Market On Close; _ B – Limit On Close. When you specify "5" or "B" – tag [59] TimeInForce should be absent or have the value "0"
Price	44	Gross-price of OMS-order in currency specified in tag [15] Currency
Currency	15	Price currency of OMS-order
GrossTradeAmt	381	Trade volume in the currency specified in the [15] Currency tag
OrderQty	38	Total quantity in an order
CumQty	14	Executed quantity of an order
LeavesQty	151	Quantity remained in an order
AvgCrossRate	5155	Weighted average cross-rate execution of an OMS order
AvgCrossRateSide	5070	Direction of the AvgCrossRate weighted average cross rate in <Currency 1>/<Currency 2> format
AvgCrossRateCalc	5159	Calculation which must be made between the total volume of reported trades in the price currency and weighted average cross-rate, specified in tag [5155] AvgCrossRate, to calculate the total executed volume in the settlement currency. Valid values:

Field name	Tag	Comments
		_ M – multiplication; _ D – division
SettlCurrFxRate	155	Cross rate for a trade
CrossRateSide	5058	Direction of cross-rate of SettlCurrFxRate trade
AvgPx	6	Weighted average price of execution in currency specified in tag [15] Currency
AvgPxInSettleCurrency	5156	Weighted average price of execution in OMS order settlement currency
LastPx	31	Price of execution in currency specified in tag [15] Currency
LastShares	32	Quantity of a current order execution
ExValue	5004	Transaction value
LastPxInSettleCurrency	5054	Price of execution in currency specified in tag [120] SettlCurrency
LastPxInTradeCurrency	5158	Price of execution in currency specified in tag [5157] TradeCurrency
TradeDate	75	Trade session date
Account	1	Trading account
ClientID	109	Client identifier
TimeInForce	59	Order's validity period. Valid values: _ 0 – Day; _ 1 – Good Till Cancel; _ 2 – At The Opening; _ 6 – Good Till Date; _ 7 – At The Close
ExpireTime	126	Date and time of order's validity period in <YYYYMMDD-HH:MM:SS> format. Only for orders with time in force Good Till Date
SettleType	63	Settlement code in QUIK system format
SettleDate	64	Settlement date
SettlCurrency	120	Settlement currency of OMS order
TrdSettlCurrency	1245	Trade settlement currency
SettlCurrAmt	119	Trade volume calculated in settlement currency
SettlCurrFxRateCalc	156	Mathematical operation that must be done with trade volume in the price currency GrossTradeAmt [381] and cross rate SettlCurrFxRate [155] to calculate the volume in the settlement currency SettlCurrency [120]. Valid values: _ M – multiplication;

Field name	Tag	Comments
		_ D – division
LastMkt	30	Venue where execution occurs
TradeCurrency	5157	Currency of the exchange execution
Commission	12	Commission amount. Value transmission depends on the CommissionReporting setting in [OMS] section (see Administrator's manual)
CommType	13	Type of commission. Valid values: _ 1 – Per Unit; _ 2 – Percent; _ 3 – Absolute; _ 7 – Base points. Value transmission depends on the CommissionReporting setting in [OMS] section (see Administrator's manual)
UserSales	7672	Attribute of executing an operation with participation of Sales. Valid values: _ 1 – Sales participates; _ 2 – Sales does not participate
Memo	5149	Users comment for OMS order
Text	58	Text response of Interface / OMS Manager module to client requests to submit/cancel/replace orders
SecurityExchange	207	Reference field returned to client from New Order Single message
SecurityType	167	Instrument type
TransactTime	60	Date and time event in <YYYYMMDD-HH:MM:SS.sss> format
TradeTimeGMT	5017	Shift of the Interface local time relative to GMT
OrderStatusReqID	790	Client identifier from OrderStatusRequest message
MassStatusReqID	584	Client identifier from OrderMassStatusRequest message
RequestID	5060	Client transaction ID in the QUIK server
LastLiquidityInd	851	Attribute of an active/passive trade. Valid values: _ 1 – Added Liquidity; _ 2 – Removed Liquidity; _ 3 – Liquidity Routed Out; _ 4 – Auction
LastRptRequested	912	Attribute of the last message (Y) sent in response to the OrderMassStatusRequest message
AccruedInterestAmt	159	Accrued coupon interest

Field name	Tag	Comments
PaymentDate	504	Payment date
DeliveryType	919	Delivery type
CstmOrdType	5057	Extended type of order
PossResend	97	Value: Y – on reporting trades by orders cancelled or replaced by OrderID
OMSFreeText1	5061	A free text of the length up to 64 symbols
OMSFreeText2	5062	
OMSFreeText3	5063	
OMSFreeText4	5064	
OMSFreeText5	5065	
LastCapacity	29	Valid values: _ 1 – Agent; _ 2 – Cross as agent; _ 3 – Cross as principal; _ 4 – Principal; _ 5 – Riskless principal
LastMarket	30	Execution market
NoTrdRegPublications	2668	Quantity of TrdRegPublication groups
→TrdRegPublicationType	2669	Value: 0 – Pre-trade transparency waiver
→TrdRegPublicationReason	2670	Valid values: _ 0 – NLIQ; _ 1 – OLIQ; _ 2 – PRIC; _ 3 – RFPT; _ 4 – ILQD; _ 5 – SIZE
NoOtcPostTradeIndicators	5067	Quantity of TrdRegPublication groups
→OtcPostTradeIndicator	5068	Valid values: _ BENC – Benchmark; _ ACTX – Agency cross; _ LRGS – Large in scale; _ ILQD – Illiquid instrument; _ SIZE – Above specified size; _ CANC – Cancellations; _ AMND – Amendments; _ SDIV – Special dividend;

Field name	Tag	Comments
		_ RPRI – Price improvement; _ DUPL – Duplicative; _ TNCP – Not contributing to the price discovery process; _ TPAC – Package; _ XFPH – Exchange for Physical
CrossRateManualIndicator	5069	The tag exists and is equal to 1, if OMS order cross rate was specified manually at its finishing
CrossRateOMS	5071	Cross rate between trade currency and OMS order currency
CrossRateOMSSide	5072	The direction of the CrossRateOMS cross rate in a string format: <CUR1>/<CUR2>
CancelReasonCode	5134	Cancellation reason code
CancelReason	5135	Cancellation reason
OrdRejReason****	103	Error code for order rejection [FIX4.2+]
OrdRejSource*****	5152	Source of the error which code is specified in the tag OrdRejReason [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway
ComplianceText*****	2404	Text from reply to order registration transaction [XML+]

**** [FIX <N>] – the tag is only available for the FIX protocol version <N> or newer or if it is allowed in the scheme.

***** – the tag is available if it is allowed in the scheme.

2.14.5 Algo orders of ICEBERG type

Supported tags:

Field name	Tag	Comments
MsgType	35	Message type. Valid value: 8
HandlInst	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
OrdStatus	39	Order status. Valid values: _ 0 – New;

Field name	Tag	Comments
		_ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replaced; _ 6 – Pending Cancel; _ 8 – Rejected; _ E – Pending Replace; _ A – Pending New; _ C – Expired (if an algo order is received in executed status but Execution Report was not sent due to the lack of trades at full quantity/volume of an algo order)
ExecType	150	Execution report type. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replace; _ 6 – Pending Cancel; _ 8 – Rejected; _ A – Pending New; _ C – Expired (for OMS orders); _ D – Restated (for OMS orders); _ E – Pending Replace; _ F – Trade – partial fill or fill (in protocol version 5.0 while reporting partially or fully executed orders); _ I – Order Status (in protocol version 5.0 for reports sent in response to the OrderStatusRequest and OrderMassStatusRequest messages); _ C – Expired (if an algo order is received in executed status but Execution Report was not sent due to the lack of trades at full quantity/volume of an algo order)
OrderQty	38	Total quantity in an order
CumQty	14	Executed quantity of an order
LastQty	32	Quantity of a current order execution
LeavesQty	151	Quantity remained in an order
ClOrdID	11	Unique identifier for Order from clients request

Field name	Tag	Comments
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side	54	Valid values: _ 1 – buy; _ 2 – sell. For calendar spread trades: direction of the parent trade
AvgPx	6	Calculated average price of all fills on this order. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
ExecTransType	20	Valid value: 0 – New. Contains the value 3 for reports sent in response to OrderMassStatusRequest message
OrderID	37	Unique identifier for order. Generated by the Interface (for format see 5.1)
ExecID	17	Unique identifier for trade. Generated by the Interface (for format see 5.1). Value 0 is valid for reports sent in response to OrderStatusRequest and OrderMassStatusRequest messages
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]
Price	44	Order price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part. Value for STOP algo orders: 0
LastPx	31	Trade price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
OrdType	40	Type of order. Valid values: _ 1 – Market; _ 2 – Limit
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Currency	15	Valid values: _ For the Currency type classes – order quantity currency; _ For the **Futures** and **Options** type classes – the Price step currency (if not specified, then the nominal currency); _ For other type classes – price currency (if any); otherwise face value currency

Field name	Tag	Comments
AdditionalTermBondCurrency *****	40006	Bond face value currency [XML]
ClientID	109	Clients ID. For details on clients identification see Administrator's manual, 2.11
Text	58	Text reply of the trading system / clients comment. For cross trades – text of the diagnostic message
UserText	9906	Users comment
ExecBroker	76	Broker identifier
TradeNum	5001	The tag may include: _ Trade number; _ Number of new order, created by stop order; _ Number of new order, if OrdStatus=Replaced
TransactTime	60	Date and time of transaction / non-trade instruction execution in <YYYYMMDD-HH:MM:SS.sss> format
TradeDate	75	Valid values: _ Trade date; _ Settlement date, for trades at FORTS
OrderNum	5002	The tag may include: _ Order / non-trade instruction number; _ Number of replaced (old) order (if OrdStatus=Replaced)
AccruedCoupon	5003	Accrued coupon interest
ExValue	5004	Transaction value
DealSettlementCode	63	Settlement code in QUIK format
Commission	12	Commission
ClearingCommission	5008	Valid values: _ Depository commission (for non-trade instructions); _ Commission for clearing
TradingCommission	5009	Commission for organization of trading session
ServiceCommission	5010	Valid values: _ Commission for cash issue (for non-tradeinstructions); _ Commission to service center
RepoValue / NearTradeValue	5011	REPO value on current date / Value of the first part of SWAP trade

Field name	Tag	Comments
		For calendar spread trades: volume of the first trade part
TradeType	5014	Valid values: _ R – Repo; _ N – NDM; _ P – Initial placement; _ T – Standard transaction
CommType	13	Valid value: 3 (absolute)
TimeInForce	59	Valid values: _ 0 – Day; _ 1 – Good Till Cancel; _ 6 – Good Till Date For market on close auction orders: 0
ExpireTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
FutSettDate	64	Specific date of trade settlement. For trades in REPO with CCP mode: price of the first trade part
SecurityExchange	207	Exchange identifier
TraderID	10039	Login in the TS of the user under which the QUIK gateway connects to the TS
SettlCurrency	120	Trade / order settlement currency
UserID	5015	ID of the QUIK user that submitted the order
StationID	5016	Traders workstation ID
TradeTimeGMT	5017	Shift of the Interface local time relative to GMT
FirmId	5018	Transaction firm ID
RepoStartDiscount	5019	Start discount (in percent)
RepoLowerDiscount	5020	Lower discount (in percent)
RepoUpperDiscount	5021	Upper discount (in percent)
MaturityMonthYear	200	Month and Year of redemtion in <YYYYMM> format for reports on execution of futures
MaturityDay	205	Day of redemtion date in DD format for reports on execution of futures
ExchangeTradeID	5022	Exchange number of a trade
NoPartyIDs	453	Number of PartyID groups

Field name	Tag	Comments
→ PartyID **	448	Valid values depending on the PartyRole value: _ 1 – firm code; _ 3 – MiFID2 client short code; _ 11 – value specified when submitting an order; _ 12 – MiFID2 executing trader short code; _ 13 – firm code in an order; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 1 – Executing Firm; _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 13 – Order Origination Firm; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
RefreshQty	6251	Visible quantity (for Iceberg orders sent via algorithmic trading module)
AlgField1	6271	Flag of related order being cancelled (for Iceberg algo orders). Valid values: _ 0 – yes; _ 1 – no
LastSpotRate	194	Conversion cross-rate. For calendar spread trades: price of a parent trade
TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
OrderQty2	192	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlDate2	193	For SWAP-trades: settlement date of a Far trade. For REPO with CCP trades: settlement date of the second trade part

Field name	Tag	Comments
Price2	640	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlCurrAmt	119	Value of trade in the settlement currency
SettlCurrFxRate	155	For trades passed through FXConverter: FX trade price. For other trades: trade cross rate (if transmitted by a corresponding Trading interface)
SettlCurrFxRateSide	5058	Side of the cross rate specified in SettlCurrFxRate [155] in format <currency 1>/<currency 2>
FxConvAvgPxInSettlCurr	5051	Weighted average price of order execution in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvLastPxInSettleCurr	5052	Trade price in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvPriceInSettleCurr	5053	Order price in the settlement currency (the tag is transmitted for trades after currency conversion made with the help of the FxConvertor module)
CumSettlCurAmt	5031	The total volume of the partial execution of the order in the destination currency of FXConverter module if the order is executed by several trades
AvgSettlCurFxRate	5032	The average value of the conversion rate from trades in the destination currency of FXConverter module if the order is executed by several trades
MassStatusReqID	584	Client identifier of the OrderMassStatusRequest message
LastRptRequested	912	Attribute of the last report in the set of messages (Y) sent in response to the OrderMassStatusRequest message
CheckLotFlag	6201	Quantity is presented in lots or pieces. Valid values: _ 0 – disabled; _ 1 – enabled; _ 2 – enabled, check of the instrument lot size is enabled; _ 3 – disabled, check of the instrument lot size is enabled
OrderStatusReqID	790	Client identifier of the status request
OrigClOrdID	41	Client identifier of the order to be cancelled/replaced
RequestID	5060	Client transaction ID in the QUIK server

Field name	Tag	Comments
LastLiquidityInd	851	Attribute of active/passive trade. Valid values: _ 1 – Added Liquidity; _ 2 – Removed Liquidity; _ 3 – Liquidity Routed Out; _ 4 – Auction
MaturityDate	541	Instrument execution date
CashOrderQty	152	Volume of order in monetary unit
PossResend	97	Value: Y – on reporting trades by orders cancelled or replaced by OrderID
LastCapacity	29	Valid values: _ 1 – Agent; _ 2 – Cross as agent; _ 3 – Cross as principal; _ 4 – Principal; _ 5 – Riskless principal
LastMarket	30	Execution market
NoTrdRegPublications	2668	Quantity of TrdRegPublication groups
→TrdRegPublicationType	2669	Value: 0 – Pre-trade transparency waiver
→TrdRegPublicationReason	2670	Valid values: _ 0 – NLIQ; _ 1 – OLIQ; _ 2 – PRIC; _ 3 – RFPT; _ 4 – ILQD; _ 5 – SIZE
NoOtcPostTradeIndicators	5067	Quantity of TrdRegPublication groups
→OtcPostTradeIndicator	5068	Valid values: _ BENC – Benchmark; _ ACTX – Agency cross; _ LRGS – Large in scale; _ ILQD – Illiquid instrument; _ SIZE – Above specified size; _ CANC – Cancellations; _ AMND – Amendments; _ SDIV – Special dividend; _ RPRI – Price improvement; _ DUPL – Duplicative; _ TNCP – Not contributing to the price discovery process; _ TPAC – Package;

Field name	Tag	Comments
		_ XFPH – Exchange for Physical
NoCommissions****	2639	Number of CommissionDataGrp groups [FIX 5.0 SP2]
→CommissionAmount****	2640	Commission value [FIX 5.0 SP2]
→CommissionAmountType****	2641	Commission type. Value: 2 – Broker [FIX 5.0 SP2]
UseWorkInterval	6280	Indicates whether the activity interval is used. Valid values: _ 0 – not used; _ 1 – used
StartTime	6254	Start time. Time format is determined by the AlgoTimeFormat setting of section [General] in the QuikFix.ini configuration file (for details, see the Administrator's manual)
EndTime	6255	End time. Time format is determined by the AlgoTimeFormat setting of section [General] in the QuikFix.ini configuration file (for details, see the Administrator's manual)
OrderRejectReason*****	5093	Order rejection reason [XML]
LinkedTradeNumber*****	5150	Linked trade number [XML+]
OrdRejReason****	103	Error code for order rejection [FIX4.2+]
OrdRejSource*****	5152	Source of the error which code is specified in the tag OrdRejReason [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway
ComplianceText*****	2404	Text from reply to order registration transaction [XML+]

**** [FIX <N>] – tag is available for the FIX protocol version <N> or newer or if it is allowed in the scheme.

***** – tag is available if it is allowed in the scheme.

2.14.6 Algo orders of TWAP type

Supported tags:

Field name	Tag	Comments
MsgType	35	Message type. Valid value: 8

Field name	Tag	Comments
HandlInst	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
OrdStatus	39	Order status. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replaced; _ 6 – Pending Cancel; _ 8 – Rejected; _ E – Pending Replace; _ A – Pending New; _ C – Expired (if an algo order is received in executed status but Execution Report was not sent due to the lack of trades at full quantity/volume of an algo order)
ExecType	150	Execution report type. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replace; _ 6 – Pending Cancel; _ 8 – Rejected; _ A – Pending New; _ C – Expired (for OMS orders); _ D – Restated (for OMS orders); _ E – Pending Replace; _ F – Trade – partial fill or fill (in protocol version 5.0 while reporting partially or fully executed orders); _ I – Order Status (in protocol version 5.0 for reports sent in response to the OrderStatusRequest and OrderMassStatusRequest messages); _ C – Expired (if an algo order is received in executed status but Execution Report was not sent due to the lack of trades at full quantity/volume of an algo order)

Field name	Tag	Comments
OrderQty	38	Total quantity in an order
CumQty	14	Executed quantity of an order
LastQty	32	Quantity of a current order execution
LeavesQty	151	Quantity remained in an order
ClOrdID	11	Unique identifier for Order from client's request
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
OrdType	40	Type of order. Valid values: _ 1 – Market; _ 2 – Limit
Side	54	Valid values: _ 1 – buy; _ 2 – sell. For calendar spread trades: direction of the parent trade
AvgPx	6	Calculated average price of all fills on this order. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
ExecTransType	20	Value: 0 – New. Contains the value 3 for reports sent in response to OrderMassStatusRequest message
OrderID	37	Unique identifier for order. Generated by the Interface (for format see 5.1)
ExecID	17	Unique identifier for trade. Generated by the Interface (for format see 5.1). Value 0 is valid for reports sent in response to OrderStatusRequest and OrderMassStatusRequest messages
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]
LastPx	31	Trade price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Currency	15	Valid values: _ For the Currency type classes – order quantity currency;

Field name	Tag	Comments
		_ For the **Futures** and **Options** type classes – the Price step currency (if not specified, then the nominal currency); _ For other type classes – price currency (if any); otherwise face value currency
AdditionalTermBondCurrency *****	40006	Bond face value currency [XML]
ClientID	109	Clients ID. For details on client's identification see Administrator's manual, 2.11
Text	58	Text reply of the trading system / clients' comment. For cross trades – text of the diagnostic message
UserText	9906	Users comment
ExecBroker	76	Broker identifier
TradeNum	5001	Valid values: _ Trade number; _ Number of new order, created by stop order; _ Number of new order, if OrdStatus=Replaced
TransactTime	60	Date and time of transaction / non-trade instruction execution in <YYYYMMDD-HH:MM:SS.sss> format
TradeDate	75	Valid values: _ Trade date; _ Settlement date, for trades at FORTS
OrderNum	5002	Valid values: _ Order / non-trade instruction number; _ Number of replaced (old) order (if OrdStatus=Replaced)
AccruedCoupon	5003	Accrued coupon interest
ExValue	5004	Transaction value
DealSettlementCode	63	Settlement code in QUIK format
Commission	12	Commission
ClearingCommission	5008	Valid values: _ Depository commission (for non-trade instructions); _ Commission for clearing
TradingCommission	5009	Commission for organization of trading session

Field name	Tag	Comments
ServiceCommission	5010	Valid values: _ Commission for cash issue (for non-tradeinstructions); _ Commission to service center
RepoValue / NearTradeValue	5011	REPO value on current date / Value of the first part of SWAP trade For calendar spread trades: volume of the first trade part
TradeType	5014	Valid values: _ R – Repo; _ N – NDM; _ P – Initial placement; _ T – Standard transaction
CommType	13	Valid value: 3 (absolute)
TimeInForce	59	Valid value: 0 – Day
CashOrderQty	152	Algo order volume
FutSettDate	64	Specific date of trade settlement. For trades in REPO with CCP mode: price of the first trade part
SecurityExchange	207	Exchange identifier
SecurityType	167	Instrument type
TraderID	10039	Login in the TS of the user under which the QUIK gateway connects to the TS
SettlCurrency	120	Trade / order settlement currency
UserID	5015	ID of the QUIK user that submitted the order
StationID	5016	Traders workstation ID
TradeTimeGMT	5017	Shift of the Interface local time relative to GMT
FirmId	5018	Transaction firm ID
RepoStartDiscount	5019	Start discount (in percent)
RepoLowerDiscount	5020	Lower discount (in percent)
RepoUpperDiscount	5021	Upper discount (in percent)
MaturityMonthYear	200	Month and Year of redemption in <YYYYMM> format for reports on execution of futures
MaturityDay	205	Day of redemption date in DD format for reports on execution of futures

Field name	Tag	Comments
ExchangeTradeID	5022	Exchange number of a trade
NoPartyIDs	453	Number of PartyID groups
→ PartyID **	448	Valid values depending on the PartyRole value: _ 1 – firm code; _ 3 – MiFID2 client short code; _ 11 – value specified when submitting an order; _ 12 – MiFID2 executing trader short code; _ 13 – firm code in an order; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 1 – Executing Firm; _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 13 – Order Origination Firm; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
StartTime	6254	Start time for TWAP, VWAP and GTD algo orders. Start of activity time for algo orders of STOP type. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
EndTime	6255	End time for TWAP, VWAP and GTD algo orders. End of activity time for algo orders of STOP type. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
Duration	6256	Number of iterations (for TWAP and VWAP algo orders)
WorkDuration	6257	Number of the current iteration (for TWAP and VWAP algo orders)
ToleranceLimit1	6264	Deviation of price in percent (for TWAP algo orders)

Field name	Tag	Comments
AlgField3	6273	Start time type (for TWAP, VWAP algo orders). Valid values: _ 0 – current time; _ 1 – time set by user
LastSpotRate	194	Conversion cross-rate. For calendar spread trades: price of a parent trade
TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
OrderQty2	192	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlDate2	193	For SWAP-trades: settlement date of a Far trade. For REPO with CCP trades: settlement date of the second trade part
Price2	640	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlCurrAmt	119	Value of trade in settlement currency
SettlCurrFxRate	155	For trades passed through FXConverter: FX trade price (in the cent scheme the value can be converted to the main currency using the coefficient in the SettleCurrFxRateInMainCurrency setting, for details see the FIX program interface Administrator's manual, 2.2.9). For other trades: trade cross rate (if transmitted by a corresponding Trading interface)
SettlCurrFxRateSide	5058	Side of the cross rate specified in SettlCurrFxRate [155] in format <currency 1>/<currency 2>
FxConvAvgPxInSettlCurr	5051	Weighted average price of order execution in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvLastPxInSettleCurr	5052	Trade price in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvPriceInSettleCurr	5053	Order price in the settlement currency (the tag is transmitted for trades after currency conversion made with the help of the FxConvertor module)
CumSettlCurAmt	5031	The total volume of the partial execution of the order in the destination currency of FXConverter module if the order is executed by several trades.

Field name	Tag	Comments
AvgSettlCurFxRate	5032	The average value of the conversion rate from trades in the destination currency of FXConverter module if the order is executed by several trades
MassStatusReqID	584	Client identifier of the OrderMassStatusRequest message
LastRptRequested	912	Attribute of the last report in the set of messages (Y) sent in response to the OrderMassStatusRequest message
Price	44	Price
CheckLotFlag	6201	Quantity is presented in lots or pieces. Valid values: _ 0 – disabled; _ 1 – enabled; _ 2 – enabled, check of the instrument lot size is enabled; _ 3 – disabled, check of the instrument lot size is enabled
OrderStatusReqID	790	Client identifier of the status request
OrigClOrdID	41	Client identifier of the order to be cancelled/replaced
RequestID	5060	Client transaction ID in the QUIK server
LastLiquidityInd	851	Attribute of active/passive trade. Valid values: _ 1 – Added Liquidity; _ 2 – Removed Liquidity; _ 3 – Liquidity Routed Out; _ 4 – Auction
MaturityDate	541	Instrument execution date
PossResend	97	Value: Y – on reporting trades by orders cancelled or replaced by OrderID
LastCapacity	29	Valid values: _ 1 – Agent; _ 2 – Cross as agent; _ 3 – Cross as principal; _ 4 – Principal; _ 5 – Riskless principal
LastMarket	30	Execution market
NoTrdRegPublications	2668	Quantity of TrdRegPublication groups
→TrdRegPublicationType	2669	Value: 0 – Pre-trade transparency waiver
→TrdRegPublicationReason	2670	Valid values: _ 0 – NLIQ;

Field name	Tag	Comments
		_ 1 – OLIQ; _ 2 – PRIC; _ 3 – RFPT; _ 4 – ILQD; _ 5 – SIZE
NoOtcPostTradeIndicators	5067	Quantity of TrdRegPublication groups
→OtcPostTradeIndicator	5068	Valid values: _ BENC – Benchmark; _ ACTX – Agency cross; _ LRGS – Large in scale; _ ILQD – Illiquid instrument; _ SIZE – Above specified size; _ CANC – Cancellations; _ AMND – Amendments; _ SDIV – Special dividend; _ RPRI – Price improvement; _ DUPL – Duplicative; _ TNCP – Not contributing to the price discovery process; _ TPAC – Package; _ XFPH – Exchange for Physical
NoCommissions****	2639	Number of CommissionDataGrp groups [FIX 5.0 SP2]
→CommissionAmount****	2640	Commission value [FIX 5.0 SP2]
→CommissionAmountType****	2641	Commission type. Value: 2 – Broker [FIX 5.0 SP2]
OrderRejectReason*****	5093	Order rejection reason [XML]
LinkedTradeNumber*****	5150	Linked trade number [XML+]
OrdRejReason****	103	Error code for the order rejection [FIX4.2+]
OrdRejSource*****	5152	Source of the error which code is specified in the OrdRejReason tag [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway
IterationTime	6259	Iteration time
IterationSetMode	6260	Iteration set mode. Valid values: _ 1 – Iteration Time; _ 0 – Iterations Number

Field name	Tag	Comments
ComplianceText*****	2404	Text from reply to order registration transaction [XML+]

**** [FIX <N>] – tag is available for the FIX protocol version <N> or newer or if it is allowed in the scheme.

***** – tag is available if it is allowed in the scheme.

2.14.7 Algo orders of VWAP type

Supported tags:

Field name	Tag	Comments
MsgType	35	Message type. Valid value: 8
HandlInst	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
OrdStatus	39	Order status. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replaced; _ 6 – Pending Cancel; _ 8 – Rejected; _ E – Pending Replace; _ A – Pending New; _ C – Expired (if an algo order is received in executed status but Execution Report was not sent due to the lack of trades at full quantity/volume of an algo order)
ExecType	150	Execution report type. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replace; _ 6 – Pending Cancel; _ 8 – Rejected; _ A – Pending New;

Field name	Tag	Comments
		_ C – Expired (for OMS orders); _ D – Restated (for OMS orders); _ E – Pending Replace; _ F – Trade – partial fill or fill (in protocol version 5.0 while reporting partially or fully executed orders); _ I – Order Status (in protocol version 5.0 for reports sent in response to the OrderStatusRequest and OrderMassStatusRequest messages); _ C – Expired (if an algo order is received in executed status but Execution Report was not sent due to the lack of trades at full quantity/volume of an algo order)
OrderQty	38	Total quantity in an order
CumQty	14	Executed quantity of an order
LastQty	32	Quantity of a current order execution
LeavesQty	151	Quantity remained in an order
ClOrdID	11	Unique identifier for Order from clients request
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side	54	Valid values: _ 1 – buy; _ 2 – sell. For calendar spread trades: direction of the parent trade
AvgPx	6	Calculated average price of all fills on this order. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
ExecTransType	20	Valid value: 0 – New. Contains the value 3 for reports sent in response to OrderMassStatusRequest message
OrderID	37	Unique identifier for order. Generated by the Interface (for format see 5.1)
ExecID	17	Unique identifier for trade. Generated by the Interface (for format see 5.1). Value 0 is valid for reports sent in response to OrderStatusRequest and OrderMassStatusRequest messages
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]

Field name	Tag	Comments
Price	44	Order price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part. Value for STOP algo orders: 0
LastPx	31	Trade price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Currency	15	Valid values: _ For the Currency type classes – order quantity currency; _ For the **Futures** and **Options** type classes – Price step currency (if not specified, then the nominal currency); _ For other type classes – price currency (if any), otherwise face value currency
AdditionalTermBondCurrency *****	40006	Bond face value currency [XML]
ClientID	109	Clients ID. For details on client's identification see Administrator's manual, 2.11
Text	58	Text reply of the trading system / clients' comment. For cross trades – text of the diagnostic message
UserText	9906	Users comment
ExecBroker	76	Broker identifier
TradeNum	5001	Valid values: _ Trade number; _ Number of new order, created by stop order; _ Number of new order, if OrdStatus=Replaced
TransactTime	60	Date and time of transaction / non-trade instruction execution in <YYYYMMDD-HH:MM:SS.sss> format
TradeDate	75	Valid values: _ Trade date; _ Settlement date, for trades at FORTS
OrderNum	5002	Valid values: _ Order / non-trade instruction number; _ Number of replaced (old) order (if OrdStatus=Replaced)
AccruedCoupon	5003	Accrued coupon interest

Field name	Tag	Comments
ExValue	5004	Transaction value
DealSettlementCode	63	Settlement code in QUIK format
Commission	12	Commission
ClearingCommission	5008	Valid values: _ Depository commission (for non-trade instructions); _ Commission for clearing
TradingCommission	5009	Commission for organization of trading session
ServiceCommission	5010	Valid values: _ Commission for cash issue (for non-tradeinstructions); _ Commission to service center
RepoValue / NearTradeValue	5011	REPO value on current date / Value of the first part of SWAP trade For calendar spread trades: volume of the first trade part
TradeType	5014	Valid values: _ R – Repo; _ N – NDM; _ P – Initial placement; _ T – Standard transaction
CommType	13	Valid value: 3 (absolute)
TimeInForce	59	Valid value: 0 – Day
FutSettDate	64	Time of execution. For trades in REPO with CCP mode: price of the first trade part
SecurityExchange	207	Exchange identifier
SecurityType	167	InstrumentType
TraderID	10039	Login in the TS of the user under which the QUIK gateway connects to the TS
SettlCurrency	120	Trade / order settlement currency
UserID	5015	ID of the QUIK user that submitted the order
StationID	5016	Traders workstation ID
TradeTimeGMT	5017	Shift of the Interface local time relative to GMT
FirmId	5018	Transaction firm ID
RepoStartDiscount	5019	Start discount (in percent)

Field name	Tag	Comments
RepoLowerDiscount	5020	Lower discount (in percent)
RepoUpperDiscount	5021	Upper discount (in percent)
MaturityMonthYear	200	Month and Year of redemption in <YYYYMM> format for reports on execution of futures
MaturityDay	205	Day of redemption date in DD format for reports on execution of futures
ExchangeTradeID	5022	Exchange number of a trade
NoPartyIDs	453	Number of PartyID groups
→ PartyID **	448	Valid values depending on the PartyRole value: _ 1 – firm code; _ 3 – MiFID2 client short code; _ 11 – value specified when submitting an order; _ 12 – MiFID2 executing trader short code; _ 13 – firm code in an order; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 1 – Executing Firm; _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 13 – Order Origination Firm; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
StartTime	6254	Start time for TWAP, VWAP and GTD algo orders. Start of activity time for algo orders of STOP type. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
EndTime	6255	End time for TWAP, VWAP and GTD algo orders. End of activity time for algo orders of STOP type.

Field name	Tag	Comments
		Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
Duration	6256	Number of iterations (for TWAP and VWAP algo orders)
WorkDuration	6257	Number of the current iteration (for TWAP and VWAP algo orders)
ToleranceLimit1	6264	Deviation of price in percent (for TWAP algo orders)
ToleranceLimit2	6265	Maximum permissible deviation from the volume weighted average price in percent (for VWAP algo orders)
AlgField3	6273	Start time type (for TWAP, VWAP algo orders). Valid values: _ 0 – current time; _ 1 – time set by user
AlgField4	6274	Flag of execution of the market volume (for VWAP algo orders). Valid values: _ 0 – no; _ 1 – yes
AlgField5	6275	Percent of market volume (for VWAP algo orders)
AlgField6	6276	Market volume
AlgField7	6277	Market quantity
AlgField8	6278	Market weighted average price
AlgField11	6281	Work in price range. Valid values: _ 0 – no; _ 1 – yes
LastSpotRate	194	Conversion cross-rate. For calendar spread trades: price of a parent trade
TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
OrderQty2	192	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlDate2	193	For SWAP-trades: settlement date of a Far trade. For REPO with CCP trades: settlement date of the second trade part
Price2	640	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part

Field name	Tag	Comments
SettlCurrAmt	119	Value of trade in the settlement currency
SettlCurrFxRate	155	For trades passed through FXConverter: FX trade price. For other trades: trade cross rate (if transmitted by a corresponding Trading interface)
SettlCurrFxRateSide	5058	Side of the cross rate specified in SettlCurrFxRate [155] in format <currency 1>/<currency 2>
FxConvAvgPxInSettlCurr	5051	Weighted average price of order execution in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvLastPxInSettleCurr	5052	Trade price in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvPriceInSettleCurr	5053	Order price in the settlement currency (the tag is transmitted for trades after currency conversion made with the help of the FxConvertor module)
CumSettlCurAmt	5031	The total volume of the partial execution of the order in the destination currency of FXConverter module if the order is executed by several trades.
AvgSettlCurFxRate	5032	The average value of the conversion rate from trades in the destination currency of FXConverter module if the order is executed by several trades
AlgoTag1	6088	Minimum price (for VWAP algo orders)
AlgoTag2	6089	Maximum price (for VWAP algo orders)
MassStatusReqID	584	Client identifier of the OrderMassStatusRequest message
LastRptRequested	912	Attribute of the last report in the set of messages (Y) sent in response to the OrderMassStatusRequest message
CheckLotFlag	6201	Quantity is presented in lots or pieces. Valid values: _ 0 – disabled; _ 1 – enabled; _ 2 – enabled, check of the instrument lot size is enabled; _ 3 – disabled, check of the instrument lot size is enabled
OrderStatusReqID	790	Client identifier of the status request
OrigClOrdID	41	Client identifier of the order to be cancelled/replaced

Field name	Tag	Comments
RequestID	5060	Client transaction ID in the QUIK server
LastLiquidityInd	851	Attribute of active/passive trade. Valid values: _ 1 – Added Liquidity; _ 2 – Removed Liquidity; _ 3 – Liquidity Routed Out; _ 4 – Auction
MaturityDate	541	Instrument execution date
CashOrderQty	152	Volume of order in monetary unit
PossResend	97	Value: Y – on reporting trades by orders cancelled or replaced by OrderID
LastCapacity	29	Valid values: _ 1 – Agent; _ 2 – Cross as agent; _ 3 – Cross as principal; _ 4 – Principal; _ 5 – Riskless principal
LastMarket	30	Execution market
NoTrdRegPublications	2668	Quantity of TrdRegPublication groups
→TrdRegPublicationType	2669	Value: 0 – Pre-trade transparency waiver
→TrdRegPublicationReason	2670	Valid values: _ 0 – NLIQ; _ 1 – OLIQ; _ 2 – PRIC; _ 3 – RFPT; _ 4 – ILQD; _ 5 – SIZE
NoOtcPostTradeIndicators	5067	Quantity of TrdRegPublication groups
→OtcPostTradeIndicator	5068	Valid values: _ BENC – Benchmark; _ ACTX – Agency cross; _ LRGS – Large in scale; _ ILQD – Illiquid instrument; _ SIZE – Above specified size; _ CANC – Cancellations; _ AMND – Amendments; _ SDIV – Special dividend; _ RPRI – Price improvement; _ DUPL – Duplicative;

Field name	Tag	Comments
		_ TNCP – Not contributing to the price discovery process; _ TPAC – Package; _ XFPH – Exchange for Physical
NoCommissions****	2639	Number of CommissionDataGrp groups [FIX 5.0 SP2]
→CommissionAmount****	2640	Commission value [FIX 5.0 SP2]
→CommissionAmountType****	2641	Commission type. Value: 2 – Broker [FIX 5.0 SP2]
OrderRejectReason*****	5093	Order rejection reason [XML]
LinkedTradeNumber*****	5150	Linked trade number [XML+]
OrdRejReason****	103	Error code for order rejection [FIX4.2+]
OrdRejSource*****	5152	Source of the error which code is specified in the tag OrdRejReason [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway
ComplianceText*****	2404	Text from reply to order registration transaction [XML+]

**** [FIX <N>] – tag is available for the FIX protocol version <N> or newer or if it is allowed in the scheme.

***** – tag is available if it is allowed in the scheme.

2.14.8 Algo orders of STOP type

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: 8
HandlInst	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
OrdStatus	39	Order status. Valid values: _ 0 – New;

Field name	Tag	Comments
		_ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replaced; _ 6 – Pending Cancel; _ 8 – Rejected; _ E – Pending Replace; _ A – Pending New; _ C – Expired (if an algo order is received in executed status but Execution Report was not sent due to the lack of trades at full quantity/volume of an algo order)
ExecType	150	Execution report type. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replace; _ 6 – Pending Cancel; _ 8 – Rejected; _ A – Pending New; _ C – Expired (for OMS orders); _ D – Restated (for OMS orders); _ E – Pending Replace; _ F – Trade – partial fill or fill (in protocol version 5.0 while reporting partially or fully executed orders); _ I – Order Status (in protocol version 5.0 for reports sent in response to the OrderStatusRequest and OrderMassStatusRequest messages); _ C – Expired (if an algo order is received in executed status but Execution Report was not sent due to the lack of trades at full quantity/volume of an algo order)
CumQty	14	Executed quantity of an order
LastQty	32	Quantity of a current order execution
ClOrdID	11	Unique identifier for Order from client's request
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2

Field name	Tag	Comments
Side	54	Valid values: _ 1 – buy; _ 2 – sell; _ 7 – direction is not defined (used for STOP algo orders) For calendar spread trades: direction of the parent trade
OrdType	40	Type of order. Valid values: _ 1 – Market; _ 2 – Limit
AvgPx	6	Calculated average price of all fills on this order. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
ExecTransType	20	Valid value: 0 – New. Contains the value 3 for reports sent in response to OrderMassStatusRequest message
OrderID	37	Unique identifier for order. Generated by the Interface (for format see 5.1)
ExecID	17	Unique identifier for trade. Generated by the Interface (for format see 5.1). Value 0 is valid for reports sent in response to OrderStatusRequest and OrderMassStatusRequest messages
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]
LastPx	31	Trade price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Currency	15	Valid values: _ For the Currency type classes – order quantity currency; _ For the **Futures** and **Options** type classes – the Price step currency (if not specified, then the nominal currency); _ For other type classes – price currency (if any); otherwise face value currency
AdditionalTermBondCurrency *****	40006	Bond face value currency [XML]
ClientID	109	Clients ID. For details on clients identification see Administrator's manual, 2.11

Field name	Tag	Comments
Text	58	Text reply of the trading system / clients comment. For cross trades – text of the diagnostic message
UserText	9906	Users comment
ExecBroker	76	Broker identifier
TradeNum	5001	Valid values: _ Trade number; _ Number of new order, created by stop order; _ Number of new order, if OrdStatus=Replaced
StopPx	99	Stop price (for Stop limit and Take profit orders)
TransactTime	60	Date and time of transaction / non-trade instruction execution in <YYYYMMDD-HH:MM:SS.sss> format
TradeDate	75	Valid values: _ Trade date; _ Settlement date, for trades at FORTS
OrderNum	5002	Valid values: _ Order / non-trade instruction number; _ Number of replaced (old) order (if OrdStatus=Replaced)
AccruedCoupon	5003	Accrued coupon interest
ExValue	5004	Transaction value
DealSettlementCode	63	Settlement code in QUIK format
Commission	12	Commission
ClearingCommission	5008	Valid values: _ Depository commission (for non-trade instructions); _ Commission for clearing
TradingCommission	5009	Commission for organization of trading session
ServiceCommission	5010	Valid values: _ Commission for cash issue (for non-trade instructions); _ Commission to service center
RepoValue / NearTradeValue	5011	REPO value on current date / Value of the first part of SWAP trade. For calendar spread trades: volume of the first trade part
TradeType	5014	Valid values: _ R – Repo;

Field name	Tag	Comments
		_ N – NDM; _ P – Initial placement; _ T – Standard transaction
CommType	13	Valid value: 3 (absolute)
TimeInForce	59	Valid values: _ 0 – Day; _ 1 – Good Till Cancel; _ 6 – Good Till Date. For market on close auction orders: 0
ExpireTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
FutSettDate	64	Specific date of trade settlement. For trades in REPO with CCP mode: price of the first trade part
SecurityExchange	207	Exchange identifier
SecurityType	167	Instrument type
TraderID	10039	Login in the TS of the user under which the QUIK gateway connects to the TS
SettlCurrency	120	Trade / order settlement currency
UserID	5015	ID of the QUIK user that submitted the order
StationID	5016	Traders workstation ID
TradeTimeGMT	5017	Shift of the Interface local time relative to GMT
FirmId	5018	Transaction firm ID
RepoStartDiscount	5019	Start discount (in percent)
RepoLowerDiscount	5020	Lower discount (in percent)
RepoUpperDiscount	5021	Upper discount (in percent)
MaturityMonthYear	200	Month and Year of redemption in <YYYYMM> format for reports on execution of futures
MaturityDay	205	Day of redemption date in DD format for reports on execution of futures
ExchangeTradeID	5022	Exchange number of a trade
NoPartyIDs	453	Number of PartyID groups
→ PartyID **	448	Valid values depending on the PartyRole value: _ 1 – firm code;

Field name	Tag	Comments
		_ 3 – MiFID2 client short code; _ 11 – value specified when submitting an order; _ 12 – MiFID2 executing trader short code; _ 13 – firm code in an order; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code; _ P – Short code identifier
→ PartyRole	452	Valid values: _ 1 – Executing Firm; _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 13 – Order Origination Firm; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
StartTime	6254	Start time for TWAP, VWAP and GTD algo orders. Start of activity time for algo orders of STOP type. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
EndTime	6255	End time for TWAP, VWAP and GTD algo orders. End of activity time for algo orders of STOP type. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
AlgField9	6279	Attribute of cancelling client orders. Valid values: _ 0 – do not cancel; _ 1 – cancel
UseWorkInterval	6280	Attribute of using the activity interval Valid values: _ 0 – do not use; _ 1 – use
AlgField12	6282	Take profit in percent
AlgoParameter1	6315	Stop limit in percent

Field name	Tag	Comments
AlgoParameter2	6316	Protective spread in percent
AlgoParameter3	6317	Take profit
AlgoParameter4	6318	Type of take profit specifying. Valid values: _ 0 – percent; _ 1 – price currency; _ 2 – not set
AlgoParameter5	6319	Type of stop-limit specifying. Valid values: _ 0 – percent; _ 1 – price currency; _ 2 – not set
LastSpotRate	194	Conversion cross-rate. For calendar spread trades: price of a parent trade
TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
OrderQty2	192	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlDate2	193	For SWAP-trades: settlement date of a Far trade. For REPO with CCP trades: settlement date of the second trade part
Price2	640	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlCurrAmt	119	Value of trade in the settlement currency
SettlCurrFxRate	155	For trades passed through FXConverter: FX trade price. For other trades: trade cross rate (if transmitted by a corresponding Trading interface)
SettlCurrFxRateSide	5058	Side of the cross rate specified in SettlCurrFxRate [155] in format <currency 1>/<currency 2>
PegOffsetValue	211	Protective spread. Value by default: 0. The tag is used for stop orders of Take profit type
PegOffsetType	836	Item of protective spread. Valid values: _ 0 (by default) – price currency; _ 1 – percent. The tag is used for stop orders of Take profit type
FxConvAvgPxInSettlCurr	5051	Weighted average price of order execution in the settlement currency.

Field name	Tag	Comments
		The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvLastPxInSettleCurr	5052	Trade price in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvPriceInSettleCurr	5053	Order price in the settlement currency (the tag is transmitted for trades after currency conversion made with the help of the FxConvertor module)
CumSettlCurAmt	5031	The total volume of the partial execution of the order in the destination currency of FXConverter module if the order is executed by several trades
AvgSettlCurFxRate	5032	The average value of the conversion rate from trades in the destination currency of FXConverter module if the order is executed by several trades
MassStatusReqID	584	Client identifier of the OrderMassStatusRequest message
LastRptRequested	912	Attribute of the last report in the set of messages (Y) sent in response to the OrderMassStatusRequest message
CheckLotFlag	6201	Quantity is presented in lots or pieces. Valid values: _ 0 – disabled; _ 1 – enabled; _ 2 – enabled, check of the instrument lot size is enabled; _ 3 – disabled, check of the instrument lot size is enabled
OrderStatusReqID	790	Client identifier of the status request
OrigClOrdID	41	Client identifier of the order to be cancelled/replaced
RequestID	5060	Client transaction ID in the QUIK server
LastLiquidityInd	851	Attribute of active/passive trade. Valid values: _ 1 – Added Liquidity; _ 2 – Removed Liquidity; _ 3 – Liquidity Routed Out; _ 4 – Auction
MaturityDate	541	Instrument execution date
CashOrderQty	152	Volume of order in monetary unit
PossResend	97	Value: Y – on reporting trades by orders cancelled or replaced by OrderID

Field name	Tag	Comments
LastCapacity	29	Valid values: _ 1 – Agent; _ 2 – Cross as agent; _ 3 – Cross as principal; _ 4 – Principal; _ 5 – Riskless principal
LastMarket	30	Execution market
NoTrdRegPublications	2668	Quantity of TrdRegPublication groups
→TrdRegPublicationType	2669	Value: 0 – Pre-trade transparency waiver
→TrdRegPublicationReason	2670	Valid values: _ 0 – NLIQ; _ 1 – OLIQ; _ 2 – PRIC; _ 3 – RFPT; _ 4 – ILQD; _ 5 – SIZE
NoOtcPostTradeIndicators	5067	Quantity of TrdRegPublication groups
→OtcPostTradeIndicator	5068	Valid values: _ BENC – Benchmark; _ ACTX – Agency cross; _ LRGS – Large in scale; _ ILQD – Illiquid instrument; _ SIZE – Above specified size; _ CANC – Cancellations; _ AMND – Amendments; _ SDIV – Special dividend; _ RPRI – Price improvement; _ DUPL – Duplicative; _ TNCP – Not contributing to the price discovery process; _ TPAC – Package; _ XFPH – Exchange for Physical
NoCommissions****	2639	Number of CommissionDataGrp groups [FIX 5.0 SP2]
→CommissionAmount****	2640	Commission value [FIX 5.0 SP2]
→CommissionAmountType****	2641	Commission type. Value: 2 – Broker [FIX 5.0 SP2]
OrderRejectReason*****	5093	Order rejection reason [XML]
LinkedTradeNumber*****	5150	Linked trade number [XML+]

Field name	Tag	Comments
OrdRejReason****	103	Error code for order rejection [FIX4.2+]
OrdRejSource*****	5152	Source of the error which code is specified in the tag OrdRejReason [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway
ComplianceText*****	2404	Text from reply to order registration transaction [XML+]

**** [FIX <N>] – tag is available for the FIX protocol version <N> or newer or if it is allowed in the scheme.

***** – tag is available if it is allowed in the scheme.

2.14.9 Algo orders of GTD type

Supported tags:

Field name	Tag	Comments
MsgType	35	Message type. Valid value: 8
HandlInst	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
OrdStatus	39	Order status. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replaced; _ 6 – Pending Cancel; _ 8 – Rejected; _ E – Pending Replace; _ A – Pending New; _ C – Expired (if an algo order is received in executed status but Execution Report was not sent due to the lack of trades at full quantity/volume of an algo order)
ExecType	150	Execution report type. Valid values:

Field name	Tag	Comments
		_ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 3 – Done For Day; _ 4 – Canceled; _ 5 – Replace; _ 6 – Pending Cancel; _ 8 – Rejected; _ A – Pending New; _ C – Expired (for OMS orders); _ D – Restated (for OMS orders); _ E – Pending Replace; _ F – Trade – partial fill or fill (in protocol version 5.0 while reporting partially or fully executed orders); _ I – Order Status (in protocol version 5.0 for reports sent in response to the OrderStatusRequest and OrderMassStatusRequest messages); _ C – Expired (if an algo order is received in executed status but Execution Report was not sent due to the lack of trades at full quantity/volume of an algo order)
OrderQty	38	Total quantity in an order (including Iceberg orders). _ For STOP algo orders value is 0
CumQty	14	Executed quantity of an order
LastQty	32	Quantity of a current order execution
LeavesQty	151	Quantity remained in an order
ClOrdID	11	Unique identifier for Order from clients request
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side	54	Valid values: _ 1 – buy; _ 2 – sell; _ 7 – direction is not defined (used for STOP algo orders). For calendar spread trades: direction of the parent trade
OrdType	40	Type of order. Valid values: _ 1 – Market; _ 2 – Limit

Field name	Tag	Comments
AvgPx	6	Calculated average price of all fills on this order. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
ExecTransType	20	Valid value: 0 – New. Contains the value 3 for reports sent in response to OrderMassStatusRequest message
OrderID	37	Unique identifier for order. Generated by the Interface (for format see 5.1)
ExecID	17	Unique identifier for trade. Generated by the Interface (for format see 5.1). Value 0 is valid for reports sent in response to OrderStatusRequest and OrderMassStatusRequest messages
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]
Price	44	Order price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part. Value for STOP algo orders: 0
LastPx	31	Trade price. For trades in REPO with CCP mode and for calendar spread trades: price of the first trade part
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Currency	15	Valid values: _ For the Currency type classes – order quantity currency; _ For the **Futures** and **Options** type classes – Price step currency (if not specified, then the nominal currency); _ For other type classes – price currency (if any), otherwise face value currency
AdditionalTermBondCurrency *****	40006	Bond face value currency [XML]
ClientID	109	Clients ID. For details on clients identification, see Administrator's manual, 2.11
Text	58	Text reply of the trading system / clients comment. For cross trades – text of the diagnostic message
UserText	9906	Users comment
ExecBroker	76	Broker identifier
TradeNum	5001	Valid values:

Field name	Tag	Comments
		_ Trade number; _ Number of new order, created by stop order; _ Number of new order, if OrdStatus=Replaced
TransactTime	60	Date and time of transaction / non-trade instruction execution in <YYYYMMDD-HH:MM:SS.sss> format
TradeDate	75	Valid values: _ Trade date; _ Settlement date, for trades at FORTS
OrderNum	5002	Valid values: _ Order / non-trade instruction number; _ Number of replaced (old) order (if OrdStatus=Replaced)
AccruedCoupon	5003	Accrued coupon interest
ExValue	5004	Transaction value
DealSettlementCode	63	Settlement code in QUIK format
Commission	12	Commission
ClearingCommission	5008	Valid values: _ Depository commission (for non-trade instructions); _ Commission for clearing
TradingCommission	5009	Commission for organization of trading session
ServiceCommission	5010	Valid values: _ Commission for cash issue (for non-trade instructions); _ Commission to service center
RepoValue / NearTradeValue	5011	REPO value on current date / Value of the first part of SWAP trade. For calendar spread trades: volume of the first trade part
TradeType	5014	Valid values: _ R – Repo; _ N – NDM; _ P – Initial placement; _ T – Standard transaction
CommType	13	Valid value: 3 (absolute)
TimeInForce	59	Valid values: _ 1 – Good Till Cancel; _ 6 – Good Till Date

Field name	Tag	Comments
ExpireTime	126	Only for orders with time in force Good Till Date, in <YYYYMMDD-HH:MM:SS> format
FutSettDate	64	Specific date of trade settlement. For trades in REPO with CCP mode: price of the first trade part
SecurityExchange	207	Exchange identifier
SecurityType	167	Instrument type
TraderID	10039	Login in the TS of the user under which the QUIK gateway connects to the TS
SettlCurrency	120	Trade / order settlement currency
UserID	5015	ID of the QUIK user that submitted the order
StationID	5016	Traders workstation ID
TradeTimeGMT	5017	Shift of the Interface local time relative to GMT
FirmId	5018	Transaction firm ID
RepoStartDiscount	5019	Start discount (in percent)
RepoLowerDiscount	5020	Lower discount (in percent)
RepoUpperDiscount	5021	Upper discount (in percent)
MaturityMonthYear	200	Month and Year of redemption in <YYYYMM> format for reports on execution of futures
MaturityDay	205	Day of redemption date in DD format for reports on execution of futures
ExchangeTradeID	5022	Exchange number of a trade
NoPartyIDs	453	Number of PartyID groups
→ PartyID **	448	Valid values depending on the PartyRole value: _ 1 – firm code; _ 3 – MiFID2 client short code; _ 11 – value specified when submitting an order; _ 12 – MiFID2 executing trader short code; _ 13 – firm code in an order; _ 122 – MiFID2 investment decision maker short code. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid values: _ D – Proprietary / Custom code;

Field name	Tag	Comments
		_ P – Short code identifier
→ PartyRole	452	Valid values: _ 1 – Executing Firm; _ 3 – ClientID; _ 11 – Order Origination Trader; _ 12 – Executing Trader; _ 13 – Order Origination Firm; _ 122 – Investment decision maker
→ PartyRoleQualifier	2376	Valid values: _ 22 – Algorithm; _ 23 – Firm or legal entity; _ 24 – Natural person
StartTime	6254	Start time for TWAP, VWAP and GTD algo orders. Start of activity time for algo orders of STOP type. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details see Administrator's manual)
EndTime	6255	End time for TWAP, VWAP and GTD algo orders. End of activity time for algo orders of STOP type. Time format is defined by the AlgoTimeFormat option in the [General] section of QuikFix.ini configuration file (for more details, see Administrator's manual)
UseWorkInterval	6280	Attribute of using the activity interval Valid values: _ 0 – do not use; _ 1 – use
LastSpotRate	194	Conversion cross-rate. For calendar spread trades: price of a parent trade
TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
OrderQty2	192	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlDate2	193	For SWAP-trades: settlement date of a Far trade. For REPO with CCP trades: settlement date of the second trade part
Price2	640	For SWAP trades: price of a Far trade. For calendar spread trades: price of the second trade part
SettlCurrAmt	119	Value of trade in the settlement currency

Field name	Tag	Comments
SettlCurrFxRate	155	For trades passed through FXConverter: FX trade price. For other trades: trade cross rate (if transmitted by a corresponding Trading interface)
SettlCurrFxRateSide	5058	Side of the cross rate specified in SettlCurrFxRate [155] in format <currency 1>/<currency 2>
FxConvAvgPxInSettlCurr	5051	Weighted average price of order execution in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
FxConvLastPxInSettleCurr	5052	Trade price in the settlement currency. The parameter is used for trades after currency conversion made with the help of the FxConvertor module
*** FxConvPriceInSettleCurr	5053	Order price in the settlement currency (the tag is transmitted for trades after currency conversion made with the help of the FxConvertor module)
CumSettlCurAmt	5031	The total volume of the partial execution of the order in the destination currency of FXConverter module if the order is executed by several trades
AvgSettlCurFxRate	5032	The average value of the conversion rate from trades in the destination currency of FXConverter module if the order is executed by several trades
MassStatusReqID	584	Client identifier of the OrderMassStatusRequest message
LastRptRequested	912	Attribute of the last report in the set of messages (Y) sent in response to the OrderMassStatusRequest message
CheckLotFlag	6201	Quantity is presented in lots or pieces. Valid values: _ 0 – disabled; _ 1 – enabled; _ 2 – enabled, check of the instrument lot size is enabled; _ 3 – disabled, check of the instrument lot size is enabled
OrderStatusReqID	790	Client identifier of the status request
OrigClOrdID	41	Client identifier of the order to be cancelled/replaced
RequestID	5060	Client transaction ID in the QUIK server
LastLiquidityInd	851	Attribute of active/passive trade. Valid values: _ 1 – Added Liquidity; _ 2 – Removed Liquidity; _ 3 – Liquidity Routed Out;

Field name	Tag	Comments
		_ 4 – Auction
MaturityDate	541	Instrument execution date
CashOrderQty	152	Volume of order in monetary unit
PossResend	97	Value: Y – on reporting trades by orders cancelled or replaced by OrderID
LastCapacity	29	Valid values: _ 1 – Agent; _ 2 – Cross as agent; _ 3 – Cross as principal; _ 4 – Principal; _ 5 – Riskless principal
LastMarket	30	Execution market
NoTrdRegPublications	2668	Quantity of TrdRegPublication groups
→TrdRegPublicationType	2669	Value: 0 – Pre-trade transparency waiver
→TrdRegPublicationReason	2670	Valid values: _ 0 – NLIQ; _ 1 – OLIQ; _ 2 – PRIC; _ 3 – RFPT; _ 4 – ILQD; _ 5 – SIZE
NoOtcPostTradeIndicators	5067	Quantity of TrdRegPublication groups
→OtcPostTradeIndicator	5068	Valid values: _ BENC – Benchmark; _ ACTX – Agency cross; _ LRGS – Large in scale; _ ILQD – Illiquid instrument; _ SIZE – Above specified size; _ CANC – Cancellations; _ AMND – Amendments; _ SDIV – Special dividend; _ RPRI – Price improvement; _ DUPL – Duplicative; _ TNCP – Not contributing to the price discovery process; _ TPAC – Package; _ XFPH – Exchange for Physical
NoCommissions****	2639	Number of CommissionDataGrp groups [FIX 5.0 SP2]

Field name	Tag	Comments
→CommissionAmount****	2640	Commission value [FIX 5.0 SP2]
→CommissionAmountType****	2641	Commission type. Value: 2 – Broker [FIX 5.0 SP2]
OrderRejectReason*****	5093	Order rejection reason [XML]
LinkedTradeNumber*****	5150	Linked trade number [XML+]
OrdRejReason****	103	Error code for order rejection [FIX4.2+]
OrdRejSource*****	5152	Source of the error which code is specified in the tag OrdRejReason [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway
ComplianceText*****	2404	Text from reply to order registration transaction [XML+]

**** [FIX <N>] – tag is available for the FIX protocol version <N> or newer or if it is allowed in the scheme.

***** – tag is available if it is allowed in the scheme.

2.14.10 Transferring risks

Supported tags:

Field name	Tag	Comments
ClOrdID	11	Identifier of client request
OrderID	37	Identifier of client request
ExecID	17	Unique identifier of message which is generated on a common basis
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
Side	54	Valid values: _ 1 – buy; _ 2 – sell
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
OrderQty	38	Total quantity in an order

Field name	Tag	Comments
OrdStatus	39	Order status. Valid values: _ 0 – New; _ 8 – Rejected; _ 2 – Filled
ExecType	150	Execution report type. Valid values: _ 0 – New; _ 8 – Rejected; _ 2 – Filled
ExecTransType	20	Valid value: 0 – New
SecurityType	167	Instrument type
Text	58	Text description of reason for cancellation of the order
TransactTime	60	Date and time of transaction / execution of non-trade instruction in <YYYYMMDD – HH:MM:SS.sss> format
ExecID	17	Unique message identifier generated on a common basis
LeavesQty	151	Valid values: _ Quantity; _ 0 if OrdStatus and ExecType = 2 – Filled; _ Quantity remained in an order
CumQty	14	Valid values: _ 0; _ Quantity from the client request if OrdStatus and ExecType = 2 – Filled; _ Executed quantity of an order
AvgPx	6	0.0
LastPx	31	0.0 if OrdStatus and ExecType = 2 – Filled
LastShares	32	Valid values: _ Quantity from the client request if OrdStatus and ExecType = 2 – Filled; _ Quantity of a current order execution
PossResend	97	Value: Y – on reporting trades by orders cancelled or replaced by OrderID
OrdRejReason****	103	Error code for order rejection [FIX4.2+]
OrdRejSource*****	5152	Source of the error which code is specified in the tag OrdRejReason [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway

Field name	Tag	Comments
ComplianceText*****	2404	Text from reply to order registration transaction [XML+]

**** [FIX <N>] – the tag is only available for the FIX protocol version <N> or newer or if it is allowed in the scheme.

***** – the tag is available if it is allowed in the scheme.

2.14.11 Orders of National settlement depositary pays change

Supported tags:

Field name	Tag	Comments
MsgType	35	Message type. Valid value: 8
HandlInst	21	Valid values: _ 1 – Automated execution order, private, no Broker intervention; _ 2 – Automated execution order, public, Broker intervention
OrdStatus	39	Order status. Valid values: _ 0 – New; _ 2 – Fill; _ 4 – Canceled; _ 8 – Rejected
ExecType	150	Execution report type. Valid values: _ 0 – New; _ 2 – Fill; _ 4 – Canceled; _ 8 – Rejected; _ F – Trade –fill (in protocol version 5.0 while reporting fully executed orders); _ I – Order Status (in protocol version 5.0 for reports sent in response to the OrderStatusRequest and OrderMassStatusRequest messages)
OrderQty*	38	Total quantity in an order
CumQty	14	Executed quantity of an order
LeavesQty	151	Quantity remained in an order
ClOrdID*	11	Clients order identifier
Side*	54	Valid value: B – As Defined

Field name	Tag	Comments
OrdType*	40	Valid value: 1 – Market
AvgPx	6	Average price of executed trades
ExecTransType	20	Value: 0 – New. Contains the value 3 for reports sent in response to OrderMassStatusRequest message
OrderID	37	Unique identifier for order. Generated by the Interface (for format see 5.1)
ExecID	17	Unique identifier for trade. Generated by the Interface (for format see 5.1). Value 0 is valid for reports sent in response to the OrderStatusRequest and OrderMassStatusRequest messages
TrdMatchID	880	Trade identifier in format [YYMMDD]-[Class code]-[Trade number]
Account	1	Trading account code
Currency	15	Price currency, if any; otherwise face value currency
ClientID	109	Client code
Text	58	Comment
UserText	9906	Users comment
TradeNum	5001	Trade number
TransactTime	60	Date and time of entering/canceling/execution in <YYYYMMDD-HH:MM:SS.sss> format
TradeDate	75	Trade date
OrderNum	5002	Order number
ExValue	5004	Trade value
DealSettlementCode	63	Settlement code in QUIK system format
TradeType	5014	Valid value: T – Standard transaction
TimeInForce*	59	Valid value: 1 – Good Till Cancel
SecurityExchange	207	Exchange identifier
SecurityType	167	Instrument type
UserID	5015	ID of the QUIK user that submitted the order
TradeTimeGMT	5017	Shift of the Interface local time relative to GMT
FirmId	5018	Diler ID in trade

Field name	Tag	Comments
ExchangeOrderID	5066	Exchange number of an order
MassStatusReqID	584	Client identifier of the OrderMassStatusRequest message
LastRptRequested	912	Attribute of the last report in the set of messages (Y) sent in response to the OrderMassStatusRequest message
OrderStatusReqID	790	Client identifier of the status request
OrigClOrdID	41	Client identifier of the transaction to be cancelled/replaced
RequestID	5060	Client transaction ID in the QUIK server
NoLegs	555	Valid value: 2
→LegSecurityID	602	Identifier of leg instrument
→LegSecurityIDSource	603	The type of leg instrument identifier specified in [602] LegSecurityID. Valid values: _ 1 – CUSIP; _ 2 – SEDOL; _ 4 – ISIN-number; _ 5 – RIC code; _ 6 – ISO code; _ 8 – exchange code; _ 100 – short name
→LegSide	624	Direction of a leg instrument trade. Valid values Valid values: _ 1 – Buy; _ 2 – Sell
→LegLastPx	637	Trade price of the leg instrument
→LegLastQty	1418	Trade quantity of the leg instrument
NoCommissions***	2639	Number of CommissionDataGrp groups [FIX 5.0 SP2]
→CommissionAmount***	2640	Commission value [FIX 5.0 SP2]
→CommissionAmountType***	2641	Commission type. Value: 2 – Broker [FIX 5.0 SP2]
OrdRejReason***	103	Error code for order rejection [FIX4.2+]
OrdRejSource****	5152	Source of the error which code is specified in the tag OrdRejReason [XML+]. Valid values: _ 1 – Trading system; _ 2 – QUIK server; _ 3 – Dealer library; _ 4 – QUIK gateway
ComplianceText****	2404	Text from reply to order registration transaction [XML+]

*** [FIX <N>] – tag is available for the FIX protocol version <N> or newer or if it is allowed in the scheme.

**** – tag is available if it is allowed in the scheme.

2.15 Trade Capture Report

2.15.1 OTC trade entry

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AE
FirmTradeID	1041	Client's trade identifier
TradeReportTransType	487	Valid value: 0 – New
TradeReportType	856	Valid values: _ 0 – Submit; _ 6 – Trade Report Cancel
TrdSubType	829	OTC trade type
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
LastQty	32	Trade quantity
LastPx	31	Trade price
NoSides	552	Value: 2
→ Side **	54	Valid values: _ 1 – buy; _ 2 – sell
→ NoPartyIDs	453	Value: 1
→→ PartyID	448	Valid values depending on the value of PartyRole: _ 1 – Broker's firm code; _ 17 – Partner's firm code
→→ PartyIDSource	447	Value: D
→→ PartyRole	452	Valid values: _ 1 – Executing Firm; _ 17 – Contra Firm
Text	58	Comment

Field name	Tag	Comments
SettlDate	64	Settlement date
SettlCode	63	Settlement code in QUIK format
TransactTime	60	Date and time of trade registration in <YYYYMMDD – HH:MM:SS> GMT format
PxQtyReviewed	7596	The attribute of disabling the validation of the price and quantity on the trading system part. Valid values: _ Y – do not check the price and quantity; _ N (by default) – check if there is no tag
SecondaryTradeID	1040	Exchange order identifier. Required for filling in cancellation of the past days orders
NoTrdRegPublications	2668	Number of TrdRegPublication groups
→TrdRegPublicationType	2669	Valid values: _ 0 – Pre-trade transparency waiver; _ 1 – Post-trade deferral
→TrdRegPublicationReason	2670	Valid values at TrdRegPublicationType(2669)=0: _ 0 – No preceding order in book as transaction price set within average spread of a liquid instrument; _ 1 – No preceding order in book as transaction price depends on system-set reference price for an illiquid instrument; _ 2 – No preceding order in book as transaction price is for transaction subject to conditions other than current market price; _ 3 – No public price for preceding order as public reference price was used for matching orders; _ 4 – No public price quoted as instrument is illiquid; _ 5 – No public price quoted as order is above standard market size. Valid values at TrdRegPublicationType(2669)=1: _ 6 – Deferral due to "Large in Scale"; _ 7 – Deferral due to "Illiquid Instrument"; _ 8 – Deferral due to "Size Specific"

2.15.2 Cancellation of OTC trade of current session (incoming message)

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AE

Field name	Tag	Comments
FirmTradeID	1041	Client's trade identifier
TradeID	1003	OTC trade identifier from the TradeCaptureReportAck message received
TradeReportTransType	487	Valid value: 0 – New
TradeReportType	856	Value: 6 – Trade Report Cancel
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2

2.15.3 Trade reporting (outgoing message)

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AE
PricingNo	9896	Main user identifier
UUID	9998	User identifier in the QUIK system
TradeReportID	571	Unique transaction identifirer
TradeReportTransType	487	Valid value: 0 – New
ExecType	150	Valid value: F – Trade – partial fill or fill
TradeDate	75	Trade date
TransactTime	60	GMT in <YYYYMMDD-HH:MM:SS.sss> format
BLPTicketType	9654	Valid value: DT – Direct Trade
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
NoSides	552	Valid value: 1
Side **	54	Valid values: _ 1 – buy; _ 2 – sell
OrderID	37	Unique identifier for Order as assigned by sell-side. ID is generated the Interface
Account	1	Trading account. For details on trading account identification see Administrator's manual, 2.10
SettlCurrency	120	Currency code of settlement denomination

Field name	Tag	Comments
		For OMS-orders: currency of calculations
LastPx	31	Price of this (last) fill
LastQty	32	Quantity (e.g. shares) bought/sold on this (last) fill
TradingSystemTicketNumber	9009	Transaction number in the QUIK system
ContractMultiplier	231	Lot size
NoPartyIDs	453	Number of PartyID groups
→ PartyID **	448	Valid values depending on the value of PartyRole: _ 1 – Firm code; _ 11 – Value which was specified in new order; _ 13 – Firm code in the order. These values are used together with additional key fields from PosKeys group for position identification
→ PartyIDSource	447	Valid value: D – Proprietary / Custom code
→ PartyRole	452	Valid values: _ 1 – Executing Firm; _ 11 – Order Origination Trader; _ 13 – Order Origination Firm
QtyType	854	Type of quantity specified in a quantity field. Valid values: _ 100 – Number Of Bonds (for obligations); _ 1 – Contracts (for futures and options); _ 0 – Units (for stocks)
SettlDate	64	Specific date of trade settlement
ExecID	17	Unique identifier of trade. Generated by the Interface. Value 0 is valid for reports sent in response to OrderStatusRequest
FirmNo	9999	Firm number

2.16 Trade Capture Report Ask

Response to client's requests for OTC trade entry and cancellation.

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AR
TradeID	1003	OTC trade identifier assigned by FIX adapter interface

Field name	Tag	Comments
FirmTradeID	1041	Client's trade identifier
TradeReportTransType	487	Value: 0 – New
TradeReportType	856	Valid values: _ 0 – Submit; _ 6 – Trade Report Cancel
TrdRptStatus	939	Valid values: _ 0 – Accepted; _ 1 – Rejected
Text	58	Text description of reason for cancellation of the request
SecondaryTradeID	1040	Trade exchange identifier. Required if TrdRptStatus=Accepted

2.17 Trade Capture Report Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AD
TradeRequestID	568	Trade capture report request ID
TradeRequestType*	569	Valid value: 1 – Matched trades
ClOrdID*	11	Unique identifier for Order

2.18 Order Cancel Reject

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: 9
OrigClOrdID	41	ClOrdID of replaced order
ClOrdID	11	Unique identifier for Order
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2

Field name	Tag	Comments
TransactTime	60	GMT in <YYYYMMDD-HH:MM:SS.sss> format
OrderID	37	Unique identifier for Order as assigned by sell-side. ID is generated by the Interface
OrdStatus	39	Order status. Valid values: _ 0 – New; _ 1 – Partially Fill; _ 2 – Fill; _ 4 – Canceled; _ 5 – Replaced; _ 6 – Pending Cancel; _ 8 – Rejected; _ E – Pending Replace
CxlRejResponseTo	434	Valid values: _ 1 – Order Cancel Request; _ 2 – Order Cancel Replace Request
Text	58	Free format text string if the trade system answer / clients comment
ContraBroker	375	Contra brokers code (only for two-sided orders [40=R])
ComplianceID	376	Reference (only for two-sided orders [40=R])
CxlRejReason	102	Valid values: _ 0 – Too late to cancel; _ 1 – Unknown order; _ 2 – Broker option; _ 3 – Already in pending state
CheckLotFlag	6201	Quantity is presented in lots or pieces. Valid values: _ 0 – disabled; _ 1 – enabled; _ 2 – enabled, check of the instrument lot size is enabled; _ 3 – disabled, check of the instrument lot size is enabled
ClientID	109	Client code of the order to be cancelled / replaced. The tag is available only if it is allowed in the scheme

2.19 Market Data Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: V

Field name	Tag	Comments
MDReqID*	262	Client identifier of the query
SubscriptionRequestType*	263	Subscription request type. Valid values: _ 0 – SNAPSHOT; _ 1 – SNAPSHOT_PLUS_UPDATES; _ 2 – DISABLE_PREVIOS
MarketDepth	264	Valid values: _ 0 – Full Book; _ 1 – Top of Book; _ N>1 – Best N Prices
MDUpdateType*	265	Market data subscription type. The tag must be filled, if SubscriptionRequestType=1. Valid values: _ 0 – Full Refresh; _ 1 – Incremental Refresh
NoMDEntryTypes	267	Number of [269] MDEntryType fields requested
→ MDEntryType **	269	Valid values: _ 0 – bid; _ 1 – offer; _ 2 – last; _ 3 – Index Value; _ 4 – open; _ 5 – close; _ 6 – settleprice; _ 7 – high; _ 8 – low; _ 9 – waprice; _ r – crossrate; _ s – real minstep; _ Q – auction clearing price; _ T – theor price; _ x – buydepo; _ y – selldepo; _ O – Official Current Price; _ o – Current Price; _ C – Official Close Price
Currency	15	Identifies currency used for price
NoRelatedSym	146	Specifies the number of repeating symbols specified. SecurityIDSource and SecurityID go with each instrument
→ <Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2

2.20 Market Data Request Reject

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: Y
MDReqID	262	Client identifier of the query
Text	58	Free format text string if the trade system answer / clients comment
MDReqRejReason	281	Code of the reason for the rejection of a Market Data request

2.21 Market Data Incremental Refresh

Supported tags:

Field name	Tag	Comments
* MsgType	35	Message type. Valid value: X
MDReqID	262	Client identifier of the query
TradeDate	75	Current trade date in format <YYYYMMDD>
NoMDEntries	268	Number of MDEntry groups in this message
→ MDUpdateAction **	279	Valid values: _ 0 – New; _ 1 – Change; _ 2 – Delete
→ MDEntryType	269	Valid values: _ 0 – bid; _ 1 – offer; _ 2 – trade; _ 3 – Index Value; _ 4 – open; _ 5 – close; _ 6 – settleprice; _ 7 – high; _ 8 – low; _ 9 – waprice; _ r – crossrate; _ s – real minstep; _ Q – Auction Clearing Price;

Field name	Tag	Comments
		_ T – theorprice; _ x – buydepo; _ y – selldepo; _ O – Official Current Price; _ o – Current Price
→ Yield	236	Yield of buy and sell quotes (for bonds) get from the Level II quotes table with depth different from 1
→ MDEntryPx	270	Price value of parameter from [269] tag
→ MDEntrySize	271	Quantity value of parameter from tag [269] MDEntryType. The tag is not sent if [279]=2
→ MDEntryTime	273	Time of market data entry
→ <Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
→ Currency	15	Currency of instrument
→ SettlCurrency	120	Related currency
→ TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
→ TotalVolumeTraded ***	387	Total quantity in all trades. [FIX 4.2]
→ TotalValueTraded	6143	The total volume of all trades
SecurityTradingStatus	326	Status of trading by the instrument. Valid values: _ 2 – Trading Halt, if status of trading session in QUIK is 'Suspended'; _ 17 – Ready to trade, if status of trading session in QUIK is 'Open'; _ 18 – Not Available for trading, if status of trading session in QUIK is 'Closed'; _ 100 – Closing; _ 101 – Opening; _ 102 – Auction; _ 103 – Closing Auction; _ 104 – Discrete Auction
TradingSessionID	336	Identifier of trading session. Valid values: _ CLOSE; _ OPEN; _ CLOSING; _ OPENING;

Field name	Tag	Comments
		_ AUCTION; _ CLOSING_AUCTION; _ DISCRETE_AUCTION; _ SUSPEND
→ MDEntryID	278	Anonymous trade number (if the value of tag [269] is 2)
→ TradeID	1003	The number of the anonymous trade. Is transmitted only if the value of tag [269] is 2 and the price transmission by the stream of anonymous trades is set up (the LastPxSource setting of the [General] section, (for more details, see the FIX Program Interface Administrator's manual)
→TradeVolume ***	1020	Anonymous trade volume. Is transmitted only if the value of tag [269] is 2. [FIX 4.4]
→AggressorSide***	2446	Anonymous trade direction. [FIX 5.0SP2+] Valid values: _ 1 – buy; _ 2 – sell. Is transmitted only if the value of tag [269] is 2 and the price transmission by the stream of anonymous trades is set up (the LastPxSource setting of the [General] section, for more details, see the FIX Program Interface Administrator's manual)
→BenchmarkCurveName ***	221	Indicator name. Transmitted only if the value of tag [269] is 2 and the price transmission by the stream of anonymous trades is set up (the LastPxSource setting of the [General] section, for more details, see the FIX program interface Administrator's manual) [FIX 4.4+]

*** [FIX <N>] – the tag is available for the FIX protocol version <N> or newer (if the version is specified) or if it is allowed in the scheme.

2.22 Market Data – Snap Shot / Full Refresh

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: W
MDReqID	262	Client identifier of the query

Field name	Tag	Comments
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
TotalVolumeTraded ***	387	Total quantity in all trades. [FIX 4.2]
TotalValueTraded	6143	The total volume of all trades
SecurityTradingStatus	326	Status of trading by the instrument. Valid values: _ 2 – Trading Halt, if status of trading session in QUIK is 'Suspended'; _ 17 – Ready to trade, if status of trading session in QUIK is 'Open'; _ 18 – Not Available for trading, if status of trading session in QUIK is 'Closed'; _ 100 – Closing; _ 101 – Opening; _ 102 – Auction; _ 103 – Closing Auction; _ 104 – Discrete Auction
TradingSessionID	336	Identifier of trading session. Valid values: _ CLOSE; _ OPEN; _ CLOSING; _ OPENING; _ AUCTION; _ CLOSING_AUCTION; _ DISCRETE_AUCTION; _ SUSPEND
TradeDate	75	Current trade date in format <YYYYMMDD>
TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
NoMDEntries	268	Number of MDEntry groups in this message
→ MDEntryType **	269	Valid values: _ 0 – bid; _ 1 – offer; _ 2 – trade; _ 3 – Index Value; _ 4 – open; _ 5 – close; _ 6 – settleprice; _ 7 – high;

Field name	Tag	Comments
		_ 8 – low; _ 9 – waprice; _ J – Null Book (in protocol version 5.0, if empty Level II Quotes table is ordered); _ r – crossrate; _ s – real minstep; _ Q – Auction Clearing Price; _ T – theorprice; _ x – buydepo; _ y – selldepo; _ O – Official Current Price; _ o – Current Price
→ Yield	236	Yield of buy and sell quotes (for bonds) get from the Level II Quotes table with depth different from 1
→ MDEntryPx	270	Price value of parameter from [269] tag
→ Currency	15	Identifies currency used for price
→ SettlCurrency	120	Related currency
→ MDEntrySize	271	Quantity value of parameter from [269] tag
→ MDEntryTime	273	Time of market data entry
→ MDEntryID	278	Anonymous trade number (if the value of tag [269] is 2)
→ TradeID	1003	The number of an anonymous trade. Is transmitted only if the value of tag [269] is 2 and the price transmission by the stream of anonymous trade is set up (the LastPxSource setting of the [General] section, for more details, see the FIX Program Interface Administrator's manual)
→TradeVolume***	1020	Anonymous trade volume. Is transmitted only if the value of tag [269] is 2. [FIX 4.4]
→AggressorSide ***	2446	Anonymous trade direction. [FIX 5.0SP2+] Valid values: _ 1 – buy; _ 2 – sell. Is transmitted only if the value of tag [269] is 2 and the price transmission by the stream of anonymous trades is set up (the LastPxSource setting of the [General] section, (for more details, see the FIX Program Interface Administrator's manual)
→BenchmarkCurve Name ***	221	Indicator name. Transmitted only if the value of tag [269] is 2 and the price transmission by the stream of anonymous trades is set up (the LastPxSource setting of the [General] section, for more details, see the FIX program interface Administrator's manual) [FIX 4.4+]

*** [FIX <N>] – the tag is available for the FIX protocol version <N> or newer (if the version is specified) or if it is allowed in the scheme.

Depending on the Interface settings using messages of this type will lead to the transmission of only best bid / best offers or best quotations. The number of lines is restricted by the settings. Every line of the Quotes table has a corresponding one in the message (Entry) of bid or offer types.

2.23 Security Definition Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: c
SecurityReqID*	320	Client identifier of a request
SecurityReqType*	321	Valid values: _ 0 – request for an instrument description; _ 3 – Request List Security Types
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2

2.24 Security Definition

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: d
SecurityReqID	320	Client identifier of request
SecurityResponseID	322	Unique identifier of the message for this request
SecurityResponseType	323	Valid value: 4 – List Security Types returned per request
TradeDate****	5085	Current trade date in format <YYYYMMDD> [XML]
TotalNumSecurities	393	The total number of instruments in the dictionary
NoRelatedSym	146	Number of securities in the current message
→ UnderlyingSymbol **	311	Underlying securitys symbol

Field name	Tag	Comments
→ UnderlyingIDSource	305	Valid value: 8 – exchange symbol
→ UnderlyingSecurityID	309	Underlying securitys SecurityID
→ UnderlyingSecurityDesc	307	Underlying securitys SecurityDesc
→ UnderlyingCurrency	318	Security currency
→ UnderlyingSecurityType	310	Valid values: _ FUT – futures; _ OPT – options; _ CS – other security types
→ UnderlyingSecurityExchange	308	Market code or class code, if the class is not included in the market
→ UnderlyingMaturityMonthYear	313	Can be used with standardized derivatives (futures and options)
→ RatioQty*****	319	Quantity of a particular leg in the security. [FIX 4.2]
→ UnderlyingPutOrCall	315	For options. Valid values: _ 0 – PUT; _ 1 – CALL
→ UnderlyingStrikePrice	316	For options
→ ScaleAndMinStep	312	<accuracy>-<price step>
→ SettlType	63	Settlement code in QUIK system format
→ SettlDate	64	Settlement date in <YYYYMMDD> format
→ SecurityDesc	107	Instrument full name
→ LowLimitPrice	1148	Minimum allowed price
→ HighLimitPrice	1149	Maximum allowed price
→ MinPriceIncrementAmount	1146	Price step value
→ Collateral	5038	Collateral
→ CollateralBuy	5039	Buyer's collateral
→ CollateralSell	5040	Seller's collateral
→ BaseAsset	5041	Code of base asset
→ BaseAssetClass	5042	Class code of base asset
→ FaceValue	5043	Face value
→ CouponValue	5044	Coupon value

Field name	Tag	Comments
→ AccruedInt	5045	ACI on a settlement date
→ BuyBackPrice	5046	Call price
→ BuyBackDate	5047	Call date
→ NextCouponDate	5048	Coupon expiration date
→ CouponPeriod	5049	Coupon period duration (in days)
→ YestMarketPrice	5050	Yesterday market price
→ IssueSize****	5086	Issue size [XML]
→ ClassName****	5087	Class name [XML]
→ DaysToMatDate****	5088	Time to maturity
→ SecurityName****	5089	Instrument full name and instrument class name in format: <Instrument name> <[Instrument class name]> [XML]
→ RegNumber****	5090	Registration number [XML]
→ StepPriceCurrency****	5091	Step price currency [XML]
→ SettlCurrency	120	Related currency
→ UnderlyingMaturityDate	542	Redemption date in <YYMMDD> format
→ QtyScale	5073	Quantity scale
→ NoLegs	555	Number of legs of multi-leg instruments
→→ LegSecurityID	602	Code of instrument of leg in QUIK
→→ LegSecurityIDSource	603	Instrument code in QUIK. Value: 8
→→ LegSecurityGroup	1594	Code of class instrument of leg
→→ LegSide	624	Direction of a leg instrument trade when performing a multi-leg instrument instrument purchase operation. Valid values: _ 1 – Buy; _ 2 – Sell
→→LegCashSettlDateUnadjusted	42299	Settlement date of instrument leg
→ AuctionType***, ****	5095	Auction type. [XML] Valid values: _ P – auction by price; _ CR – auction by coupon rate
→ DescriptionRu***, ****	5096	Name in Russian [XML]

Field name	Tag	Comments
→ DescriptionEn*, ****	5097	Name in English [XML]
→ OfferingPrice*, ****	5098	Offering price [XML]
→ MinCouponRate*, ****	5099	Minimum coupon rate [XML]
→ MaxCouponRate*, ****	5100	Maximum coupon rate [XML]
→ FinCouponRate*, ****	5101	Final coupon rate [XML]
→ OrderPlacementMode*, ****	5102	Order submitting mode. [XML] Valid values: _ A – automatically; _ CS – on client command
→ NoPhases*, ****	5103	Amount of submitting phases [XML]
→→ PhaseID*, ****	5104	Phase identifier. [XML] Valid values: _ 1 – order collecting phase; _ 2 – order processing phase; _ 3 – order submitting phase
→→ PhaseStartDt*, ****	5105	Date and time of phase start in UTC format (<YYYYMMDD-HH:MM:SS>) [XML]
→→ PhaseEndDt*, ****	5106	Date and time of phase end in UTC format (<YYYYMMDD-HH:MM:SS>) [XML]
→ComplexProductType****	5108	Type of a complex financial product [XML]
→ExecutionDate****	5109	Instrument execution date. Transmitted only for derivatives [XML]
→ExDestination	100	Class code
→PriceType****	423	Price type. [XML] Valid values: _ 1 – as a percentage of face value; _ 2 – per unit of a financial instrument
→BaseCurrency****	5139	Base currency
→TermCurrency****	5140	Quoted currency
→ContractTerm****	5162	Contract term [XML+]
→CFICode*****	461	CFI code of security [FIX 4.4+]
→PrevClosePx****	140	Previous close price [XML+]

*** – parameters are transmitted only for the Bookbuilding Module instruments.

**** – the tag is available only if it is allowed in the scheme.

***** [FIX <N>] – the tag is available for the FIX protocol version <N> or newer (if the version is specified) or if it is allowed in the scheme.

2.25 Order Status Request

Supported tags:

Field name	Tag	Comments
* MsgType	35	Message type. Valid value: H
ClOrdID	11	Unique identifier for Order
OrderID	37	Unique identifier for Order. Generated by the Interface (for format, see 5.1)
OrderStatusReqID	790	Order identifier
SecurityIDSource	22	Method of security identification. Valid values: _ 1 – CUSIP; _ 2 – SEDOL; _ 4 – ISIN-number; _ 5 – RIC code; _ 6 – ISO code; _ 8 – exchange code; _ 100 – short name; _ 101 – registration number

2.26 Order Mass Status Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AF
MassStatusReqID*	584	Clients identifier of the request
MassStatusReqType*	585	Value: 7 – Status for all orders

2.27 Security Status Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: e
SecurityStatusReqID*	324	Unique ID of a Security Status Request message
SubscriptionRequestType*	263	Subscription request type. Valid values: _ 1 – SNAPSHOT_PLUS_UPDATES; _ 2 – DISABLE_PREVIOS
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2

2.28 Security Status

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: f
SecurityStatusReqID	324	Unique ID of a Security Status Request message
UnsolicitedIndicator	325	Indicates whether or not message is being sent as a result of a subscription request or not. Valid value: Y
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
SecurityExchange	207	Market used to help identify a security
SecurityType	167	Indicates type of security
SettlDate	64	Settlement date in <YYYYMMDD> format
MaturityMonthYear	200	Month and Year of redemption in <YYYYMM> format for reports on execution of futures
MaturityDay	205	Day of redemption date in DD format for reports on execution of futures
PutOrCall	201	Indicates whether an Option is for a put or call. Valid values: _ 1 – call; _ 0 – put

Field name	Tag	Comments
StrikePrice	202	Option strike price
Currency	15	Identifies currency used for price
SecurityTradingStatus	326	Identifies the trading status applicable to the transaction. Valid values: _ 2 – Trading Halt, if trading status in QUIK is Frozen; _ 17 – Ready to trade, if trading status in QUIK is Opened; _ 18 – Not Available for trading, if trading status in QUIK is Closed; _ 100 – Closing; _ 101 – Opening; _ 102 – Auction; _ 103 – Closing Auction; _ 104 – Discrete Auction
TradingSessionID	336	Status of trading session. Valid values: _ CLOSE; _ OPEN; _ CLOSING; _ OPENING; _ AUCTION; _ CLOSING_AUCTION; _ DISCRETE_AUCTION; _ SUSPEND
TradingSessionSubID	625	The tag contains the string value of the Exchange status of trading session (tradingphase) parameter. The set of possible values is specific for each trading interface
HighPx	332	Represents an indication of the high end of the price range for a security prior to the open or reopen
LowPx	333	Represents an indication of the low end of the price range for a security prior to the open or reopen
LastPx	31	Price of last fill
NextTradingPeriodStartTime***	5160	Start time of next trading period, in <HH:MM:SS> format. Transmitted for instruments of the Specialized auctions module [XML+]
NextTradingPeriod***	5161	Next trading period. Transmitted for instruments of the Specialized auctions module [XML+]
MinOrderAmt***	5163	Minimum order amount. Transmitted for instruments of the Specialized auctions module [XML+]

Field name	Tag	Comments
MaxOrderAmt***	5164	Maximum order amount. Transmitted for instruments of the Specialized auctions module [XML+]
MaxNumberOfOrdersFromParticipant***	5165	Maximum number of orders from 1 participant. Transmitted for instruments of the Specialized auctions module [XML+]
OpenAuctionIndicator***	5166	Open auction indicator. Valid values: _ N – No; _ Y – Yes. Transmitted for instruments of the Specialized auctions module [XML+]

*** – the tag is available only if it is allowed in the scheme.

2.29 User Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: BE
UserRequestID*	923	User request ID
UserRequestType*	924	User request type. Valid values: _ 1 – Log On User; _ 2 – Log Off User; _ 3 – Change Password For User
UserName*	553	User name
Password*	554	Current password
NewPassword	925	New password (only for UserRequestType=3)

2.30 User Response

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: BF
UserRequestID	923	User request ID

Field name	Tag	Comments
UserName	553	User name
UserStatus	926	User status. Valud values: _ 1 – Logged In; _ 2 – Not Logged In; _ 3 – User Not Recognized; _ 4 – Password Incorrect; _ 5 – Password Changed
UserStatusText	927	Text status or error description (depending on the UserStatus value)

2.31 Request for Positions

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AN
PosReqID*	710	Client identifier of request
PosReqType*	724	Valid value: 0 – Positions
SubscriptionRequestType*	263	Subscription type. Valid values: _ 0 – SNAPSHOT; _ 1 – SNAPSHOT_PLUS_UPDATES; _ 2 – DISABLE_PREVIOS_SNAPSHOT_PLUS_UPDATES
NoPartyIDs	453	Number of PartyID groups. If used, the value is 2
→ PartyID **	448	Valid values depending on the PartyRole value: _ 3 – client code for cash and instrument positions; _ 13 –firm code; _ 38 – trading account for futures restrictions and positions
→ PartyIDSource	447	Valid value: D – Proprietary / Custom code
→ PartyRole	452	Valid values: _ 3 – ClientID; _ 13 – Order Origination Firm; _ 38 – Position account

2.32 Request for Positions Ack

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AO
PosMaintRptID	721	Unique reply identifier. Parameter is generated in format "RfPA<N>", where N – integer growing number
PosReqID	710	Client identifier of request
PosReqType	724	Valid value: 0 – Positions
PosReqResult	728	Valid values: _ 0 – Valid request; _ 1 – Invalid or unsupported request
PosReqStatus	729	Valid values: _ 0 – Completed; _ 2 – Rejected
Text	58	Text description of reason for rejection
TotalNumPosReports	727	Total number of 'Position Report' messages that will be sent for Request for Positions with Snapshot subscription type (tag 263=0)

2.33 Position Report

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AP
PosMaintRptID	721	Unique reply identifier. Parameter is generated in format "RfPA<N>", where N – integer growing number
PosReqID	710	Client identifier of request
PosReqType	724	Valid value: 0 – Positions
UnsolicitedIndicator	325	Valid value: N
ClearingBusinessDate	715	Current trading date in <YYYYMMDD> format
NoPartyIDs	453	Number of PartyID groups
→PartyID **	448	Valid values depending on the value of PartyRole:

Field name	Tag	Comments
		_ 3 – Client code for spot positions; _ 13 – Firm code; _ 38 – Trading account for futures positions. These values are used together with additional key fields from PosKeys group for position identification
→PartyIDSource	447	Valid value: D – Proprietary / Custom code
→PartyRole	452	Valid values: _ 3 – ClientID; _ 13 – Order Origination Firm; _ 37 – Position account
NoPositions	702	Positions number in message
→PosType **	703	Position type: _ ML – Spot money position; _ DL – Spot instrument position; _ FL – Futures limit on client account; _ FP – Futures position on client account
→PosUpdateAction	5024	Valid values: _ 0 – New (position was created/received for the first time); _ 1 – Change (values of position fields were modified); _ 2 – Delete (position was deleted)
→NoPosKeys	5025	Number of position key fields
→→PosKeyType **,***	5026	Type of position key field: _ CUR – Currency (ML, FL); _ TAG – Position code (ML); _ SEC – Instrument code (DL, FP); _ ACC – Trading account (DL); _ FLT – Futures position type (FL); _ KIND – Settlement period of cash / instrument position (ML, DL); _ STLDATE – Settlement date (ML, DL)
→→PosKeyValue	5027	The tag has corresponding numerical and string value for all position key fields besides FLT and STLDATE. Valid values: If PosKeyType = STLDATE, the value is displayed in the following form: _ YYYY.MM.DD – Settlement date position. If PosKeyType = FLT: _ MONEY – money; _ DEPOSIT_MONEY – secured money; _ DEPOSIT_MONEY_FOREIGN_CURR – Deposit funds in foreign currency; _ DEPOSIT_MONEY_FOREIGN_CURR_RUB – Total deposit funds in foreign currency (in rubles);

Field name	Tag	Comments
		_ CLEARING_MONEY – clearing money; _ DEPOSIT_CLEARING_MONEY – clearing secured money; _ SPOT_OPEN_POS – limit for open positions at spot market; _ AGG – for aggregated capital
→NoPosItems	5028	Number of position fields
→→PosItemType **	5029	Type of position field ***. Valid values: _ OPEN_BAL – Open balance (ML, DL); _ OPEN_LIM – Open limit (ML, DL); _ CUR_BAL – Current balance (ML, DL); _ CUR_LIM – Current limit (ML, DL); _ LOCKED – Locked (ML, DL); _ AVG_POS_PRICE – WA.position price (DL); _ AVG_POS_PRICE_CCY – Position WAP currency (DL); _ LIQUID_FACTOR – Liquidity coefficient (FL); _ PREV_OPEN_POS_LIM – Previous limit of open positions (FL); _ CUR_OPEN_POS_LIM – Open position limit (FL); _ CUR_NET_POS – Current net position (FL, FP); _ CUR_NET_POS_ORD – Current net position for orders (FL); _ CUR_NET_POS_OPEN_POS – Current net position for open positions (FL); _ PLAN_NET_POS – Plan net positions (FL, FP); _ VAR_MARGIN – Variation margin (FL, FP); _ ACCRUED_INC – Accrued income (FL); _ OPTION_PREMIUM – Option premium (FL); _ TS_COMM – Exchange fees (FL); _ KGO – Coefficient of client guarantee (FL); _ FP_ACC_GROUP_TYPE – Client account group type (FP); _ START_LONG_POS – Open long position (FP); _ START_SHORT_POS – Open short position (FP); _ START_NET_POS – Open net position (FP); _ CUR_LONG_POS – Current long position (FP); _ CUR_SHORT_POS – Current short position (FP); _ OPEN_LONG – Active purchase (FP); _ OPEN_SHORT – Active sell (FP); _ CUR_NET_POS_EVAL – Estimation of current net position (FP); _ EFFECT_POS_PRICE – Effective position price (FP)
→→PosItemValue	5030	The tag has corresponding number or string value for all the types of position fields besides FP_ACC_GROUP_TYPE. Valid values, if PosItemType = FP_ACC_GROUP_TYPE: _ NO_GROUP – Without groups; _ ONLY_MAIN – Main account; _ ONLY_CLIENT – Client and additional accounts; _ ALL – All accounts of trade parties

Field name	Tag	Comments
StreamPhaseIndicator****	5110	Marker of the position stream transmission phase. [XML] Valid values: _ PS – message in a snapshot; _ ES – last message in a snapshot; _ OU – update on position state after a snapshot is fully sent

*** – position type corresponding to the field value is given in brackets after value description.

**** – the tag is available if it is allowed in the scheme.

2.34 Quote Request

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: R
ClientID	109	Client code
QuoteReqID	131	Client identifier of a request
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
OrderQty	38	Volume of quotes requested
Account	1	Trading account
Side	54	Type of request for quotes. Valid values: _ 0 – two-sided; _ 1 – buy; _ 2 – sell
FutSettDate	64	Settlement date
Currency	15	Currency of the quantity
SecurityType	167	Type of security. Valid values: _ FXSPOT; _ FXFWD; _ FXNDF; _ FXFLEXFWD
StartDate	5142	FXFLEXFWD (Flexible Forward) contract start date in the format <YYYYMMDD>
QuoteType	5082	Quote type

Field name	Tag	Comments
VenueClassCode	5143	Exchange class. Required tag when placing an OMSFX class order
DealerBook	5144	Dealer book

2.35 Quote Request Reject

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: AG
QuoteReqID	131	Client identifier of a rejected request
QuoteRequestRejectReason	658	Valid value: 99 – Other
Text	58	Reason for request reject

2.36 Quote

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: S
QuoteReqID	131	Client identifier of a request
QuoteID	117	Request identifier in the SOR module
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
OrderQty	38	Volume of quotes requested
BidSize	134	Volume of buy quotes requested
OfferSize	135	Volume of sell quotes requested
BidPx	132	Price of a buy quote
OfferPx	133	Price of a sell quote
Account	1	Trading account
FixingDate	541	Fixing date

Field name	Tag	Comments
FutSettDate	64	Settlement date
Currency	15	Currency of the quantity
SecurityType	167	Type of security
QuoteType	5082	Quote type
QuoteCondition	276	Price status of quotes. Valid values: _ A – Open / Tradeable; _ B – Closed / Indicative
BidSpotRate	188	Bid spot rate
OfferSpotRate	190	Offer spot rate
BidForwardPoints	189	Bid forward points
OfferForwardPoints	191	Offer forward points

2.37 Quote Cancel

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: Z
QuoteReqID	131	Client identifier of a rejected request
QuoteCancelType	298	Valid value: 1 – Cancel for Symbol(s)

2.38 Quote Status Report

Supported tags:

Field name	Tag	Comments
MsgType*	35	Message type. Valid value: Al
QuoteReqID	131	Client identifier of a rejected request
QuoteID	117	Request identifier in the SOR module
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2

Field name	Tag	Comments
OrderQty	38	Volume of quotes requested
BidSize	134	Volume of buy quotes requested
OfferSize	135	Volume of sell quotes requested
BidPx	132	Price of a buy quote
OfferPx	133	Price of a sell quote
QuoteStatus	297	Valid values: _ 0 – Accepted; _ 1 – Canceled for Symbol(s); _ 6 – Removed from Market; _ 9 – Quote Not Found
QuoteCancelType	298	Valid value: 1 – Cancel for Symbol(s)
Text	58	Reason for request reject

2.39 Indication of Interest (IOI)

Supported tags:

Field name	Tag	Comments
MsgTypeIOIID*	35	Message type. Valid value: 6
IOIID	23	Unique identifier of message. Filled by incremental counter unique within the session for all IOI messages. Value is reset to 1 each time when establishing a FIX session
IOITransType	28	Valid values: _ N – New (for the first quotes for the instrument in current session or when transmitting is resumed after zeroing); _ R – Replace (for the last quotes); _ C – Cancel (when zeroing quotes or finishing a session/Interface stop)
IOIRefID	26	Identifier of the previous message for the instrument. Filled if IOITransType=R, C
<Instrument>		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
Side	54	Direction of quote. Valid values: _ 1 – buy; _ 2 – sell

Field name	Tag	Comments
IOIShares	27	Quantity of quote
Price	44	Price of quote
Currency	15	Instrument currency
NoIOIQualifier	199	Number of qualifiers of quote. Value: 2
→IOIQualifier **	104	Valid values: _ A – All Or None; _ P – Taking a position
NoRoutingIDs	215	Number of identifiers of recievers
→RoutingType **	216	Value: _ 2 – Target List
→RoutingID	217	Value corresponding to the instrument class in section [for more information contact QUIK support technical service)
SenderSubID	50	The value of the same name setting of the [for more information contact QUIK support technical service)

2.40 Quote Acknowledgment

2.40.1 Client notification about request rejection

Supported tags:

Field name	Tag	Comments
MsgType*	35	Type of message. Value: b
QuoteReqID	131	Client`s identifier of request
QuoteAckStatus	297	Value:5 – Rejected
Text	58	Rejection reason

2.40.2 Client request to terminate a translation of quotes

Supported tags:

Field name	Tag	Comments
MsgType*	35	Type of message. Value: b

Field name	Tag	Comments
QuoteReqID	131	Client`s identifier of request

2.41 QUIK Session Change Request

> **The message is only available for the FIX adapter program interface with transactions limits (QUIKFIXBE).**

Supported tags:

Name	Tag	Comments
SessionChangeReqID*	5113	Client identifier of the request for session status change
ExDestination*	100	Class code in QUIK
SecurityID	48	Instrument code in QUIK
SessionOperation	5114	Operation code. If this tag is missing or have the value not supported by the Interface, a response message will have the list of supported values
CancelActiveOrders	5115	Indicates whether active orders have to be cancelled. Valid values: _ Y – yes; _ N (by default) – no

2.42 QUIK Session Change Response

> **The message is only available for the FIX adapter program interface with transactions limits (QUIKFIXBE).**

Supported tags:

Name	Tag	Comments
SessionChangeReqID*	5113	Client identifier of the request for session status change
SessionChangeReqStatus*	5116	Request result. Valid values: _ 0 – request completed; _ 1 – request rejected by the Interface; _ 2 – request rejected by the QUIK server or the Interface

Name	Tag	Comments
Text	58	Text diagnostics of request result
NoSessionOperations	5117	Number of SessionOperationGrp groups. A set of groups that are supported by the session control operation. Transmitted if the request was rejected due to unspecified or unsupported operation code
→ SessionOperation	5114	Operation code
→ SessionOperationDescription	5118	Operation description

2.43 POS Order Allocation Request

Supported tags:

Name	Tag	Comments
AllocationReqID*	5119	Client identifier of the request for allocations
OrderID*	37	Order unique identifier. Generated by the Interface (for the format, see 5.1)
OrderQty*	38	New quantity of an order

2.44 POS Security Allocation Request

Supported tags:

Name	Tag	Comments
AllocationReqID*	5119	Client identifier of the request for allocations
<Instrument>*		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
AllocationPercentage	5120	Allocation percentage
AllocationQty	5121	Allocation quantity

2.45 POS Allocation Response

Supported tags:

Name	Tag	Comments
AllocationReqID*	5119	Client identifier of the request for allocations
AllocationReqStatus*	5132	Request result. Valid values: _ 0 – request completed; _ 1 – request rejected by the Interface; _ 2 – request rejected by the QUIK server or the Interface
Text	58	Text diagnostics of request result
<Instrument>*		Set of fields describing an instrument. For the description of the <Instrument> component block, see 5.2
NoOrders*	73	Number of AllocatedOrderGrp groups
→ OrderID	37	Order unique identifier. Generated by the Interface (for the format, see 5.1)
→ OrderSizeEntryType	5122	Type of order size. Valid values: _ Q – quantity; _ V – volume
→ OrderSizePriorToAllocation	5123	Order size before allocation is applied
→ OrderSizeAfterAllocation	5124	Order size after allocation is applied

3. Correspondences of OMS order client statuses

The following table has OMS order client statuses and values of OrdStatus tag from Execution Report message correspondent to them:

OMS order status	OrdStatus
New	Pending New
Active	Valid values: _ New – for a new order; _ Replaced – for a replaced order
Rejected	Rejected

OMS order status	OrdStatus
Replace Request	Pending Replace
Cancel Request	Pending Cancel
Canceled	Canceled
Filled	Valid values: _ Filled – for a fully executed order; _ Done For Day – for a partially executed order

4. Diagnostics of request rejection

4.1 New Order Single

Diagnostics	Description
ClOrdId is empty	Client order identifier (tag [11]) is not specified
ClOrdId is not unique	Client order identifier (tag [11]) is duplicated within the session
Unsupported type of HandlInst. Valid values: 1, 3	Unsupported value of tag [21] is sent
OMS class is not found	OMS class is not found
OMS class description is not found	Reference to the file with OMS class description is not specified or specified incorrectly
Unsupported algorithm	Reference to the file with algo class description is not specified or specified incorrectly
NEW_ORDER transaction is not defined for OMS class	OMS class description does not content description of new order transaction
NEW_ORDER transaction is not defined for algorithm	Algo class description does not content description of new order transaction
Unsupported type of OrderRestrictions. Valid values: 5	Unsupported value of tag [529] is sent
Unknown ExDestination [<EXDEST>]	Value of tag [100] is not neither a class code or an exchange code
Unknown RIC-code [<RIC>]	There is no corresponding ISIN code for the RIC code sent
ExpiryDate isn't supported for board «<CLASS>»	The transaction interface of the <CLASS> class does not allow to transmit the order expiration date

Diagnostics	Description
ExpiryTime isn't supported for board «<CLASS>»	The transaction interface of the <CLASS> class does not allow to transmit the order expiration time
Unsupported value of tag22 [IDSource]. Valid values: 1, 2, 4, 6, 8, 100	Unsupported value of tag [22] is sent
Specified security is not found [<SECID>]	Instrument could not be found
Ambiguously security specification	More than one instrument corresponds with the received instrument identifier. Class code or exchange code must be specified
Security is locked now, try later	Instrument identifier at the QUIK server is unknown at the moment – there is no connection with the server
Trading by specified class is unavailable	Trading operations with the current class are prohibited by the settings (classes option in the [quik] section)
Makler transaction for class <CLASS> is not available	Makler transaction for the class is not found
Unsupported type of OrdType. Valid values: 1, 2, 3, 4 and R	Unsupported value of tag [40] is sent
ContraBroker is not defined	Partner is not specified (for address orders)
Stop-orders for class <CLASS> are not available	Stop orders with the current class are unavailable
StopPx is not specified	Stop price is not specified
Unsupported type of TimeInForce. Valid values: 0, 1, 2, 3, 4, 6 and X	Unsupported value of tag [59] is sent
Unsupported type of Side. Valid values: 1 and 2	Unsupported value of tag [54] is sent
Nominal value of security is undefined	Nominal value of the instrument is not specified (for obligations only)
Invalid OrderQty(<QTY>): Nominal(<NOMINAL>) is not respected	The received order value is not divisible by the nominal value (for obligations only)
Invalid OrderQty(<QTY>): LotSize(<LOTSIZE>) is not respected	The received order quantity in items is divisible into the lot size
Iceberg-orders are not supported for specified security	Iceberg orders are unavailable for the current class

Diagnostics	Description
Undescripted QuikApi-Error	The transaction is rejected by the QuikApi library, but error description is not received
Value [<VALUE>] is unsupported for transaction field [<FIELD>]	The received value of the countable transaction field is not supported
Rejected due to schema-level restriction	The request is rejected according to the restriction specified on the scheme level
Specified SettleDate is not allowed	Specified settlement date is not allowed
Unsupported PegOffsetType	Unsupported value of tag [836] is received
Unsupported DiscretionOffsetType	Unsupported value of tag [842] is received
Invalid OrderQty(<ORDERQTY>): Must be integer	Unsupported value of tag [38] is received
SecurityType [<NNNN>] isn't supported. Valid values: FXSPOT, FXFWD, FXNDF.	Unsupported value of tag [167] is received
SecurityType [<FXSPOT>] isn't supported for security [<FXClass_USDRUB>]. Supported value: FXNDF.	Unsupported by the instrument value of tag [167] is received

4.2 Order Cancel Request

Diagnostics	Description
ClOrdId is empty	Client order identifier (tag [11]) is not specified
ClOrdId is not unique	Client order identifier (tag [11]) is duplicated within the session
Order is not found by OrigClOrdID: <ORIGCLORDID>	The order to be cancelled is not found by OrigClOrdID
SessionID mismatch, cancel is impossible	Session identifier assigned for the order while entering differs from the current one (for OMS only)
OMS class description is not found	Reference to the file with OMS class description is not specified or specified incorrectly
Unsupported algorithm	Reference to the file with algo class description is not specified or specified incorrectly
Unsupported algorithm class	Algo class corresponding to the algorithm is not found

Diagnostics	Description
Trading by specified class is unavailable	Trading operations with the current class are prohibited by the settings (classes option in the [quik] section)
Order is already in pending cancel status	Order is already in pending cancel status
Order is already in pending replace status	Order is already in pending replace status
Order is already canceled	Order is already canceled
Order is already expired	Order is already expired
Order is done for day	Order execution is already confirmed
Order is in replaced status	Order is already replaced
OrderQty is invalid	The received quantity differs from the quantity to be cancelled
Nominal value of security is undefined	Nominal value of the instrument is not specified (for obligations only)
Invalid OrderQty(<QTY>): Nominal(<NOMINAL>) is not respected	The received order value is not divisible by the nominal value (for obligations only)
Invalid OrderQty(<QTY>): LotSize(<LOTSIZE>) is not respected	The received order quantity in items is divisible into the lot size
Side is invalid	The received direction is not coincide with the order to be cancelled
Unsupported type of Side. Valid values: 1 and 2	Unsupported value of tag [54] is sent
OrdType is invalid	The received order type is not coincide with the type of order to be cancelled
Undescripted QuikApi-Error	The transaction is rejected by the QuikApi library, but error description is not received

4.3 Order Cancel Replace Request

Diagnostics	Description
ClOrdId is empty	Client order identifier (tag [11]) is not specified
ClOrdId is not unique	Client order identifier (tag [11]) is duplicated within the session
Order is not found by OrigClOrdID: <ORIGCLORDID>	The order to be cancelled is not found by OrigClOrdID

Diagnostics	Description
Unsupported type of HandlInst. Valid values: 1, 3	Unsupported value of tag [21] is sent
OMS class is not found	OMS class is not found
OMS class description is not found	Reference to the file with OMS class description is not specified or specified incorrectly
Unsupported algorithm	Reference to the file with algo class description is not specified or specified incorrectly
Unsupported algorithm class	Algo class corresponding to the algorithm is not found
REPLACE_ORDER transaction is not defined for OMS class	OMS class description does not have transaction for order replacement
CHANGE_ORDER transaction is not defined for algorithm	Algo class description does not have transaction for order replacement
Unknown ExDestination [<EXDEST>]	Value of tag [100] is not neither a class code or an exchange code
Unknown RIC-code [<RIC>]	There is no corresponding ISIN code for the RIC code sent
Unsupported value of tag22 [IDSource]. Valid values: 1, 2, 4, 6, 8, 100	Unsupported value of tag [22] is sent
Specified security is not found [<SECID>]	Instrument could not be found
Ambiguously security specification	More than one instrument corresponds with the received instrument identifier. Class code or exchange code must be specified
Security is locked now, try later	Instrument identifier at the QUIK server is unknown at the moment – there is no connection with the server
Trading by specified class is unavailable	Trading operations with the current class are prohibited by the settings (classes option in the [quik] section)
Amendment of orders is not allowed	Order replacement is prohibited by the settings
Wrong HandlInst for OMS-order replace	Unsupported value of tag [21] is sent (OMS only)
SessionID mismatch, replace is impossible	Session identifier assigned for the order while entering differs from the current one (for OMS only)
Amendment of address orders is not allowed	Address order replacement is not supported
Order is already in pending cancel status	Order is already in pending cancel status

Diagnostics	Description
Order is already in pending replace status	Order is already in pending replace status
Order is done for day	Order execution is already confirmed
Too late to cancel	Order is already cancelled or replaced
Side is invalid	The received direction is not coincide with the order to be replaced
Unsupported type of Side. Valid values: 1 and 2	Unsupported value of tag [54] is sent
Security is invalid	The received instrument differs from the instrument of order to be replaced
Unsupported type of TimeInForce. Valid values: 0, 1, 2, 3, 4, 6 and X	Unsupported value of tag [59] is sent
Unsupported type of OrdType. Valid values: 1, 2, 3, 4 and R	Unsupported value of tag [40] is sent
OrdType mismatch	It was an attempt to replace a stop order by a standard order or vice versa
Stop-order type mismatch	The received stop order type is not coincide with the type of stop order to be replaced
Nominal value of security is undefined	Nominal value of the instrument is not specified (for obligations only)
Invalid OrderQty(<QTY>): Nominal(<NOMINAL>) is not respected	The received order value is not divisible by the nominal value (for obligations only)
Invalid OrderQty(<QTY>): LotSize(<LOTSIZE>) is not respected	The received order quantity in items is divisible into the lot size
Iceberg-orders are not supported for specified security	Iceberg orders are unavailable for the current class
Order cannot be reopened	Replacement of executed orders is prohibited by the settings
OrderQty is invalid	The received quantity is less than the executed quantity of the order to be replaced
Unable to reopen filled order – new value of OrderQty must be greater than previous	The received quantity is less or equal to the executed quantity of the order to be replaced
ServiceField is too long	The summary length of values of tag [100] and [207] is longer than the corresponding transaction field (for OMS only)

Diagnostics	Description
Undescripted QuikApi-Error	The transaction is rejected by the QuikApi library, but error description is not received
Rejected due to schema-level restriction	The request is rejected according to the restriction specified on the scheme level
Specified SettleDate is not allowed	Specified settlement date is not allowed
Unsupported PegOffsetType	Unsupported value of tag [836] is received
Unsupported DiscretionOffsetType	Unsupported value of tag [842] is received

5. APPENDIX

5.1 The format of filling the order cancel / replace request

The list of tags:

Field name	Tag	Comments
OrderID	37	<[Order registration date]-[Class code]-[Order number]>, where: _ [Order registration date] * is the date of order registration in the current session, even if the local time zone of the computer, on which the Interface is installed, shifted to the next data on order registration The maximum permissible length of the identifier is 40 characters
ExecID	17	For report on execution: <[Class code]-[Fill identifier in Base62]-[B/S]-[Number of revision]-[Link revision]-[N/C]> The maximum permissible length of the identifier is 32 characters For reports on changes of order status: <[Current date]*-[Class code]-[Order number in Base62]-[ExecType]-[TimeStamp in Base62]> The maximum permissible length of the identifier is 39 characters

* – the format of the date is <YYMMDD>

5.2 <Instrument> component block

The following tags are supported:

Field name	Tag	Comments
Symbol	55	Instrument short name
IDSource*	22	Method of instrument identification. Valid values: _ 1 – CUSIP; _ 2 – SEDOL; _ 4 – ISIN-number; _ 5 – RIC code; _ 6 – ISO code; _ 8 – exchange code; _ 100 – short name; _ 101 – registration number
SecurityID*	48	For details on instrument identification, see Administrator's manual, 2.8
ExDestination	100	For details on instrument identification, see Administrator's manual, 2.8
Tenor	6215	Tenor. Is optionally used for FX instrument identification

* – the tags which are necessary to be filled.