

Linux and Unix xargs command tutorial with examples

Tutorial on using xargs, a UNIX and Linux command for building and executing command lines from standard input. Examples of cutting by character, byte position, cutting based on delimiter and how to modify the output delimiter.

Estimated reading time: 3 minutes

Table of contents

- [What is the xargs command in UNIX?](#)
- [How to use xargs](#)
- [How to use xargs with find](#)
- [xargs v exec](#)
- [How to print commands that are executed](#)
- [How to view the command and prompt for execution](#)
- [How to run multiple commands with xargs](#)
- [Further reading](#)

```
XARGS(1)                General Commands Manual                XARGS(1)

NAME
  xargs - build and execute command lines from standard
  input
```

What is the xargs command in UNIX?

The **xargs** command in UNIX is a command line utility for building an execution pipeline from standard input. Whilst tools like **grep** (<https://shapedshed.com/unix-grep/>) can accept standard input as a parameter, many other tools cannot. Using **xargs** allows tools like **echo** and **rm** (<https://shapedshed.com/unix-rm/>) and **mkdir** (<https://shapedshed.com/unix-mkdir/>) to accept standard input as arguments.

How to use xargs

By default **xargs** reads items from standard input as separated by blanks and executes a command once for each argument. In the following example standard input is piped to xargs and the **mkdir** command is run for each argument, creating three folders.

```
echo 'one two three' | xargs mkdir
ls
one two three
```

When filenames contains spaces you need to use -d option to change delimiter

```
ls 'one two three.txt' 'four.txt' find . -name '*.txt' | xargs -d '\n' rm
```

How to use xargs with find

The most common usage of `xargs` is to use it with the `find` (<https://shapedshed.com/unix-find/>) command. This uses `find` to search for files or directories and then uses `xargs` to operate on the results. Typical examples of this are changing the ownership of files or moving files.

`find` and `xargs` can be used together to operate on files that match certain attributes. In the following example files older than two weeks in the `tmp` folder are found and then piped to the `xargs` command which runs the `rm` command on each file and removes them.

```
find /tmp -mtime +14 | xargs rm
```

xargs v exec

The `find` command supports the `-exec` option that allows arbitrary commands to be performed on found files. The following are equivalent.

```
find ./foo -type f -name "*.txt" -exec rm {} \;  
find ./foo -type f -name "*.txt" | xargs rm
```

So which one is faster? Let's compare a folder with 1000 files in it.

```
time find . -type f -name "*.txt" -exec rm {} \;  
0.35s user 0.11s system 99% cpu 0.467 total  
  
time find ./foo -type f -name "*.txt" | xargs rm  
0.00s user 0.01s system 75% cpu 0.016 total
```

Clearly using `xargs` is far more efficient. In fact [several](https://danielmiessler.com/blog/linux-xargs-vs-exec/) (<https://danielmiessler.com/blog/linux-xargs-vs-exec/>) [benchmarks](https://www.everythingcli.org/find-exec-vs-find-xargs/) (<https://www.everythingcli.org/find-exec-vs-find-xargs/>) suggest using `xargs` over `exec {}` is six times more efficient.

How to print commands that are executed

The `-t` option prints each command that will be executed to the terminal. This can be helpful when debugging scripts.

```
echo 'one two three' | xargs -t rm  
rm one two three
```

How to view the command and prompt for execution

The `-p` command will print the command to be executed and prompt the user to run it. This can be useful for destructive operations where you really want to be sure on the command to be run. I

```
echo 'one two three' | xargs -p touch  
touch one two three ?...
```

How to run multiple commands with xargs

It is possible to run multiple commands with `xargs` by using the `-I` flag. This replaces occurrences of the argument with the argument passed to `xargs`. The following echos a string and creates a folder.

```
cat foo.txt  
one
```

```
two
three

cat foo.txt | xargs -I % sh -c 'echo %; mkdir %'
one
two
three

ls
one two three
```

Further reading

- [xargs man page \(http://man7.org/linux/man-pages/man1/xargs.1.html\)](http://man7.org/linux/man-pages/man1/xargs.1.html)
- [xargs vs. exec {} \(https://danielmiessler.com/blog/linux-xargs-vs-exec/\)](https://danielmiessler.com/blog/linux-xargs-vs-exec/)
- [find exec vs find xargs \(https://www.everythingcli.org/find-exec-vs-find-xargs/\)](https://www.everythingcli.org/find-exec-vs-find-xargs/)

Have an update or suggestion for this article? [You can edit it here and send me a pull request.](https://github.com/shapedshed/shapedshed.com/edit/master/content/posts/unix-xargs.md)
(<https://github.com/shapedshed/shapedshed.com/edit/master/content/posts/unix-xargs.md>)

Tags

- [UNIX \(/tags/unix\)](/tags/unix)
- [Linux \(/tags/linux\)](/tags/linux)

Recent Posts

About the author

George Ornbo is a UK based human.

He is interested in people, music, food and writing. In a previous version of himself he wrote [books \(https://www.amazon.com/Sams-Teach-Yourself-Hours-Programming/dp/0672338033\)](https://www.amazon.com/Sams-Teach-Yourself-Hours-Programming/dp/0672338033) on [technology \(https://www.amazon.com/Sams-Teach-Yourself-Node-js-Hours/dp/0672335956\)](https://www.amazon.com/Sams-Teach-Yourself-Node-js-Hours/dp/0672335956).

← [http://shapedshed.com \(/\)](http://shapedshed.com/)

Content is licensed under a Creative Commons [Attribution-NonCommercial-ShareAlike 4.0 International \(CC BY-NC-SA 4.0\)](https://creativecommons.org/licenses/by-nc-sa/4.0/) (<https://creativecommons.org/licenses/by-nc-sa/4.0/>)