

# Rajalakshmi Engineering College

Name: Kamaleshwaran K  
Email: 241501079@rajalakshmi.edu.in  
Roll no:  
Phone: 9943398659  
Branch: REC  
Department: I AIML AD  
Batch: 2028  
Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 3

Attempt : 3  
Total Mark : 10  
Marks Obtained : 0

#### Section 1 : Coding

##### 1. Problem Statement

Imagine you are working on a text processing tool and need to implement a feature that allows users to insert characters at a specific position.

Implement a program that takes user inputs to create a singly linked list of characters and inserts a new character after a given index in the list.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of characters in the linked list.

The second line consists of a sequence of N characters, representing the linked list.

The third line consists of an integer index, representing the index(0-based) after

which the new character node needs to be inserted.

The fourth line consists of a character value representing the character to be inserted after the given index.

### ***Output Format***

If the provided index is out of bounds (larger than the list size):

1. The first line of output prints "Invalid index".
2. The second line prints "Updated list: " followed by the unchanged linked list values.

Otherwise, the output prints "Updated list: " followed by the updated linked list after inserting the new character after the given index.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

a b c d e

2

X

Output: Updated list: a b c X d e

### ***Answer***

```
#include<stdio.h>
#include<stdlib.h>
typedef struct Node{
    char data;
    struct Node *next;
}Node;
void insert(Node **head,char data,int index){
    Node *newNode=(Node*)malloc(sizeof(Node));
    newNode->data=data;
    newNode->next=NULL;
    if(index==0){newNode->next=*head;*head=newNode;return;}
    Node* temp=*head;
```

```

    for(int i=0;temp&& i<index;i++)temp=temp->next;
    if(!temp){printf("Invalid index\n");free(newNode);return;}
    newNode->next=temp->next;
    temp->next=newNode;
}
void printList(Node *head){
    printf("Updated list:");
    while(head){printf("%c ",head->data);head=head->next;}printf("\n");
}
int main(){
    int n,index;char ch;
    scanf("%d",&n);
    Node *head=NULL,*tail=NULL;
    for(int i=0;i<n;i++){
        scanf("%c",&ch);
        insert(&tail,ch,-1);
        if(!head)head=tail;
        else tail=tail->next;
    }
    scanf("%d %c",&index,&ch);
    insert(&head,ch,index);
    printList(head);
}

```

**Status : Wrong**

**Marks : 0/10**