Recharge Info(---RETIRED---)

Grade settings: Maximum grade: 100
Disable external file upload, paste and drop external content: Yes
Based on: [Recharge Info(---RETIRED---)](#)
Run: Yes **Evaluate**: Yes
Automatic grade: Yes
Write a query to display the Recharge Information. Give an alias name as
"RECHARGE_INFO".

Sort the records based on the RECHARGE_INFO in ascending order.

Sample Data:

RECHARGE_INFO

On **Recharge_Date, Customer_Name** recharged his/her phone number

Sample Output:

RECHARGE_INFO

On April, Justin Geller recharged his/her phone number

Mobile Prepaid System

CUSTOMER

P *	PHONE_NUMBER	VARCHAR (10)
	CUSTOMER_NAME	VARCHAR (20)
	EMAIL_ID	VARCHAR (35)
	ADDRESS	VARCHAR (50)

PLAN

P *	PLAN_AMOUNT	INT(6)
	VALIDITY_INDAYS	INT(4)
	LOCAL_VOICE_INMINS_PERDAY_SN	INT(3)
	LOCAL_VOICE_INMINS_PERDAY_ON	INT(3)
	STD_VOICE_INMINS_PERDAY_SN	INT(3)
	STD_VOICE_INMINS_PERDAY_ON	INT(3)
	DATA_INGB_PERDAY	DOUBLE (3.1)
	SMS_PERDAY	INT (3)
	PLAN_TYPE	VARCHAR (10)

SUBSCRIPTION

F	PHONE_NUMBER	VARCHAR(10)
F	PLAN_AMOUNT	INT (6)
	RECHARGE_DATE	DATE
	EXPIRY_DATE	DATE

P- Primary key
F- Foreign key
* - Not Null