

模板方法

```
namespace LeetCode.Properties
{
    public class 委托
    {
        static void Main(string[] args)
        {
            ProductFactory productFactory=new ProductFactory();
            WarpFactory warpFactory=new WarpFactory();
            Func<Product> func1 = new Func<Product>(productFactory.MakePizza);
            Func<Product> func2 = new Func<Product>(productFactory.MakeToyCar);
            Box box1=warpFactory.WarpProduct(func1);
            Box box2 = warpFactory.WarpProduct(func2);
            Console.WriteLine(box1.Product.Name);
            Console.WriteLine(box2.Product.Name);
        }
    }
    class Product
    {
        public string Name { get; set; }
    }
    class Box
    {
        public Product Product { get; set; }
    }
    class WarpFactory
    {
        public Box WarpProduct(Func<Product> getProduct)
        {
            Box box=new Box();
            Product product = getProduct();
            box.Product = product;
            return box;
        }
    }
    class ProductFactory
    {

```

```

        public Product MakePizza()
        {
            Product product=new Product();
            product.Name = "Pizza";
            return product;
        }

        public Product MakeToyCar()
        {
            Product product=new Product();
            product.Name = "ToyCar";
            return product;
        }
    }
}

```

添加回调方法之后

```

namespace LeetCode.Properties
{
    public class 委托
    {

        static void Main(string[] args)
        {
            ProductFactory productFactory=new ProductFactory();
            WarpFactory warpFactory=new WarpFactory();

            Func<Product> func1 = new Func<Product>(productFactory.MakePizza);
            Func<Product> func2 = new Func<Product>(productFactory.MakeToyCar);

            Logger logger=new Logger();

            Action<Product> action1=new Action<Product>(logger.Log);

            Box box1=warpFactory.WarpProduct(func1,action1);
            Box box2 = warpFactory.WarpProduct(func2,action1);

```

```
Console.WriteLine(box1.Product.Name);
```

```
Console.WriteLine(box2.Product.Name);
```

```
}
```

```
}
```

```
class Product
```

```
{
```

```
    public string Name { get; set; }
```

```
    public double Price { get; set; }
```

```
}
```

```
class Logger
```

```
{
```

```
    public void Log(Product product)
```

```
{
```

```
        Console.WriteLine("Product '{0}' created at {1} Price  
is {2}", product.Name, DateTime.UtcNow, product.Price);
```

```
}
```

```
}
```

```
class Box
```

```
{
```

```
    public Product Product { get; set; }
```

```
}
```

```
class WarpFactory
```

```
{
```

```
    public Box WarpProduct(Func<Product> getProduct, Action<Product> action)
```

```
{
```

```
        Box box = new Box();
```

```
        Product product = getProduct();
```

```
        box.Product = product;
```

```
        if (product.Price > 18)
```

```
{
```

```
            action(product);
```

```
}
```

```
        return box;
```

```

    }
}

class ProductFactory
{
    public Product MakePizza()
    {
        Product product=new Product();
        product.Name = "Pizza";
        return product;
    }

    public Product MakeToyCar()
    {
        Product product=new Product();
        product.Price = 20;
        product.Name = "ToyCar";
        return product;
    }
}
}

```

接口代替委托

```

namespace LeetCode.Properties
{
    public class 委托
    {

        static void Main(string[] args)
        {
            IProductFactory pizzaFactory=new PizzayFactory();
            IProductFactory toyCarFactory=new ToyCarFactory();

            WarpFactory warpFactory=new WarpFactory();
            Logger logger = new Logger();

            Action<Product> action = new Action<Product>(logger.Log);
            Box box1=warpFactory.WarpProduct(pizzaFactory, action);

```

```
Box box2 = warpFactory.WarpProduct(toycarFactory, action);
```

```
Console.WriteLine(box1.Product.Name);
```

```
Console.WriteLine(box2.Product.Name);
```

```
}
```

```
}
```

```
class Product
```

```
{
```

```
    public string Name { get; set; }
```

```
    public double Price { get; set; }
```

```
}
```

```
interface IProductFactory
```

```
{
```

```
    Product Make();
```

```
}
```

```
class PizzayFactory:IProductFactory
```

```
{
```

```
    public Product Make()
```

```
{
```

```
        Product product=new Product();
```

```
        product.Name = "Pizza";
```

```
        product.Price = 10;
```

```
        return product;
```

```
}
```

```
}
```

```
class ToyCarFactory:IProductFactory
```

```
{
```

```
    public Product Make()
```

```
{
```

```
        Product product=new Product();
```

```
        product.Price = 20;
```

```
        product.Name = "ToyCar";
```

```

        return product;
    }
}

class Logger
{
    public void Log(Product product)
    {
        Console.WriteLine("Product' {0}' created at {1} Price
is {2}", product.Name, DateTime.UtcNow, product.Price);
    }
}

class Box
{
    public Product Product { get; set; }
}

class WarpFactory
{
    public Box WarpProduct(IProductFactory productFactory, Action<Product> action)
    {
        Box box=new Box();
        Product product = productFactory.Make();
        box.Product = product;
        if (product.Price>18)
        {
            action(product);
        }
        return box;
    }
}
}

```