使用react-native-ffmpeg示例

笔记本: 我的第一个笔记本

创建时间: 2021/3/22 19:26 **更新时间:** 2021/3/22 20:47

作者: 136iqdlb602

URL: file:///C:/Users/Lenovo/Desktop/使用react-native-ffmpeg示例.docx

因为react-native-ffmpeg工作势必涉及到本地文件系统的操作,所以顺便把react-native-fs一起装了

首先配置fs

安装:

```
npm i react-native-fs
```

Settings.gradle最上面加上

```
include ':react-native-fs'
project(':react-native-
fs').projectDir=newFile(rootProject.projectDir,'../node_modules/react-native-
fs/android')
```

官方文档有一点老,很多提到的设置操作实际发现不需要进行(而且会报错),这样应该就可以 运行了。

然后是ffmpeg

安装:

```
npm i react-native-ffmpeg
```

在android/build.gradle 文件buildscript.ext框下加上

```
buildscript {
    ...
    ext {
        ...
        reactNativeFFmpegPackage = "full"
    }
    ...
}
```

最后启用app读写文件的权限


在 main/res/AndroidManifest.xml内

```
<manifest xmlns:android="http://schemas.android.com/apk/res/android"
package="com.kgeapp">
    ...
    <uses-permission android:name="android.permission.INTERNET" />
        <uses-permission android:name="android.permission.WRITE_EXTERNAL_STORAGE"/>
    ...
</manifest>
```

```
import { LogLevel, RNFFmpeg, RNFFprobe } from 'react-native-ffmpeg';
import RNFS from 'react-native-fs';

const ffmpegCommand = '-i ' + RNFS.ExternalStorageDirectoryPath+
  '/test/wx_camera_1582897957311.mp4 ';
RNFFmpeg.execute(ffmpegWatermarkCommand).then(result => console.log(`FFmpeg
process exited with rc=${result}.`));
```

RNFS.ExternalStorageDirectoryPath代表手机文件系统根目录,在我的手机上是 storage/emulated/0



react-native-ffmpeg简单使用示例

```
import { LogLevel, RNFFmpeg } from 'react-native-ffmpeg';
//直接执行文本命令,这条-i: 输入文件 -c: v 输出视频格式 -c: a 输出音频格式
RNFFmpeg.execute('-i file1.mp4 -c:v mpeg4 file2.mp4').then(result =>
console.log(`FFmpeg process exited with rc=${result}.`));
//上一条指令的参数化形式
RNFFmpeg.executeWithArguments(["-i", "file1.mp4", "-c:v", "mpeg4"]
"file2.mp4"]).then(result => console.log(`FFmpeg process exited with
rc=${result}.`));
//执行异步指令
RNFFmpeg.executeAsync('-i file1.mp4 -c:v mpeg4 file2.mp4', completedExecution =>
   if (completedExecution.returnCode === 0) {
      console.log("FFmpeg process completed successfully");
   } else {
      console.log(`FFmpeg process failed with
rc=${completedExecution.returnCode}.`);
}).then(executionId => console.log(`Async FFmpeg process started with executionId
${executionId}.`));
//执行FFprobe命令(计算音视频信息的ffmpeg组件),
import { LogLevel, RNFFprobe } from 'react-native-ffmpeg';
RNFFprobe.execute('-i file1.mp4').then(result => console.log(`FFprobe process
exited with rc=${result}.`));
//检查上一条指令返回的信息
RNFFmpegConfig.getLastReturnCode().then(returnCode => {
   console.log(`Last return code: ${returnCode}`);
});
RNFFmpegConfig.getLastCommandOutput().then(output => {
   console.log(`Last command output: ${output}`);
```

```
});
//停止所有指令
RNFFmpeg.cancel();
//停止特定指令
RNFFmpeg.cancelExecution(executionId);
//注意以上两条指令不会等到真的停止了才返回,而是立即返回。
//获取文件信息
//获取全部信息
RNFFprobe.getMediaInformation('<file path or uri>').then(information => {
    console.log('Result: ' + JSON.stringify(information));
});
//获取指定信息
RNFFprobe.getMediaInformation('<file path or uri>').then(information => {
    if (information.getMediaProperties() !== undefined) {
       if (information.getMediaProperties().filename !== undefined) {
            console.log(`Path: ${information.getMediaProperties().filename}`);
       if (information.getMediaProperties().format_name !== undefined) {
            console.log(`Format:
${information.getMediaProperties().format_name}`);
       if (information.getMediaProperties().bit_rate !== undefined) {
            console.log(`Bitrate: ${information.getMediaProperties().bit_rate}`);
       if (information.getMediaProperties().duration !== undefined) {
            console.log(`Duration:
${information.getMediaProperties().duration}`);
       if (information.getMediaProperties().start_time !== undefined) {
            console.log(`Start time:
${information.getMediaProperties().start_time}`);
       if (information.getMediaProperties().nb_streams !== undefined) {
            console.log(`Number of streams:
${information.getMediaProperties().nb_streams.toString()}`);
       let tags = information.getMediaProperties().tags;
       if (tags !== undefined) {
           Object.keys(tags).forEach((key) => {
               console.log(`Tag: ${key}:${tags[key]}`);
            });
       }
       let streams = information.getStreams();
       if (streams !== undefined) {
            for (let i = 0; i < streams.length; ++i) {</pre>
              let stream = streams[i];
              console.log("---");
              if (stream.getAllProperties().index !== undefined) {
                  console.log(`Stream index:
${stream.getAllProperties().index.toString()}`);
              if (stream.getAllProperties().codec_type !== undefined) {
                  console.log(`Stream type:
${stream.getAllProperties().codec type}`);
              if (stream.getAllProperties().codec name !== undefined) {
                  console.log(`Stream codec:
${stream.getAllProperties().codec name}`);
            }
       }
    }
});
//重定向log信息到指定地方
logCallback = (log) => {
```

```
this.appendLog(`${log.executionId}:${log.message}`);
};
RNFFmpegConfig.enableLogCallback(this.logCallback);
//返回音视频的实时统计信息
statisticsCallback = (statistics) => {
    console.log(`Statistics; executionId: ${statistics.executionId}, video frame
number: ${statistics.videoFrameNumber}, video fps: ${statistics.videoFps}, video
quality: ${statistics.videoQuality}, size: ${statistics.size}, time:
${statistics.time}, bitrate: ${statistics.bitrate}, speed: ${statistics.speed}`);
};
RNFFmpegConfig.enableStatisticsCallback(this.statisticsCallback);
//返回上一次的统计信息
RNFFmpegConfig.getLastReceivedStatistics().then(statistics => console.log('Stats:
' + JSON.stringify(statistics)));
//列出正在运行的操作
RNFFmpeg.listExecutions().then(executionList => {
    executionList.forEach(execution => {
       console.log(`Execution id is ${execution.executionId}`);
       console.log(`Execution start time is ` + new Date(execution.startTime));
       console.log(`Execution command is ${execution.command}`);
    });
});
//设置log等级
RNFFmpegConfig.setLogLevel(LogLevel.AV LOG WARNING);
```

附:官方示例中对于ffmpeg的api封装

```
//react-native-ffmpeg-test-master\src\react-native-ffmpeg-api-wrapper.js
import React from 'react';
import {RNFFmpeg, RNFFmpegConfig, RNFFprobe} from 'react-native-ffmpeg';
import {ffprint} from './util';
export function ffprint(text) {
    console.log(text.endsWith('\n') ? text.replace('\n', '') : text);
}
export async function executeFFmpeg(command) {
   return await RNFFmpeg.execute(command)
}
export function executeFFmpegWithArguments(commandArguments) {
    RNFFmpeg.executeWithArguments(commandArguments).then(rc => ffprint(`FFmpeg
process exited with rc ${rc}`));
}
export async function executeFFmpegAsync(command, callback) {
    return await RNFFmpeg.executeAsync(command, callback);
}
export function executeFFmpegAsyncWithArguments(commandArguments, callback) {
    RNFFmpeg.executeAsyncWithArguments(commandArguments,
callback).then(executionId => ffprint(`FFmpeg process started with executionId
${executionId}.`));
}
export function executeFFmpegCancel() {
   RNFFmpeg.cancel();
```

```
export function executeFFmpegCancelExecution(executionId) {
    RNFFmpeg.cancelExecution(executionId);
export function getLastCommandOutput() {
    return RNFFmpegConfig.getLastCommandOutput();
export function getLogLevel() {
    return RNFFmpegConfig.getLogLevel();
export function setLogLevel(logLevel) {
    return RNFFmpegConfig.setLogLevel(logLevel);
export function enableLogCallback(logCallback) {
    RNFFmpegConfig.enableLogCallback(logCallback);
export function enableStatisticsCallback(statisticsCallback) {
    RNFFmpegConfig.enableStatisticsCallback(statisticsCallback);
export function listExecutions() {
    RNFFmpeg.listExecutions().then(executionList => {
        executionList.forEach(execution => {
            ffprint(`Execution id is ${execution.executionId}`);
            ffprint(`Execution start time is ` + new Date(execution.startTime));
            ffprint(`Execution command is ${execution.command}`);
        });
    });
}
export async function executeFFprobe(command) {
    return await RNFFprobe.execute(command);
}
export function executeFFprobeWithArguments(commandArguments) {
    RNFFprobe.executeWithArguments(commandArguments).then(rc => ffprint(`FFprobe
process exited with rc ${rc}`));
export function resetStatistics() {
    RNFFmpegConfig.resetStatistics();
export function parseArguments(command) {
    return RNFFmpeg.parseArguments(command);
export function getFFmpegVersion() {
    return RNFFmpegConfig.getFFmpegVersion();
}
```

```
export function getPlatform() {
    return RNFFmpegConfig.getPlatform();
export function getPackageName() {
    return RNFFmpegConfig.getPackageName();
export function getExternalLibraries() {
    return RNFFmpegConfig.getExternalLibraries();
export function getLastReturnCode() {
    return RNFFmpegConfig.getLastReturnCode();
export function getLastReceivedStatistics() {
    return RNFFmpegConfig.getLastReceivedStatistics();
export function setFontDirectory(path, mapping) {
    RNFFmpegConfig.setFontDirectory(path, mapping);
export function setFontconfigConfigurationPath(path) {
    RNFFmpegConfig.setFontconfigConfigurationPath(path);
}
export function setEnvironmentVariable(name, value) {
    RNFFmpegConfig.setEnvironmentVariable(name, value);
export function getMediaInformation(path) {
    return RNFFprobe.getMediaInformation(path);
}
export function registerNewFFmpegPipe() {
    return RNFFmpegConfig.registerNewFFmpegPipe();
export function writeToPipe(inputPath, pipePath) {
    return RNFFmpegConfig.writeToPipe(inputPath, pipePath);
}
```