



NumPy Splitting Array

[< Previous](#)[Next >](#)

Splitting NumPy Arrays

Splitting is reverse operation of Joining.

Joining merges multiple arrays into one and Splitting breaks one array into multiple.

We use `array_split()` for splitting arrays, we pass it the array we want to split and the number of splits.

Example

[Get your own Python Server](#)

Split the array in 3 parts:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 6])

newarr = np.array_split(arr, 3)

print(newarr)
```

[Try it Yourself »](#)



If the array has less elements than required, it will adjust from the end accordingly.

Example

Split the array in 4 parts:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 6])

newarr = np.array_split(arr, 4)

print(newarr)
```

[Try it Yourself »](#)

Note: We also have the method `split()` available but it will not adjust the elements when elements are less in source array for splitting like in example above, `array_split()` worked properly but `split()` would fail.

ADVERTISEMENT



Split Into Arrays

The return value of the `array_split()` method is an array containing each of the split as an array.

If you split an array into 3 arrays, you can access them from the result just like any array element:

Example

Access the splitted arrays:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 6])

newarr = np.array_split(arr, 3)

print(newarr[0])
print(newarr[1])
print(newarr[2])
```

[Try it Yourself »](#)



Use the `array_split()` method, pass in the array you want to split and the number of splits you want to do.

Example

Split the 2-D array into three 2-D arrays.

```
import numpy as np

arr = np.array([[1, 2], [3, 4], [5, 6], [7, 8], [9, 10], [11, 12]])

newarr = np.array_split(arr, 3)

print(newarr)
```

[Try it Yourself »](#)

The example above returns three 2-D arrays.

Let's look at another example, this time each element in the 2-D arrays contains 3 elements.

Example

Split the 2-D array into three 2-D arrays.

```
import numpy as np

arr = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9], [10, 11, 12], [13, 14, 15],
               [16, 17, 18]])

newarr = np.array_split(arr, 3)

print(newarr)
```



The example above returns three 2-D arrays.

In addition, you can specify which axis you want to do the split around.

The example below also returns three 2-D arrays, but they are split along the row (axis=1).

Example

Split the 2-D array into three 2-D arrays along rows.

```
import numpy as np

arr = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9], [10, 11, 12], [13, 14, 15],
               [16, 17, 18]])

newarr = np.array_split(arr, 3, axis=1)

print(newarr)
```

[Try it Yourself »](#)

An alternate solution is using `hsplit()` opposite of `hstack()`

Example

Use the `hsplit()` method to split the 2-D array into three 2-D arrays along rows.

```
import numpy as np

arr = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9], [10, 11, 12], [13, 14, 15],
               [16, 17, 18]])

newarr = np.hsplit(arr, 3)
```

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)

SQL PYTHON JAVA PHP HOW TO W3.CSS C C++ C# BOOTSTRAP

Note: Similar alternates to `vstack()` and `dstack()` are available as `vsplit()` and `dsplit()`.

Exercise [?]

One of these functions can be used to split an array into multiple arrays.
Which one?

- ☐ `array_split()`
- ☐ `decatenate()`
- ☐ `decat()`

[Submit Answer »](#)

[< Previous](#)[Next >](#)

Track your progress - it's free!

[Sign Up](#)[Log in](#)



Tutorials ▼

Exercises ▼


Services ▼



Sign Up

Log in

SQL PYTHON JAVA PHP HOW TO W3.CSS C C++ C# BOOTSTRA





Tutorials ▼

Exercises ▼

Services ▼



Sign Up

Log in



SQL

PYTHON

JAVA

PHP

HOW TO

W3.CSS

C

C++

C#

BOOTSTRA



ADVERTISEMENT

ADVERTISEMENT



ADVERTISEMENT



PLUS

SPACES

GET CERTIFIED

FOR TEACHERS

FOR BUSINESS

CONTACT US

Top Tutorials

- HTML Tutorial
- CSS Tutorial
- JavaScript Tutorial
- How To Tutorial
- SQL Tutorial
- Python Tutorial
- W3.CSS Tutorial
- Bootstrap Tutorial
- PHP Tutorial
- Java Tutorial

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#) [C++](#) [C#](#) [BOOTSTRA](#)[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)[FORUM](#) [ABOUT](#) [ACADEMY](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.

Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2025 by Refsnes Data. All Rights Reserved. [W3Schools is Powered by W3.CSS](#).