



Pandas - Cleaning Empty Cells

[< Previous](#)[Next >](#)

Empty Cells

Empty cells can potentially give you a wrong result when you analyze data.

Remove Rows

One way to deal with empty cells is to remove rows that contain empty cells.

This is usually OK, since data sets can be very big, and removing a few rows will not have a big impact on the result.

Example

[Get your own Python Server](#)

Return a new Data Frame with no empty cells:

```
import pandas as pd

df = pd.read_csv('data.csv')

new_df = df.dropna()

print(new_df.to_string())
```



Note: By default, the `dropna()` method returns a *new* DataFrame, and will not change the original.

If you want to change the original DataFrame, use the `inplace = True` argument:

Example

Remove all rows with NULL values:

```
import pandas as pd

df = pd.read_csv('data.csv')

df.dropna(inplace = True)

print(df.to_string())
```

Try it Yourself »

Note: Now, the `dropna(inplace = True)` will NOT return a new DataFrame, but it will remove all rows containing NULL values from the original DataFrame.

Replace Empty Values

Another way of dealing with empty cells is to insert a *new* value instead.

This way you do not have to delete entire rows just because of some empty cells.



Tutorials ▼

Exercises ▼

Services ▼



Sign Up

Log in

≡ PYTHON JAVA PHP HOW TO W3.CSS C C++ C# BOOTSTRAP REACT

Example

Replace NULL values with the number 130:

```
import pandas as pd

df = pd.read_csv('data.csv')

df.fillna(130, inplace = True)
```

Try it Yourself »

Replace Only For Specified Columns

The example above replaces all empty cells in the whole Data Frame.

To only replace empty values for one column, specify the *column name* for the DataFrame:

Example

Replace NULL values in the "Calories" columns with the number 130:

```
import pandas as pd

df = pd.read_csv('data.csv')

df.fillna({"Calories": 130}, inplace=True)
```

Try it Yourself »

Replace Using Mean, Median, or Mode



values for a specified column:

Example

Calculate the MEAN, and replace any empty values with it:

```
import pandas as pd

df = pd.read_csv('data.csv')

x = df["Calories"].mean()

df.fillna({"Calories": x}, inplace=True)
```

[Try it Yourself »](#)

Mean = the average value (the sum of all values divided by number of values).

Example

Calculate the MEDIAN, and replace any empty values with it:

```
import pandas as pd

df = pd.read_csv('data.csv')

x = df["Calories"].median()

df.fillna({"Calories": x}, inplace=True)
```

[Tutorials ▾](#)[Exercises ▾](#)[Services ▾](#)[Sign Up](#)[Log in](#)[≡](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#) [C++](#) [C#](#) [BOOTSTRAP](#) [REACT](#)

Median = the value in the middle, after you have sorted all values ascending.

Example

Calculate the MODE, and replace any empty values with it:

```
import pandas as pd

df = pd.read_csv('data.csv')

x = df["Calories"].mode()[0]

df.fillna({"Calories": x}, inplace=True)
```


[Try it Yourself »](#)

Mode = the value that appears most frequently.

[< Previous](#)[Next >](#)

Track your progress - it's free!

[Sign Up](#)[Log in](#)

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#) [C++](#) [C#](#) [BOOTSTRAP](#) [REACT](#)

COLOR PICKER

[PLUS](#)[SPACES](#)

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#) [C++](#) [C#](#) [BOOTSTRAP](#) [REAC](#)[FOR BUSINESS](#)[CONTACT US](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)



[Tutorials](#) ▼[Exercises](#) ▼[Services](#) ▼[Sign Up](#)[Log in](#)[≡](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#) [C++](#) [C#](#) [BOOTSTRAP](#) [REACT](#)

warrant full correctness
of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#),
[cookie and privacy policy](#).

Copyright 1999-2025 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.