



NumPy Searching Arrays

[< Previous](#)[Next >](#)

Searching Arrays

You can search an array for a certain value, and return the indexes that get a match.

To search an array, use the `where()` method.

Example

[Get your own Python Server](#)

Find the indexes where the value is 4:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 4, 4])

x = np.where(arr == 4)

print(x)
```

[Try it Yourself »](#)

The example above will return a tuple: `(array([3, 5, 6]),)`

Which means that the value 4 is present at index 3, 5, and 6.



```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 6, 7, 8])

x = np.where(arr%2 == 0)

print(x)
```

[Try it Yourself »](#)

Example

Find the indexes where the values are odd:

```
import numpy as np

arr = np.array([1, 2, 3, 4, 5, 6, 7, 8])

x = np.where(arr%2 == 1)

print(x)
```

[Try it Yourself »](#)

Search Sorted

There is a method called `searchsorted()` which performs a binary search in the array, and returns the index where the specified value would be inserted to maintain the search order.



Example

Find the indexes where the value 7 should be inserted:

```
import numpy as np

arr = np.array([6, 7, 8, 9])

x = np.searchsorted(arr, 7)

print(x)
```

[Try it Yourself »](#)

Example explained: The number 7 should be inserted on index 1 to remain the sort order.

The method starts the search from the left and returns the first index where the number 7 is no longer larger than the next value.

Search From the Right Side

By default the left most index is returned, but we can give `side='right'` to return the right most index instead.

Example

Find the indexes where the value 7 should be inserted, starting from the right:

```
import numpy as np

arr = np.array([6, 7, 8, 9])

x = np.searchsorted(arr, 7, side='right')
```



Example explained: The number 7 should be inserted on index 2 to remain the sort order.

The method starts the search from the right and returns the first index where the number 7 is no longer less than the next value.

Multiple Values

To search for more than one value, use an array with the specified values.

Example

Find the indexes where the values 2, 4, and 6 should be inserted:

```
import numpy as np

arr = np.array([1, 3, 5, 7])

x = np.searchsorted(arr, [2, 4, 6])

print(x)
```

Try it Yourself »

The return value is an array: `[1 2 3]` containing the three indexes where 2, 4, 6 would be inserted in the original array to maintain the order.

Exercise ?

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[HOW TO](#)[W3.CSS](#)[C](#)[C++](#)[C#](#)[BOOTSTRAP](#)

```
x = np.where(arr%2 == 1)  
print(x)
```

What will be the printed result?

- ☐ (array([1, 3]),)
- ☐ (array([15, 41]),)
- ☐ (array([0, 2]),)
- ☐ (array([38, 46]),)

[Submit Answer »](#)

[◀ Previous](#)[Next ▶](#)

Track your progress - it's free!

[Sign Up](#)[Log in](#)

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#) [C++](#) [C#](#) [BOOTSTRA](#)

COLOR PICKER

[PLUS](#)[SPACES](#)[GET CERTIFIED](#)[FOR TEACHERS](#)

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#) [C++](#) [C#](#) [BOOTSTRA](#)

Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [Java Reference](#)
- [Angular Reference](#)
- [jQuery Reference](#)

Top Examples

- [HTML Examples](#)
- [CSS Examples](#)
- [JavaScript Examples](#)
- [How To Examples](#)
- [SQL Examples](#)
- [Python Examples](#)
- [W3.CSS Examples](#)
- [Bootstrap Examples](#)
- [PHP Examples](#)
- [Java Examples](#)
- [XML Examples](#)
- [jQuery Examples](#)

Get Certified

- [HTML Certificate](#)
- [CSS Certificate](#)
- [JavaScript Certificate](#)
- [Front End Certificate](#)
- [SQL Certificate](#)
- [Python Certificate](#)
- [PHP Certificate](#)
- [jQuery Certificate](#)
- [Java Certificate](#)
- [C++ Certificate](#)
- [C# Certificate](#)
- [XML Certificate](#)

[FORUM](#) [ABOUT](#) [ACADEMY](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.

Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot



Tutorials ▼

Exercises ▼

Services ▼



Sign Up

Log in

☰ SQL PYTHON JAVA PHP HOW TO W3.CSS C C++ C# BOOTSTRA