

Started on	Sunday, 22 October 2023, 7:46 PM
State	Finished
Completed on	Sunday, 22 October 2023, 8:49 PM
Time taken	1 hour 3 mins
Grade	40.50 out of 100.00

Question 1

Complete

Mark 0.00 out of 11.00

Fill in the underlined blank lines in the following code.

```
public static int roundedLog( int n) {
    // Pre-Condition:  n is a positive integer.
    // Post-Condition: returns  $\lfloor \log n \rfloor$  , i.e., logarithm of input n base 2 rounded down.
    int r = 0 ;
    while ( n > 1 ) {
        // Loop Invariant: _____ // fill in this line
        _____ // fill in loop body
    }
    return r ;
}
```

- ☐ a. // Loop Invariant: the return value stated in the post-condition equals the current value of $r + \lfloor \log n \rfloor$ // fill in this line
n /=2; r++; // fill in loop body
- ☐ b. // Loop Invariant: r will eventually become $\lfloor \log n \rfloor$ // fill in this line
n /=2; r++; // fill in loop body
- ☐ c. // Loop Invariant: the loop repeatedly increments r and halves n // fill in this line
n /=2; r++; // fill in loop body
- ☐ d. // Loop Invariant: the purpose of the loop is to compute $\lfloor \log n \rfloor$ // fill in this line
r = (int) (Math.log10(n) / Math.log10(2)) ; // fill in loop body
- ☒ e. More than one of the other choices are correct.
- ☐ f. None of the other choices are correct.

Question 2

Complete

Mark 8.00 out of 8.00

What is type erasure in Java generics?

- ☐ a. The process of adding generic type information during compilation
- ☒ b. The process of removing all generic type information during compilation
- ☐ c. The process of enforcing generic type information at runtime
- ☐ d. The process of dynamically updating generic type information during program execution

Question 3

Complete

Mark 10.00 out of 10.00

Mark 10.00 out of 10.00

- ☐ a. n
- ☐ b. $n \log n$
- ☐ c. None of the other choices.
- ☐ d. $\log n$
- ☒ e. n^2

Question 4

Complete

Mark 11.00 out of 11.00

Mark 11.00 out of 11.00

- ☐ a. n
- ☐ b. $\log \log n$
- ☐ c. None of the other choices.
- ☒ d. $\log n$
- ☐ e. $\log^2 n$

Question 5

Complete

Mark 0.00 out of 10.00

```
/**
 * Pre-Cond: Input is an integer array A.
 * Post-Cond: Elements of A are rearranged into two groups.
 *           Non-negative elements form the first group; negative elements the second group.
 *           The relative order of elements within each group remains undisturbed.
 * Example:  [-4, 6, 2, 8, -9, -7, 0, -5, 3] becomes [6, 2, 8, 0, 3, -4, -9, -7, -5].
 */
public static void splitBySign(Integer[] A) {
    // TODO: place a correct subset of the numbered lines below in correct
    order here.
}
```

1. `int r = A.length -1;`
2. `r = A.length -1;`
3. `int r = 0;`
4. `r = 0;`
5. `A[r--] = S.pop();`
6. `A[r++] = S.pop();`
7. `if (A[i] >= 0) A[r++] = A[i]; else S.push(A[i]);`
8. `if (A[i] < 0) A[r--] = A[i]; else S.push(A[i]);`
9. `while (!S.empty())`
10. `Stack<Integer> S = new Stack<>();`
11. `for (int i = 0; i < A.length; i++)`
12. `for (int i = A.length -1; i >= 0; i--)`

- ☐ a. None of the other choices are correct.
- ☐ b. 3, 10, 11, 7, 2, 9, 5.
- ☐ c. 3, 10, 11, 7, 9, 5.
- ☐ d. 1, 10, 12, 8, 9, 5.
- ☒ e. More than one of the other choices are correct.
- ☐ f. 10, 3, 12, 7, 9, 5.

Question 6

Complete

Mark 0.00 out of 8.00

If $T_1(n) = O(f(n))$ and $T_2(n) = O(f(n))$, then $T_1(n) = O(T_2(n))$.

- ☐ a. False
- ☒ b. True

Question 7

Complete

Mark 0.00 out of 11.00

The worst-case running time of the algorithm below is $T(n) = \Theta(\text{_____?_____})$.

```
public static double foo( double x , int n) {  
    if ( x < 10 || n < 5 ) return 2*x*(n+5) ;  
    double e = 0;  
    for ( int i = 0; i < n; i++ ) e += 5*(i+7)*(i+n);  
    return foo(x+4 , n/2) + foo(x+7 , n/2) + 5*(e+3)*(n+7) ;  
}
```

- ☐ a. n
- ☐ b. n^2
- ☒ c. $n^2 \log n$
- ☐ d. This method may not terminate.
- ☐ e. $n \log n$
- ☐ f. 2^n

Question 8

Complete

Mark 11.00 out of 11.00

What is the asymptotic running time of the method below as a function of n ?

```
public void doubleLoop ( int n ) {  
    for ( int k = 1; k < n*n; k +=5 )  
        for ( int m = 1; m < k; m *=3 )  
            System.out.println( k*m*m );  
}
```

- ☒ a. $\Theta(n^2 \log n)$
- ☐ b. None of the other choices.
- ☐ c. $\Theta(n^2)$
- ☐ d. $O(n \log n)$
- ☐ e. $O(n \log^2 n)$
- ☐ f. $\Omega(n^4 \log n)$

Question 9

Complete

Mark 0.00 out of 10.00

Order the following three functions of n in increasing order of growth rate:

$$F(n) = \frac{3n^2 \log^5 n + 4n^3}{7 \log^2 n + 2\sqrt{6n \log^2 n}}, \quad G(n) = \frac{5n \log^{100} n + 7n^3 \sqrt{n} \log n}{n^{1.7} + n^2 \log n}, \quad H(n) = \frac{5n^4 + n \log n}{n + 5\sqrt{n} \log n}.$$

- ☐ a. $F(n) \ll G(n) \ll H(n)$
- ☐ b. $H(n) \ll G(n) \ll F(n)$
- ☐ c. $G(n) \ll F(n) \ll H(n)$
- ☐ d. None of the other choices.
- ☒ e. $G(n) \ll H(n) \ll F(n)$
- ☐ f. $H(n) \ll F(n) \ll G(n)$

Question 10

Complete

Mark 0.50 out of 10.00

Consider the following:

1. fully parenthesized infix expression $((x + 3) - (y * z)) / ((7 * y) - (5 * x))$
2. un-parenthesized postfix expression $5\ x\ *\ 7\ y\ *\ -\ y\ z\ *\ x\ 3\ +\ -\ /$
3. un-parenthesized postfix expression $x\ 3\ +\ y\ z\ *\ -\ 7\ y\ *\ 5\ x\ *\ -\ /$
4. un-parenthesized prefix expression $/\ -\ +\ x\ 3\ *\ y\ z\ -\ *\ 7\ y\ *\ 5\ x$

The question is which of them are equivalent, i.e., represent exactly the same expression.

- ☐ a. No two of them are equivalent.
- ☐ b. Only 1, 3 are equivalent.
- ☐ c. Only 1, 4 are equivalent.
- ☐ d. Only 1, 3, 4 are equivalent.
- ☒ e. Only 1, 2, 4 are equivalent.
- ☐ f. 1 is equivalent to 3, and 2 is equivalent to 4.

Previous activity

Sample Midterm Tests & Solutions

Jump to...

Next activity

Practice Quiz for Final Exam