TTFTOTYPE42(1) TTFTOTYPE42(1)

#### **NAME**

ttftotype42 – create PostScript Type 42 wrapper of TrueType font

#### **SYNOPSIS**

ttftotype42 [input [output]]

### **DESCRIPTION**

**Ttftotype42** converts TrueType or TrueType-flavored OpenType font programs into PostScript Type 42 format, which is a wrapper for the TrueType outlines. This conversion preserves all outlines and hint information from the original TrueType font. The Type 42 wrapper uses glyph names identical to those expected by **pdflatex**(1) or **otftotfm**(1), so encoding files suitable for TrueType fonts and **pdflatex** will also work for the Type 42 fonts and **dvips**(1). If the file *output* is not specified output goes to the standard output. If the file *input* is not specified input comes from the standard input.

# **OPTIONS**

# $- o {\it file}, -\!\!-\!\!output {\it file}$

Write output font to file instead of the standard output.

### -q, --quiet

Do not generate any error messages.

# -h, --help

Print usage information and exit.

#### -v, --version

Print the version number and some short non-warranty information and exit.

### **SEE ALSO**

```
cfftot1(1), otftotfm(1), pdftex(1), dvips(1)
```

Adobe Technical Note #5012, The Type 42 Font Format Specification

OpenType Specification, Version 1.4

# **AUTHOR**

Eddie Kohler (ekohler@gmail.com)

The latest version is available from:

http://www.lcdf.org/type/