



---

## FUNDAMENTALS OF PROGRAMMING

### LAB 08 - FUNCTIONS/BEHAVIORS

---

Saif Hassan

Date: 21<sup>st</sup> October, 2019

#### **READ IT FIRST**

Prior to start solving the problems in this assignments, please give full concentration on following points.

1. **WORKING** - This is individual lab. If you are stuck in a problem contact your teacher, but, in mean time start doing next question (don't waste time).
2. **DEADLINE** - Before Next Lab.
3. **SUBMISSION** - This assignment needs to be submitted in a soft copy.
4. **WHERE TO SUBMIT** - Please visit your Google Classroom.
5. **HOW TO SUBMIT** - rename all .cpp file as 000-00-0000\_lab08.cpp, and submit .cpp file ONLY.

#### **KEEP IT WITH YOU!**

1. Indent your code inside the main () function. It's a good practice!
2. It is not bad if you keep your code indented inside the loops, if and else blocks as well.
3. Comment your code, where it is necessary.
4. Read the entire question. Don't jump to the formula directly.

## Exercises

You can answer all functions asked in this section in a single .cpp file and test them in main ( ) function.

1. Write a function that will take 3 arguments as an input i.e. acceleration, time and initial velocity, and return the distance covered. The formula of distance is  $S = V_i + 0.5 * a * t^2$ . The prototype of the function is given as: `float distance (float acc, float time, float initial)`. You can test in main function as:


```
1. float s = distance(60, 1.5, 10);  
2. cout<<s;
```

2. Write a function with the name `printFancy` which takes two input params i.e. a character `x` and an integer `n`. You have to print `x` up to `n` times. For example, if I use: `printFancy ('*', 10);` it will print on screen `* 10 times` as `*****`. You can test in main function as: `printFancy ('*', 10);`
3. What should be done with the function above to give space after each character? For example, if I use: `printFancy2 ('-', 10);` it will print on screen - 10 times as `- - - - - - - - - -`.
4. Write a function that will take two params as an integer input i.e start and end and return the sum of all numbers existing in between.
5. Write a function that will take three params as an integer input i.e start, end and `n`. And then print the numbers that are divisible by `n` in the range defined by start and end.
6. Write a function named `swap(x, y)` where `x` and `y` are integers.
7. Write a function that take three inputs: `x`, `y` and choice and return value based on user's choice. Choice may be: (S → SQUARE, C → CUBIC, ^ → POWER, M → MAX, N → MIN, + → ADDITION, \* → MULTIPLICATION).
8. Write following math functions, calculate formula and return value:

$$f(x) = 0.1 + \cos(3x) + 3 \sin\left(\frac{1}{0.1 + (x - 3)^2}\right) + \cos(\sqrt{11} x)$$

You may use `cmath` library for sin/cos functions.

Note: You can test  $f(x)$  on x-axis in given graph.



9. Write a function that takes one param as integer input `taskNo` and calls function accordingly. Let's say user's input is 6, then ask user input `x, y` then call `swap(x, y)` function. The prototype of the function is given as: `void execTask (int taskNo)`
10. Write a `void` function named `showMenu()` in which you have to show user, all the tasks number and name in proper manner. Output may be:

```
1- Calculate Distance
2- Fancy
3- Improved Fancy
4- Sum of all numbers in given range
and so on.
```

Now ask user any input to call execute that task.

11. Code for `main ()` function is as follows:

```
1. // Do Not Change main function
2. int main ()
3. {
4.     int choice;
5.
6.     showMenu()
7.     cin>>choice;
8.     execTask(int taskNo);
9.
10.    system ("PAUSE") ;
11.    return 0 ;
12. }
```