

autorecon

AutoRecon is a multi-threaded network reconnaissance tool which performs automated enumeration of services. It is intended as a time-saving tool for use in CTFs and other penetration testing environments (e.g. OSCP). It may also be useful in real-world engagements.

Installed size: 1.24 MB

How to install: `sudo apt install autorecon`

Dependencies:

- curl
- dirb
- dirsearch
- dnsrecon
- enum4linux
- enum4linux-ng
- ffuf
- gobuster
- impacket-scripts
- nbtscan
- nikto
- nmap
- onesixtyone
- oscanner
- python3
- python3-colorama
- python3-impacket
- python3-platformdirs
- python3-psutil
- python3-requests
- python3-toml
- python3-unidecode

- redis-tools
- seclists
- sipvicious
- smbclient
- smbmap
- snmp
- sslscan
- tnscommand10g
- whatweb

root@kali:~# autorecon -h

```
usage: autorecon [-t TARGET_FILE] [-p PORTS] [-m MAX_SCANS]
               [-mp MAX_PORT_SCANS] [-c CONFIG_FILE] [-g GLOBAL_FILE]
               [--tags TAGS] [--exclude-tags TAGS] [--port-scans PLUGINS]
               [--service-scans PLUGINS] [--reports PLUGINS]
               [--plugins-dir PLUGINS_DIR] [--add-plugins-dir PLUGINS_DIR]
               [-l [TYPE]] [-o OUTPUT] [--single-target] [--only-scans-dir]
               [--no-port-dirs] [--heartbeat HEARTBEAT] [--timeout TIMEOUT]
               [--target-timeout TARGET_TIMEOUT] [--nmap NMAP |
               --nmap-append NMAP_APPEND] [--proxychains]
               [--disable-sanity-checks] [--disable-keyboard-control]
               [--ignore-plugin-checks]
               [--force-services SERVICE [SERVICE ...]]
               [-mpti PLUGIN:NUMBER [PLUGIN:NUMBER ...]]
               [-mpgi PLUGIN:NUMBER [PLUGIN:NUMBER ...]] [--accessible] [-v]
               [--version] [--curl.path VALUE]
               [--dirbuster.tool {feroxbuster,gobuster,dirsearch,ffuf,dirb}]
               [--dirbuster.wordlist VALUE [VALUE ...]]
```

[--dirbuster.threads VALUE] [--dirbuster.ext VALUE]
[--dirbuster.recursive] [--dirbuster.extras VALUE]
[--enum4linux.tool {enum4linux-ng,enum4linux}]
[--onesixtyone.community-strings VALUE]
[--subdomain-enum.domain VALUE]
[--subdomain-enum.wordlist VALUE [VALUE ...]]
[--subdomain-enum.threads VALUE]
[--vhost-enum.hostname VALUE]
[--vhost-enum.wordlist VALUE [VALUE ...]]
[--vhost-enum.threads VALUE] [--wpscan.api-token VALUE]
[--global.username-wordlist VALUE]
[--global.password-wordlist VALUE] [--global.domain VALUE]
[-h]
[targets ...]

Network reconnaissance tool to port scan and automatically enumerate services found on multiple targets.

positional arguments:

targets IP addresses (e.g. 10.0.0.1), CIDR notation (e.g. 10.0.0.1/24), or resolvable hostnames (e.g. foo.bar) to scan.

options:

-t, --target-file TARGET_FILE
 Read targets from file.

-p, --ports PORTS Comma separated list of ports / port ranges to scan.

Specify TCP/UDP ports by prepending list with T:/U: To

scan both TCP/UDP, put port(s) at start or specify B:

e.g. 53,T:21-25,80,U:123,B:123. Default: None

-m, --max-scans MAX_SCANS

The maximum number of concurrent scans to run.

Default: 50

-mp, --max-port-scans MAX_PORT_SCANS

The maximum number of concurrent port scans to run.

Default: 10 (approx 20% of max-scans unless specified)

-c, --config CONFIG_FILE

Location of AutoRecon's config file. Default:

/root/.config/AutoRecon/config.toml

-g, --global-file GLOBAL_FILE

Location of AutoRecon's global file. Default:

/root/.config/AutoRecon/global.toml

--tags TAGS Tags to determine which plugins should be included.

Separate tags by a plus symbol (+) to group tags

together. Separate groups with a comma (,) to create

multiple groups. For a plugin to be included, it must

have all the tags specified in at least one group.

Default: default

--exclude-tags TAGS Tags to determine which plugins should be excluded.

Separate tags by a plus symbol (+) to group tags

together. Separate groups with a comma (,) to create

multiple groups. For a plugin to be excluded, it must

have all the tags specified in at least one group.

Default: None

`--port-scans PLUGINS` Override `--tags` / `--exclude-tags` for the listed

PortScan plugins (comma separated). Default: None

`--service-scans PLUGINS`

Override `--tags` / `--exclude-tags` for the listed

ServiceScan plugins (comma separated). Default: None

`--reports PLUGINS` Override `--tags` / `--exclude-tags` for the listed Report

plugins (comma separated). Default: None

`--plugins-dir PLUGINS_DIR`

The location of the plugins directory. Default:

`/root/.local/share/AutoRecon/plugins`

`--add-plugins-dir PLUGINS_DIR`

The location of an additional plugins directory to add

to the main one. Default: None

`-l, --list [TYPE]` List all plugins or plugins of a specific type. e.g.

`--list`, `--list port`, `--list service`

`-o, --output OUTPUT` The output directory for results. Default: results

`--single-target` Only scan a single target. A directory named after the

target will not be created. Instead, the directory

structure will be created within the output directory.

Default: False

`--only-scans-dir` Only create the "scans" directory for results. Other

directories (e.g. exploit, loot, report) will not be

created. Default: False

`--no-port-dirs` Don't create directories for ports (e.g. scans/tcp80,

scans/udp53). Instead store all results in the "scans" directory itself. Default: False

--heartbeat HEARTBEAT

Specifies the heartbeat interval (in seconds) for scan status messages. Default: 60

--timeout TIMEOUT Specifies the maximum amount of time in minutes that AutoRecon should run for. Default: None

--target-timeout TARGET_TIMEOUT

Specifies the maximum amount of time in minutes that a target should be scanned for before abandoning it and moving on. Default: None

--nmap NMAP Override the {nmap_extra} variable in scans. Default:
-vv --reason -Pn -T4

--nmap-append NMAP_APPEND

Append to the default {nmap_extra} variable in scans.
Default:

--proxychains Use if you are running AutoRecon via proxychains.
Default: False

--disable-sanity-checks

Disable sanity checks that would otherwise prevent the scans from running. Default: False

--disable-keyboard-control

Disables keyboard control ([s]tatus, Up, Down) if you are in SSH or Docker.

--ignore-plugin-checks

Ignores errors from plugin check functions that would

otherwise prevent AutoRecon from running. Default:

False

--force-services SERVICE [SERVICE ...]

A space separated list of services in the following

style: tcp/80/http tcp/443/https/secure

-mpti, --max-plugin-target-instances PLUGIN:NUMBER [PLUGIN:NUMBER ...]

A space separated list of plugin slugs with the max

number of instances (per target) in the following

style: nmap-http:2 dirbuster:1. Default: None

-mpgi, --max-plugin-global-instances PLUGIN:NUMBER [PLUGIN:NUMBER ...]

A space separated list of plugin slugs with the max

number of global instances in the following style:

nmap-http:2 dirbuster:1. Default: None

--accessible Attempts to make AutoRecon output more accessible to
screenreaders. Default: False

-v, --verbose Enable verbose output. Repeat for more verbosity.

--version Prints the AutoRecon version and exits.

-h, --help Show this help message and exit.

plugin arguments:

These are optional arguments for certain plugins.

--curl.path VALUE The path on the web server to curl. Default: /

--dirbuster.tool {feroxbuster,gobuster,dirsearch,ffuf,dirb}

The tool to use for directory busting. Default:

feroxbuster

`--dirbuster.wordlist VALUE [VALUE ...]`

The wordlist(s) to use when directory busting.

Separate multiple wordlists with spaces. Default: ['/root/.local/share/AutoRecon/wordlists/dirbuster.txt']

`--dirbuster.threads VALUE`

The number of threads to use when directory busting.

Default: 10

`--dirbuster.ext VALUE`

The extensions you wish to fuzz (no dot, comma separated). Default: txt,html,php,asp,aspx,jsp

`--dirbuster.recursive`

Enables recursive searching (where available).

Warning: This may cause significant increases to scan times. Default: False

`--dirbuster.extras VALUE`

Any extra options you wish to pass to the tool when it runs. e.g. `--dirbuster.extras='-s 200,301 --discover-backup'`

`--enum4linux.tool {enum4linux-ng,enum4linux}`

The tool to use for doing Windows and Samba enumeration. Default: enum4linux-ng

`--onesixtyone.community-strings VALUE`

The file containing a list of community strings to try. Default:

/usr/share/seclists/Discovery/SNMP/common-snmp-community-strings-onesixtyone.txt

--subdomain-enum.domain VALUE

The domain to use as the base domain (e.g. example.com) for subdomain enumeration. Default: None

--subdomain-enum.wordlist VALUE [VALUE ...]

The wordlist(s) to use when enumerating subdomains.

Separate multiple wordlists with spaces. Default:

['/usr/share/seclists/Discovery/DNS/subdomains-top1million-110000.txt']

--subdomain-enum.threads VALUE

The number of threads to use when enumerating subdomains. Default: 10

--vhost-enum.hostname VALUE

The hostname to use as the base host (e.g. example.com) for virtual host enumeration. Default: None

--vhost-enum.wordlist VALUE [VALUE ...]

The wordlist(s) to use when enumerating virtual hosts.

Separate multiple wordlists with spaces. Default:

['/usr/share/seclists/Discovery/DNS/subdomains-top1million-110000.txt']

--vhost-enum.threads VALUE

The number of threads to use when enumerating virtual hosts. Default: 10

--wpscan.api-token VALUE

An API Token from wpvulndb.com to help search for more vulnerabilities.

global plugin arguments:

These are optional arguments that can be used by all plugins.

`--global.username-wordlist VALUE`

A wordlist of usernames, useful for bruteforcing.

Default: /usr/share/seclists/Username/top-username-shortlist.txt

`--global.password-wordlist VALUE`

A wordlist of passwords, useful for bruteforcing.

Default:

/usr/share/seclists/Passwords/darkweb2017-top100.txt

`--global.domain VALUE`

The domain to use (if known). Used for DNS and/or

Active Directory. Default: None