

gobuster

Gobuster is a tool used to brute-force: URIs (directories and files) in web sites, DNS subdomains (with wildcard support), Virtual Host names on target web servers, Open Amazon S3 buckets, Open Google Cloud buckets and TFTP servers.

Gobuster is useful for pentesters, ethical hackers and forensics experts. It also can be used for security tests.

Installed size: 9.16 MB

How to install: `sudo apt install gobuster`

Dependencies:

libc6

```
root@kali:~# gobuster -h
```

NAME:

gobuster - the tool you love

USAGE:

gobuster command [command options]

VERSION:

3.8

AUTHORS:

Christian Mehlmauer (@firefart)

OJ Reeves (@TheColonial)

COMMANDS:

- dir Uses directory/file enumeration mode
- vhost Uses VHOST enumeration mode (you most probably want to use the IP address as the URL parameter)
- dns Uses DNS subdomain enumeration mode
- fuzz Uses fuzzing mode. Replaces the keyword FUZZ in the URL, Headers and the request body
- tftp Uses TFTP enumeration mode
- s3 Uses aws bucket enumeration mode
- gcs Uses gcs bucket enumeration mode
- help, h Shows a list of commands or help for one command

GLOBAL OPTIONS:

- help, -h show help
- version, -v print the version