Android Sale Discount Service Guide

The Merchant Sale Discount Service provides all sale discount-related operations—such as retrieval, creation, updating, and deletion of sale discount data.

Below are the key utility features available:

- **Create Merchant Sale Item Discounts**: Creates one or more sale item discounts under the merchant's account.
- **Get All/Specific Sale Item Discounts**: Processes the get merchant discount request and retrieves the specified discounts for the merchant.
- **Update Existing Sale Item Discounts**: Processes the update merchant sale discount request and applies the specified changes to the merchant's sale discount.
- **Delete Merchant Sale Item Discount**: Processes the Delete Merchant Sale Discount request and removes the specified sale discount for the merchant.

Prerequisites

Before you continue, ensure you have the following prerequisites completed and ready:

- **Merchant Client Application Credentials and Access Token:** Ensure that merchant onboarding is complete and that you've received your client application credentials and access token before proceeding.
- **Access to Deluxe Developer Portal:** This portal provides additional resources, API documentation, and integration tools.
- **Merchant Authorization & Accounts Guide:** This step is required to obtain the merchant authorization token and retrieve associated merchant accounts, which are necessary to establish a connection with the terminal.
  - Android Merchant Authorization & Accounts Guide

ON THIS PAGE

Prerequisites

Create Merchant Sale Discount

Get All/Specific Sale Item Discounts

Update Existing Sale Item Discounts

Delete Merchant Sale Item Discount

Create Merchant Sale Discount

Creates one or more sale item discounts under the merchant's account.

Step 1: Create a MerchantDiscountService Object

```
var merchantDiscountService =
MerchantDiscountService()
```

Step 2: Create a Merchant Sale Item Discount

The CreateMerchantDiscountRequest is used to create new discounts for a merchant account. It includes accessToken(via MerchantAccountService), userId, and a discountList of MerchantDiscount objects with details like discountId, discountName, and more.

```
var discount = MerchantDiscount(
discountId: "DISC1001",
discountName: "Summer Sale",
isPercent: true,
discountValue: 15.0,
isEnabled: true
)

var merchantDiscountRequest =
CreateMerchantDiscountRequest(
accessToken: "761f497a-65c4-489e-973d-
79ab84fd3011",
userId: "",
discountList: discountList
);
```

Pass the request and bearer token to the createMerchantDiscount() function.

```
 var response =
merchantDiscountService.createMerchantDiscount(
        createMerchantDiscountRequest =
merchantDiscountRequest,
        bearerToken = token
    )
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

- **If success = true**, the response will include a list of created MerchantDiscount objects, each containing fields such as discountId, discountName, and more.
- **If success = false**, the response indicates a failure, and the corresponding reasons can be found in the errorCode and message fields.

Get All/Specific Sale Item Discounts

Takes the get merchant discount request and then retrieves the requested discounts for the merchant. This can be used to fetch either particular discount details or the entire discounts for the requested user.

Step 1: Create a MerchantDiscountService Object

```
var merchantDiscountService =
MerchantDiscountService()
```

Step 2: Get Merchant Sale Item Discount

The GetMerchantDiscountRequest includes accessToken (via MerchantAccountService), userId, and discountId, the unique identifier of the discount to be fetched.

```
var saleItemDiscountRequest =
GetMerchantDiscountRequest(
accessToken: "761f497a-65c4-489e-973d-
79ab84fd3011",
userId: "",
discountId: "123456"
);
```

Note: *If there is a valid discountId given in the request, then only that specific sale item discount details will be fetched, otherwise it will fetch the entire sale item discounts for the requested merchant.*

Pass the request and bearer token to the getMerchantDiscount() function.

```
 var response =
merchantDiscountService.getMerchantDiscount(
        getMerchantDiscountRequest =
saleItemDiscountRequest,
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

The getMerchantDiscount() function returns a GetMerchantDiscountResponse object which contains the following:

- **If success = true**, response will contain list of MerchantDiscount objects, each containing fields such as discountId, discountName, and more.
- **If success = false**, the response indicates a failure, and the corresponding reasons can be found in the errorCode and message fields.

Update Existing Sale Item Discounts

Processes the update merchant sale discount request and applies the specified changes to the merchant's sale discount.

Step 1: Create a MerchantDiscountService Object

```
var merchantDiscountService =
MerchantDiscountService()
```

Step 2: Update Merchant Sale Item Discount

The UpdateMerchantDiscountRequest includes accessToken (via MerchantAccountService), userId, and a discountList of MerchantDiscount objects with details like discountId, discountName, and more to be updated.

```
var updateSaleItemDiscountRequest =
UpdateMerchantDiscountRequest(
accessToken: "761f497a-65c4-489e-973d-
79ab84fd3011",
userId: "",
discountList: discountList
);
```

Pass the request and bearer token to the updateMerchantDiscount() function.

```
 var response =
merchantDiscountService.updateMerchantDiscount(
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

The updateMerchantDiscount() function returns a UpdateMerchantDiscountResponse object which contains the following:

- **If success = true**, response will contain list of updated MerchantDiscount objects, each containing fields such as discountId, discountName, and more.
- **If success = false**, the response indicates a failure, and the corresponding reasons can be found in the errorCode and message fields.

Delete Merchant Sale Item Discount

Takes the delete merchant sale discount request and then deletes the requested merchant sale discount.

Step 1: Create a MerchantDiscountService Object

```
var merchantDiscountService =
MerchantDiscountService()
```

Step 2: Delete a Merchant Sale Item Discount

The DeleteMerchantDiscountRequest includes accessToken (via MerchantAccountService), userId, and discountId, the unique identifier of the discount to be deleted.

```
var deleteSaleItemDiscountRequest =
DeleteMerchantDiscountRequest(
accessToken: "761f497a-65c4-489e-973d-
79ab84fd3011",
userId: "",
discountId: "1234"
);
```

Pass the request and bearer token to the deleteMerchantDiscount() function.

```
        bearerToken = token
    )
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

The deleteMerchantDiscount() function returns a DeleteMerchantDiscountResponse object which contains the following:

- **If success = true**, response will contain list of MerchantDiscount object which is deleted.
- **If success = false**, the response indicates a failure, and the corresponding reasons can be found in the errorCode and message fields.

Note: *Please refer to the Complete SDK Reference for additional details Android SDK Reference Guide*

Deluxe Corporation, 801 S Marquette Ave,
Minneapolis, MN 55402.

© 2026 Deluxe Corporation