Android Sale Tax Service Guide

The Merchant Sale Tax Service provides a comprehensive set of methods for creating, updating, deleting, and retrieving merchant-specific taxes.

Below are the key utility features available through the Sales Tax Service classes:

- **Create Merchant Sales Taxes**: Registers one or more sales tax entries under the merchant's account.
- **Get All/Specific Merchant Taxes**: Processes the request and retrieves the specified merchant tax records.
- **Update Existing Merchant Taxes**: Processes the request and updates the specified merchant tax records accordingly.
- **Delete a Merchant Tax**: Processes the request and removes the specified merchant tax from the merchant's account.

Prerequisites

Before you continue, ensure you have the following prerequisites completed and ready:

- **Merchant Client Application Credentials and Access Token:** Ensure that merchant onboarding is complete and that you've received your client application credentials and access token before proceeding.
- **Access to Deluxe Developer Portal:** This portal provides additional resources, API documentation, and integration tools.
- **Merchant Authorization & Accounts Guide:** This step is required to obtain the merchant authorization token and retrieve associated merchant accounts, which are necessary to establish a connection with the terminal.
  - Android Merchant Authorization & Accounts Guide

Note: *If you don't have a Deluxe Merchant Account or Access Token, simply visit Merchant Services Get Started and contact*

ON THIS PAGE

Prerequisites

Create Merchant Sales Taxes

Get All/Specific Merchant Taxes

Update Existing Merchant Taxes

Delete a Merchant Tax

Registers one or more sales tax entries under the merchant's account.

Step 1: Create a MerchantTaxService Object

```
var merchantTaxService = MerchantTaxService()
```

Step 2: Create a Merchant Tax

CreateMerchantTaxRequest object is used to create new sales taxes for a merchant account. It includes an accessToken for the selected merchant (via MerchantAccountService) and a taxList of MerchantTax objects with details like tax name, percentage, status, default flag, and other relevant info.

```
var merchantTax1 = MerchantTax(
taxID: "tax_123456",
taxName: "GST",
taxPercentage: 18.0,
isEnabled: true,
isDefault: false,
setForAllItems: true,
defaultForQuickItems: false
)

var merchantTaxRequest = CreateMerchantTaxRequest(
accessToken: token,
taxList: merchantTaxes
);
```

Pass the request and bearer token to the createMerchantTax() function.

```
 var response =
merchantTaxService.createMerchantTax(
       createMerchantTaxRequest =
merchantTaxRequest,
       bearerToken = token
   )
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

On success, the createMerchantTax() function returns a CreateMerchantTaxResponse object containing the relevant response data:

tax and more.

- **If success = false**, the response indicates a failure, and the corresponding reasons can be found in the errorCode and message fields.

Get All/Specific Merchant Taxes

Processes the request and retrieves the specified merchant tax records.

This can be used to retrieve either specific tax details or all taxes associated with the requested user.

Step 1: Create a MerchantTaxService Object

```
var merchantTaxService = MerchantTaxService()
```

Step 2: Get Merchant Taxes

The GetMerchantTaxRequest includes accessToken for the selected merchant account (retrieved via MerchantAccountService) and taxID, the unique identifier of the sales tax to be fetched.

```
var taxRequest = GetMerchantTaxRequest(
accessToken: token,
taxID: taxId
);
```

Note: *If there is a valid taxID given in the request, then only those specific sale tax details will be fetched, otherwise it will fetch the entire sale taxes for the requested merchant.*

Pass the request and bearer token to the getMerchantTax() function.

```
var response = merchantTaxService.getMerchantTax(
      getMerchantTaxRequest = taxRequest,
      bearerToken = token
  )
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

GetMerchantTaxResponse object which contains the following:

- **If success = true**, the response will contain a list of MerchantTax objects, with details such as tax name, tax percentage, whether the tax is enabled, if it is the default tax and more.
- **If success = false**, the response indicates a failure, with details provided in the errorCode and message fields.

Update Existing Merchant Taxes

Processes the request and updates the specified merchant tax records accordingly.

Step 1: Create a MerchantTaxService Object

```
var merchantTaxService = MerchantTaxService()
```

Step 2: Update Merchant Tax

The UpdateMerchantTaxRequest includes accessToken for the selected merchant account (via MerchantAccountService) and a taxList of MerchantTax objects to be updated, with details like tax name, percentage, enabled status, default flag, and other relevant info.

```
var updateTaxRequest = UpdateMerchantTaxRequest(
accessToken: "761f497a-65c4-489e-973d-
79ab84fd3011",
taxList: taxlist
);
```

Pass the request and bearerToken to the updateMerchantTax() function.

```
 var response =
merchantTaxService.updateMerchantTax(
       updateMerchantTaxRequest = updateTaxRequest,
       bearerToken = token
   )
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

- **If success = true**, the response includes a list of MerchantTax objects containing details such as the tax name, tax percentage, whether the tax is enabled, if it is the default tax, and other related information.
- **If success = false**, the response indicates a failure, with the reasons provided in the errorCode and message fields.

Delete a Merchant Tax

Deletes merchant sale taxes by using taxID.

Step 1: Create a MerchantTaxService Object

```
var merchantTaxService = MerchantTaxService()
```

Step 2: Delete Merchant Tax

The DeleteMerchantTaxRequest includes accessToken for the selected merchant account (via MerchantAccountService) and taxID, the unique identifier of the sales tax to be deleted.

```
var deleteTaxRequest = DeleteMerchantTaxRequest(
accessToken: "761f497a-65c4-489e-973d-
79ab84fd3011",
taxID: "existing-tax-id-123"
);
```

Pass the request and bearer token to the deleteMerchantTax() function.

```
 var response =
merchantTaxService.deleteMerchantTax(
       deleteMerchantTaxRequest =
deleteMerchantTax,
       bearerToken = token
   )
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

The deleteMerchantTax() function returns a DeleteMerchantTaxResponse object which contains the

MerchantTax object that was successfully deleted.

- If success = false, the response indicates a failure, with details provided in the errorCode and message fields.

Note: *Please refer to the Complete SDK Reference for additional details Android SDK Reference Guide*

Deluxe.com | Privacy Policy | Do Not Sell My Personal Information

Deluxe Corporation, 801 S Marquette Ave, Minneapolis, MN 55402.

© 2026 Deluxe Corporation