Android Transaction Services Guide

The Transaction Services Guide offers a comprehensive overview of the various merchant transaction services supported by the POS SDK.

Below are the key utility features available through the transaction service classes:

- **Sending Transaction Receipts**: To support digital confirmations, you can send transaction receipts via email or SMS using the Transaction Receipt Service. This enables customers to receive proof of payment through their preferred communication channel.
- **Retrieving Transaction Summary**: Use the Transaction Summary Service to access summary data such as total amounts, transaction counts, and categorized breakdowns—helpful for evaluating overall sales performance.
- **Retrieving Transaction History**: The Transaction Summary Service allows merchants to view past sales by applying various search filters, with support for pagination to navigate large datasets efficiently.
- **Retrieving Transaction Details**: With the Transaction Detail Service, you can access comprehensive information for any specific transaction, including prices, taxes, discounts, tips, and items sold.

Prerequisites

Before you continue, ensure you have the following prerequisites completed and ready:

- **Merchant Client Application Credentials and Access Token:** Ensure that merchant onboarding is complete and that you've received your client application credentials and access token before proceeding.
- **Access to Deluxe Developer Portal:** This portal provides additional resources, API documentation, and integration

ON THIS PAGE

Prerequisites

Sending Transaction Receipts

Retrieving Transaction Summary

Retrieving Transaction History

Retrieving Transaction Details

retrieve associated merchant accounts, which are necessary to establish a connection with the terminal.

Android Merchant Authorization & Accounts Guide

Note: *If you don't have a Deluxe Merchant Account or Access Token, simply visit Merchant Services Get Started and contact us today.*

Sending Transaction Receipts

Transaction Receipt service sends transaction receipts via email or SMS using the provided transaction ID. It supports seamless, digital delivery of payment confirmations to customers.

Step 1: Create a ReceiptService Object

```
var receiptService = ReceiptService()
```

Step 2: Create a ReceiptRequest object

Create a ReceiptRequest with the required parameters: transactionId, and either an emailTo address or an smsTo phone number along with smsCode. If sending via SMS, emailTo can be null; if sending via email, smsTo and smsCode can be null.

```
var request = ReceiptRequest(
transactionId: "TXN1234567890",
emailTo: "customer@example.com",
smsCode: "",
smsTo: "",
);
```

Step 3: Send Transaction Receipt

Pass the request and bearerToken to the getTransactionReceipt() function.

```
var receiptResponse =
receiptService.getTransactionReceipt(
        receiptRequest = request,
        bearerToken = token
    )
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

object with the following details:

- **If success = true**, the receipt was delivered successfully, and the response includes a message confirming delivery via email or SMS.
- **If success = false**, the failure reason is provided in the errorCode and message fields.

Retrieving Transaction Summary

Transaction Summary service fetches total transaction amounts, counts, and breakdowns by status or payment type.

Step 1: Construct a TransactionSummaryService Object

```
var transactionSummaryService =
TransactionSummaryService()
```

Step 2: Construct a TransactionSummaryRequest Object

Create a TransactionSummaryRequest with the required parameters: dateFrom and dateTo (in YYYY-MM-DD format) to define the report's date range, paymentType to filter by payment method, and transactionStatus to specify which transaction statuses to include.

```
val summaryRequest = TransactionSummaryRequest(
userId = "12345",
accessToken = "761f497a-65c4-489e-973d-
79ab84fd3011",
dateFrom = "2025-01-21",
dateTo = "2025-05-21",
paymentType = "Credit",
transactionStatus = "Approved"
)
```

accessToken: This should be the access token for the merchant account selected by the user. Available merchant accounts can be retrieved using the MerchantAccountService.

Step 3: Retrieve Transaction Summary

Pass the request and bearerToken to the getTransactionSummary() function.

```
        bearerToken = bearerToken
    )
```

The **bearerToken** should be the token received from the MerchantAuthorizationService.

Step 4: Handling the TransactionSummaryResponse Object

The getTransactionSummary() function returns a TransactionSummaryResponse object which contains following:

- **If success = true,** the response includes a TransactionSummaryDetails object containing summary information such as total sales, refunds, discounts, number of transactions, tax, average sale amount, and tip amount.
- **If success = false**, the failure reason is provided in the errorCode and message fields.

Retrieving Transaction History

Transaction History service retrieves a paginated list of transactions within a specified date range. It provides structured access to individual transaction records and totals.

Step 1: Construct a TransactionHistoryService Object

```
var transactionHistoryService =
TransactionHistoryService()
```

Step 2: Construct a TransactionHistoryRequest Object

Create a TransactionHistoryRequest with the necessary parameters: queryStartDate and queryEndDate to define the date range for filtering (should be in YYYY-MM-DD format), page and pageSize for pagination, and searchString to filter transactions by a specific keyword or value.

```
val transactionHistoryRequest =
TransactionHistoryRequest(
userId = "12345",
queryStartDate = "2025-01-21",
queryEndDate = "2025-05-21",
page = 1,
pageSize = 10,
searchString = "invoice123",
accessToken = "761f497a-65c4-489e-973d-
```

accessToken: The access token associated with the merchant account selected by the user.

Step 3: Retrieve Transaction History

Pass the request and bearerToken to the getTransactionHistory() function.

```
val transactionHistoryResponse =
transactionHistoryService.getTransactionHistory(
        transactionHistoryRequest =
transactionHistoryRequest,
        bearerToken = token
    )
```

The **bearerToken** should be the token received from the MerchantAuthorizationService.

Step 4: Handling the TransactionHistoryResponse object

The getTransactionHistory() function returns a TransactionHistoryResponse object which contains following:

- **If success = true**, the response includes a list of HistoryResponse objects containing transaction details such as date, time, amount, payment ID, and other relevant information.
- **If success = false**, the response indicates a failure, and the reasons can be found in the errorCode and message fields.

Retrieving Transaction Details

Transaction Detail Service retrieves detailed information for a specific transaction ID. It returns complete data including items, taxes, tips, and card details.

Step 1: Construct a TransactionDetailsService Object

```
val detailService = TransactionDetailsService()
```

Step 2: Construct a TransactionDetailRequest Object

Create a GetTransactionDetailsRequest with the required transactionId parameter, which uniquely identifies the transaction for which the receipt is requested.

```
accessToken ="761f497a-65c4-489e-973d-79ab84fd3011"
)
```

accessToken: The access token associated with the merchant account selected by the user.

Step 3: Retrieve Transaction Details

Pass the request and bearerToken to the getTransactionDetails() function.

```
val transactionDetailsResponse =
transactionDetailsService.getTransactionDetails(
        transactionHistoryRequest =
transactionDetailsRequest,
        bearerToken = token
    )
```

The **bearerToken** should be the token received from the MerchantAuthorizationService.

Step 4: Handling the GetTransactionDetailsResponse Object

The getTransactionDetails() function returns a GetTransactionDetailsResponse object which contains the following:

- **If success = true**, the response contains a HistoryResponse object with detailed transaction information, including date, time, amount, payment ID, and other relevant data.
- **If success = false**, the response indicates a failure, and the corresponding reason can be found in the errorCode and message fields.

Note: *Please refer to the Complete SDK Reference for more details: Android SDK Reference Guide*

deluxe. connect

Payments API

Deluxe.com | Privacy Policy | Do Not Sell My Personal Information

Deluxe Corporation, 801 S Marquette Ave, Minneapolis, MN 55402.

© 2026 Deluxe Corporation