iOS Sale Tax Service Guide

The Merchant Sale Tax Service provides a comprehensive set of methods for creating, updating, deleting, and retrieving merchant-specific taxes.

Below are the key utility features available through the Sales Tax Service classes.

- **Create Merchant Sales Taxes**: Create and add a merchant tax service object.
- **Get All/Specific Merchant Taxes**: Processes the request and retrieves the specified merchant tax records.
- **Update Existing Merchant Taxes**: Processes the request and updates the specified merchant tax records accordingly.
- **Delete a Merchant Tax**: Processes the request and removes the specified merchant tax from the merchant's account.

Prerequisites

Before you continue, ensure you have the following prerequisites completed and ready:

- **Merchant Client Application Credentials and Access Token:** Ensure that merchant onboarding is complete and that you've received your client application credentials and access token before proceeding.
- **Access to Deluxe Developer Portal:** This portal provides additional resources, API documentation, and integration tools.
- **Merchant Authorization & Accounts Guide:** This step is required to obtain the merchant authorization token and retrieve associated merchant accounts, which are necessary to establish a connection with the terminal.
  - iOS Merchant Authorization & Accounts Guide

Note: *If you don't have a Deluxe Merchant Account or Access Token, simply visit Merchant Services Get Started and contact us today.*

ON THIS PAGE

Prerequisites

Create Merchant Sales Taxes

Get All/Specific Merchant Taxes

Update Existing Merchant Taxes

Delete a Merchant Tax

```
let transactionService = MerchantTaxService()
```

Step 2: Create a Merchant Tax

Construct a CreateMerchantTaxRequest by providing the required input parameters, including taxList, which is a list of MerchantTax objects representing the new taxes to be created.

```
let merchantTax = MerchantTax(
   taxName: "GST",
   taxPercentage: 18.0,
   isEnabled: true,
   isDefault: false,
   setForAllItems: true,
   defaultForQuickItems: false,
   taxID: "tax_123456"
)

let request = CreateMerchantTaxRequest(
   accessToken: "761f497a-65c4-489e-973d-
79ab84fd3011",
   taxList: [merchantTax]
)
```

accessToken: This should be the access token for the merchant account selected by the user. Available merchant accounts can be retrieved using the MerchantAccountService.

Pass the request and bearer token to the createMerchantTaxes() method.

```
taxService.createMerchantTaxes(request: request,
bearerToken: bearerToken) { response, error in
if let taxResponse = response {

} else if let error = error {

}
}
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

On success, the createMerchantTaxes() method returns a CreateMerchantTaxResponse object containing the relevant response data:

- **If success = false**, the response indicates a failure, and the corresponding reasons can be found in the errorCode and message fields.

On failure, the method returns an error object that describes the cause of the failure.

Get All/Specific Merchant Taxes

Processes the request and retrieves the specified merchant tax records.

This can be used to retrieve either specific tax details or all taxes associated with the requested user.

Step 1: Create a MerchantTaxService Object

```
let transactionService = MerchantTaxService()
```

Step 2: Get Merchant Taxes

Construct a GetMerchantTaxRequest by providing the required input parameters, including taxID, which is the unique identifier for the tax to be retrieved; if taxID is null or empty, all taxes for the given merchant will be returned.

```
let request = GetMerchantTaxRequest(
accessToken: "761f497a-65c4-489e-973d-
79ab84fd3011",
taxID: "84f547e3-3158-4751-bbaf-0fa58a0e33ba"
)
```

accessToken: This should be the access token for the merchant account selected by the user. Available merchant accounts can be retrieved using the MerchantAccountService.

Pass the request and bearer token to the getMerchantTaxes() method.

```
taxService.getMerchantTaxes(request: request,
bearerToken: bearerToken) { response, error in
if let response = response {

} else if let error = error {
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

On success, getMerchantTaxes() method returns a GetMerchantTaxResponse object containing the following:

- **If success = true**, the response includes a list of MerchantTax objects that were successfully retrieved.
- **If success = false**, the response indicates a failure, with details provided in the errorCode and message fields.

On failure, the method returns an error object that describes the cause of the failure.

Update Existing Merchant Taxes

Processes the request and updates the specified merchant tax records accordingly.

Step 1: Create a MerchantTaxService Object

```
let taxService = MerchantTaxService()
```

Step 2: Update Merchant Tax

The UpdateMerchantTaxRequest object is used to define the data required to update taxes for a merchant account, including a taxList of MerchantTax objects that represent the taxes to be updated.

```
let updateRequest = UpdateMerchantTaxRequest(
accessToken: "761f497a-65c4-489e-973d-
79ab84fd3011",
taxList: [MerchantTax]
)
```

accessToken: This should be the access token for the merchant account selected by the user. Available merchant accounts can be retrieved using the MerchantAccountService.

Pass the request and bearer token to the updateMerchantTaxes() method.

```
} else if let error = error {

}
}
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

On success, updateMerchantTaxes() method returns a UpdateMerchantTaxResponse object containing the following:

- **If success = true**, the response includes a list of MerchantTax objects representing the tax details that were successfully updated.
- **If success = false**, the response indicates a failure, with the reasons provided in the errorCode and message fields.

On failure, the method returns an error object that describes the cause of the failure.

Delete a Merchant Tax

Processes the request and removes the specified merchant tax from the merchant's account.

Step 1: Create a MerchantSaleItemService Object

```
let taxService = MerchantTaxService()
```

Step 2: Delete Merchant Tax

The DeleteMerchantTaxRequest object is used to define the data required to delete a tax for a merchant account, including the taxID, which is the unique identifier of the tax to be deleted.

```
let deleteRequest = DeleteMerchantTaxRequest(
accessToken: "761f497a-65c4-489e-973d-
79ab84fd3011",
taxID: "existing-tax-id-123"
)
```

Pass the request and bearer token to the deleteMerchantSaleItems() method.

```
taxService.deleteMerchantTaxes(request:
deleteRequest, bearerToken: bearerToken) {
response, error in
if let result = response {

} else if let error = error {

}
}
```

The **bearerToken** should be the token obtained from the MerchantAuthorizationService.

Step 3: Response Handling

On success, deleteMerchantTaxes() method returns a DeleteMerchantTaxResponse object containing the following:

- **If success = true**, the response includes a list containing the MerchantTax object that was successfully deleted.
- **If success = false**, the response indicates a failure, with details provided in the errorCode and message fields.

On failure, the method returns an error object that describes the cause of the failure.

Note: *Please refer to the Complete SDK Reference for additional details iOS SDK Reference Guide*

deluxe. connect

Payments API

Deluxe.com | Privacy Policy | Do Not Sell My Personal Information

Deluxe Corporation, 801 S Marquette Ave,
Minneapolis, MN 55402.

© 2026 Deluxe Corporation