

# My Configuration - Architecture




Disclaimer : This documentation is not intended as substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

My Configuration - IO list

Input/Output type description	Totals	My Configuration
Digital inputs	8	
Digital input 24 Vdc	8	8
Digital outputs	8	
Digital output 24 Vdc, Current 100 mA per output, Transmission time 100 µs, Short-circuit protection	8	8
Touchprobe input	4	
Touchprobe input 24 Vdc, input filter 100 µs, TP0 to TP15 10 µs	4	4

Disclaimer : This documentation is not intended as substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

My Configuration - Island configuration



My Configuration - IO list

Input/Output type description	Totals	1 - LMC216CAA1 0000
Digital inputs	8	
Digital input 24 Vdc	8	8
Digital outputs	8	
Digital output 24 Vdc, Current 100 mA per output, Transmission time 100 µs, Short-circuit protection	8	8
Touchprobe input	4	
Touchprobe input 24 Vdc, input filter 100 µs, TP0 to TP15 10 µs	4	4

Disclaimer : This documentation is not intended as substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.