

Aim:- Programs to understand for loops for iterative statements.

Software Required:- Turbo C/C++

Theory:- A loop is used for executing a block of statements repeatedly until a given condition return false.

C For loop:-

This is one of the most frequently used loop in C programming.

Syntax of For loop

```
for (initialization ; condition test ; Increment or decrement)
{
    // Statements to be executed repeatedly
}
```

CODE

```
1 #include <stdio.h>
#include <conio.h>
void main()
{
    int i, n, p;
    clrscr();
    printf("Enter the number : ");
    scanf("%d", &n);
    for (i = 1; i <= 10; i++)
    {
        p = n * i;
        printf("%d * %d = %d\n", n, i, p);
    }
    getch(); }
```

Output of Code 1

Enter the number : 7

7x1 = 7

7x2 = 14

7x3 = 21

7x4 = 28

7x5 = 35

7x6 = 42

7x7 = 49

7x8 = 56

7x9 = 63

7x10 = 70

Output of Code 2

```
*
* *
* * *
* * * *
```

Output of Code 3

```
* * * *
* * *
* *
*
```

actical No.

PAGE NO.

28

DATE:

```
2. #include <stdio.h>
#include <conio.h>
void main()
{
    int i, j;
    clrscr();
    for (i=1; i<=4; i++)
    {
        for (j=1; j<=i; j++)
        {
            printf(" * ");
        }
        printf("\n");
    }
    getch();
}
```

```
3. #include <stdio.h>
#include <conio.h>
void main()
{
    int i, j;
    clrscr();
    for (i=1; i<=4; i++)
    {
        for (j=1; j<=4; j++)
        {
            printf(" * ");
        }
        printf("\n");
    }
    getch();
}
```

Instructor's Sign

Output of the Code:-

```

      *
    * * *
  * * * * *
* * * * *

```

```

4. #include <stdio.h>
   #include <conio.h>
   void main()
   {
     int i, j;
     clrscr();
     for (i=1; i<=4; i++)
     {
       for (j=1; j<=4-i; j++)
       {
         printf(" ");
       }
       for (int k=1; k<=2*i-1; k++)
       {
         printf(" *");
       }
       printf("\n");
     }
     getch();
   }

```

Output of the Code 5

```

      *
     **
    ***
   ****
  *****
 *****
*****
*****
 *****
  *****
   ****
    ***
     **
      *
```

tical No.

PAGE NO.

30

DATE:

```
5. #include <stdio.h>
#include <conio.h>
void main()
{
    int i, j, k;
    clrscr();
    for (i = 1; i <= 5; i++)
    {
        for (j = 1; j <= 5 - i + 1; j++)
        {
            printf("\t");
        }
        for (k = 1; k <= (2 * i); k++)
        {
            printf("* ");
        }
        printf("\n");
    }
    for (i = 4; i >= 1; i--)
    {
        printf("\t");
    }
    for (k = 1; k <= (i * 2); k++)
    {
        printf("* ");
    }
    printf("\n");
}
getch();
```

Instructor's Sign

Viva Question

Q1 Is for loop an entry-controlled loop or an exit-controlled loop?

Ans A for loop is an entry controlled loop. This means that the condition is checked before the loop is executed. If the statement is false from the start, the loop body will not be executed at all.

Q2 What is the difference between for loop & while loop?

Ans The main difference between for loop and while loop is that a for loop is used when the number of iterations is known, while a while loop is used when the number of iterations is unknown.

Q3 What is a nested-loop?

Ans A nested loop is a loop that appears inside the body of another loop. The inside loop is called the inner loop & the loop outside is called outer loop.

Q4 How many times this loop will execute?

```
int main()
{
    int i;
    for (i=0; i<10; i++)
        printf("%d\n", i++);
    i = ++i;
    return 0;
}
```


Ans This code will execute the loop 10 times
initialization $\Rightarrow i = 0 \Rightarrow 1$ time
loop condition : $i \leq 10 \Rightarrow 9$ values
total 10 times.

Q5 Why is for loop used most frequently in programming compared to other loops.

Ans The for loop is a common programming construct because, it is a concise and intuitive way to repeat a block of code a known number of times. For loops are often easier to parallelize.

Aim:- Programs to learn about array & string operations.

Software Required:- Turbo C/C++

Theory:-

- Array - An array is a group (or collection) of same data types. For example an int array holds the element of int types while a float array holds the elements of float types.

How to declare Array in C.

E. `int num[35];` /* An integer array of 35 elements */
`char ch[10];` /* An array of characters for 10 elements */

Similarly an array can be of any data type such as double, float, short etc.

- String - String is an array of characters. In this guide, we learn how to declare strings, how to work with strings in C programming and how to use the pre-defined string handling functions.

We will see how to compare two strings, concatenate strings, copy one string to another & perform such operations using the pre-defined functions of "string.h" header file. In

Output of the Code 7

Enter number of terms: 4

Enter the elements: 5

2

1

8

Array is:

x[0] = 5

x[1] = 2

x[2] = 1

x[3] = 8

Order to use these string functions you must include string.h file in your C program.

Method 1:-

char address[] = {'T', 'E', 'X', 'A', 'S', 'O'};

Code:-

```
#include <stdio.h>
#include <conio.h>
void main()
{
    int x[10], i, n;
    printf("Enter number of terms:");
    scanf("%d", &n);
    printf("Enter the elements:");
    for (i = 0; i < n; i++)
    {
        scanf("%d", &x[i]);
    }
    printf("Array is: \n");
    for (i = 0; i < n; i++)
    {
        printf("x[%d] = %d\n", i, x[i]);
    }
    getch();
}
```


Output of the Code 2

Enter the element: 1

2

3

4

5

6

7

8

9

Actual matrix is:

1 2 3

4 5 6

7 8 9

Transpose is:

1 4 7

2 5 8

3 6 9

Practical No.

PAGE NO.

35

DATE:

```
#include <stdio.h>
#include <conio.h>
void main()
{
    int x[3][3], y[3][3], i, j;
    clrscr();
    printf("Enter the elements:");
    for (i=0; i<3; i++)
    {
        for (j=0; j<3; j++)
        {
            scanf("%d", &x[i][j]);
        }
    }
    printf("Actual matrix is:\n");
    for (i=0; i<3; i++)
    {
        for (j=0; j<3; j++)
        {
            printf("%d\t", x[i][j]);
        }
        printf("\n");
    }
    printf("Transpose is:\n");
    for (i=0; i<3; i++)
    {
        for (j=0; j<3; j++)
        {
            y[i][j] = x[j][i];
        }
    }
    printf("Transpose matrix is:\n");
    for (i=0; i<3; i++)
    {
        for (j=0; j<3; j++)
        {
            printf("%d\t", y[i][j]);
        }
        printf("\n");
    }
    getch();
}
```

Instructor's Sign

Output of the Code 3

Enter I string: Computer

Enter II string: lab

Enter III string: global

length of I string = 8

Reversed string: bal

Copied string: bal

Concatenated string: balglobal

BAL GLOBAL

ical No.

PAGE NO.

36

DATE:

```
#include <string.h>
3. #include <stdio.h>
#include <conio.h>
void main()
{
    char a[10], b[10], c[10];
    int i;
    clrscr();
    printf("Enter I string: ");
    gets(a);
    printf("Enter II string: ");
    gets(b);
    printf("Enter III string: ");
    gets(c);
    i = strlen(a);
    printf("length of I string = %d", i);
    strcpy(b, a);
    printf("In Reversed string: ");
    puts(b);
    strcpy(a, b);
    printf("Copied string: ");
    puts(a);
    strcat("Concatenated string: ");
    puts(a);
    strcpy(c, a);
    puts(c);
    getch();
}
```

Instructor's Sign

Viva Questions

Q1: What is the Difference between an array & a variable?

Ans: The main difference between an array & a variable is that an array can store multiple values, while a variable can only store one value.

Q2: What do you mean by 2-dimensional array?

Ans: A two-dimensional array is a multi-dimensional array data structure that store information in rows and columns, similar to a matrix.

Q3: Differentiate between reading a string using scanf() with "%s" format specifier and using gets().

Ans: gets() considers a whitespace as a part of the string and ends the input upon encountering '\n' or EOF. On the other hand scanf() ends taking input upon encountering a whitespace, '\n' and EOF. scanf() allows to specifying the max character length to be scanned.

Q4: What is the role of "\0" string?

Ans: "\0" (pronounced "null") is a special character used to mark the end of a string.

5. What is the role of strcpy() and strcat()?

Ans strcpy() is used to completely copy one string to another, while strcat() is used to append one string to the end of another string.