



OPERATORS IN JAVA

Velocity



JULY 25, 2022

VELOCITY
Version : 1.1

Operators in Java

“Operators are symbols that perform operations on variables and values.”

Java provides many types of operators which can be used according to the need. They are classified based on the functionality they provide. Some of the types are:

- Arithmetic operators
- Logical operators
- Relational operators
- Assignment operators
- Bitwise operators
- Unary operators
- Ternary operators
- Shift operators
- New operator
- . operator
- Instanceof operator

Let's look at them in details

1. **Arithmetic operators:** They are used to perform simple arithmetic operations on primitive data types.
 - * : Multiplication
 - / : Division
 - % : Modulo
 - + : Addition
 - - : Subtraction

Example

```
public class Demo {  
  
    public static void main(String[] args) {  
        int a = 10;  
        int b = 20;  
        System.out.println("Addition of a and b is :"+(a+b));  
        System.out.println("Subtraction of b and a is :"+(b-a));  
        System.out.println("Multiplication of a and b is:"+ (a*b));  
        System.out.println("Division of a and b is :"+(20/10));  
        System.out.println("Modules of a and b is:"+ (20%10));  
    }  
}
```

Markers Properties Servers Data Source Explorer Snippets Console

<terminated> Demo [Java Application] C:\Program Files\Java\jre1.8.0_331\bin\javaw.exe (16-Jul-2022, 5:39:45 PM)

Addition of a and b is :30
 Substraction of b and a is :10
 Multiplication of a and b is:200
 Division of a and b is :2
 Modules of a and b is:0

2. **Logical Operators:** These operators are used to perform “logical AND” and “logical OR” operations, i.e., a function similar to AND gate and OR gate in digital electronics.

-Logical operators are used to check whether an expression is true or false. They are used in decision making.

Operator	Example	Meaning
&& (Logical AND)	expression1 && expression2	true only if both expression1 and expression2 are true
(Logical OR)	expression1 expression2	true if either expression1 or expression2 is true
! (Logical NOT)	! expression	true if expression is false and vice versa

Example:

```
public class Demo {

    public static void main(String[] args) {
        int x = 5;
        int y = 3;
        int z = 8;

        // && operator
        System.out.println((x > y) && (z > x)); // true
        System.out.println((x > y) && (z < x)); // false

        // || operator
        System.out.println((x < y) || (z > x)); // true
        System.out.println((x > y) || (z < x)); // true
        System.out.println((x < y) || (z < x)); // false

        // ! operator
        System.out.println(!(x == y)); // true
        System.out.println(!(x > y)); // false
    }
}
```

3. **Relational Operators:** These operators are used to check for relations like equality, greater than, and less than. They return Boolean results after the comparison and are extensively used in looping statements as well as conditional if-else statements.

Operator	Description	Example
==	Is Equal To	3 == 5 returns false
!=	Not Equal To	3 != 5 returns true
>	Greater Than	3 > 5 returns false
<	Less Than	3 < 5 returns true
>=	Greater Than or Equal To	3 >= 5 returns false
<=	Less Than or Equal To	3 <= 5 returns true

Example


```
public class Demo {  
  
    public static void main(String[] args) {  
        int x = 10;  
        int y = 20;  
        System.out.println(x>y); //false  
        System.out.println(x<y); //true  
        System.out.println(x>=y); //false  
        System.out.println(x<=y); //true  
        System.out.println(x==y); //false  
        System.out.println(x!=y); //true  
    }  
}
```

4. **Assignment Operators:** Assignment operators are used in Java to assign values to variables.

Operator	Example	Equivalent to
=	a = b;	a = b;
+=	a += b;	a = a + b;
-=	a -= b;	a = a - b;
*=	a *= b;	a = a * b;
/=	a /= b;	a = a / b;
%=	a %= b;	a = a % b;

Example :

```
public class Demo {  
    public static void main(String[] args) {  
        // create variables  
        int a = 10;  
        int b;  
  
        // assign value using =  
        b = a;  
        System.out.println("value of b using =: " + b);  
  
        // assign value using +=  
        b += a;  
        System.out.println("value of b using +=: " + b);  
  
        // assign value using *=  
        b *= a;  
        System.out.println("value of b using *=: " + b);  
  
        // assign value using /=  
        b /= a;  
        System.out.println("value of b using /=: " + b);  
  
        // assign value using %=  
        b %= a;  
        System.out.println("value of b using %=: " + b);  
    }  
}
```



The screenshot shows an IDE interface with a toolbar at the top containing icons for Markers, Properties, Servers, Data Source Explorer, Snippets, and Console. The Console tab is active, displaying the output of the Java application. The output consists of five lines, each corresponding to an assignment operation in the code above. The first line shows 'value of b using =: 10'. The second line shows 'value of b using +=: 20'. The third line shows 'value of b using *=: 200'. The fourth line shows 'value of b using /=: 20'. The fifth line shows 'value of b using %=: 0'.

```
<terminated> Demo [Java Application] C:\Program Files\Java\jre1.8.0_331\bin\javaw.exe (16-Jul-2022, 6:28:23 PM)  
value of b using =: 10  
value of b using +=: 20  
value of b using *=: 200  
value of b using /=: 20  
value of b using %=: 0
```


5. **Bitwise operators:** This operator is used to perform bitwise AND & OR operation.
- a) Bitwise AND (&): The bitwise & operator always checks both conditions whether first condition is true or false.

Expression-1	Expression-2	Result
T	T	T
T	F	F
F	T	F
F	F	F

Example-1

```
public class Demo {  
  
    public static void main(String[] args) {  
  
        int a = 10;  
        int b = 20;  
        int c = 30;  
  
        System.out.println((a > b) & (a < c));  
  
    }  
  
}
```


In this example, first condition $10 > 20$ become false and second condition $10 < 30$ becomes true, hence output is false.



Example-2

```
public class Demo {  
  
    public static void main(String[] args) {  
  
        int a = 10;  
        int b = 20;  
        int c = 30;  
  
        System.out.println((a < b) & (a < c));  
  
    }  
  
}
```

In second example, first condition $10 < 20$ becomes true and second condition $10 < 30$ becomes true, hence output is true.




b) Bitwise OR (|) : The bitwise | operator always checks both conditions whether first condition is true or false.

Expression-1	Expression-2	Result
T	T	T
T	F	T
F	T	T
F	F	F

Example-1


```
public class Demo {  
  
    public static void main(String[] args) {  
  
        int a = 10;  
        int b = 20;  
        int c = 30;  
  
        System.out.println((a > b) | (a < c));  
  
    }  
}
```

In this example, first condition $10 > 20$ becomes false and second condition $10 < 30$ becomes true; hence output is true.



6. **Unary operators:** These operators are used to perform an operation like increment (++) or decrement (--).

```
public class Demo {  
  
    public static void main(String[] args) {  
  
        int x = 10;  
        System.out.println(x++); // 10 (11)  
        System.out.println(++x); // 12  
        System.out.println(x--); // 12 (11)  
        System.out.println(--x); // 10  
  
    }  
}
```



```
<terminated> Demo [Java Application] C:\Program Files\Java\jre1.8.0_331\bin\javaw.exe (16-Jul-2022, 8:48:11 PM)
10
12
12
10
```


7. **Ternary operators:** Java ternary operator is the only conditional operator that takes three operands. It's a one-liner replacement for the if-then-else statement and is used a lot in Java programming.

```
public class Demo {

    public static void main(String[] args) {

        int x = 8;
        int y = 10;
        int result1 = (x<y)?x:y;
        int result2 = (x>y)?x:y;

        System.out.println("Result-1 is : "+result1);
        System.out.println("Result-2 is : "+result2);
    }
}
```



```
<terminated> Demo [Java Application] C:\Program Files\Java\jre1.8.0_331\bin\javaw.exe (16-Jul-2022, 8:58:24 PM)
Result-1 is : 8
Result-2 is : 10
```

8. Shift operators:

Right shift operator (>>) : it is used to move left operands value to right by the number of bits specified by the right operand.

Left shift operator (<<) : it is used to shift all of the bits in a value to the left side of a specified number of times.


```

1
2 public class Demo {
3
4     public static void main(String[] args) {
5
6         int x = 10;
7
8         System.out.println(x<<2); //Left shift
9         System.out.println(x<<3); //Left shift
10        System.out.println(x>>2); //Right shift
11        System.out.println(x>>3); //Right shift
12    }
13
14 }

```

Markers Properties Servers Data Source Explorer Snippets Console

<terminated> Demo [Java Application] C:\Program Files\Java\jre1.8.0_331\bin\javaw.exe (16-Jul-2022, 9:24:42 PM)

```

40
80
2
1

```

Explanation:

- i. On line 8, left shift operators occurs two times (<<), so we write it as 2, On right hand side we shift the position by 2 bits (i.e., numeric 2), Hence statement is 2^2 .
We will always perform the multiplication operation on left shift operators. So, we are putting value of a variable is 10.
Then will calculate, $10 * 2^2 = ?$
Square of 2 is 4, so $10 * 4 = 40$.
We will get the output as 40
- ii. On line 9, left shift operators occurs two times (<<), so we write it as 2, On right hand side we shift the position by 3 bits (i.e., numeric 3), Hence statement is 2^3 .
We will always perform the multiplication operation on left shift operators. So, we are putting value of a variable is 10.
Then will calculate, $10 * 2^3 = ?$
Cube of 2 is 8, so $10 * 8 = 80$.
We will get the output as 80
- iii. On line 10, right shift operators occur two times (>>), so we write it as 2, On right hand side we shift the position by 2 bits (i.e., numeric 2), Hence statement is 2^2 .
We will always perform the division operation on right shift operators. So, we are putting value of a variable is 10.
Then will calculate, $10 / 2^2 = ?$
Square of 2 is 4, so $10 / 4 = 2$.
We will get the output as 2


- iv. On line 11, right shift operators occur two times (\gg), so we write it as 2, On right hand side we shift the position by 3 bits (i.e., numeric 3), Hence statement is 2^3 . We will always perform the division operation on right shift operators. So, we are putting value of a variable is 10. Then will calculate, $10 / 2^3 = ?$ Cube of 2 is 8, so $10 / 8 = 1.25$ but the rounded value is 1. We will get the output as 1

9. **(.) operators:** It is used to refer the member of class using class name or objects.

10. **new operator:** It is used to create the object of class.

11. **instanceof Operator:** The instanceof operator checks whether an object is an instanceof a particular class.

```
public class Demo {  
  
    public static void main(String[] args) {  
  
        String str = "Velocity";  
        boolean result;  
        // checks if str is an instance of  
        // the String class  
        result = str instanceof String;  
        System.out.println("Is str an object of String? " + result);  
  
        Demo demo = new Demo();  
        // checks if demo is an instance of  
        // the Demo class  
        result = demo instanceof Demo;  
        System.out.println("Is demo an object of Demo class? " + result);  
  
    }  
}
```



The screenshot shows the IDE's console window with the following content:

```
<terminated> Demo [Java Application] C:\Program Files\Java\jre1.8.0_331\bin\javaw.exe (16-Jul-2022, 10:00:05 PM)  
Is str an object of String? true  
Is demo an object of Demo class? true
```