

Measurement failures and prospective safeguardsin OMI

Observed failure	Scientific threat	Prospective safeguard	Empirical anchor
1. Parent-value leakage	Designated context not computationally necessary	Remove parent value from current prompt; verify prompt-alone closure	Earlier R2/MCAL S/T prompts reprinted parent values
2. Scorer censoring	Completed/readable model errors could leave denominator	Exact deterministic scorer; retain all completed/readable nonexact outputs as errors	Prospective scorer repair after OMI-3057 audit
3. Stochastic finalizer	Second model call could change worker measurement	Remove unnecessary stochastic finalizer	Finalizer removed prospectively
4. False all-zero derived ledger	Extraction erased completed raw behavior	Persist raw custody; reconstruct deterministically with frozen oracle/scorer/analyzer	336 raw responses preserved; corrected 138/168 LOCAL vs 131/168 CROSS; p=.29398
5. 2048 resource truncation	Planned response absent because output cap exhausted	Classify integrity failure and stop; no replay/resume of exposed bank	Ordinal 335 incomplete max_output_tokens; no confirmatory prefix
6. 8192 prospective requalification	Resource change after exposure could become outcome-driven tuning	Fresh LOCAL-only non-confirmatory qualification before new bank	32/32 complete/readable; zero integrity failures
7. Fresh fixed-bank confirmation	Outcome-informed exploratory signal could be mistaken for confirmation	Wholly fresh N=124 bank; frozen L=(D_U-D_S)/2; no retry/replacement	1,488/1,488 complete; depth primary +0.016129, p=.5368; escalation stopped

Historical states were preserved; the sequence represents measurement hardening, not accumulation of positive evidence.