## Mocka

# B304 포팅 매뉴얼

빌드 및 배포 정리

## 버전 정리

#### **Back-end**

```
Java - 17
SpringBoot - 2.7.0
SpringCloud - 2021.0.3
Swagger - 1.6.6
JavaMail - 1.6.2
QueryDSL - 5.0.0
MariaDB - 11.3.2
Redis - 7.2.4
Kafka - 2.8.1
zookeeper - 3.4.13
Jenkins - 2.440.1
Docker - 2.25
```

#### Front-end

```
node - 22.0.0
npm - 10.5.1
axios - 1.6.8
js-cookie - 3.0.5
pretty-print-json - 3.0.1
react - 18.2.0
react-dom - 18.2.0
zustand - 4.5.2
tailwindcss - 3.4.3
vite - 5.2.0
@faker-js/faker - 8.4.1
```

## 환경 변수 - application.yml - 각 서버마다 다른 파일 사용

```
// mocka Server
server:
port: 8081
spring:
profiles:
  include: env
 datasource:
  url: jdbc:postgresql://k10b304.p.ssafy.io:5432/dbname
  username: username
  password: password
  driver-class-name: org.postgresql.Driver
jpa:
  hibernate:
  properties:
   hibernate:
    dialect: org.hibernate.dialect.PostgreSQLDialect
 mail:
  host: smtp.gmail.com
  port: 587
  username: username
  password: password
  properties:
   mail:
    debug: true
    smtp:
     auth: true
     starttls:
      enable: true
  default-encoding: UTF-8
 security:
  oauth2:
   client:
    registration:
     google:
      scope:
       - profile
       - email
      client-name: google
      client-id: client-id
      client-secret: client-secret
      authorization-grant-type: authorization_code
      redirect-uri:redirect-uri
    provider:
     google:
      authorization-uri: https://mock-a.com/oauth2/authorization/google
      user-info-uri: https://www.googleapis.com/oauth2/v3/userinfo
```

```
token-uri: https://oauth2.googleapis.com/token
jwt:
secret:
data:
redis:
host: k10b304.p.ssafy.io
port: 6379
database: 0
springdoc:
swagger-ui:
path: /api/swagger
hash:
key: key
```

```
// mock server
server:
 port: 8082
spring:
 datasource:
  url: jdbc:postgresql://k10b304.p.ssafy.io:5432/dbname
  username: username
  password: password
  driver-class-name: org.postgresql.Driver
 jpa:
  hibernate:
   ddl-auto: update
  show-sql: true
  properties:
   hibernate:
    format_sql: true
    dialect: org.hibernate.dialect.PostgreSQLDialect
hash:
 key: key
```

### **ERD**

