

NIM : H1D022006

Nama : Jehian Athaya Tsani Az Zuhry

Kasus : 6. Sistem Informasi Mahasiswa

1. Tech Stack


Laravel 11, Breeze, MySQL, Inertia, Vue, SSR, Pest.

2. Skema Database

- [Tabel generate dari laravel dan breeze]
- Tabel program_studi (id, nama, timestamps)
- Tabel mahasiswa (id, nama, nim, program_studi_id, timestamps)
- Tabel mata_kuliah (id, kode, nama, sks, timestamps)
- Tabel nilai (id, mahasiswa_id, mata_kuliah_id, nilai, timestamps)

3. Screenshot Code Migrations

- 2024_06_28_090538_create_program_studi_table.php



```
2024_06_28_090538_create_program_studi_table.php X 2024_06_28_090545_create_mahasiswa...
database > migrations > 2024_06_28_090538_create_program_studi_table.php
1  <?php
2
3  use Illuminate\Database\Migrations\Migration;
4  use Illuminate\Database\Schema\Blueprint;
5  use Illuminate\Support\Facades\Schema;
6
7  return new class extends Migration
8  {
9      public function up(): void
10     {
11         Schema::create('program_studi', function (Blueprint $table) {
12             $table->id();
13             $table->string('nama');
14             $table->timestamps();
15         });
16     }
17
18     public function down(): void
19     {
20         Schema::dropIfExists('program_studi');
21     }
22 };
23
```

- 2024_06_28_090545_create_mahasiswa_table.php

```
2024_06_28_090545_create_mahasiswa_table.php X
database > migrations > 2024_06_28_090545_create_mahasiswa_table.php
1  <?php
2
3  use Illuminate\Database\Migrations\Migration;
4  use Illuminate\Database\Schema\Blueprint;
5  use Illuminate\Support\Facades\Schema;
6
7  return new class extends Migration
8  {
9      public function up(): void
10     {
11         Schema::create('mahasiswa', function (Blueprint $table) {
12             $table->id();
13             $table->string('nama');
14             $table->string('nim')->unique();
15             $table->foreignId('program_studi_id')
16                 ->constrained('program_studi')
17                 ->onDelete('cascade');
18             $table->timestamps();
19         });
20     }
21
22     public function down(): void
23     {
24         Schema::dropIfExists('mahasiswa');
25     }
26 };
```

c. 2024_06_28_090603_create_mata_kuliah_table.php

```
2024_06_28_090603_create_mata_kuliah_table.php X
database > migrations > 2024_06_28_090603_create_mata_kuliah_table.php
1  <?php
2
3  use Illuminate\Database\Migrations\Migration;
4  use Illuminate\Database\Schema\Blueprint;
5  use Illuminate\Support\Facades\Schema;
6
7  return new class extends Migration
8  {
9      public function up(): void
10     {
11         Schema::create('mata_kuliah', function (Blueprint $table) {
12             $table->id();
13             $table->string('kode')->unique();
14             $table->string('nama');
15             $table->integer('sks');
16             $table->timestamps();
17         });
18     }
19
20     public function down(): void
21     {
22         Schema::dropIfExists('mata_kuliah');
23     }
24 };

```

d. 2024_06_28_090624_create_nilai_table.php

```
2024_06_28_090624_create_nilai_table.php X
database > migrations > 2024_06_28_090624_create_nilai_table.php
1  <?php
2
3  use Illuminate\Database\Migrations\Migration;
4  use Illuminate\Database\Schema\Blueprint;
5  use Illuminate\Support\Facades\Schema;
6
7  return new class extends Migration
8  {
9      public function up(): void
10     {
11         Schema::create('nilai', function (Blueprint $table) {
12             $table->id();
13             $table->foreignId('mahasiswa_id')
14                 ->constrained('mahasiswa')
15                 ->onDelete('cascade');
16             $table->foreignId('mata_kuliah_id')
17                 ->constrained('mata_kuliah')
18                 ->onDelete('cascade');
19             $table->float('nilai');
20             $table->timestamps();
21         });
22     }
23
24     public function down(): void
25     {
26         Schema::dropIfExists('nilai');
27     }
28 };
```

4. Screenshot Kode CRUD

a. resources/js/Pages/Auth/Login.vue

```
<script setup>
import Checkbox from '@/Components/Checkbox.vue';
import GuestLayout from '@/Layouts/GuestLayout.vue';
import InputError from '@/Components/InputError.vue';
import InputLabel from '@/Components/InputLabel.vue';
import PrimaryButton from '@/Components/PrimaryButton.vue';
import TextInput from '@/Components/TextInput.vue';
import { Head, Link, useForm } from '@inertiajs/vue3';

defineProps({
  canResetPassword: {
    type: Boolean,
  },
  status: {
    type: String,
  },
});
```

```

const form = useForm({
  email: '',
  password: '',
  remember: false,
});

const submit = () => {
  form.post(route('login'), {
    onFinish: () => form.reset('password'),
  });
};
</script>

<template>
  <GuestLayout>
    <Head title="Log in" />

    <div v-if="status" class="mb-4 font-medium text-sm text-green-600">
      {{ status }}
    </div>

    <form @submit.prevent="submit">
      <div>
        <InputLabel for="email" value="Email" />

        <TextInput
          id="email"
          type="email"
          class="mt-1 block w-full"
          v-model="form.email"
          required
          autofocus
          autocomplete="username"
        />

        <InputError class="mt-2" :message="form.errors.email" />
      </div>

      <div class="mt-4">
        <InputLabel for="password" value="Password" />

        <TextInput
          id="password"
          type="password"
          class="mt-1 block w-full"
          v-model="form.password"
          required
          autocomplete="current-password"

```

```

        />

        <InputError class="mt-2" :message="form.errors.password" />
    </div>

    <div class="block mt-4">
        <label class="flex items-center">
            <Checkbox name="remember" v-model:checked="form.remember"
/>
            <span class="ms-2 text-sm text-gray-600">Remember me</span>
        </label>
    </div>

    <div class="flex items-center justify-end mt-4">
        <Link
            v-if="canResetPassword"
            :href="route('password.request')"
            class="underline text-sm text-gray-600 hover:text-gray-900
rounded-md focus:outline-none focus:ring-2 focus:ring-offset-2
focus:ring-indigo-500"
            >
            Forgot your password?
        </Link>

        <PrimaryButton class="ms-4" :class="{ 'opacity-25':
form.processing }" :disabled="form.processing">
            Log in
        </PrimaryButton>
    </div>
</form>
</GuestLayout>
</template>

```

b. resources/js/Pages/Auth/Register.vue

```

<script setup>
import GuestLayout from '@/Layouts/GuestLayout.vue';
import InputError from '@/Components/InputError.vue';
import InputLabel from '@/Components/InputLabel.vue';
import PrimaryButton from '@/Components/PrimaryButton.vue';
import TextInput from '@/Components/TextInput.vue';
import { Head, Link, useForm } from '@inertiajs/vue3';

const form = useForm({
    name: '',
    email: '',
    password: '',
    password_confirmation: '',
});

```

```
const submit = () => {
  form.post(route('register'), {
    onFinish: () => form.reset('password', 'password_confirmation'),
  });
};
</script>

<template>
  <GuestLayout>
    <Head title="Register" />

    <form @submit.prevent="submit">
      <div>
        <InputLabel for="name" value="Name" />

        <TextInput
          id="name"
          type="text"
          class="mt-1 block w-full"
          v-model="form.name"
          required
          autofocus
          autocomplete="name"
        />

        <InputError class="mt-2" :message="form.errors.name" />
      </div>

      <div class="mt-4">
        <InputLabel for="email" value="Email" />

        <TextInput
          id="email"
          type="email"
          class="mt-1 block w-full"
          v-model="form.email"
          required
          autocomplete="username"
        />

        <InputError class="mt-2" :message="form.errors.email" />
      </div>

      <div class="mt-4">
        <InputLabel for="password" value="Password" />

        <TextInput
          id="password"
          type="password"

```

```

        class="mt-1 block w-full"
        v-model="form.password"
        required
        autocomplete="new-password"
    />

    <InputError class="mt-2" :message="form.errors.password" />
</div>

<div class="mt-4">
    <InputLabel for="password_confirmation" value="Confirm
Password" />

    <TextInput
        id="password_confirmation"
        type="password"
        class="mt-1 block w-full"
        v-model="form.password_confirmation"
        required
        autocomplete="new-password"
    />

    <InputError class="mt-2"
:message="form.errors.password_confirmation" />
</div>

<div class="flex items-center justify-end mt-4">
    <Link
        :href="route('login')"
        class="underline text-sm text-gray-600 hover:text-gray-900
rounded-md focus:outline-none focus:ring-2 focus:ring-offset-2
focus:ring-indigo-500"
    >
        Already registered?
    </Link>

    <PrimaryButton class="ms-4" :class="{ 'opacity-25':
form.processing }" :disabled="form.processing">
        Register
    </PrimaryButton>
</div>
</form>
</GuestLayout>
</template>

```

c. routes/web.php

```

<?php

use App\Http\Controllers\ProfileController;

```



```

use App\Http\Controllers\ProgramStudiController;
use App\Http\Controllers\MahasiswaController;
use App\Http\Controllers\MataKuliahController;
use App\Http\Controllers\NilaiController;
use App\Http\Controllers\DashboardController;
use Illuminate\Foundation\Application;
use Illuminate\Support\Facades\Route;
use Inertia\Inertia;

Route::get('/', function () {
    return Inertia::render('Welcome', [
        'canLogin' => Route::has('login'),
        'canRegister' => Route::has('register'),
        'laravelVersion' => Application::VERSION,
        'phpVersion' => PHP_VERSION,
    ]);
});

Route::get('/dashboard', [DashboardController::class, 'index'])
    ->middleware(['auth', 'verified'])
    ->name('dashboard');

Route::middleware('auth')->group(function () {
    Route::get('/profile', [ProfileController::class,
'edit'])->name('profile.edit');
    Route::patch('/profile', [ProfileController::class,
'update'])->name('profile.update');
    Route::delete('/profile', [ProfileController::class,
'destroy'])->name('profile.destroy');

    Route::delete('/program-studi/bulk-destroy',
[ProgramStudiController::class,
'bulkDestroy'])->name('program-studi.bulk-destroy');
    Route::delete('/mahasiswa/bulk-destroy', [MahasiswaController::class,
'bulkDestroy'])->name('mahasiswa.bulk-destroy');
    Route::delete('/mata-kuliah/bulk-destroy', [MataKuliahController::class,
'bulkDestroy'])->name('mata-kuliah.bulk-destroy');
    Route::delete('/nilai/bulk-destroy', [NilaiController::class,
'bulkDestroy'])->name('nilai.bulk-destroy');
    Route::resource('program-studi', ProgramStudiController::class);
    Route::resource('mahasiswa', MahasiswaController::class);
    Route::resource('mata-kuliah', MataKuliahController::class);
    Route::resource('nilai', NilaiController::class);
});

require __DIR__.'/auth.php';

```

d. Models/ProgramStudi.php

```
ProgramStudi.php X
app > Models > ProgramStudi.php > ProgramStudi
1  <?php
2
3  namespace App\Models;
4
5  use Illuminate\Database\Eloquent\Factories\HasFactory;
6  use Illuminate\Database\Eloquent\Model;
7
8  class ProgramStudi extends Model
9  {
10     use HasFactory;
11
12     protected $table = 'program_studi';
13     protected $fillable = ['nama'];
14
15     public function mahasiswa()
16     {
17         return $this->hasMany(Mahasiswa::class);
18     }
19 }
```

e. Models/Mahasiswa.php

```
Mahasiswa.php X
app > Models > Mahasiswa.php > Mahasiswa
1  <?php
2
3  namespace App\Models;
4
5  use Illuminate\Database\Eloquent\Factories\HasFactory;
6  use Illuminate\Database\Eloquent\Model;
7
8  class Mahasiswa extends Model
9  {
10     use HasFactory;
11
12     protected $table = 'mahasiswa';
13     protected $fillable = ['nama', 'nim', 'program_studi_id'];
14
15     public function programStudi()
16     {
17         return $this->belongsTo(ProgramStudi::class);
18     }
19
20     public function nilai()
21     {
22         return $this->hasMany(Nilai::class);
23     }
24 }
```

f. Models/MataKuliah.php

```
PHP MataKuliah.php X
app > Models > PHP MataKuliah.php > MataKuliah
1  <?php
2
3  namespace App\Models;
4
5  use Illuminate\Database\Eloquent\Factories\HasFactory;
6  use Illuminate\Database\Eloquent\Model;
7
8  class MataKuliah extends Model
9  {
10     use HasFactory;
11
12     protected $table = 'mata_kuliah';
13     protected $fillable = ['kode', 'nama', 'sks'];
14
15     public function nilai()
16     {
17         return $this->hasMany(Nilai::class);
18     }
19 }
```

g. Models/Nilai.php

```
PHP Nilai.php X
app > Models > PHP Nilai.php > Nilai
1  <?php
2
3  namespace App\Models;
4
5  use Illuminate\Database\Eloquent\Factories\HasFactory;
6  use Illuminate\Database\Eloquent\Model;
7
8  class Nilai extends Model
9  {
10     use HasFactory;
11
12     protected $table = 'nilai';
13     protected $fillable = ['mahasiswa_id', 'mata_kuliah_id', 'nilai'];
14
15     public function mahasiswa()
16     {
17         return $this->belongsTo(Mahasiswa::class);
18     }
19
20     public function mataKuliah()
21     {
22         return $this->belongsTo(MataKuliah::class);
23     }
24 }
```

h. ProgramStudiController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\ProgramStudi;
use App\Models\Mahasiswa;
use Illuminate\Http\Request;
use Inertia\Inertia;
use Illuminate\Support\Facades\DB;

class ProgramStudiController extends Controller
{
    public function index(Request $request)
    {
        $search = $request->input('search');
        $page = $request->input('page', 1);
        $sort = $request->input('sort');
        $direction = $request->input('direction', 'asc');

        $query = ProgramStudi::query();

        if ($search) {
            $query->where('nama', 'like', "%{$search}%");
        }

        if ($sort) {
            $query->orderBy($sort, $direction);
        }

        $programStudi = $query->paginate(10, ['*'], 'page',
        $page)->withQueryString();

        return Inertia::render('ProgramStudi/Index', [
            'programStudi' => $programStudi->items(),
            'pagination' => [
                'current_page' => $programStudi->currentPage(),
                'last_page' => $programStudi->lastPage(),
                'per_page' => $programStudi->perPage(),
                'total' => $programStudi->total(),
                'next_page_url' => $programStudi->nextPageUrl(),
                'prev_page_url' => $programStudi->previousPageUrl(),
            ],
            'search' => $search,
            'sort' => [
                'column' => $sort,
                'direction' => $direction,
            ],
        ]);
    }
}
```

```

    }

    public function create()
    {
        return Inertia::render('ProgramStudi/Create');
    }

    public function store(Request $request)
    {
        $validated = $request->validate([
            'nama' => 'required|string|max:255|unique:program_studi,nama',
        ]);

        ProgramStudi::create($validated);

        return redirect()->route('program-studi.index')->with('message',
'Program Studi berhasil ditambahkan');
    }

    public function edit(ProgramStudi $programStudi)
    {
        return Inertia::render('ProgramStudi/Edit', ['programStudi' =>
$programStudi]);
    }

    public function update(Request $request, ProgramStudi $programStudi)
    {
        $validated = $request->validate([
            'nama' => 'required|string|max:255|unique:program_studi,nama,' .
$programStudi->id,
        ]);

        $programStudi->update($validated);

        return redirect()->route('program-studi.index')->with('message',
'Program Studi berhasil diperbarui');
    }

    public function destroy(ProgramStudi $programStudi)
    {
        DB::transaction(function () use ($programStudi) {
            Mahasiswa::where('program_studi_id', $programStudi->id)->delete();
            $programStudi->delete();
        });

        return redirect()->route('program-studi.index')->with('message',
'Program Studi berhasil dihapus');
    }

    public function bulkDestroy(Request $request)

```

```

{
    $sids = $request->input('ids');
    DB::transaction(function () use ($sids) {
        Mahasiswa::whereIn('program_studi_id', $sids)->delete();
        ProgramStudi::whereIn('id', $sids)->delete();
    });
    return redirect()->route('program-studi.index')->with('message',
'Program Studi terpilih berhasil dihapus');
}
}

```

i. MahasiswaController.php

```

<?php

namespace App\Http\Controllers;

use App\Models\Mahasiswa;
use App\Models\ProgramStudi;
use App\Models\Nilai;
use Illuminate\Http\Request;
use Inertia\Inertia;
use Illuminate\Support\Facades\DB;

class MahasiswaController extends Controller
{
    public function index(Request $request)
    {
        $search = $request->input('search');
        $page = $request->input('page', 1);
        $sort = $request->input('sort');
        $direction = $request->input('direction', 'asc');

        $query = Mahasiswa::with('programStudi');

        if ($search) {
            $query->where('nama', 'like', "%{$search}%");
        }

        if ($sort) {
            $query->orderBy($sort, $direction);
        }

        $mahasiswa = $query->paginate(10, ['*'], 'page',
$page)->withQueryString();

        return Inertia::render('Mahasiswa/Index', [
            'mahasiswa' => $mahasiswa->items(),
            'pagination' => [
                'current_page' => $mahasiswa->currentPage(),

```

```

        'last_page' => $mahasiswa->lastPage(),
        'per_page' => $mahasiswa->perPage(),
        'total' => $mahasiswa->total(),
        'next_page_url' => $mahasiswa->nextPageUrl(),
        'prev_page_url' => $mahasiswa->previousPageUrl(),
    ],
    'search' => $search,
    'sort' => [
        'column' => $sort,
        'direction' => $direction,
    ],
]);
}

public function create()
{
    $programStudi = ProgramStudi::all();
    return Inertia::render('Mahasiswa/Create', ['programStudi' =>
$programStudi]);
}

public function store(Request $request)
{
    $validated = $request->validate([
        'nama' => 'required|string|max:255',
        'nim' => 'required|string|unique:mahasiswa,nim',
        'program_studi_id' => 'required|exists:program_studi,id',
    ]);

    Mahasiswa::create($validated);

    return redirect()->route('mahasiswa.index')->with('message', 'Mahasiswa
berhasil ditambahkan');
}

public function edit(Mahasiswa $mahasiswa)
{
    $programStudi = ProgramStudi::all();
    return Inertia::render('Mahasiswa/Edit', [
        'mahasiswa' => $mahasiswa,
        'programStudi' => $programStudi
    ]);
}

public function update(Request $request, Mahasiswa $mahasiswa)
{
    $validated = $request->validate([
        'nama' => 'required|string|max:255',
        'nim' => 'required|string|unique:mahasiswa,nim','.$mahasiswa->id,

```

```

        'program_studi_id' => 'required|exists:program_studi,id',
    ]);

    $mahasiswa->update($validated);

    return redirect()->route('mahasiswa.index')->with('message', 'Mahasiswa
berhasil diperbarui');
}

public function destroy(Mahasiswa $mahasiswa)
{
    DB::transaction(function () use ($mahasiswa) {
        Nilai::where('mahasiswa_id', $mahasiswa->id)->delete();
        $mahasiswa->delete();
    });
    return redirect()->route('mahasiswa.index')->with('message', 'Mahasiswa
berhasil dihapus');
}

public function bulkDestroy(Request $request)
{
    $ids = $request->input('ids');
    DB::transaction(function () use ($ids) {
        Nilai::whereIn('mahasiswa_id', $ids)->delete();
        Mahasiswa::whereIn('id', $ids)->delete();
    });
    return redirect()->route('mahasiswa.index')->with('message', 'Mahasiswa
terpilih berhasil dihapus');
}
}

```

j. MataKuliahController.php

```

<?php

namespace App\Http\Controllers;

use App\Models\MataKuliah;
use App\Models\Nilai;
use Illuminate\Http\Request;
use Inertia\Inertia;
use Illuminate\Support\Facades\DB;

class MataKuliahController extends Controller
{
    public function index(Request $request)
    {
        $search = $request->input('search');
        $page = $request->input('page', 1);
        $sort = $request->input('sort');
    }
}

```



```

$direction = $request->input('direction', 'asc');

$query = MataKuliah::query();

if ($search) {
    $query->where('nama', 'like', "%{$search}%");
}

if ($sort) {
    $query->orderBy($sort, $direction);
}

$mataKuliah = $query->paginate(10)->withQueryString();

return Inertia::render('MataKuliah/Index', [
    'mataKuliah' => $mataKuliah->items(),
    'pagination' => [
        'current_page' => $mataKuliah->currentPage(),
        'last_page' => $mataKuliah->lastPage(),
        'per_page' => $mataKuliah->perPage(),
        'total' => $mataKuliah->total(),
        'next_page_url' => $mataKuliah->nextPageUrl(),
        'prev_page_url' => $mataKuliah->previousPageUrl(),
    ],
    'search' => $search,
    'sort' => [
        'column' => $sort,
        'direction' => $direction,
    ],
]);

}

public function create()
{
    return Inertia::render('MataKuliah/Create');
}

public function store(Request $request)
{
    $validated = $request->validate([
        'kode' => 'required|string|unique:mata_kuliah,kode',
        'nama' => 'required|string|max:255',
        'sks' => 'required|integer|min:1',
    ]);

    MataKuliah::create($validated);

    return redirect()->route('mata-kuliah.index')->with('message', 'Mata
Kuliah berhasil ditambahkan');
}

```

```

    }

    public function edit(MataKuliah $mataKuliah)
    {
        return Inertia::render('MataKuliah/Edit', ['mataKuliah' =>
$mataKuliah]);
    }

    public function update(Request $request, MataKuliah $mataKuliah)
    {
        $validated = $request->validate([
            'kode' =>
'required|string|unique:mata_kuliah,kode, '.$mataKuliah->id,
            'nama' => 'required|string|max:255',
            'sks' => 'required|integer|min:1',
        ]);

        $mataKuliah->update($validated);

        return redirect()->route('mata-kuliah.index')->with('message', 'Mata
Kuliah berhasil diperbarui');
    }

    public function destroy(MataKuliah $mataKuliah)
    {
        DB::transaction(function () use ($mataKuliah) {
            Nilai::where('mata_kuliah_id', $mataKuliah->id)->delete();
            $mataKuliah->delete();
        });
        return redirect()->route('mata-kuliah.index')->with('message', 'Mata
Kuliah berhasil dihapus');
    }

    public function bulkDestroy(Request $request)
    {
        $ids = $request->input('ids');
        DB::transaction(function () use ($ids) {
            Nilai::whereIn('mata_kuliah_id', $ids)->delete();
            MataKuliah::whereIn('id', $ids)->delete();
        });
        return redirect()->route('mata-kuliah.index')->with('message', 'Mata
Kuliah terpilih berhasil dihapus');
    }
}

```

k. NilaiController.php

```

<?php

namespace App\Http\Controllers;

```

```

use App\Models\Nilai;
use App\Models\Mahasiswa;
use App\Models\MataKuliah;
use Illuminate\Http\Request;
use Inertia\Inertia;
use Illuminate\Support\Facades\DB;

class NilaiController extends Controller
{
    public function index(Request $request)
    {
        $search = $request->input('search');
        $page = $request->input('page', 1);
        $sort = $request->input('sort');
        $direction = $request->input('direction', 'asc');

        $query = Nilai::with(['mahasiswa', 'mataKuliah']);

        if ($search) {
            $query->where('mahasiswa_id', 'like', "%{$search}%");
        }

        if ($sort) {
            $query->orderBy($sort, $direction);
        }

        $nilai = $query->paginate(10, ['*'], 'page', $page)->withQueryString();
        return Inertia::render('Nilai/Index', [
            'nilai' => $nilai->items(),
            'pagination' => [
                'current_page' => $nilai->currentPage(),
                'last_page' => $nilai->lastPage(),
                'per_page' => $nilai->perPage(),
                'total' => $nilai->total(),
                'next_page_url' => $nilai->nextPageUrl(),
                'prev_page_url' => $nilai->previousPageUrl(),
            ],
            'search' => $search,
            'sort' => [
                'column' => $sort,
                'direction' => $direction,
            ],
        ]);
    }

    public function create()
    {
        $mahasiswa = Mahasiswa::all();
    }
}

```

```

        $mataKuliah = MataKuliah::all();
        return Inertia::render('Nilai/Create', [
            'mahasiswa' => $mahasiswa,
            'mataKuliah' => $mataKuliah
        ]);
    }

    public function store(Request $request)
    {
        $validated = $request->validate([
            'mahasiswa_id' => 'required|exists:mahasiswa,id',
            'mata_kuliah_id' => 'required|exists:mata_kuliah,id',
            'nilai' => 'required|numeric|min:0|max:100',
        ]);

        Nilai::create($validated);

        return redirect()->route('nilai.index')->with('message', 'Nilai
berhasil ditambahkan');
    }

    public function edit(Nilai $nilai)
    {
        $mahasiswa = Mahasiswa::all();
        $mataKuliah = MataKuliah::all();
        return Inertia::render('Nilai/Edit', [
            'nilai' => $nilai,
            'mahasiswa' => $mahasiswa,
            'mataKuliah' => $mataKuliah
        ]);
    }

    public function update(Request $request, Nilai $nilai)
    {
        $validated = $request->validate([
            'mahasiswa_id' => 'required|exists:mahasiswa,id',
            'mata_kuliah_id' => 'required|exists:mata_kuliah,id',
            'nilai' => 'required|numeric|min:0|max:100',
        ]);

        $nilai->update($validated);

        return redirect()->route('nilai.index')->with('message', 'Nilai
berhasil diperbarui');
    }

    public function destroy(Nilai $nilai)
    {
        DB::transaction(function () use ($nilai) {

```

```

        $nilai->delete();
    });
    return redirect()->route('nilai.index')->with('message', 'Nilai
berhasil dihapus');
}

public function bulkDestroy(Request $request)
{
    $ids = $request->input('ids');
    DB::transaction(function () use ($ids) {
        Nilai::whereIn('id', $ids)->delete();
    });
    return redirect()->route('nilai.index')->with('message', 'Nilai
terpilih berhasil dihapus');
}
}

```

- l. DashboardController.php (bukan crud, hanya untuk menampilkan kesimpulan aliran data)

```

DashboardController.php X
app > Http > Controllers > DashboardController.php > DashboardController
1  <?php
2
3  namespace App\Http\Controllers;
4
5  use Inertia\Inertia;
6  use App\Models\ProgramStudi;
7  use App\Models\Mahasiswa;
8  use App\Models\MataKuliah;
9  use App\Models\Nilai;
10
11 class DashboardController extends Controller
12 {
13     public function index()
14     {
15         $programStudiData = ProgramStudi::withCount('mahasiswa')->get();
16         $jumlahMahasiswa = Mahasiswa::count();
17         $jumlahMataKuliah = MataKuliah::count();
18         $rataRataNilai = Nilai::avg('nilai');
19
20         return Inertia::render('Dashboard', [
21             'programStudiData' => $programStudiData,
22             'jumlahMahasiswa' => $jumlahMahasiswa,
23             'jumlahMataKuliah' => $jumlahMataKuliah,
24             'rataRataNilai' => round($rataRataNilai, 2),
25         ]);
26     }
27 }

```

- m. resources/js/Pages/ProgramStudi/Index.vue

```

<script setup>
import AuthenticatedLayout from '@Layouts/AuthenticatedLayout.vue';
import { Head, Link, useForm, router, usePage } from '@inertiajs/vue3';

```

```

import { ref, defineProps, computed, watch, onMounted } from 'vue';

const props = defineProps({
  programStudi: Array,
  pagination: {
    type: Object,
    required: true,
  },
  search: String,
  sort: Object,
});

const handleDelete = (id) => {
  if (window.confirm('Apakah Anda yakin ingin menghapus data ini?')) {
    router.delete(route('program-studi.destroy', { program_studi: id }));
  }
};

const selectedItems = ref([]);

const form = useForm({
  ids: [],
});

const handleBulkDelete = () => {
  if (window.confirm('Apakah Anda yakin ingin menghapus data yang dipilih?')) {
    {
      form.ids = selectedItems.value;
      form.delete(route('program-studi.bulk-destroy'), {
        preserveScroll: true,
        preserveState: true,
        onSuccess: () => {
          selectedItems.value = [];
        },
      });
    }
  }
};

const toggleSelectAll = (event) => {
  if (event.target.checked) {
    selectedItems.value = props.programStudi.map(program_studi =>
program_studi.id);
  } else {
    selectedItems.value = [];
  }
};

const isAllSelected = computed(() => {
  return selectedItems.value.length === props.programStudi.length;
});

```

```

});

const selectedCount = computed(() => {
  return selectedItems.value.length;
});

const previousPage = () => {
  if (props.pagination.prev_page_url) {
    router.get(route('program-studi.index', { search: search.value, page:
props.pagination.current_page - 1 }));
  }
};

const nextPage = () => {
  if (props.pagination.next_page_url) {
    router.get(route('program-studi.index', { search: search.value, page:
props.pagination.current_page + 1 }));
  }
};

const goToPage = (page) => {
  router.get(route('program-studi.index', { search: search.value, page: page
}));
};

const paginationRange = () => {
  const current = props.pagination.current_page;
  const last = props.pagination.last_page;
  const delta = 2;
  const range = [];
  const rangeWithDots = [];

  for (let i = Math.max(2, current - delta); i <= Math.min(last - 1, current
+ delta); i++) {
    range.push(i);
  }

  if (current - delta > 2) rangeWithDots.push('...');
  rangeWithDots.push(...range);
  if (current + delta < last - 1) rangeWithDots.push('...');

  return rangeWithDots;
};

const search = ref(props.search || '');
let searchTimer = null;

const sort = ref(props.sort || { column: null, direction: 'asc' });

```

```

const performSearch = () => {
  clearTimeout(searchTimer);
  searchTimer = setTimeout(() => {
    router.get(route('program-studi.index', {
      search: search.value,
      page: 1,
      sort: sort.value.column,
      direction: sort.value.direction
    })), {
      preserveState: true,
      replace: true,
    });
  }, 300);
};

watch(search, performSearch);

const handleSort = (column) => {
  if (sort.value.column === column) {
    if (sort.value.direction === 'asc') {
      sort.value.direction = 'desc';
    } else if (sort.value.direction === 'desc') {
      sort.value.column = null;
      sort.value.direction = 'asc';
    } else {
      sort.value.direction = 'asc';
    }
  } else {
    sort.value.column = column;
    sort.value.direction = 'asc';
  }
  router.get(route('program-studi.index', {
    search: search.value,
    page: props.pagination.current_page,
    sort: sort.value.column,
    direction: sort.value.direction
  })), {
    preserveState: true,
    replace: true,
  });
};

const getSortIcon = (column) => {
  if (sort.value.column === column) {
    return sort.value.direction === 'asc' ? '▲' : '▼';
  }
  return '🔍';
};

```


[illegible]

```

        class="border rounded px-2 py-1
focus:outline-none focus:ring-2 focus:ring-blue-500"
      />
      <svg
        class="h-5 w-5 text-gray-400 absolute
right-2 top-1/2 transform -translate-y-1/2"
        xmlns="http://www.w3.org/2000/svg"
        fill="none"
        viewBox="0 0 24 24"
        stroke="currentColor"
      >
        <path
          stroke-linecap="round"
          stroke-linejoin="round"
          stroke-width="2"
          d="M21 21l-6-6m2-5a7 7 0 11-14 0 7 7 0
0 114 0z"
        />
      </svg>
    </div>
  </div>
  <div class="flex justify-between mb-2">
    <span v-if="selectedCount > 0" class="text-sm
text-gray-600">
      {{ selectedCount }} item terpilih
    </span>
    <button v-if="selectedCount > 0"
@click="handleBulkDelete" class="px-4 py-1 bg-red-600 text-white rounded-md
hover:bg-red-700">
      Hapus Data
    </button>
  </div>

  <div v-if="props.programStudi.length === 0"
class="text-center py-4 text-gray-600">
    Tidak ada data yang sesuai.
  </div>

  <table v-else class="min-w-full divide-y
divide-gray-200">
    <thead>
      <tr>
        <th class="px-6 py-3 bg-gray-50 text-left">
          <input class="rounded-[4px]"
type="checkbox" @change="toggleSelectAll" :checked="isAllSelected">
        </th>
        <th @click="handleSort('nama')" class="px-6
py-3 bg-gray-50 text-left text-xs leading-4 font-medium text-gray-500 uppercase
tracking-wider cursor-pointer">

```

```

Nama
    <span class="ml-1">{{
getSortIcon('nama') }}</span>
    </th>
    <th class="px-6 py-3 bg-gray-50 text-left
text-xs leading-4 font-medium text-gray-500 uppercase tracking-wider">Aksi</th>
    </tr>
</thead>
<tbody class="bg-white divide-y divide-gray-200">
    <tr v-for="program_studi in props.programStudi"
:key="program_studi.id">
        <td class="px-6 py-4 whitespace-no-wrap">
            <input class="rounded-[4px]"
type="checkbox" v-model="selectedItems" :value="program_studi.id">
        </td>
        <td class="px-6 py-4 whitespace-no-wrap">{{
program_studi.nama }}</td>
        <td class="px-6 py-4 whitespace-no-wrap
flex gap-2">
            <Link
:href="route('program-studi.edit', { program_studi: program_studi.id })"
class="text-yellow-600 hover:text-yellow-900">Edit</Link>
            <button
@click="handleDelete(program_studi.id)" class="text-red-600
hover:text-red-900">Hapus</button>
        </td>
    </tr>
</tbody>
</table>

<div class="mt-4 flex justify-between items-center">
    <div>
        Tampil {{ (props.pagination.current_page - 1) *
props.pagination.per_page + 1 }}-{{ Math.min(props.pagination.current_page *
props.pagination.per_page, props.pagination.total) }} dari {{
props.pagination.total }} data
    </div>
    <div class="flex space-x-2">
        <button @click="previousPage"
:disabled="!props.pagination.prev_page_url" class="px-4 py-2 bg-gray-800
text-white rounded-md" :class="{ 'opacity-50 cursor-not-allowed':
!props.pagination.prev_page_url }">
            <span class="hidden sm:inline">Prev</span>
            <span class="sm:hidden"><</span>
        </button>
        <button @click="goToPage(1)" class="hidden
sm:inline px-4 py-2 bg-gray-800 text-white rounded-md" :class="{ 'bg-blue-500':
props.pagination.current_page === 1 }">

```

```

</button>
<template v-for="page in paginationRange()"
:key="page">
    <span v-if="page === '...' " class="hidden
sm:inline px-4 py-2">...</span>
    <button v-else @click="goToPage(page)"
class="hidden sm:inline px-4 py-2 bg-gray-800 text-white rounded-md" :class="{
'bg-blue-500': props.pagination.current_page === page }">
        {{ page }}
    </button>
</template>
<button v-if="props.pagination.last_page > 1"
@click="goToPage(props.pagination.last_page)" class="hidden sm:inline px-4 py-2
bg-gray-800 text-white rounded-md" :class="{ 'bg-blue-500':
props.pagination.current_page === props.pagination.last_page }">
    {{ props.pagination.last_page }}
</button>
<button @click="nextPage"
:disabled="!props.pagination.next_page_url" class="px-4 py-2 bg-gray-800
text-white rounded-md" :class="{ 'opacity-50 cursor-not-allowed':
!props.pagination.next_page_url }">
    <span class="hidden sm:inline">Next</span>
    <span class="sm:hidden">></span>
</button>
</div>
</div>
</div>
</div>
</div>
</AuthenticatedLayout>
</template>

```

n. resources/js/Pages/ProgramStudi/Create.vue

```

<script setup>
import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout.vue';
import { Head, useForm, usePage } from '@inertiajs/vue3';
import { ref, computed } from 'vue';

const form = useForm({
    nama: '',
});

const submit = () => {
    form.post(route('program-studi.store'));
};

const errors = computed(() => usePage().props.errors);
</script>

```

```

<template>
  <Head title="Tambah Program Studi" />

  <AuthenticatedLayout>
    <template #header>
      <h2 class="font-semibold text-xl text-gray-800 leading-tight">Tambah Program Studi</h2>
    </template>

    <div class="py-12">
      <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
        <div v-if="Object.keys(errors).length > 0" class="mb-4 bg-red-100 border border-red-400 text-red-700 px-4 py-3 rounded relative" role="alert">
          <strong class="font-bold">Oops! </strong>
          <span class="block sm:inline">Ada beberapa kesalahan:</span>
          <ul class="mt-2 list-disc list-inside">
            <li v-for="(error, key) in errors" :key="key">{{ error }}</li>
          </ul>
        </div>
        <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
          <div class="p-6 text-gray-900">
            <form @submit.prevent="submit">
              <div>
                <label for="nama" class="block font-medium text-sm text-gray-700">Nama Program Studi</label>
                <input id="nama" v-model="form.nama" type="text" class="mt-1 block w-full" required autofocus>
                <div v-if="form.errors.nama" class="text-red-500 mt-2 text-sm">{{ form.errors.nama }}</div>
              </div>

              <div class="flex items-center justify-end mt-4">
                <button type="submit" class="px-4 py-2 bg-gray-800 text-white rounded-md" :disabled="form.processing">Simpan</button>
              </div>
            </form>
          </div>
        </div>
      </div>
    </div>
  </AuthenticatedLayout>
</template>

```

o. resources/js/Pages/ProgramStudi/Edit.vue

```
<script setup>
```

```

import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout.vue';
import { Head, useForm, usePage } from '@inertiajs/vue3';
import { ref, computed } from 'vue';

const props = defineProps({
  programStudi: Object,
});

const form = useForm({
  nama: props.programStudi.nama,
});

const submit = () => {
  form.put(route('program-studi.update', props.programStudi.id));
};

const errors = computed(() => usePage().props.errors);
</script>

<template>
  <Head title="Edit Program Studi" />

  <AuthenticatedLayout>
    <template #header>
      <h2 class="font-semibold text-xl text-gray-800 leading-tight">Edit
Program Studi</h2>
    </template>

    <div class="py-12">
      <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
        <div v-if="Object.keys(errors).length > 0" class="mb-4
bg-red-100 border border-red-400 text-red-700 px-4 py-3 rounded relative"
role="alert">

          <strong class="font-bold">Oops! </strong>
          <span class="block sm:inline">Ada beberapa
kesalahan:</span>

          <ul class="mt-2 list-disc list-inside">
            <li v-for="(error, key) in errors" :key="key">{{ error
}}</li>
          </ul>
        </div>
        <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
          <div class="p-6 text-gray-900">
            <form @submit.prevent="submit">
              <div>
                <label for="nama" class="block font-medium
text-sm text-gray-700">Nama Program Studi</label>
                <input id="nama" v-model="form.nama"
type="text" class="mt-1 block w-full" required autofocus>

```

```

        <div v-if="form.errors.nama"
class="text-red-500 mt-2 text-sm">{{ form.errors.nama }}</div>
        </div>

        <div class="flex items-center justify-end mt-4">
            <button type="submit" class="px-4 py-2
bg-gray-800 text-white rounded-md" :disabled="form.processing">Update</button>
        </div>
    </form>
</div>
</div>
</div>
</div>
</AuthenticatedLayout>
</template>

```

p. resources/js/Pages/Mahasiswa/Index.vue

```

<script setup>
import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout.vue';
import { Head, Link, useForm, router, usePage } from '@inertiajs/vue3';
import { ref, defineProps, computed, watch, onMounted } from 'vue';

const props = defineProps({
    mahasiswa: Array,
    pagination: {
        type: Object,
        required: true,
    },
    search: String,
    sort: Object,
});

const handleDelete = (id) => {
    if (window.confirm('Apakah Anda yakin ingin menghapus data ini?')) {
        router.delete(route('mahasiswa.destroy', { mahasiswa: id }));
    }
};

const selectedItems = ref([]);

const form = useForm({
    ids: [],
});

const handleBulkDelete = () => {
    if (window.confirm('Apakah Anda yakin ingin menghapus data yang dipilih?')) {
        form.ids = selectedItems.value;
        form.delete(route('mahasiswa.bulk-destroy'), {

```

```

        preserveScroll: true,
        preserveState: true,
        onSuccess: () => {
            selectedItems.value = [];
        },
    });
}
});

const toggleSelectAll = (event) => {
    if (event.target.checked) {
        selectedItems.value = props.mahasiswa.map(mhs => mhs.id);
    } else {
        selectedItems.value = [];
    }
};

const isAllSelected = computed(() => {
    return selectedItems.value.length === props.mahasiswa.length;
});

const selectedCount = computed(() => {
    return selectedItems.value.length;
});

const previousPage = () => {
    if (props.pagination.prev_page_url) {
        router.get(route('mahasiswa.index', { search: search.value, page:
props.pagination.current_page - 1 }));
    }
};

const nextPage = () => {
    if (props.pagination.next_page_url) {
        router.get(route('mahasiswa.index', { search: search.value, page:
props.pagination.current_page + 1 }));
    }
};

const goToPage = (page) => {
    router.get(route('mahasiswa.index', { search: search.value, page: page }));
};

const paginationRange = () => {
    const current = props.pagination.current_page;
    const last = props.pagination.last_page;
    const delta = 2;
    const range = [];
    const rangeWithDots = [];

```



```

    for (let i = Math.max(2, current - delta); i <= Math.min(last - 1, current
+ delta); i++) {
        range.push(i);
    }

    if (current - delta > 2) rangeWithDots.push('...');
    rangeWithDots.push(...range);
    if (current + delta < last - 1) rangeWithDots.push('...');

    return rangeWithDots;
};

const search = ref(props.search || '');
let searchTimer = null;

const sort = ref(props.sort || { column: null, direction: 'asc' });

const performSearch = () => {
    clearTimeout(searchTimer);
    searchTimer = setTimeout(() => {
        router.get(route('mahasiswa.index', {
            search: search.value,
            page: 1,
            sort: sort.value.column,
            direction: sort.value.direction
        })), {
            preserveState: true,
            replace: true,
        });
    }, 300);
};

watch(search, performSearch);

const handleSort = (column) => {
    if (sort.value.column === column) {
        if (sort.value.direction === 'asc') {
            sort.value.direction = 'desc';
        } else if (sort.value.direction === 'desc') {
            sort.value.column = null;
            sort.value.direction = 'asc';
        } else {
            sort.value.direction = 'asc';
        }
    } else {
        sort.value.column = column;
        sort.value.direction = 'asc';
    }
}

```

```

router.get(route('mahasiswa.index', {
  search: search.value,
  page: props.pagination.current_page,
  sort: sort.value.column,
  direction: sort.value.direction
})), {
  preserveState: true,
  replace: true,
});
});

const getSortIcon = (column) => {
  if (sort.value.column === column) {
    return sort.value.direction === 'asc' ? '▲' : '▼';
  }
  return '↕';
};

const page = usePage();
const message = ref('');

watch(() => page.props.flash.message, (newMessage) => {
  message.value = newMessage;
  if (newMessage) {
    setTimeout(() => {
      message.value = '';
    }, 5000);
  }
}, { immediate: true });
</script>

<template>
  <Head title="Mahasiswa" />

  <AuthenticatedLayout>
    <template #header>
      <h2 class="font-semibold text-xl text-gray-800 leading-tight">Mahasiswa</h2>
    </template>

    <div class="py-12">
      <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
        <div v-if="message" class="mb-4 bg-green-100 border border-green-400 text-green-700 px-4 py-3 rounded relative" role="alert">
          <span class="block sm:inline">{{ message }}</span>
        </div>
        <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
          <div class="p-6 text-gray-900">
            <div class="flex justify-between mb-2">

```

```

<div class="space-x-2">
  <Link :href="route('mahasiswa.create')"
class="inline-flex items-center px-4 py-2 bg-gray-800 border border-transparent
rounded-md font-semibold text-xs text-white uppercase tracking-widest
hover:bg-gray-700 focus:bg-gray-700 active:bg-gray-900 focus:outline-none
focus:ring-2 focus:ring-indigo-500 focus:ring-offset-2 transition ease-in-out
duration-150">

    <span class="hidden sm:inline">Tambah
Mahasiswa</span>

    <span class="sm:hidden">+</span>
  </Link>

</div>
<div class="relative">
  <input
    v-model="search"
    type="text"
    placeholder="Cari mahasiswa..."
    class="border rounded px-2 py-1
focus:outline-none focus:ring-2 focus:ring-blue-500"
  />
  <svg
    class="h-5 w-5 text-gray-400 absolute
right-2 top-1/2 transform -translate-y-1/2"
    xmlns="http://www.w3.org/2000/svg"
    fill="none"
    viewBox="0 0 24 24"
    stroke="currentColor"
  >
    <path
      stroke-linecap="round"
      stroke-linejoin="round"
      stroke-width="2"
      d="M21 21l-6-6m2-5a7 7 0 11-14 0 7 7 0
0 114 0z"
    />
  </svg>
</div>
</div>
<div class="flex justify-between mb-2">
  <span v-if="selectedCount > 0" class="text-sm
text-gray-600">

    {{ selectedCount }} item terpilih
  </span>
  <button v-if="selectedCount > 0"
@click="handleBulkDelete" class="px-4 py-1 bg-red-600 text-white rounded-md
hover:bg-red-700">

    Hapus Data
  </button>

```

```

        </div>

        <div v-if="props.mahasiswa.length === 0"
class="text-center py-4 text-gray-600">
            Tidak ada data yang sesuai.
        </div>

        <table v-else class="min-w-full divide-y
divide-gray-200">
            <thead>
                <tr>
                    <th class="px-6 py-3 bg-gray-50 text-left">
                        <input class="rounded-[4px]"
type="checkbox" @change="toggleSelectAll" :checked="isAllSelected">
                    </th>
                    <th @click="handleSort('nama')" class="px-6
py-3 bg-gray-50 text-left text-xs leading-4 font-medium text-gray-500 uppercase
tracking-wider cursor-pointer">
                        Nama
                        <span class="ml-1">{{
getSortIcon('nama') }}</span>
                    </th>
                    <th @click="handleSort('nim')" class="px-6
py-3 bg-gray-50 text-left text-xs leading-4 font-medium text-gray-500 uppercase
tracking-wider cursor-pointer">
                        NIM
                        <span class="ml-1">{{
getSortIcon('nim') }}</span>
                    </th>
                    <th @click="handleSort('program_studi_id')"
class="px-6 py-3 bg-gray-50 text-left text-xs leading-4 font-medium
text-gray-500 uppercase tracking-wider cursor-pointer">
                        Program Studi
                        <span class="ml-1">{{
getSortIcon('program_studi_id') }}</span>
                    </th>
                    <th class="px-6 py-3 bg-gray-50 text-left
text-xs leading-4 font-medium text-gray-500 uppercase tracking-wider">Aksi</th>
                </tr>
            </thead>
            <tbody class="bg-white divide-y divide-gray-200">
                <tr v-for="mhs in props.mahasiswa"
:key="mhs.id">
                    <td class="px-6 py-4 whitespace-no-wrap">
                        <input class="rounded-[4px]"
type="checkbox" v-model="selectedItems" :value="mhs.id">
                    </td>
                    <td class="px-6 py-4 whitespace-no-wrap">{{
mhs.nama }}</td>

```

```

<td class="px-6 py-4 whitespace-no-wrap">{{
mhs.nim }}</td>

<td class="px-6 py-4 whitespace-no-wrap">{{
mhs.program_studi.nama }}</td>

<td class="px-6 py-4 whitespace-no-wrap
flex gap-2">

<Link :href="route('mahasiswa.edit', {
mahasiswa: mhs.id }}" class="text-yellow-600 hover:text-yellow-900">Edit</Link>
<button @click="handleDelete(mhs.id)"
class="text-red-600 hover:text-red-900">Hapus</button>

</td>
</tr>
</tbody>
</table>

<div class="mt-4 flex justify-between items-center">
<div>
Tampil {{ (props.pagination.current_page - 1) *
props.pagination.per_page + 1 }}-{{ Math.min(props.pagination.current_page *
props.pagination.per_page, props.pagination.total) }} dari {{
props.pagination.total }} data

</div>
<div class="flex space-x-2">
<button @click="previousPage"
:disabled="!props.pagination.prev_page_url" class="px-4 py-2 bg-gray-800
text-white rounded-md :class='{ 'opacity-50 cursor-not-allowed':
!props.pagination.prev_page_url }'">
<span class="hidden sm:inline">Prev</span>
<span class="sm:hidden"><</span>
</button>
<button @click="goToPage(1)" class="hidden
sm:inline px-4 py-2 bg-gray-800 text-white rounded-md :class='{ 'bg-blue-500':
props.pagination.current_page === 1 }'">
1
</button>
<template v-for="page in paginationRange()"
:key="page">
<span v-if="page === '...' " class="hidden
sm:inline px-4 py-2">...</span>
<button v-else @click="goToPage(page)"
class="hidden sm:inline px-4 py-2 bg-gray-800 text-white rounded-md :class='{
'bg-blue-500': props.pagination.current_page === page }'">
{{ page }}
</button>
</template>
<button v-if="props.pagination.last_page > 1"
@click="goToPage(props.pagination.last_page)" class="hidden sm:inline px-4 py-2
bg-gray-800 text-white rounded-md :class='{ 'bg-blue-500':
props.pagination.current_page === props.pagination.last_page }'">

```

```

                {{ props.pagination.last_page }}
            </button>
            <button @click="nextPage"
:disabled="!props.pagination.next_page_url" class="px-4 py-2 bg-gray-800
text-white rounded-md :class='{ 'opacity-50 cursor-not-allowed':
!props.pagination.next_page_url }">
                <span class="hidden sm:inline">Next</span>
                <span class="sm:hidden">></span>
            </button>
        </div>
    </div>
</div>
</div>
</div>
</div>
</AuthenticatedLayout>
</template>

```

q. resources/js/Pages/Mahasiswa/Create.vue

```

<script setup>
import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout.vue';
import { Head, useForm, usePage } from '@inertiajs/vue3';
import { ref, computed } from 'vue';

const props = defineProps({
    programStudi: Array,
});

const form = useForm({
    nama: '',
    nim: '',
    program_studi_id: '',
});

const submit = () => {
    form.post(route('mahasiswa.store'));
};

const errors = computed(() => usePage().props.errors);
</script>

<template>
    <Head title="Tambah Mahasiswa" />

    <AuthenticatedLayout>
        <template #header>
            <h2 class="font-semibold text-xl text-gray-800
leading-tight">Tambah Mahasiswa</h2>
        </template>
    </AuthenticatedLayout>
</template>

```

```

<div class="py-12">
  <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
    <div v-if="Object.keys(errors).length > 0" class="mb-4
bg-red-100 border border-red-400 text-red-700 px-4 py-3 rounded relative"
role="alert">

      <strong class="font-bold">Oops! </strong>
      <span class="block sm:inline">Ada beberapa
kesalahan:</span>

      <ul class="mt-2 list-disc list-inside">
        <li v-for="(error, key) in errors" :key="key">{{ error
}}</li>

      </ul>
    </div>
    <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
      <div class="p-6 text-gray-900">
        <form @submit.prevent="submit">
          <div>
            <label for="nama" class="block font-medium
text-sm text-gray-700">Nama Mahasiswa</label>
            <input id="nama" v-model="form.nama"
type="text" class="mt-1 block w-full" required autofocus>
            <div v-if="form.errors.nama"
class="text-red-500 mt-2 text-sm">{{ form.errors.nama }}</div>
          </div>
          <div>
            <label for="nim" class="block font-medium
text-sm text-gray-700">NIM</label>
            <input id="nim" v-model="form.nim" type="text"
class="mt-1 block w-full" required autofocus>
            <div v-if="form.errors.nim" class="text-red-500
mt-2 text-sm">{{ form.errors.nim }}</div>
          </div>
          <div>
            <label for="program_studi_id" class="block
font-medium text-sm text-gray-700">Program Studi</label>
            <select id="program_studi_id"
v-model="form.program_studi_id" class="mt-1 block w-full" required>
              <option v-for="program_studi in
props.programStudi" :key="program_studi.id" :value="program_studi.id">{{
program_studi.nama }}</option>
            </select>
            <div v-if="form.errors.program_studi_id"
class="text-red-500 mt-2 text-sm">{{ form.errors.program_studi_id }}</div>
          </div>

          <div class="flex items-center justify-end mt-4">
            <button type="submit" class="px-4 py-2
bg-gray-800 text-white rounded-md" :disabled="form.processing">Simpan</button>

```

```

        </div>
      </form>
    </div>
  </div>
</div>
</AuthenticatedLayout>
</template>

```

r. resources/js/Pages/Mahasiswa/Edit.vue

```

<script setup>
import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout.vue';
import { Head, useForm, usePage } from '@inertiajs/vue3';
import { ref, computed } from 'vue';

const props = defineProps({
  mahasiswa: Object,
  programStudi: Array,
});

const form = useForm({
  nama: props.mahasiswa.nama,
  nim: props.mahasiswa.nim,
  program_studi_id: props.mahasiswa.program_studi_id,
});

const submit = () => {
  form.put(route('mahasiswa.update', props.mahasiswa.id));
};

const errors = computed(() => usePage().props.errors);
</script>

<template>
  <Head title="Edit Mahasiswa" />

  <AuthenticatedLayout>
    <template #header>
      <h2 class="font-semibold text-xl text-gray-800 leading-tight">Edit
Mahasiswa</h2>
    </template>

    <div class="py-12">
      <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
        <div v-if="Object.keys(errors).length > 0" class="mb-4
bg-red-100 border border-red-400 text-red-700 px-4 py-3 rounded relative"
role="alert">
          <strong class="font-bold">Oops! </strong>

```



```

        <span class="block sm:inline">Ada beberapa
kesalahan:</span>

        <ul class="mt-2 list-disc list-inside">
            <li v-for="(error, key) in errors" :key="key">{{ error
        }}</li>

        </ul>
    </div>
    <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
        <div class="p-6 text-gray-900">
            <form @submit.prevent="submit">
                <div>
                    <label for="nama" class="block font-medium
text-sm text-gray-700">Nama Mahasiswa</label>
                    <input id="nama" v-model="form.nama"
type="text" class="mt-1 block w-full" required autofocus>
                    <div v-if="form.errors.nama"
class="text-red-500 mt-2 text-sm">{{ form.errors.nama }}</div>
                </div>
                <div>
                    <label for="nim" class="block font-medium
text-sm text-gray-700">NIM</label>
                    <input id="nim" v-model="form.nim" type="text"
class="mt-1 block w-full" required>
                    <div v-if="form.errors.nim" class="text-red-500
mt-2 text-sm">{{ form.errors.nim }}</div>
                </div>
                <div>
                    <label for="program_studi_id" class="block
font-medium text-sm text-gray-700">Program Studi</label>
                    <select id="program_studi_id"
v-model="form.program_studi_id" class="mt-1 block w-full" required>
                        <option v-for="program_studi in
props.programStudi" :key="program_studi.id" :value="program_studi.id">{{
program_studi.nama }}</option>
                    </select>
                    <div v-if="form.errors.program_studi_id"
class="text-red-500 mt-2 text-sm">{{ form.errors.program_studi_id }}</div>
                </div>

                <div class="flex items-center justify-end mt-4">
                    <button type="submit" class="px-4 py-2
bg-gray-800 text-white rounded-md" :disabled="form.processing">Update</button>
                </div>
            </form>
        </div>
    </div>
</div>
</div>
</AuthenticatedLayout>

```

```
</template>
```

s. resources/js/Pages/MataKuliah/Index.vue

```
<script setup>
import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout.vue';
import { Head, Link, useForm, router, usePage } from '@inertiajs/vue3';
import { ref, defineProps, computed, watch, onMounted } from 'vue';

const props = defineProps({
  mataKuliah: Array,
  pagination: {
    type: Object,
    required: true,
  },
  search: String,
  sort: Object,
});

const handleDelete = (id) => {
  if (window.confirm('Apakah Anda yakin ingin menghapus data ini?')) {
    router.delete(route('mata-kuliah.destroy', { mata_kuliah: id }));
  }
};

const selectedItems = ref([]);

const form = useForm({
  ids: [],
});

const handleBulkDelete = () => {
  if (window.confirm('Apakah Anda yakin ingin menghapus data yang dipilih?')) {
    {
      form.ids = selectedItems.value;
      form.delete(route('mata-kuliah.bulk-destroy'), {
        preserveScroll: true,
        preserveState: true,
        onSuccess: () => {
          selectedItems.value = [];
        },
      });
    }
  }
};

const toggleSelectAll = (event) => {
  if (event.target.checked) {
    selectedItems.value = props.mataKuliah.map(mata_kuliah =>
mata_kuliah.id);
  } else {
```

```

        selectedItems.value = [];
    }
};

const isAllSelected = computed(() => {
    return selectedItems.value.length === props.mataKuliah.length;
});

const selectedCount = computed(() => {
    return selectedItems.value.length;
});

const previousPage = () => {
    if (props.pagination.prev_page_url) {
        router.get(route('mata-kuliah.index', { search: search.value, page:
props.pagination.current_page - 1 }));
    }
};

const nextPage = () => {
    if (props.pagination.next_page_url) {
        router.get(route('mata-kuliah.index', { search: search.value, page:
props.pagination.current_page + 1 }));
    }
};

const goToPage = (page) => {
    router.get(route('mata-kuliah.index', {
        search: search.value,
        page: page,
        sort: sort.value.column,
        direction: sort.value.direction,
    }));
};

const paginationRange = () => {
    const current = props.pagination.current_page;
    const last = props.pagination.last_page;
    const delta = 2;
    const range = [];
    const rangeWithDots = [];

    for (let i = Math.max(2, current - delta); i <= Math.min(last - 1, current
+ delta); i++) {
        range.push(i);
    }

    if (current - delta > 2) rangeWithDots.push('...');
    rangeWithDots.push(...range);

```

```

    if (current + delta < last - 1) rangeWithDots.push('...');

    return rangeWithDots;
  };

const search = ref(props.search || '');
let searchTimer = null;

const sort = ref(props.sort || { column: null, direction: 'asc' });

const performSearch = () => {
  clearTimeout(searchTimer);
  searchTimer = setTimeout(() => {
    router.get(route('mata-kuliah.index', {
      search: search.value,
      page: 1,
      sort: sort.value.column,
      direction: sort.value.direction
    }), {
      preserveState: true,
      replace: true,
    });
  }, 300);
};

watch(search, performSearch);

const handleSort = (column) => {
  if (sort.value.column === column) {
    if (sort.value.direction === 'asc') {
      sort.value.direction = 'desc';
    } else if (sort.value.direction === 'desc') {
      sort.value.column = null;
      sort.value.direction = 'asc';
    } else {
      sort.value.direction = 'asc';
    }
  } else {
    sort.value.column = column;
    sort.value.direction = 'asc';
  }
  router.get(route('mata-kuliah.index', {
    search: search.value,
    page: 1,
    sort: sort.value.column,
    direction: sort.value.direction
  }), {
    preserveState: true,
    replace: true,
  });
};

```

```

    });
  });

const getSortIcon = (column) => {
  if (sort.value.column === column) {
    return sort.value.direction === 'asc' ? '▲' : '▼';
  }
  return '↕';
};

const page = usePage();
const message = ref('');

watch(() => page.props.flash.message, (newMessage) => {
  message.value = newMessage;
  if (newMessage) {
    setTimeout(() => {
      message.value = '';
    }, 5000);
  }
}, { immediate: true });
</script>

<template>
  <Head title="Mata Kuliah" />

  <AuthenticatedLayout>
    <template #header>
      <h2 class="font-semibold text-xl text-gray-800 leading-tight">Mata
Kuliah</h2>
    </template>

    <div class="py-12">
      <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
        <div v-if="message" class="mb-4 bg-green-100 border
border-green-400 text-green-700 px-4 py-3 rounded relative" role="alert">
          <span class="block sm:inline">{{ message }}</span>
        </div>
        <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
          <div class="p-6 text-gray-900">
            <div class="flex justify-between mb-2">
              <div class="space-x-2">
                <Link :href="route('mata-kuliah.create')"
class="inline-flex items-center px-4 py-2 bg-gray-800 border border-transparent
rounded-md font-semibold text-xs text-white uppercase tracking-widest
hover:bg-gray-700 focus:bg-gray-700 active:bg-gray-900 focus:outline-none
focus:ring-2 focus:ring-indigo-500 focus:ring-offset-2 transition ease-in-out
duration-150">

```

```

<span class="hidden sm:inline">Tambah Mata
Kuliah</span>

<span class="sm:hidden">+</span>
</Link>

</div>
<div class="relative">
  <input
    v-model="search"
    type="text"
    placeholder="Cari mata kuliah..."
    class="border rounded px-2 py-1
focus:outline-none focus:ring-2 focus:ring-blue-500"
  />
  <svg
    class="h-5 w-5 text-gray-400 absolute
right-2 top-1/2 transform -translate-y-1/2"
    xmlns="http://www.w3.org/2000/svg"
    fill="none"
    viewBox="0 0 24 24"
    stroke="currentColor"
  >
    <path
      stroke-linecap="round"
      stroke-linejoin="round"
      stroke-width="2"
      d="M21 21l-6-6m2-5a7 7 0 11-14 0 7 7 0
0 114 0z"
    />
  </svg>
</div>
</div>
<div class="flex justify-between mb-2">
  <span v-if="selectedCount > 0" class="text-sm
text-gray-600">
    {{ selectedCount }} item terpilih
  </span>
  <button v-if="selectedCount > 0"
@click="handleBulkDelete" class="px-4 py-1 bg-red-600 text-white rounded-md
hover:bg-red-700">
    Hapus Data
  </button>
</div>

<div v-if="props.mataKuliah.length === 0"
class="text-center py-4 text-gray-600">
  Tidak ada data yang sesuai.
</div>

```

```

<table v-else class="min-w-full divide-y
divide-gray-200">

    <thead>
        <tr>
            <th class="px-6 py-3 bg-gray-50 text-left">
                <input class="rounded-[4px]"
type="checkbox" @change="toggleSelectAll" :checked="isAllSelected">
            </th>
            <th @click="handleSort('kode')" class="px-6
py-3 bg-gray-50 text-left text-xs leading-4 font-medium text-gray-500 uppercase
tracking-wider cursor-pointer">
                Kode
                <span class="ml-1">{{
getSortIcon('kode') }}</span>
            </th>
            <th @click="handleSort('nama')" class="px-6
py-3 bg-gray-50 text-left text-xs leading-4 font-medium text-gray-500 uppercase
tracking-wider cursor-pointer">
                Nama
                <span class="ml-1">{{
getSortIcon('nama') }}</span>
            </th>
            <th @click="handleSort('sks')" class="px-6
py-3 bg-gray-50 text-left text-xs leading-4 font-medium text-gray-500 uppercase
tracking-wider cursor-pointer">
                SKS
                <span class="ml-1">{{
getSortIcon('sks') }}</span>
            </th>
            <th class="px-6 py-3 bg-gray-50 text-left
text-xs leading-4 font-medium text-gray-500 uppercase tracking-wider">Aksi</th>
        </tr>
    </thead>
    <tbody class="bg-white divide-y divide-gray-200">
        <tr v-for="mata_kuliah in props.mataKuliah"
:key="mata_kuliah.id">
            <td class="px-6 py-4 whitespace-no-wrap">
                <input class="rounded-[4px]"
type="checkbox" v-model="selectedItems" :value="mata_kuliah.id">
            </td>
            <td class="px-6 py-4 whitespace-no-wrap">{{
mata_kuliah.kode }}</td>
            <td class="px-6 py-4 whitespace-no-wrap">{{
mata_kuliah.nama }}</td>
            <td class="px-6 py-4 whitespace-no-wrap">{{
mata_kuliah.sks }}</td>
            <td class="px-6 py-4 whitespace-no-wrap
flex gap-2">

```

```

<Link :href="route('mata-kuliah.edit',
{ mata_kuliah: mata_kuliah.id }}" class="text-yellow-600
hover:text-yellow-900">Edit</Link>

<button
@click="handleDelete(mata_kuliah.id)" class="text-red-600
hover:text-red-900">Hapus</button>

</td>
</tr>
</tbody>
</table>

<div class="mt-4 flex justify-between items-center">
<div>
Tampil {{ (props.pagination.current_page - 1) *
props.pagination.per_page + 1 }}-{{ Math.min(props.pagination.current_page *
props.pagination.per_page, props.pagination.total) }} dari {{
props.pagination.total }} data
</div>
<div class="flex space-x-2">
<button @click="previousPage"
:disabled="!props.pagination.prev_page_url" class="px-4 py-2 bg-gray-800
text-white rounded-md" :class="{ 'opacity-50 cursor-not-allowed':
!props.pagination.prev_page_url }">
<span class="hidden sm:inline">Prev</span>
<span class="sm:hidden"><<</span>
</button>
<button @click="goToPage(1)" class="hidden
sm:inline px-4 py-2 bg-gray-800 text-white rounded-md" :class="{ 'bg-blue-500':
props.pagination.current_page === 1 }">
1
</button>
<template v-for="page in paginationRange()"
:key="page">
<span v-if="page === '...' " class="hidden
sm:inline px-4 py-2">...</span>
<button v-else @click="goToPage(page)"
class="hidden sm:inline px-4 py-2 bg-gray-800 text-white rounded-md" :class="{
'bg-blue-500': props.pagination.current_page === page }">
{{ page }}
</button>
</template>
<button v-if="props.pagination.last_page > 1"
@click="goToPage(props.pagination.last_page)" class="hidden sm:inline px-4 py-2
bg-gray-800 text-white rounded-md" :class="{ 'bg-blue-500':
props.pagination.current_page === props.pagination.last_page }">
{{ props.pagination.last_page }}
</button>
<button @click="nextPage"
:disabled="!props.pagination.next_page_url" class="px-4 py-2 bg-gray-800

```



```

        <span class="block sm:inline">Ada beberapa
kesalahan:</span>

        <ul class="mt-2 list-disc list-inside">
            <li v-for="(error, key) in errors" :key="key">{{ error
        }}</li>

        </ul>
    </div>
    <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
        <div class="p-6 text-gray-900">
            <form @submit.prevent="submit">
                <div>
                    <label for="kode" class="block font-medium
text-sm text-gray-700">Kode Mata Kuliah</label>
                    <input id="kode" v-model="form.kode"
type="text" class="mt-1 block w-full" required autofocus>
                    <div v-if="form.errors.kode"
class="text-red-500 mt-2 text-sm">{{ form.errors.kode }}</div>
                </div>
                <div>
                    <label for="nama" class="block font-medium
text-sm text-gray-700">Nama Mata Kuliah</label>
                    <input id="nama" v-model="form.nama"
type="text" class="mt-1 block w-full" required autofocus>
                    <div v-if="form.errors.nama"
class="text-red-500 mt-2 text-sm">{{ form.errors.nama }}</div>
                </div>
                <div>
                    <label for="sks" class="block font-medium
text-sm text-gray-700">SKS</label>
                    <input id="sks" v-model="form.sks"
type="number" class="mt-1 block w-full" required autofocus>
                    <div v-if="form.errors.sks" class="text-red-500
mt-2 text-sm">{{ form.errors.sks }}</div>
                </div>

                <div class="flex items-center justify-end mt-4">
                    <button type="submit" class="px-4 py-2
bg-gray-800 text-white rounded-md" :disabled="form.processing">Simpan</button>
                </div>
            </form>
        </div>
    </div>
</div>
</AuthenticatedLayout>
</template>

```

u. resources/js/Pages/MataKuliah/Edit.vue

```
<script setup>
```

```

import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout.vue';
import { Head, useForm, usePage } from '@inertiajs/vue3';
import { ref, computed } from 'vue';

const props = defineProps({
  mataKuliah: Object,
});

const form = useForm({
  kode: props.mataKuliah.kode,
  nama: props.mataKuliah.nama,
  sks: props.mataKuliah.sks,
});

const submit = () => {
  form.put(route('mata-kuliah.update', props.mataKuliah.id));
};

const errors = computed(() => usePage().props.errors);
</script>

<template>
  <Head title="Edit Mata Kuliah" />

  <AuthenticatedLayout>
    <template #header>
      <h2 class="font-semibold text-xl text-gray-800 leading-tight">Edit
Mata Kuliah</h2>
    </template>

    <div class="py-12">
      <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
        <div v-if="Object.keys(errors).length > 0" class="mb-4
bg-red-100 border border-red-400 text-red-700 px-4 py-3 rounded relative"
role="alert">

          <strong class="font-bold">Oops! </strong>
          <span class="block sm:inline">Ada beberapa
kesalahan:</span>

          <ul class="mt-2 list-disc list-inside">
            <li v-for="(error, key) in errors" :key="key">{{ error
}}</li>
          </ul>
        </div>
        <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
          <div class="p-6 text-gray-900">
            <form @submit.prevent="submit">
              <div>
                <label for="kode" class="block font-medium
text-sm text-gray-700">Kode Mata Kuliah</label>

```

```

<input id="kode"
v-model="props.mataKuliah.kode" type="text" class="mt-1 block w-full" required
autofocus>

<div v-if="form.errors.kode"
class="text-red-500 mt-2 text-sm">{{ form.errors.kode }}</div>
</div>
<div>
<label for="nama" class="block font-medium
text-sm text-gray-700">Nama Mata Kuliah</label>
<input id="nama" v-model="form.nama"
type="text" class="mt-1 block w-full" required autofocus>
<div v-if="form.errors.nama"
class="text-red-500 mt-2 text-sm">{{ form.errors.nama }}</div>
</div>
<div>
<label for="sks" class="block font-medium
text-sm text-gray-700">SKS</label>
<input id="sks" v-model="form.sks"
type="number" class="mt-1 block w-full" required autofocus>
<div v-if="form.errors.sks" class="text-red-500
mt-2 text-sm">{{ form.errors.sks }}</div>
</div>

<div class="flex items-center justify-end mt-4">
<button type="submit" class="px-4 py-2
bg-gray-800 text-white rounded-md" :disabled="form.processing">Update</button>
</div>
</form>
</div>
</div>
</div>
</AuthenticatedLayout>
</template>

```

v. resources/js/Pages/Nilai/Index.vue

```

<script setup>
import AuthenticatedLayout from '@Layouts/AuthenticatedLayout.vue';
import { Head, Link, useForm, router, usePage } from '@inertiajs/vue3';
import { ref, defineProps, computed, watch, onMounted } from 'vue';

const props = defineProps({
  nilai: Array,
  pagination: {
    type: Object,
    required: true,
  },
  search: String,
  sort: Object,

```

```

});

const handleDelete = (id) => {
  if (window.confirm('Apakah Anda yakin ingin menghapus data ini?')) {
    router.delete(route('nilai.destroy', { nilai: id }));
  }
};

const selectedItems = ref([]);

const form = useForm({
  ids: [],
});

const handleBulkDelete = () => {
  if (window.confirm('Apakah Anda yakin ingin menghapus data yang dipilih?')) {
    {
      form.ids = selectedItems.value;
      form.delete(route('nilai.bulk-destroy'), {
        preserveScroll: true,
        preserveState: true,
        onSuccess: () => {
          selectedItems.value = [];
        },
      });
    }
  }
};

const toggleSelectAll = (event) => {
  if (event.target.checked) {
    selectedItems.value = props.nilai.map(nilai => nilai.id);
  } else {
    selectedItems.value = [];
  }
};

const isAllSelected = computed(() => {
  return selectedItems.value.length === props.nilai.length;
});

const selectedCount = computed(() => {
  return selectedItems.value.length;
});

const previousPage = () => {
  if (props.pagination.prev_page_url) {
    router.get(route('nilai.index', { search: search.value, page:
props.pagination.current_page - 1 }));
  }
}

```

```

};

const nextPage = () => {
  if (props.pagination.next_page_url) {
    router.get(route('nilai.index', { search: search.value, page:
props.pagination.current_page + 1 }));
  }
};

const goToPage = (page) => {
  router.get(route('nilai.index', { search: search.value, page: page }));
};

const paginationRange = () => {
  const current = props.pagination.current_page;
  const last = props.pagination.last_page;
  const delta = 2;
  const range = [];
  const rangeWithDots = [];

  for (let i = Math.max(2, current - delta); i <= Math.min(last - 1, current
+ delta); i++) {
    range.push(i);
  }

  if (current - delta > 2) rangeWithDots.push('...');
  rangeWithDots.push(...range);
  if (current + delta < last - 1) rangeWithDots.push('...');

  return rangeWithDots;
};

const search = ref(props.search || '');
let searchTimer = null;

const sort = ref(props.sort || { column: null, direction: 'asc' });

const performSearch = () => {
  clearTimeout(searchTimer);
  searchTimer = setTimeout(() => {
    router.get(route('nilai.index', {
      search: search.value,
      page: 1,
      sort: sort.value.column,
      direction: sort.value.direction
    })), {
      preserveState: true,
      replace: true,
    });
  });
};

```

```

    }, 300);
  };

  watch(search, performSearch);

  const handleSort = (column) => {
    if (sort.value.column === column) {
      if (sort.value.direction === 'asc') {
        sort.value.direction = 'desc';
      } else if (sort.value.direction === 'desc') {
        sort.value.column = null;
        sort.value.direction = 'asc';
      } else {
        sort.value.direction = 'asc';
      }
    } else {
      sort.value.column = column;
      sort.value.direction = 'asc';
    }
    router.get(route('nilai.index', {
      search: search.value,
      page: props.pagination.current_page,
      sort: sort.value.column,
      direction: sort.value.direction
    })), {
      preserveState: true,
      replace: true,
    });
  };

  const getSortIcon = (column) => {
    if (sort.value.column === column) {
      return sort.value.direction === 'asc' ? '▲' : '▼';
    }
    return '¶';
  };

  const page = usePage();
  const message = ref('');

  watch(() => page.props.flash.message, (newMessage) => {
    message.value = newMessage;
    if (newMessage) {
      setTimeout(() => {
        message.value = '';
      }, 5000);
    }
  }, { immediate: true });
</script>

```

```

<template>
  <Head title="Nilai" />

  <AuthenticatedLayout>
    <template #header>
      <h2 class="font-semibold text-xl text-gray-800 leading-tight">Nilai</h2>
    </template>

    <div class="py-12">
      <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
        <div v-if="message" class="mb-4 bg-green-100 border border-green-400 text-green-700 px-4 py-3 rounded relative" role="alert">
          <span class="block sm:inline">{{ message }}</span>
        </div>
        <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
          <div class="p-6 text-gray-900">
            <div class="flex justify-between mb-2">
              <div class="space-x-2">
                <Link :href="route('nilai.create')"
class="inline-flex items-center px-4 py-2 bg-gray-800 border border-transparent rounded-md font-semibold text-xs text-white uppercase tracking-widest hover:bg-gray-700 focus:bg-gray-700 active:bg-gray-900 focus:outline-none focus:ring-2 focus:ring-indigo-500 focus:ring-offset-2 transition ease-in-out duration-150">
                  <span class="hidden sm:inline">Tambah
Nilai</span>
                  <span class="sm:hidden">+</span>
                </Link>
              </div>
              <div class="relative">
                <input
                  v-model="search"
                  type="text"
                  placeholder="Cari nilai..."
                  class="border rounded px-2 py-1 focus:outline-none focus:ring-2 focus:ring-blue-500"
                />
                <svg
                  class="h-5 w-5 text-gray-400 absolute right-2 top-1/2 transform -translate-y-1/2"
                  xmlns="http://www.w3.org/2000/svg"
                  fill="none"
                  viewBox="0 0 24 24"
                  stroke="currentColor"
                >
                  <path

```



```

                                stroke-linecap="round"
                                stroke-linejoin="round"
                                stroke-width="2"
                                d="M21 21l-6-6m2-5a7 7 0 11-14 0 7 7 0
0114 0z"
                                />
                            </svg>
                        </div>
                    </div>
                    <div class="flex justify-between mb-2">
                        <span v-if="selectedCount > 0" class="text-sm
text-gray-600">
                            {{ selectedCount }} item terpilih
                        </span>
                        <button v-if="selectedCount > 0"
@click="handleBulkDelete" class="px-4 py-1 bg-red-600 text-white rounded-md
hover:bg-red-700">
                            Hapus Data
                        </button>
                    </div>

                    <div v-if="props.nilai.length === 0" class="text-center
py-4 text-gray-600">
                        Tidak ada data yang sesuai.
                    </div>

                    <table v-else class="min-w-full divide-y
divide-gray-200">
                        <thead>
                            <tr>
                                <th class="px-6 py-3 bg-gray-50 text-left">
                                    <input class="rounded-[4px]"
type="checkbox" @change="toggleSelectAll" :checked="isAllSelected">
                                </th>
                                <th @click="handleSort('mahasiswa_id')"
class="px-6 py-3 bg-gray-50 text-left text-xs leading-4 font-medium
text-gray-500 uppercase tracking-wider cursor-pointer">
                                    Nama Mahasiswa
                                    <span
v-html="getSortIcon('mahasiswa_id')"></span>
                                </th>
                                <th @click="handleSort('mata_kuliah_id')"
class="px-6 py-3 bg-gray-50 text-left text-xs leading-4 font-medium
text-gray-500 uppercase tracking-wider cursor-pointer">
                                    Nama Mata Kuliah
                                    <span
v-html="getSortIcon('mata_kuliah_id')"></span>
                                </th>

```

```

                <th @click="handleSort('nilai')"
class="px-6 py-3 bg-gray-50 text-left text-xs leading-4 font-medium
text-gray-500 uppercase tracking-wider cursor-pointer">
                    Nilai
                <span
v-html="getSortIcon('nilai')"></span>
            </th>
            <th class="px-6 py-3 bg-gray-50 text-left
text-xs leading-4 font-medium text-gray-500 uppercase tracking-wider">Aksi</th>
        </tr>
    </thead>
    <tbody class="bg-white divide-y divide-gray-200">
        <tr v-for="nilai in props.nilai"
:key="nilai.id">
            <td class="px-6 py-4 whitespace-no-wrap">
                <input class="rounded-[4px]"
type="checkbox" v-model="selectedItems" :value="nilai.id">
            </td>
            <td class="px-6 py-4 whitespace-no-wrap">{{
nilai.mahasiswa.nama }}</td>
            <td class="px-6 py-4 whitespace-no-wrap">{{
nilai.mata_kuliah.nama }}</td>
            <td class="px-6 py-4 whitespace-no-wrap">{{
nilai.nilai }}</td>
            <td class="px-6 py-4 whitespace-no-wrap
flex gap-2">
                <Link :href="route('nilai.edit', {
nilai: nilai.id })" class="text-yellow-600 hover:text-yellow-900">Edit</Link>
                <button @click="handleDelete(nilai.id)"
class="text-red-600 hover:text-red-900">Hapus</button>
            </td>
        </tr>
    </tbody>
</table>

    <div class="mt-4 flex justify-between items-center">
        <div>
            Tampil {{ (props.pagination.current_page - 1) *
props.pagination.per_page + 1 }}-{{ Math.min(props.pagination.current_page *
props.pagination.per_page, props.pagination.total) }} dari {{
props.pagination.total }} data
        </div>
        <div class="flex space-x-2">
            <button @click="previousPage"
:disabled="!props.pagination.prev_page_url" class="px-4 py-2 bg-gray-800
text-white rounded-md :class='{ 'opacity-50 cursor-not-allowed':
!props.pagination.prev_page_url }'">
                <span class="hidden sm:inline">Prev</span>
                <span class="sm:hidden"><</span>

```

```

        </button>
        <button @click="goToPage(1)" class="hidden
sm:inline px-4 py-2 bg-gray-800 text-white rounded-md" :class="{ 'bg-blue-500':
props.pagination.current_page === 1 }">
            1
        </button>
        <template v-for="page in paginationRange()"
:key="page">
            <span v-if="page === '...' " class="hidden
sm:inline px-4 py-2">...</span>
            <button v-else @click="goToPage(page)"
class="hidden sm:inline px-4 py-2 bg-gray-800 text-white rounded-md" :class="{
'bg-blue-500': props.pagination.current_page === page }">
                {{ page }}
            </button>
        </template>
        <button v-if="props.pagination.last_page > 1"
@click="goToPage(props.pagination.last_page)" class="hidden sm:inline px-4 py-2
bg-gray-800 text-white rounded-md" :class="{ 'bg-blue-500':
props.pagination.current_page === props.pagination.last_page }">
            {{ props.pagination.last_page }}
        </button>
        <button @click="nextPage"
:disabled="!props.pagination.next_page_url" class="px-4 py-2 bg-gray-800
text-white rounded-md" :class="{ 'opacity-50 cursor-not-allowed':
!props.pagination.next_page_url }">
            <span class="hidden sm:inline">Next</span>
            <span class="sm:hidden">></span>
        </button>
    </div>
</div>
</div>
</div>
</div>
</AuthenticatedLayout>
</template>

```

w. resources/js/Pages/Nilai/Create.vue

```

<script setup>
import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout.vue';
import { Head, useForm, usePage } from '@inertiajs/vue3';
import { ref, computed } from 'vue';
import SearchableSelect from '@/Components/SearchableSelect.vue';

const props = defineProps({
    mahasiswa: Array,
    mataKuliah: Array
});

```

```

const form = useForm({
  mahasiswa_id: '',
  mata_kuliah_id: '',
  nilai: '',
});

const submit = () => {
  form.post(route('nilai.store'));
};

const errors = computed(() => usePage().props.errors);

const mahasiswaOptions = computed(() =>
  props.mahasiswa.map(m => ({ value: m.id, label: `${m.nim} - ${m.nama}` }))
);

const mataKuliahOptions = computed(() =>
  props.mataKuliah.map(mk => ({ value: mk.id, label: `${mk.kode} - ${mk.nama}`
}))
);
</script>

<template>
  <Head title="Tambah Nilai" />

  <AuthenticatedLayout>
    <template #header>
      <h2 class="font-semibold text-xl text-gray-800 leading-tight">Tambah Nilai</h2>
    </template>

    <div class="py-12">
      <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
        <div v-if="Object.keys(errors).length > 0" class="mb-4 bg-red-100 border border-red-400 text-red-700 px-4 py-3 rounded relative" role="alert">
          <strong class="font-bold">Oops! </strong>
          <span class="block sm:inline">Ada beberapa kesalahan:</span>
          <ul class="mt-2 list-disc list-inside">
            <li v-for="(error, key) in errors" :key="key">{{ error }}</li>
          </ul>
        </div>
        <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
          <div class="p-6 text-gray-900">
            <form @submit.prevent="submit">
              <div>

```

```

        <SearchableSelect
            v-model="form.mahasiswa_id"
            :options="mahasiswaOptions"
            label="Mahasiswa"
            placeholder="Pilih mahasiswa"
        />
        <div v-if="form.errors.mahasiswa_id"
class="text-red-500 mt-2 text-sm">{{ form.errors.mahasiswa_id }}</div>
        </div>
        <div>
            <SearchableSelect
                v-model="form.mata_kuliah_id"
                :options="mataKuliahOptions"
                label="Mata Kuliah"
                placeholder="Pilih mata kuliah"
            />
            <div v-if="form.errors.mata_kuliah_id"
class="text-red-500 mt-2 text-sm">{{ form.errors.mata_kuliah_id }}</div>
            </div>
            <div>
                <label for="nilai" class="block font-medium
text-sm text-gray-700">Nilai</label>
                <input id="nilai" v-model="form.nilai"
type="text" class="mt-1 block w-full" required autofocus>
                <div v-if="form.errors.nilai"
class="text-red-500 mt-2 text-sm">{{ form.errors.nilai }}</div>
            </div>

            <div class="flex items-center justify-end mt-4">
                <button type="submit" class="px-4 py-2
bg-gray-800 text-white rounded-md" :disabled="form.processing">Simpan</button>
            </div>
        </form>
    </div>
</div>
</div>
</AuthenticatedLayout>
</template>

```

x. resources/js/Pages/Nilai/Edit.vue

```

<script setup>
import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout.vue';
import { Head, useForm, usePage } from '@inertiajs/vue3';
import { ref, computed } from 'vue';
import SearchableSelect from '@/Components/SearchableSelect.vue';

const props = defineProps({
    nilai: Object,

```

```

    mahasiswa: Array,
    mataKuliah: Array,
  });

const form = useForm({
  mahasiswa_id: props.nilai.mahasiswa_id,
  mata_kuliah_id: props.nilai.mata_kuliah_id,
  nilai: props.nilai.nilai,
});

const submit = () => {
  form.put(route('nilai.update', props.nilai.id));
};

const errors = computed(() => usePage().props.errors);

const mahasiswaOptions = computed(() =>
  props.mahasiswa.map(m => ({ value: m.id, label: `${m.nim} - ${m.nama}` }))
);

const mataKuliahOptions = computed(() =>
  props.mataKuliah.map(mk => ({ value: mk.id, label: `${mk.kode} - ${mk.nama}`
  )))
);
</script>

<template>
  <Head title="Edit Nilai" />

  <AuthenticatedLayout>
    <template #header>
      <h2 class="font-semibold text-xl text-gray-800 leading-tight">Edit
Nilai</h2>
    </template>

    <div class="py-12">
      <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
        <div v-if="Object.keys(errors).length > 0" class="mb-4
bg-red-100 border border-red-400 text-red-700 px-4 py-3 rounded relative"
role="alert">
          <strong class="font-bold">Oops! </strong>
          <span class="block sm:inline">Ada beberapa
kesalahan:</span>
          <ul class="mt-2 list-disc list-inside">
            <li v-for="(error, key) in errors" :key="key">{{ error
}}</li>
          </ul>
        </div>
        <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">

```

```

<div class="p-6 text-gray-900">
  <form @submit.prevent="submit">
    <div>
      <SearchableSelect
        v-model="form.mahasiswa_id"
        :options="mahasiswaOptions"
        label="Mahasiswa"
        placeholder="Pilih mahasiswa"
      />
      <div v-if="form.errors.mahasiswa_id"
class="text-red-500 mt-2 text-sm">{{ form.errors.mahasiswa_id }}</div>
    </div>
    <div>
      <SearchableSelect
        v-model="form.mata_kuliah_id"
        :options="mataKuliahOptions"
        label="Mata Kuliah"
        placeholder="Pilih mata kuliah"
      />
      <div v-if="form.errors.mata_kuliah_id"
class="text-red-500 mt-2 text-sm">{{ form.errors.mata_kuliah_id }}</div>
    </div>
    <div>
      <label for="nilai" class="block font-medium
text-sm text-gray-700">Nilai</label>
      <input id="nilai" v-model="form.nilai"
type="number" class="mt-1 block w-full" required>
      <div v-if="form.errors.nilai"
class="text-red-500 mt-2 text-sm">{{ form.errors.nilai }}</div>
    </div>

    <div class="flex items-center justify-end mt-4">
      <button type="submit" class="px-4 py-2
bg-gray-800 text-white rounded-md" :disabled="form.processing">Update</button>
    </div>
  </form>
</div>
</div>
</div>
</AuthenticatedLayout>
</template>

```

y. resources/js/Pages/Dashboard.vue

```

<script setup>
import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout.vue';
import { Head } from '@inertiajs/vue3';
import PieChart from '@/Components/PieChart.vue';

```

```

const props = defineProps({
  programStudiData: Array,
  jumlahMahasiswa: Number,
  jumlahMataKuliah: Number,
  rataRataNilai: Number,
});
</script>

<template>
  <Head title="Dashboard" />

  <AuthenticatedLayout>
    <template #header>
      <h2 class="font-semibold text-xl text-gray-800
leading-tight">Dashboard</h2>
    </template>

    <div class="py-2">
      <div class="max-w-7xl mx-auto sm:px-6 lg:px-8">
        <div class="bg-white overflow-hidden shadow-sm sm:rounded-lg">
          <div class="p-6 text-gray-900">
            <h3 class="text-lg font-semibold mb-4">Selamat datang di Sistem
Informasi Mahasiswa!</h3>

            <div class="grid grid-cols-1 md:grid-cols-3 gap-4 mb-8">
              <div class="bg-blue-100 p-4 rounded-lg">
                <h4 class="font-semibold">Jumlah Mahasiswa</h4>
                <p class="text-2xl">{{ jumlahMahasiswa }}</p>
              </div>
              <div class="bg-green-100 p-4 rounded-lg">
                <h4 class="font-semibold">Jumlah Mata Kuliah</h4>
                <p class="text-2xl">{{ jumlahMataKuliah }}</p>
              </div>
              <div class="bg-yellow-100 p-4 rounded-lg">
                <h4 class="font-semibold">Rata-rata Nilai</h4>
                <p class="text-2xl">{{ rataRataNilai }}</p>
              </div>
            </div>
            <div class="mb-8 flex flex-col justify-center items-center">
              <div class="max-w-xs">
                <h4 class="font-semibold mb-4">Distribusi Mahasiswa per
Program Studi</h4>
                <PieChart :data="programStudiData" />
              </div>
            </div>
          </div>
        </div>
      </div>
    </div>
  </div>
</div>


```




```
</AuthenticatedLayout>
</template>
```

5. Screenshot Tampilan


a. Welcome




b. Register




c. Login




d. Dashboard





e. Profile






f. Program Studi - Index




g. Program Studi - Create




h. Program Studi - Edit





i. Program Studi - Delete






j. Mahasiswa - Index



k. Mahasiswa - Create



1. Mahasiswa - Edit



m. Mahasiswa - Delete

The screenshot shows a web application interface for managing students. A confirmation dialog box is displayed over the main content area, asking for confirmation to delete a selected student. The dialog has 'Ok' and 'Cancel' buttons.

localhost:8000 says
Apakah Anda yakin ingin menghapus data yang dipilih?

TAMBAH MAHASISWA

7 item terpilih

<input checked="" type="checkbox"/>	NAMA	NIM	PROGRAM STUDI	AKSI
<input checked="" type="checkbox"/>	November	A040	Kedokteran Gigi	Edit Hapus
<input checked="" type="checkbox"/>	Oscar	A041	Kedokteran Gigi	Edit Hapus
<input checked="" type="checkbox"/>	Papa	A042	Kedokteran Gigi	Edit Hapus
<input checked="" type="checkbox"/>	Quebec	A043	Teknik Geologi	Edit Hapus
<input checked="" type="checkbox"/>	Romeo	A044	Teknik Geologi	Edit Hapus
<input checked="" type="checkbox"/>	Sierra	A045	Teknik Geologi	Edit Hapus
<input checked="" type="checkbox"/>	Si Fulan	H1D022006	Informatika	Edit Hapus

Tampil 31-37 dari 37 data

Prev 1 2 3 4 Next

TAMBAH MAHASISWA

Cari mahasiswa...

Hapus Data

67% Reset

Mahasiswa


Mahasiswa terpilih berhasil dihapus

<input type="checkbox"/>	NAMA	NIM	PROGRAM STUDI	AKSI
<input type="checkbox"/>	Wali	A10023032	Teknik Sipil	Edit Hapus
<input type="checkbox"/>	Bob	A002	Teknik Sipil	Edit Hapus
<input type="checkbox"/>	Charlie	A003	Teknik Sipil	Edit Hapus
<input type="checkbox"/>	David	A004	Informatika	Edit Hapus
<input type="checkbox"/>	Eve	A005	Informatika	Edit Hapus
<input type="checkbox"/>	Frank	A006	Informatika	Edit Hapus
<input type="checkbox"/>	Grace	A007	Teknik Mesin	Edit Hapus
<input type="checkbox"/>	Henry	A008	Teknik Mesin	Edit Hapus
<input type="checkbox"/>	Ivy	A009	Teknik Mesin	Edit Hapus
<input type="checkbox"/>	Jack	A010	Teknik Elektro	Edit Hapus



Tampil 1-10 dari 30 data

Prev 1 2 3 4 Next




n. Mata Kuliah - Index





o. Mata Kuliah - Create




p. Mata Kuliah - Edit





q. Mata Kuliah - Delete






r. Nilai - Index



s. Nilai - Create



t. Nilai - Edit



u. Nilai - Delete

