Fiscal Year:	FY 2012	**Task Last Updated:**	FY 07/26/2012
PI Name:	McKinley, Gareth Ph.D.		
Project Title:	Shear History Extensional Rheology Experiment II (SHERE II)		
Division Name:	Physical Sciences		
Program/Discipline:	FLUID PHYSICS		
Program/Discipline--Element/Subdiscipline:	FLUID PHYSICS--Fluid physics		
Joint Agency Name:		**TechPort:**	No
Human Research Program Elements:	None		
Human Research Program Risks:	None		
Space Biology Element:	None		
Space Biology Cross-Element Discipline:	None		
Space Biology Special Category:	None		
PI Email:	gareth@mit.edu	**Fax:**	FY
PI Organization Type:	UNIVERSITY	**Phone:**	617 258-0754
Organization Name:	Massachusetts Institute of Technology		
PI Address 1:	3-270, MIT		
PI Address 2:	77 Massachusetts Avenue		
PI Web Page:			
City:	Cambridge	**State:**	MA
Zip Code:	02139-4307	**Congressional District:**	8
Comments:			
Project Type:	Flight	**Solicitation / Funding Source:**	2009-10 Fluid Physics Rapid Turn Around Flight Opportunity
Start Date:	09/03/2009	**End Date:**	09/02/2013
No. of Post Docs:	1	**No. of PhD Degrees:**	
No. of PhD Candidates:	1	**No. of Master' Degrees:**	
No. of Master's Candidates:	0	**No. of Bachelor's Degrees:**	
No. of Bachelor's Candidates:		**Monitoring Center:**	NASA GRC
Contact Monitor:	Hall, Nancy Rabel	**Contact Phone:**	216-433-5643
Contact Email:	nancy.r.hall@nasa.gov		
Flight Program:	ISS		
Flight Assignment:	ISS NOTE: Extended to 9/2/2013 per NSSC and N. Hall/GRC (Ed., 8/20/2012) NOTE: Extended to 9/02/2012 per NSSC information (Ed., 2/25/2011)		
Key Personnel Changes/Previous PI:	Dr. Simon Haward completed his post-doctoral work at MIT in June 2012 and is not on the SHERE II team any longer.		
COI Name (Institution):	Haward, Simon (Massachusetts Institute of Technology) Jaishankar, Aditya (Massachusetts Institute of Technology)		
Grant/Contract No.:	NNX09AV99G		
Performance Goal No.:			
Performance Goal Text:			

Task Description:

The SHERE II experiment was operated on board the International Space Station (ISS) during Increment 27/28. SHERE II is an extension of the SHERE project, and both used the same hardware but different test fluid. The experiment is a glovebox investigation developed at NASA Glenn Research Center (GRC) and intended for operation in the Microgravity Science Glovebox (MSG) aboard the ISS. It is the first instrument capable of assessing the effects of a pre-shear history on the extensional properties of dilute polymer solutions during the extended range of time scales that can be accessed because of the absence of gravitational sagging.
As a logical extension to the SHERE project, SHERE II looks to study the effect of torsional pre-shear on the extensional behavior of a different non-Newtonian fluid. We specifically chose to study dilute suspensions of rigid micro-particles in dilute polymer solutions (0.025 wt. %). The suspending particles used are rigid inert poly(methyl methacyrlate) (PMMA) spheres, 6 μm in diameter, and the polymeric matrix is narrow polydispersity high molecular weight polystyrene dissolved in oligomeric styrene, which is the same fluid used in SHERE.

The SHERE II experiment will allow us to measure for the first time the effects of rotational pre-shear on the axial stretching of a polymeric fluid with small particles dispersed within it. The experiment also allows the study of the fluid's relaxation after the axial stretching, which is only possible in a microgravity environment. The results will provide new insights into the behavior of non-Newtonian fluids in industrial processes with both rotational and axial flows. The results of SHERE II will provide high quality experimental data to compare with recently developed theories on filler materials in plastics. Comparison of the SHERE (no particles) and SHERE II (particles) experiments is expected to be enlightening. The goal of the SHERE II experiment is to study the effects of a rotational pre-shear history on the transient extensional viscosity in a uniaxial stretching flow for dilute suspensions of inert, rigid micro-spheres (particles) suspended in a viscoelastic matrix fluid consisting of a dilute polymer solution. Constitutive equations for viscoelastic fluids such as dilute polymer or wormlike micelles solutions generally predict large changes in the extensional rheology of the material as the elongation rate is increased. However, the validity of these theories has not yet been confirmed due to the lack of experimental data obtained in extensional flows. Prior to this research, quantitative rheological measurements in shear-free flows were only possible for highly elastic materials such as polymer melts which could easily be elongated without sagging under a gravitational body force. The SHERE and SHERE II experiments allow us to obtain, for the first time, accurate measurements of the extensional viscosity for less elastic fluids such as polymer solutions, suspensions and liquid crystalline materials.

Rationale for HRP Directed Research:

Research Impact/Earth Benefits:

Understanding the rheological properties of highly viscoelastic suspensions may be of paramount importance for lunar in-situ resource utilization and for the future construction of a permanent lunar base. Indeed, the lunar soil, referred to as regolith, is composed of loose dust and broken rocks that could be used as a high volume fraction filler when mixed with a polymeric binder or matrix for building foundation or roadbed materials. The viscoelastic dilute suspension used for SHERE II thus serves as a highly idealized model system amenable to theoretical analysis which can shed light on future development of lunar regolith-based construction materials.
Suspensions of particles in viscoelastic liquids are used in many Earth processing operations: polymer melts with fillers, ceramic pastes, biomedical materials, food, cosmetics and detergents. The final properties of the suspensions are greatly determined by the shape, concentration and size of the filler. In particular, the fillers can range from nanoscopic to microscopic characteristic dimensions, which leads to very different types of flow behaviors, filler/matrix interactions and dynamics.

The results of SHERE II will provide new insights into the behavior of this important class of non-Newtonian fluids in industrially relevant mixed shear and extensional flows. This information is particularly relevant for understanding the deformation and evolution of fluid threads in a wide variety of industries, including polymer processing, food and consumer product processing, biomedical diagnostics, and pressure-sensitive adhesives. This research has direct applications in many industrial processes such as fiber spinning, film coating, injection molding, extrusion, and blow molding. Additionally, shear free flows arise whenever liquid interfaces are present; for example in "containerless processing" operations. These rheological data obtained will enable designers of both space- and ground-based material processes to use improved constitutive models in numerical simulations of complex two- and three-dimensional fluid flows. This includes stability and breakup of jets, enhanced oil recovery, and turbulent drag reduction for advanced aircraft, boats, and submarines.

Due to the delays in the launch of STS-134, the delivery of the SHERE II test fluids to the Microgravity Science Glovebox (MSG) aboard the International Space Station (ISS) was delayed until 16th May 2011. Experiments were completed on 08/20/11. There were further delays in the delivery of the tapes containing the HD videos of the test runs to the PI's laboratory. These tapes, which are critical to the data analysis protocol, were delivered to the PI's laboratory on 06/25/12. Therefore, all the research tasks planned at the end of last year could not be carried through to completion. However, some preliminary analysis was performed using the lower-quality down-linked video data, and this is summarized below. Full analysis of all the test points will be the focus of the research to be carried out between 2012 and 2013.
A preliminary analysis on the data reveals that the difference in temperature between the start and end of the test is within specified requirements for a successful test and the displacement of the endplate provides an extension rate in agreement with the expected imposed value.

Inspection of the downlinked video images acquired during experiments shows that as the left-hand endplate commences to displace exponentially to the left, a symmetric fluid filament is formed and stretched homogeneously between the two endplates. Finally, when the stretching phase has completed the fluid drains towards the endplates under the action of surface tension. This final stage is impossible to observe in filament stretching experiments performed on Earth as gravitational body forces are too great and cause sagging of the filament.

Images from the down-linked video recordings have been used to obtain a provisional estimate of the mid-point filament diameter as a function of time during the stretching phase using a digital edge detection method implemented in Matlab. The data obtained from the video recording during stretching has been fitted with an exponential decay curve, and the time constant so obtained is reasonably close to the reciprocal of the imposed extension rate. The agreement will probably be improved somewhat by the analysis of the higher quality video data.

Task Progress:	Analysis of the transient filament radius as a function of time during the capillary thinning phase of the experiment following the cessation of the stretch reveals that the mid-plane diameter of the fluid column as it thins under the action of capillarity is well described by a single mode exponential decay function. The time constant of this decay provides a measure of the fluid relaxation time, which is in reasonable agreement with the results of ground-based small angle oscillatory shear (SAOS) rheometric testing. However, this relaxation time is slightly longer compared with ground-based capillary-thinning (CaBER) measurements. Using the data measured by the force transducer and the fluid filament mid-plane determined as described above, the apparent extensional viscosity and Trouton ratio are calculated. We observe an increase in the extensional viscosity and Trouton ratio of around 2 orders of magnitude as the Hencky strain applied to the fluid increases. The magnitude of the extensional viscosity at high Hencky strains is comparable with that observed in groundbased CaBER experiments although it must be noted that the CaBER device does not allow control of an imposed extension rate. The limiting Trouton ratio for the viscoelastic suspension is nearly two orders of magnitude higher than the expected Trouton ratio for a Newtonian fluid in a uniaxial extensional flow, showing how the SHERE II test fluid is considerably strain hardening. The SHERE and SHERE II experiments have allowed us for the first time to obtain accurate measurements of the extensional viscosity for less elastic fluids such as polymer solutions, suspensions, and liquid crystalline materials without sagging of the fluid under a gravitational body force. The new SHERE II data are of good quality, and further detailed examination utilizing the high-quality video data are expected to provide verification of existing theories for the effects of particles on the viscous behavior of complex non-Newtonian fluids. Understanding and quantifying the extensional rheology of complex fluids allows to improve and control Earth-based manufacturing processes such as fiber micro/nanofabrication, atomization, electrospinning, and to understand the flow and quantify the rheological properties of biofluids.
Bibliography Type:	Description: (Last Updated: 09/04/2025)
Articles in Peer-reviewed Journals	Haward SJ, McKinley GH. "Stagnation point flow of wormlike micellar solutions in a microfluidic cross-slot device: Effects of surfactant concentration and ionic environment." Physical Review E, 2012 Mar;85(3):031502, 14 p. http://dx.doi.org/10.1103/PhysRevE.85.031502 , Mar-2012
Articles in Peer-reviewed Journals	Haward SJ, Sharma V, Butts CP, McKinley GH, Rahatekar SS. "Shear and extensional rheology of cellulose/ionic liquid solutions." Biomacromolecules, 2012 May 14;13(5):1688-99. http://dx.doi.org/10.1021/bm300407q , May-2012