Fiscal Year:	FY 2006	**Task Last Updated:**	FY 04/21/2006
PI Name:	Troian, Sandra M Ph.D.		
Project Title:	MICROFLUIDS: ACTUATION BY MODULATION OF SURFACE STRESSES-FLOW MODELING TO DEVICE IMPLEMENTATION		
Division Name:	Physical Sciences		
Program/Discipline:	FLUID PHYSICS		
Program/Discipline--Element/Subdiscipline:	FLUID PHYSICS--Interfacial phenomena		
Joint Agency Name:		**TechPort:**	No
Human Research Program Elements:	None		
Human Research Program Risks:	None		
Space Biology Element:	None		
Space Biology Cross-Element Discipline:	None		
Space Biology Special Category:	None		
PI Email:	stroian@caltech.edu	**Fax:**	FY
PI Organization Type:	UNIVERSITY	**Phone:**	626.395.3362
Organization Name:	California Institute of Technology		
PI Address 1:	1200 E. California Blvd. - MC 128-95		
PI Address 2:	Dept of Applied Physics		
PI Web Page:			
City:	Pasadena	**State:**	CA
Zip Code:	91125	**Congressional District:**	29
Comments:			
Project Type:	Ground	**Solicitation / Funding Source:**	2001 Physical Sciences 01-OBPR-08
Start Date:	01/28/2004	**End Date:**	01/26/2007
No. of Post Docs:	1	**No. of PhD Degrees:**	4
No. of PhD Candidates:	3	**No. of Master' Degrees:**	0
No. of Master's Candidates:	1	**No. of Bachelor's Degrees:**	0
No. of Bachelor's Candidates:	0	**Monitoring Center:**	NASA GRC
Contact Monitor:	Rame, Enrique	**Contact Phone:**	216-433-2842
Contact Email:	Rame@grc.nasa.gov		
Flight Program:			
Flight Assignment:	NOTE: Received NCE to 1/26/2007 per PI. Also, moved to California Institute of Technology from Princeton (10/06)		
Key Personnel Changes/Previous PI:			
COI Name (Institution):			
Grant/Contract No.:	NNC06GA44G ; NNC04GA52G		
Performance Goal No.:			
Performance Goal Text:			

Task Description:

YR3 (terminal yr) Task: A novel microfluidic device reliant on thermocapillary forcing will be used to induce complex flow profiles in thin liquid films containing DNA target (analyte) molecules to increase their local density in surface capture experiments involving substrate immobilized DNA probe molecules. An in-situ planar thin film waveguide beneath the liquid film will be used to induce fluorescence in the liquid sample via an evanescent wave. We plan to study the effect of substrate geometry, spot diameter and pitch, flow speed and thermal profile on the efficiency of substrate DNA capture. To develop an innovative microfluidic chip based on thermocapillary actuation of liquid films and droplets for space flight applications. This open format device is capable of a number of fluidic operations including control over droplet speed and direction, variable timing and droplet volume for on chip dispensing, multi droplet mixing, coalescence and scission. An integrated planar thin film waveguide beneath the tranported droplets allows in situ sensing of droplet position and composition as well as direct measurement of reaction rate constants as a function of substrate temperature. The final objective involves thermocapillary actuation of thin liquid films in studies involving DNA substrate immobilization and hybridization in surface capture assays to improve the density of target DNA in the vicinity of patterned probe DNA spots. Commercial interest in microfluidic devices for propelling and manipulating liquids samples through hundreds of small channels has grown considerably over the past decade. The highly parallelized design for reaction, synthesis and analysis have reduced reagent volumes, waste products and cost. Device fabrication has benefited enormously from advances in silicon processing and MEMS technology as well as widespread use of inexpensive elastomeric polymers for surface patterning and encapsulation. As a result, microfluidic devices are being developed for such diverse applications as liquid transport in DNA microarrays, drug screening, optical display technologies, tunable fiber optic waveguides, thermal management of semiconducting devices and lasers, clinical and forensic analysis, and environmental monitoring for both earth and space based applications. We are particularly interested in developing hand held, low power fluidic platforms for both environmental cabin monitoring and and biodiagnostic assays necessary for evaluating astronaut health during space flight.
Most fluidic devices rely on internal flow within enclosed microchannels made of glass or silicon which is generated by application of electroosmotic, electrohydrodynamic, magnetohydrodynamic, centrifugal, capillary or pneumatic forces. Transport based on modulation of interfacial stresses, however, is especially effective in controlling the speed, shape and composition of liquid droplets and films for microfluidic devices since the surface to volume ratio is very large. Controlled modulation of interfacial forces has been demonstrated by other research groups using electrowetting, dielectrophoresis, and Marangoni stresses. Our group has demonstrated film and droplet actuation (including flow speed and direction, mixing, splitting) using thermocapillary stresses. These stresses are induced by activating linear arrays of embedded microheaters which can be tuned to present various surface thermal maps useful for various fluidic functions. This type of open architecture format allows direct accessibility to liquid samples for handling, sensing and diagnostic purposes. It is also a powerful method for fluidic actuation in the absence of significant gravitational forces. Lower operating voltages have also been demonstrated because the retentive frictional losses affecting microdroplets are only confined to the supporting liquid-solid boundary, which in conventional internal flows is present on all four sides. Gas-liquid interfaces are also effective as flexible capture surfaces for environmental applications targetted to airborne contaminants since these are readily attracted and adsorbed to the interface through electrostatic or van der Waals forces (via the liquid surface tension). The main disadvantage of open systems is evaporative mass loss which can be significantly reduced through encapsulation by a second liquid or by lowering the operating temperatures while maintaining the same thermal gradient since thermocapillary stresses are proportional to the local temperature gradient.

The significance of our recent work in this area involves direct integration of evanescent wave sensing into our previous design. A planar waveguide was fabricated onto the microheater surface and the attenuation of light launched into this waveguide was used to monitor droplet position, dye concentration in bioassays upon reaction, and in-situ measurements of reaction rate constants as a function of temperature for key chromogenic bioreactions. This demonstration illustrates just a few of the capabilities possible by direct integration of optical sensing with “open platform” fluidic devices.

Rationale for HRP Directed Research:

Research Impact/Earth Benefits:

(1) Effect of Contact Angle Hysteresis on Thermocapillary Droplet Actuation Participants: Chen, Darhuber and Troian Open microfluidic devices based on actuation techniques such as electrowetting, dielectrophoresis, or thermocapillary stresses require controlled motion of small liquid droplets along the open surface of glass or silicon substrates. We explored the physical mechanisms affecting thermocapillary migration of droplets generated by surface temperature gradients on homogeneous silicon substrates coated by self assembling monolayers of OTS or DTS. These coated substrates presented a partially wetting surfaces to droplets of squalane (C30H62, 99%), n-decane (C10H22, 99%), n-dodecane (C12H26, 99%), n-tetradecane (C14H30, 99%), and n-hexadecane (C16H34, 99%). Using a combination of experiment and a simplified two dimensional model incorporating the effects of capillary, thermocapillary, gravity and contact angle hysteretic forces, we investigated the behavior of the threshold force required for droplet mobilization and the speed after depinning as a function of the droplet size, the applied thermal gradient and the liquid material parameters like surface tension and viscosity. The experimental results were found to be well described by a generalized hydrodynamic model based on earlier work by Ford and Nadim [Phys. Fluids 6, 3183 (1994)]. The results of this study highlight the critical role of chemical or mechanical hysteresis and the need to reduce this retentive force for minimizing power requirements in microfluidic devices.

(2) Microfluidic Detection and Analysis by Integration of Thermocapillary Actuation with a Planar Thin Film Waveguide Participants: Valentino and Troian

We demonstrated a non-intrusive optical method for microfluidic detection and analysis based on evanescent wave sensing. The device consists of a planar thin film waveguide made of silicon nitride SiNx (refractive index n2=1.84) deposited by plasma enhanced chemical vapor deposition integrated with a microfluidic chip based on thermocapillary actuation flow. Microliter droplets were electronically transported and positioned over the waveguide surface by thermocapillary actuation. The attenuated intensity of propagating modes was used to detect droplet location, monitor dye concentration in aqueous solutions, and measure reaction rates with increasing surface temperature for a chromogenic biochemical assay. This project and the device integration achieved illustrate just a few of the capabilities made possible by direct integration of optical sensing with surface directed fluidic devices. As far as we know, this is the first time that an evanescent wave based sensor has been integrated into an open microfluidic device.

(3) Slip Behavior in Thin Films Subject to Planar Shear: Comparison Between Molecular Level Models and Continuum

Task Progress:

Based Simulations Participants: Priezjev, Darhuber and Troian

(i) We investigated the behavior of the slip length in Newtonian liquids subject to planar shear bounded by substrates with mixed boundary conditions. The upper wall, consisting of a homogenous surface of finite or vanishing slip, was translated at a constant speed parallel to a lower stationary wall, whose surface was patterned with an array of stripes representing alternating regions of no shear and finite or no slip. Velocity fields and effective slip lengths were computed for flow configurations either parallel or perpendicular to the stripes. Excellent agreement between the hydrodynamic and MD results was obtained when the normalized width of the slip regions, a/sigma > O(10) where sigma is the fluid molecular diameter characterizing the Lennard-Jones interaction potential. In this regime, the effective slip length increases monotonically with a/sigma toward an asymptotic value. For a/sigma < O(10) and transverse flow configurations, the non-homogeneous interaction potential along the lower wall constitutes a roughened type surface whose molecular scale corrugations strongly reduce the effective slip length below the hydrodynamic prediction. The translational symmetry for longitudinal flow eliminates the influence of molecular scale roughness; however, the reduced molecular ordering above the wetting regions of finite slip for small values of a/sigma increases the value of the effective slip length far above the hydrodynamic predictions. The strong correlation between the effective slip length and the liquid structure factor representative of the first fluid layer near the patterned wall illustrates the influence of molecular ordering effects on slip in non-inertial flows.

(ii) The influence of surface roughness on the slip behavior of a Newtonian liquid in steady planar shear was investigated using three different approaches, namely Stokes flow calculations, molecular dynamics (MD) simulations and a statistical mechanical model for the friction coefficient between a corrugated wall and the first liquid layer. These approaches were used to probe the behavior of the slip length as a function of the slope parameter ka =2 pi a/lambda, where a and lambda represent the amplitude and wavelength characterizing the periodic corrugation of the bounding surface. The molecular and continuum approaches both confirm a monotonic decay in the slip length with increasing ka but the rate of decay as well as the magnitude of the slip length obtained from the Stokes flow solutions exceed the MD predictions as the wall feature sizes approach the liquid molecular dimensions. In the limit of molecular – scale wall corrugation, a Green–Kubo analysis based on the fluctuation–dissipation theorem accurately reproduces the MD results for the behavior of the slip length as a function of the roughness amplitude a. In combination, these three approaches provide a detailed picture of the influence of periodic roughness on the slip length which spans multiple length scales ranging from molecular to macroscopic dimensions.

(4) Generalized linear stability of non-inertial coating flows over substrates with topographical features Participants: Jeffrey M. Davis and Sandra M. Troian

Actuation of thin liquid films along the surface of an open microfluidic device requires an understanding of the stability of non-inertial flows over surfaces with topological features. These topological features can represent bumps or indentations which are intentionally patterned onto the substrate for various purposes or which can occur accidentally as a result of various etching and deposition processes. We therefore investigated the transient evolution of perturbations to steady lubrication flow over a topographically patterned surface via a non-modal linear stability analysis of the non-normal disturbance operator. In contrast to the capillary ridges that form near moving contact lines in the forced spreading of thin liquid films on uniformly flat substrates, the stationary capillary ridges near trenches or elevations have only stable eigenvalues. Minimal transient amplification of perturbations occurs, regardless of the magnitude or steepness of the topographical features. The absence of transient amplification and stability of the ridge can be explained on physical grounds. By comparison to unstable ridge formation on smooth, flat, and homogeneous surfaces, the lack of closed, recirculating streamlines beneath the capillary ridge is directly linked to the linear (fingering) stability.

Book Chapter Published During Reporting Period (2005-2006)

• Principles of Microfluidic Actuation By Modulation of Surface Stresses, A. A. Darhuber and S. M. Troian, Annu. Rev. Fluid Mech., Vol. 37, pp. 425-455 (2005).

Papers Published During Reporting Period (2005-2006)

• Effect of Contact Angle Hysteresis on Thermocapillary Droplet Actuation, Jian Z. Chen, Sandra M. Troian, Anton A. Darhuber and Sigurd Wagner, J. Appl. Phys. 97, 014906:1-9 (2005).

• Microfluidic Detection and Analysis by Integration of Evanescent Wave Sensing with Thermocapillary Actuation, Joseph P. Valentino, Sandra M. Troian and Sigurd Wagner, Technical Digest of the 18th IEEE International Conference on Micro Electro Mechanical Systems, Miami, FL, pp. 770-773 (2005).

• Experimental Study of Entrainment and Drainage Flow in Microscale Soap Films, Steffen Berg, Eric A. Adelizzi and Sandra M. Troian, Langmuir 21, 3867-3876 (2005).

• Slip Behavior in Liquid Films on Surfaces of Patterned Wettability: Comparison Between Continuum and Molecular Dynamics Simulations, Nikolai V. Priezjev, Anton A. Darhuber and Sandra M. Troian, Phys. Rev. E 71, 041608:1-11 (2005).

• Microfluidic Detection and Analysis by Integration of Thermocapillary Actuation with a Thin Film Optical Waveguide, Joseph P. Valentino, Sandra M. Troian and Sigurd Wagner, Appl. Phys. Lett. 86, 184101:1-3 (2005).

• Generalized Linear Stability of Non-Inertial Coating Flows Over Topographical Features, Jeffrey M. Davis and Sandra M. Troian, Phys. Fluids 17(7), 072103:1-9 (2005).

• Interfacial Profile and Spreading Rate of a Surfactant Film Advancing on a Thin Liquid Layer: Comparison Between Theory and Experiment, Anne D. Dussaud, Omar K. Matar and Sandra M. Troian, J. Fluid Mech. 544, 23-51 (2005).

• Infuence of Periodic Wall Roughness on the Slip Behavior at Liquid/Solid Interfaces: Molecular-Scale Simulations versus Continuum Predictions, Nikolai V. Priezjev and Sandra M. Troian, J. Fluid Mech. 554, 25-46 (2006).

Papers in Review During Reporting Period (2005-2006)

• Lateral Phase Segregation and 4-Fold Symmetry in Bilayer Films: Molecular Complexation in Extreme Confinement, Steffen Berg and Sandra M. Troian, submitted to Phys. Rev. Lett.

• Asymptotic Instability of Thin Film Flows Subject to a Step Increase in Shear Stress, Benjamin J. Fischer and Sandra M. Troian, submitted to J. Fluid Mech.

	• Transient Dynamics and Structure of Optimal Excitations in Thermocapillary Spreading: Precursor Film Model, Jeffrey M. Davis, Dawn E. Kataoka and Sandra M. Troian, submitted to Phys. Fluids.
Bibliography Type:	Description: (Last Updated: 03/26/2021)
Articles in Peer-reviewed Journals	Darhuber AA, Troian SM. "Principles of microfluidic actuation by modulation of surface stresses." Annual Review of Fluid Mechanics. 2005;37:425-55. https://doi.org/10.1146/annurev.fluid.36.050802.122052 , Jan-2005
Articles in Peer-reviewed Journals	Chen JZ, Troian SM, Darhuber AA, Wagner S. "Effect of contact angle hysteresis on thermocapillary droplet actuation." J Appl Phys. 2005 Jan;97(1):014906:1-9. https://doi.org/10.1063/1.1819979 , Jan-2005
Articles in Peer-reviewed Journals	Berg S, Adelizzi EA, Troian SM. "Experimental study of entrainment and drainage flows in microscale soap films." Langmuir. 2005 Apr 26;21(9):3867-76. https://doi.org/10.1021/la047178+ ; PMID: 15835948 , Apr-2005
Articles in Peer-reviewed Journals	Priezjev NV, Darhuber AA, Troian SM. "Slip behavior in liquid films on surfaces of patterned wettability: comparison between continuum and molecular dynamics simulations." Phys Rev E Stat Nonlin Soft Matter Phys. 2005 Apr;71(4 Pt 1):041608. https://doi.org/10.1103/PhysRevE.71.041608 ; PMID: 15903683 , Apr-2005
Articles in Peer-reviewed Journals	Valentino JP, Troian SM, Wagner S. "Microfluidic detection and analysis by integration of thermocapillary actuation with a thin-film optical waveguide." Applied Physics Letters 2005 May;86(18):184101. https://doi.org/10.1063/1.1922075 , May-2005
Articles in Peer-reviewed Journals	Davis JM, Troian SM. "Generalized linear stability of noninertial coating flows over topographical features." Physics of Fluids. 2005 Jul;17(7):072103. https://doi.org/10.1063/1.1945627 , Jul-2005
Articles in Peer-reviewed Journals	Dussaud AD, Matar OK, Troian SM. "Spreading characteristics of an insoluble surfactant film on a thin liquid layer: comparison between theory and experiment." J Fluid Mech. 2005 Dec;544:23-51. https://doi.org/10.1017/S002211200500621X , Dec-2005
Articles in Peer-reviewed Journals	Priezjev NV, Troian SM. "Influence of periodic wall roughness on the slip behaviour at liquid/solid interfaces: molecular-scale simulations versus continuum predictions." J Fluid Mech. 2006 May;554:25-46. https://doi.org/10.1017/S0022112006009086 , May-2006
Awards	Sandra M. Troian. "Fellow, American Physical Society, Division of Fluid Dynamics, December 2005." Dec-2005
Awards	Sandra M. Troian. "Moore Distinguished Scholar Award, California Institute of Technology (October 2004 - September 2005), September 2005." Sep-2005
Papers from Meeting Proceedings	Valentino JP, Troian SM, Wagner S. "Microfluidic Detection and Analysis by Integration of Evanescent Wave Sensing with Thermocapillary Actuation." 18th IEEE International Conference on Micro Electro Mechanical Systems, Miami, FL, January 30 - February 3, 2005. Technical Digest of the 18th IEEE International Conference on Micro Electromechanical Systems, Miami, FL, July 2005. p. 730-733. http://dx.doi.org/10.1109/MEMSYS.2005.1454033 , Jul-2005
Patents	US Patent Application 10/016,294. Patent Pending, April 2006. Apr-2006 Troian SM, Darhuber AA, Wagner S. "Method and Device for Controlling Liquid Flow on the Surface of a Microfluidic Chip."
Significant Media Coverage	Sandra M Troian. "Article on Troian research in droplet based microfluidics, Diving into Droplets." Analytical Chemistry, Diving into Droplets, March 1, 2006 issue, p. 1401-4., Mar-2006
Significant Media Coverage	Sandra M Troian. "Article on Troian method for integration of evanescent wave sensing with open microfluidic chip." Analytical Chemistry: Analytical Currents, article 'Non-intrusive Droplet Analysis,' July 2005., Jul-2005