Fiscal Year:	FY 2024	**Task Last Updated:**	FY 02/29/2024
PI Name:	Koochesfahani, Manoochehr Ph.D.		
Project Title:	Phase 2: ZBOT-2 Thermometry Diagnostics Development		
Division Name:	Physical Sciences		
Program/Discipline:			
Program/Discipline--Element/Subdiscipline:	FLUID PHYSICS--Fluid physics		
Joint Agency Name:		**TechPort:**	No
Human Research Program Elements:	None		
Human Research Program Risks:	None		
Space Biology Element:	None		
Space Biology Cross-Element Discipline:	None		
Space Biology Special Category:	None		
PI Email:	koochesf@egr.msu.edu	**Fax:**	FY
PI Organization Type:	UNIVERSITY	**Phone:**	(517) 353-5311
Organization Name:	Michigan State University		
PI Address 1:	Department of Mechanical Engineering		
PI Address 2:	428 S. Shaw Lane, Room 2555		
PI Web Page:			
City:	E. Lansing	**State:**	MI
Zip Code:	48824	**Congressional District:**	8
Comments:			
Project Type:	Flight	**Solicitation / Funding Source:**	Physical Sciences Unsolicited
Start Date:	05/01/2021	**End Date:**	04/30/2025
No. of Post Docs:	0	**No. of PhD Degrees:**	0
No. of PhD Candidates:	0	**No. of Master' Degrees:**	0
No. of Master's Candidates:	0	**No. of Bachelor's Degrees:**	0
No. of Bachelor's Candidates:	1	**Monitoring Center:**	NASA GRC
Contact Monitor:	Pearlman, Howard G.	**Contact Phone:**	216-433-4000
Contact Email:	howard.g.pearlman@nasa.gov		
Flight Program:			
Flight Assignment:			
Key Personnel Changes/Previous PI:			
COI Name (Institution):	Olson, David A Ph.D. (Michigan State University)		
Grant/Contract No.:	80NSSC21M0128		
Performance Goal No.:			
Performance Goal Text:			

In-orbit or on-surface cryogenic storage of propellant and life support consumables is essential to all stages of NASA’s Exploration Program. However, heat leakage from the surroundings results in liquid vaporization and significant mass loss and/or significant increase in the storage tank pressure. To mitigate the unwanted effects of cryogen vaporization, the Zero Boil-Off (ZBO) concept is being considered as an innovative approach for ventless means of controlling tank pressure through the application of active heat removal and forced liquid jet mixing. The Zero Boil-Off Tank (ZBOT) experiment on the International Space Station (ISS) is designed to examine the ZBO concept and, along with computational fluid dynamics (CFD) modeling efforts, provide information on the fundamental physics of the underlying complex thermofluids environment, which is needed for engineering design optimization of the ZBO concept. The optical diagnostics for whole-field thermometry that are being developed in the current proposal is crucial to providing scientific data and measurements for validation and further refinement of the two-phase CFD models developed by the ZBOT microgravity investigation. The ZBOT project directly aligns with NASA exploration needs for

Task Description:	Cryogenic Fluid Management of future propellant and life support storage tanks, and the ZBO tank pressure control is an important technology achievement that enables human missions to Moon, Mars, and other planets. Under NASA support we have successfully demonstrated the feasibility of a novel non-intrusive optical method for whole-field temperature measurement suitable for the ZBOT microgravity experiment. The technique of Quantum Dot Thermometry (QDT), specifically developed for the planned ZBOT experiments on the ISS, relies on laser induced fluorescence (LIF) thermometry based on quantum dots (QD) that are solubilized/dispersed in the working fluid of the ZBOT experiment. We have quantified the influence of the various interconnected parameters, and the tradeoffs among them, that influence the ability to make accurate temperature measurements, and we have shown that the science requirements are expected to be met by the judicious selection of detection strategy and data processing methods. The objectives of the proposed research are to capitalize on our progress to date and further develop the technique with a focus on the tradeoffs connected to the actual engineering constraints in implementation and design optimization of experiments on the ISS. A core element of this effort will be the close collaboration with NASA engineering and hardware design experts, and providing our scientific know-how in fluid flow optical diagnostics and data processing/analysis, as we transition the measurement technique to actual implementation for the ZBOT experiments on the ISS.
Rationale for HRP Directed Research:	
Research Impact/Earth Benefits:	The ZBOT project directly aligns with NASA exploration needs for Cryogenic Fluid Management of future propellant and life support storage tanks, and the ZBO tank pressure control is an important technology achievement that enables human missions to Moon, Mars, and other planets. Development of Quantum Dot Thermometry enables the measurements needed for obtaining scientific data for validation and refinement of the two-phase two-component CFD models being developed as part of the ZBOT project.
Task Progress:	Over the last several years under NASA support, we have developed the novel optical method of Quantum Dot Thermometry (QDT) for non-intrusive whole-field mapping of the temperature field in the Zero Boil-Off Tank (ZBOT) microgravity experiment. The technique relies on ratiometric laser induced fluorescence (LIF) thermometry based on quantum dots (QD) that are solubilized/dispersed in the working fluid of the ZBOT experiment, Perfluoro-n-Pentane (PnP). The objectives of the current research effort are to capitalize on our progress to date and further develop the QDT technique for the ZBOT-NC experiment with a focus on the tradeoffs connected to the actual engineering constraints in implementation and optimization of experiments aboard the International Space Station (ISS). [Ed. Note: "NC" refers to the addition of a non-condensable gas in the tank]. A core element of this effort is the close collaboration between our scientific know-how in fluid flow optical diagnostics, data processing/analysis, and the NASA engineering and hardware design experts as we transition the measurement technique to actual implementation for the ZBOT-NC experiments aboard the ISS. In the first year of this effort, we reported on the identification of QDs that are suitable for QDT and can be solubilized/dispersed in PnP. Characterization of the QDs continued in the second year and led to determination of the key attributes of the QDs that make for ideal candidates for QDT, and, more importantly, for the particular camera selected for ZBOT-NC experiments. While a color camera with a Bayer filter is not the preferred implementation of QDT for achieving the highest temperature sensitivity, factors connected to implementation constraints for ISS experiments have led to it being the optimum choice for ZBOT-NC. This puts additional emphasis on optimizing the performance of the QD that works best with the particular Bayer filter color camera. Finalization/optimization of the QD for flight is ongoing. During the second year of this effort, we conducted two separate flight tank tests at ZIN Technologies, the first in April of 2022 and the second in September of 2022. The initial testing identified several aspects of the initial ZBOT-NC optical design that were detrimental to QDT performance. We tested attributes of the system in conditions as similar as possible to their flight condition (such as the laser illumination uniformity, lens vignetting), and established the overall QDT performance curves for the entire system, which determine the expected temperature uncertainty of the measurements. The second round of testing showed notable improvements in the design but also highlighted that further optimization of the components was still needed. In addition to the flight tank testing, a self-pressurization experiment and sub-cooled jet experiment were conducted within the ZBOT fluid breadboard at ZIN. These were representative of the type of experiments being planned aboard the ISS. These preliminary measurements demonstrated promising results even with the less-than-ideal arrangement of the illumination and imaging hardware. More importantly, these collaborative tests demonstrated the initial performance of QDT with the flight hardware in a fluid system similar to the flight hardware. The results of the breadboard tests have been shared with the entire ZBOT-NC team. During the third year of this effort, progress on three distinct areas were made. First, the final batches of QDs were synthesized and characterized, the outcome of which was the final QD selection for flight operations. Second, we made progress in the development of QDT processing approaches that utilize detailed camera response calibrations to recover data in situations that were previously deemed unreliable. Third, several 1g test cases from the ZBOT-NC test matrix were performed at ZIN Technologies within their fluid breadboard. Their breadboard system received several improvements that more closely represented the flight system and was instrumented such that the actual test boundary conditions were sufficiently characterized for Computational Fluid Dynamics (CFD) to simulate the actual test conditions. We focused our initial efforts on the self-pressurization test point with 0.8-Watt strip heaters. Quantitative comparisons between the QDT temperature fields and the CFD simulations were presented at the Annual Meeting of the American Society for Gravitational and Space Research (ASGSR 2023). Overall, the comparisons between the experiments and simulations were excellent. The side-by-side videos of the temperature field evolution over time were complemented with temperature profiles at selected times that highlighted the agreement between the QDT measurements and CFD simulations in the temperature gradients within the tank over the duration of the experiment. These were the first quantitative comparisons made between QDT and CFD for the ZBOT-NC project. The lack of suitable reference conditions during the 1g experiments presented several challenges that were overcome in order to produce the QDT data in sufficient fidelity to quantitatively compare to the CFD simulations. Our scientific investigation into the root cause of these issues is ongoing but the initial guidance on best practices to avoid or mitigate the issues are being provided to NASA/ZIN. The progress made by a summer research intern with successfully applying

	the camera response calibration yielded additional insight into the root cause of observed issues and is being investigated for possibly providing an alternative pathway to address some of these challenges.
Bibliography Type:	Description: (Last Updated: 03/02/2026)
Abstracts for Journals and Proceedings	Bush M, Olson D. "Image processing of Quantum Dot Thermometry for NASA Zero Boil-Off Experiment." 13th Annual Mid-Michigan Symposium for Undergraduate Research Experiences (Mid-SURE), East Lansing, MI, July 26, 2023. Abstracts. 13th Annual Mid-Michigan Symposium for Undergraduate Research Experiences (Mid-SURE), East Lansing, MI, July 26, 2023. , Jul-2023
Abstracts for Journals and Proceedings	Olson D, Kahwaji Janho M, Koochesfahani M. "Quantum Dot Thermometry in the ZBOT fluid breadboard." 39th Annual Meeting of the American Society for Gravitational and Space Research, Washington, DC, November 13-18, 2023. Abstracts. 39th Annual Meeting of the American Society for Gravitational and Space Research, Washington, DC, November 13-18, 2023. , Nov-2023
Abstracts for Journals and Proceedings	Hylton S, Olson D, Kahwaji Janho M, Winter R, Kartuzova O, Koochesfahani M, Kassemi M. "The Zero Boil-Off Tank Experiment: The effects of non-condensable gases on pressurization and pressure control of propellant tanks in microgravity." 39th Annual Meeting of the American Society for Gravitational and Space Research, Washington, DC, November 13-18, 2023. Abstracts. 39th Annual Meeting of the American Society for Gravitational and Space Research, Washington, DC, November 13-18, 2023. , Nov-2023