Fiscal Year:	FY 2006	**Task Last Updated:**	FY 08/28/2006
PI Name:	Neitzel, G. Paul Ph.D.		
Project Title:	Novel Applications of Permanent Nonwetting		
Division Name:	Physical Sciences		
Program/Discipline:	FLUID PHYSICS		
Program/Discipline--Element/Subdiscipline:	FLUID PHYSICS--Interfacial phenomena		
Joint Agency Name:		**TechPort:**	No
Human Research Program Elements:	None		
Human Research Program Risks:	None		
Space Biology Element:	None		
Space Biology Cross-Element Discipline:	None		
Space Biology Special Category:	None		
PI Email:	paul.neitzel@gatech.edu	**Fax:**	FY
PI Organization Type:	UNIVERSITY	**Phone:**	404-894-3242
Organization Name:	Georgia Institute of Technology		
PI Address 1:	Mechanical Engineering		
PI Address 2:	771 Ferst Drive		
PI Web Page:			
City:	Atlanta	**State:**	GA
Zip Code:	30332	**Congressional District:**	5
Comments:			
Project Type:	Ground	**Solicitation / Funding Source:**	2002 Physical Sciences 02-OBPR-03-C
Start Date:	01/01/2005	**End Date:**	12/31/2008
No. of Post Docs:		**No. of PhD Degrees:**	
No. of PhD Candidates:	2	**No. of Master' Degrees:**	
No. of Master's Candidates:		**No. of Bachelor's Degrees:**	
No. of Bachelor's Candidates:	2	**Monitoring Center:**	NASA GRC
Contact Monitor:	Niederhaus, Charles	**Contact Phone:**	(216) 433-5461
Contact Email:	charles.niederhaus@grc.nasa.gov		
Flight Program:			
Flight Assignment:	NOTE: received notification 8/2006 that funding reinstated through 12/31/2008, per J. Cohen (HQ)		
Key Personnel Changes/Previous PI:			
COI Name (Institution):			
Grant/Contract No.:	NNC05GA33G		
Performance Goal No.:			
Performance Goal Text:			
	Long-duration space-exploration missions require that new solutions be sought for the resolution of issues for which short-mission solutions are unsatisfactory. Up-mass constraints require that these new solutions be mass-efficient and robust. A class of new methods that falls into this category are embodied in so-called "lab-on-a-chip" devices for the analysis of minute volumes of liquid. Many of these devices rely on the use of hard-wired channels or "capillaries," through which liquid is forced. Since the pressure difference required to drive liquid at a given flow rate through a pipe varies as R^-4, this becomes increasingly difficult as capillary radius R decreases. Other recent work has used surface forces such as thermocapillarity to move liquid along a surface, although in contact with it, the transport being slowed by viscous action through the no-slip condition. We have shown that permanent nonwetting of a solid by a normally wetting liquid may be achieved by providing relative tangential motion between the liquid and solid surfaces in		

Task Description:	question. This may be accomplished by physically moving one surface relative to the other (e.g., sliding a solid surface past a liquid droplet) or by employing a mechanism such as thermocapillarity to cause the liquid surface to move tangentially. In either case, a lubricating film of surrounding gas is drawn into the space between the two surfaces, causing them to remain far enough apart that attractive van der Waals forces are ineffective. The proposed research intends to demonstrate that liquid droplets may be levitated above (or between) solid surfaces and moved from one position to another using directional heating to propel a droplet in a nearly frictionless manner, thus avoiding the capillary-pumping restrictions. The heating is done optically using infrared radiation that is controllable to a degree necessary to effect precise transport of the droplets. To eliminate undesirable sample evaporation, and to permit the transport of aqueous solutions that are resistant to the use of thermocapillarity, we shall employ liquid encapsulation of aqueous droplets in less-volatile silicone oils, which have been shown to exhibit excellent thermocapillary transport properties. Three side benefits of encapsulation of this type are: i) minimization of sample-to-sample contamination (crucial to such lab-on-a-chip applications as DNA testing); ii) minimization of evaporation losses of volatile (and often valuable) aqueous samples; and iii) the provision of a less-viscous core within a silicone-oil droplet enabling more vigorous surface motion, and hence, enhanced transport, using smaller surface-temperature gradients. The proposed scheme has positive implications for the design of a new class of lab-on-a-chip architectures for use in space-exploration applications. In fact, the method will perform better in a microgravity environment than in a terrestrial one, due to the absence of body forces that may require the application of additional pumping force to overcome.
Rationale for HRP Directed Research:	
Research Impact/Earth Benefits:	This research identifies a novel droplet transport scheme with possible applications to lab-on-a-chip devices. This new scheme permits more rapid transport of droplets due to extremely small frictional forces and virtually no droplet-to-droplet contamination due to levitation.
Task Progress:	We have quantified failure modes, have made preliminary measurements of sliding-drop friction and demonstrated that droplets can be levitated and transported using the proposed mechanism. Furthermore, we have done some preliminary quantification of evaporation effects and can predict that droplets of nanoliter size will have survival times of O(100 s).
Bibliography Type:	Description: (Last Updated: 12/31/2020)
Articles in Other Journals or Periodicals	Kuo C-W, Chen J-C, Neitzel GP. "Numerical simulation of isothermal nonwetting." International Journal for Numerical Methods in Fluids, 2007, in press. , Jan-2007
Articles in Other Journals or Periodicals	Chen J-C, Kuo C-W, Neitzel GP. "Numerical simulation of thermocapillary nonwetting." International Journal of Heat and Mass Transfer, to appear 2006 Nov. , Nov-2006
Articles in Peer-reviewed Journals	van den Doel LR, Nagy PT, van Vliet LJ, Neitzel P. "Regularized phase tracker with isophase scanning strategy for analysis of dynamic interferograms of nonwetting droplets under excitation." Appl Opt. 2005 May 10;44(14):2695-704. PMID: 15943320 , May-2005
Articles in Peer-reviewed Journals	Smith MK, Neitzel GP. "Multiscale modeling in the numerical computation of isothermal nonwetting." Journal of Fluid Mechanics 2006 May;554:67-83. https://doi.org/10.1017/S0022112006009074 , May-2006
Journal/Magazine covers	van den Doel LR, Nagy PT, van Vliet LJ, Neitzel P. "Cover in journal Applied Optics for article, 'Regularized phase-tracker with iso-phase scanning strategy for analysis of dynamic interferograms of nonwetting droplets under excitation.' " Appl Opt. 2005 May 10;44(14):2695-704. PMID: 15943320 [PubMed] Applied Optics 44, 2695- 2704 , May-2005