

CSA0503-DATABASE MANAGEMENT SYSTEMS

EXPERIMENT 20 - MYSQL STRING FUNCTIONS- REPLACE, REPEAT, REVERSE, RIGHT, LEFT, RPAD, LPAD

1)

```
mysql> -- REPLACE()
mysql> SELECT REPLACE('Hello World', 'World', 'MySQL') AS Replace_Result;
+-----+
| Replace_Result |
+-----+
| Hello MySQL    |
+-----+
1 row in set (0.01 sec)
```

```
mysql> -- REPEAT()
mysql> SELECT REPEAT('SQL ', 3) AS Repeat_Result;
+-----+
| Repeat_Result |
+-----+
| SQL SQL SQL   |
+-----+
1 row in set (0.00 sec)
```

```
mysql> -- REVERSE()
mysql> SELECT REVERSE('MySQL') AS Reverse_Result;
+-----+
| Reverse_Result |
+-----+
| LQSyM         |
+-----+
1 row in set (0.00 sec)
```

```
mysql> -- RIGHT()
mysql> SELECT RIGHT('DATABASE', 4) AS Right_Result;
+-----+
| Right_Result |
+-----+
| BASE         |
+-----+
1 row in set (0.00 sec)
```

```
mysql> -- LEFT()
mysql> SELECT LEFT('DATABASE', 4) AS Left_Result;
+-----+
| Left_Result |
+-----+
| DATA       |
+-----+
1 row in set (0.00 sec)
```

```
mysql>
mysql> -- RPAD()
mysql> SELECT RPAD('SQL', 8, '*') AS Rpad_Result;
+-----+
| Rpad_Result |
+-----+
| SQL*****  |
+-----+
1 row in set (0.01 sec)
```

```
mysql>
mysql> -- LPAD()
mysql> SELECT LPAD('SQL', 8, '*') AS Lpad_Result;
+-----+
| Lpad_Result |
+-----+
| *****SQL  |
+-----+
1 row in set (0.00 sec)
```

```
mysql>
mysql> -- ASCII()
mysql> SELECT ASCII('A') AS ASCII_Result;
+-----+
| ASCII_Result |
+-----+
|          65 |
+-----+
1 row in set (0.00 sec)
```

```
mysql>
mysql> -- BIN()
mysql> SELECT BIN(10) AS Binary_Result;
+-----+
| Binary_Result |
+-----+
| 1010         |
+-----+
1 row in set (0.00 sec)
```

```
mysql>
mysql> -- OCT()
mysql> SELECT OCT(10) AS Octal_Result;
+-----+
| Octal_Result |
+-----+
| 12          |
+-----+
1 row in set (0.01 sec)
```

RESULT:

Thus the String Functions such as space, substr, upper, lower, trim, length are executed successfully.