Do System One Models Make Better Rerankers?

Anonymous

Anonymous

Abstract. System One models, or decision models, answer a question about an input with a calibrated probability. They are only a month old but much discussed, and first reports have tried them as rerankers. For six Qwen models (0.6B to 27B parameters) and ten test collections, we compare the untuned model with its decision fine-tunes and its reranker fine-tunes, one of which we trained ourselves. The reranker fine-tunes rank better wherever both exist, while decision fine-tuning adds little to the untuned model. Decision models are not better calibrated either: with a fixed probability threshold, reranker fine-tunes select better passages, and our own reranker fine-tune gives the most reliable probabilities of all systems we tested.

Keywords: Reranking · Calibration · System One Models · Fine-Tuning

1 Introduction

System One models, also called decision models, answer a question about an input (the *state*) with a probability instead of generated text, like fast, intuitive thinking [14]. TypeSafe AI released the first of them, Jev, on 15 September 2026, trained with a new method it calls RLCD (reinforcement learning for calibrated decisions) [31]. The model class is only about a month old, yet it is marketed widely, and first reports show Jev reranking BM25 candidates about as well as strong cross-encoders [11, 13, 15, 26]. Open alternatives with the same kind of output followed within weeks: Kev by the end of September [22] and Cloudflare's Clef on 1 October [4]. They fine-tune open Qwen models, but not with RLCD, which is unpublished; Kev, for instance, uses a standard cross-entropy loss [21]. Still, the largest Kev matches Jev as a reranker in our experiments. We therefore study *decision fine-tuning*, i.e. fine-tuning an open model to give Jev's kind of output, and ask, one month after Jev's release, whether it is of use for retrieval.

A fair test compares decision fine-tuning with the established alternative, reranker fine-tuning, on the same *foundation model*, i.e. the same pretrained language model of a given size, such as Qwen3.5-4B. For six Qwen foundation models from 0.6B to 27B parameters and ten test collections, we compare three variants: the base model asked zero-shot, its decision fine-tune and its reranker fine-tune. Since decision models are advertised for their calibrated probabilities, we also check whether they at least deliver that:

RQ1 On the same foundation model, does decision fine-tuning make a better reranker than reranker fine-tuning or no fine-tuning?

RQ2 Are decision models at least better calibrated than reranker fine-tunes of the same foundation model?

Both answers are negative. (1) Wherever both exist (0.6B to 9B), the reranker fine-tune ranks better than the decision fine-tune, also on collections without training data, and up to 9B decision fine-tuning hardly improves on the base model. (2) Decision models are not better calibrated than reranker fine-tunes of the same model. Our own reranker fine-tune of Qwen3.5-9B ranks as well as the best published one and is the best calibrated system we tested. Code, raw outputs and the results on all collections are available.[1]

2 Related Work

Fine-tuned rerankers. Cross-encoders fine-tuned on MS MARCO [19, 20] and their LLM successors read relevance from the score of a relevance token or a scoring head. LLM rerankers fine-tune open models such as LLaMA [17] or Qwen [34, 35]. Listwise rerankers output a ranking instead [24, 29], and the Set-Encoder lets passages attend to each other [27]. Abdallah et al. [1] compare many of them on our candidates.

System One models in retrieval. Besides Jev [31], Kev [22], Clef [4] and Laya [5] are open System One models. Their use as rerankers has so far only been tried in reports that are not peer-reviewed: S1Rank and jev-rerank score BM25 candidates with Jev [13, 26], blog posts report on Jev as a reranker [11, 15, 32], and Laya has been used as a relevance gate before recall [28]. None compares decision fine-tuning with reranker fine-tuning on the same model.

Calibration and cutoffs. Modern neural networks tend to be overconfident, and temperature scaling is a simple fix after training [12]; neural rankers are no exception [23]. Calibrated probabilities matter wherever a score is read on an absolute scale, e.g. to cut off a ranked list [2].

3 Experimental Setup

Triplets. For each of six foundation models (Qwen3-0.6B and 8B, Qwen3.5-0.8B, 4B and 9B, and Qwen3.8-27B) we compare three variants. *Base*: the released model, asked the decision models' question in its chat format (thinking off) and scored by the probability of "yes" as the first answer token. *Decision fine-tune*: Kev [21, 22] (LoRA on the pretrained checkpoints up to 9B, a full fine-tune at 27B), Clef-Flash (9B) and Clef (27B) [4]. *Reranker fine-tune*: Qwen3-Reranker [35] (on the same pretrained checkpoints as Kev) and Prism [34], scored by the probability of "yes" against "no"; none is public for 27B. For Qwen3.5-9B we add our own (*Ours-9B*), trained without any decision data: LoRA ($r = 32$),

[1] [TODO: anonymised link]

Table 1. Base model, decision fine-tune and reranker fine-tune of the same foundation model (nDCG@10, ×100, BM25 top-100). Avg: mean over all ten collections, including DL20 and DL22, which are not shown for space; ZS: mean over the collections without a training split (TREC-COVID, Touché, DBPedia). Per foundation model and column: best in bold, second best underlined. Paired t-test, Holm-corrected over the ten collections, $p < 0.05$: * reranker fine-tune vs. the decision fine-tune with the best Avg, † that decision fine-tune vs. the base model, ‡ joint vs. isolated. No reranker fine-tune of the 27B model exists.

			TREC DL			BEIR						
System	Training	Mode	DL19	DL21	DL23	COVID	NFC	SciF	Touché	DBP	Avg	ZS
Qwen3-0.6B												
Qwen3-0.6B	base		32.6	32.5	14.3	50.3	16.2	18.8	11.5	14.3	23.8	25.4
Kev-0.6B	decision	joint	18.4‡	19.1‡	11.0‡	34.0‡	12.0‡	1.1‡	4.5‡	6.1‡	13.2	14.9
Kev-0.6B	decision	isolated	33.4	39.8	18.8	58.2	17.0	16.2	13.0	21.5†	27.0	30.9
Qwen3-Reranker-0.6B	reranker		**69.5***	**65.2***	**38.8***	**86.2***	**36.4***	**76.6***	**35.7***	**42.7***	**56.1**	**54.9**
Qwen3-8B												
Qwen3-8B	base		70.4	65.8	42.1	80.2	34.1	72.8	24.0	37.1	53.3	47.1
Kev-8B	decision	joint	63.4‡	60.1	35.7	48.2‡	19.8‡	19.2‡	9.7‡	36.7‡	38.8	31.5
Kev-8B	decision	isolated	71.2	61.4†	37.6†	80.8	35.2	73.9	26.5	40.0†	52.7	49.1
Qwen3-Reranker-8B	reranker		**73.2**	**67.0***	**45.2***	**84.0**	**37.3***	**79.9***	**43.1***	**46.2***	**59.4**	**57.8**
Qwen3.5-0.8B												
Qwen3.5-0.8B	base		47.7	53.3	27.9	65.3	20.4	41.1	21.9	25.8	37.6	37.7
Kev-0.8B	decision	joint	35.7	38.6‡	18.2‡	45.3‡	18.6	20.2‡	9.4‡	14.6‡	25.3	23.1
Kev-0.8B	decision	isolated	42.8	48.3	23.8	71.9	20.9	36.0	18.0	32.2†	36.0	40.7
Prism-0.8B	reranker		**72.3***	**66.3***	**43.7***	**84.2***	**36.1***	**76.3***	**35.6***	**41.7***	**57.1**	**53.8**
Qwen3.5-4B												
Qwen3.5-4B	base		69.0	66.2	40.1	79.5	34.1	72.9	24.8	37.0	52.7	47.1
Kev-4B	decision	joint	65.5	62.4	38.3	75.3‡	29.3‡	62.4‡	23.7	40.7	49.8	46.6
Kev-4B	decision	isolated	62.6†	62.0	35.4	82.6	34.1	70.7	23.0	39.7†	51.3	48.4
Prism-4B	reranker		**74.4***	**70.3***	**46.2***	**84.6**	**37.4***	**76.9***	**34.3***	**43.7***	**58.7**	**54.2**
Qwen3.5-9B												
Qwen3.5-9B	base		69.6	67.7	38.1	81.2	33.6	75.0	27.5	35.8	53.7	48.2
Kev-9B	decision	joint	63.1	63.6	39.1	78.2	31.5	60.9‡	22.6	38.5‡	50.2	46.4
Kev-9B	decision	isolated	65.7	60.8	35.4	77.7	32.8	72.6	19.8	34.1	50.1	43.8
Clef-Flash	decision	joint	68.8	64.3	40.4	82.1	35.1‡	65.4	21.3	38.8‡	52.8	47.4
Clef-Flash	decision	isolated	68.8	66.4	43.8†	82.3	**37.3**†	68.7†	22.1	42.6†	54.7	49.0
Prism-9B	reranker		**74.0***	**71.0***	44.2	83.0	37.2	**79.8***	34.7*	43.2	59.0	53.7
Ours-9B	reranker		73.8*	67.3	**47.0**	**84.2**	37.1	77.9*	**36.5***	**47.7***	**59.4**	**56.1**
Qwen3.8-27B												
Qwen3.8-27B	base		71.6	68.5	44.1	83.0	37.6	78.5	30.2	45.0	57.4	52.7
Kev-27B	decision	joint	**73.9**	69.9	**49.3**†	**85.9**†	**38.7**†	**81.1**†	**40.8**‡†	46.9†	**61.1**	**57.9**
Kev-27B	decision	isolated	73.4	**70.1**	46.8	85.5	38.3	79.9	34.0	**47.5**	59.8	55.7
Clef	decision	joint	71.4	68.6	45.9	82.9	36.3	62.9‡	30.8	42.8	56.1	52.2
Clef	decision	isolated	69.4	66.7	42.9	83.5	37.8	71.9	33.9	44.1	56.4	53.8

one epoch over 100k MS MARCO training queries with one relevant and 15 hard negative passages each, a ranking loss (InfoNCE) plus a yes/no classification loss (binary cross-entropy). We removed training queries that match a test or development topic and chose the checkpoint on 200 MS MARCO dev queries. Qwen3-Reranker, Prism and Ours-9B saw MS MARCO; Kev's training data contain neither MS MARCO nor BEIR [21].

Collections and candidates. TREC DL 2019–2023 [6–10] (MS MARCO v1/v2 passages [18]) and TREC-COVID, NFCorpus, SciFact, Touché and DBPedia from BEIR [30]. TREC-COVID, Touché and DBPedia have no training split in any fine-tune's data and form the *zero-shot subset* (ZS). Every system reranks

the BM25 top-100 of Pyserini [16], the candidates of S1Rank [26], RankGPT [29], RankZephyr [24] and Abdallah et al. [1], whose published numbers we use where we did not rerun a system.

Decision models. All decision models get S1Rank's question [26], fixed in advance ("Is document `{doc}` relevant to the `query`? Relevant means it answers the query or contains information that directly addresses it."), with a state that holds all 100 candidates (*joint*) or one (*isolated*). Besides the triplets we run Jev 1.13.0 (closed), Laya [5] (isolated only, as its context is too short), monoT5-3B [20], bge-reranker-v2-m3 [3], the Set-Encoder [27] and RankZephyr (DL only).

Metrics. nDCG@10, with paired t-tests over queries, Holm-corrected across the ten collections ($p < 0.05$). Expected calibration error (ECE, 15 bins) [12] on the judged pairs of DL 2019–2023 (relevant from grade 2), the only collections that also judge non-relevant passages. *One cutoff*: we keep every candidate with $p \geq 0.5$ and report the F_1 of this set and its regret, i.e. how much F_1 the best cutoff per collection would add (unjudged passages count as non-relevant). *After the fact*: temperature and Platt scaling of each reranker's score, fitted on the BM25 top-100 of 1,000 MS MARCO dev queries. *Sanity checks*: our BM25 matches Pyserini's reproductions [25], monoT5-3B and RankZephyr are within 0.2 points of their published DL 2019/2020 numbers [1], and Jev joint is within 0.5 of S1Rank's [26] on four of five shared collections (1.5 below on TREC-COVID).

4 Decision vs. Reranker Fine-Tuning

Reranker fine-tuning wins on every model. For all five foundation models where both exist, the reranker fine-tune ranks better than the decision fine-tune in either mode (Table 1; average over ten collections, Qwen3-0.6B: 56.1 vs. 27.0; Qwen3-8B: 59.4 vs. 52.7; Qwen3.5-0.8B: 57.1 vs. 36.0; Qwen3.5-4B: 58.7 vs. 51.3; Qwen3.5-9B: 59.0 for Prism and 59.4 for Ours-9B vs. 54.7 for Clef-Flash). The difference is significant on 46 of the 60 pairs of model and collection, and the decision fine-tune is never significantly better (*). The zero-shot subset shows the same (e.g. 54.9 vs. 30.9 at 0.6B, 56.1 vs. 49.0 at 9B), so the gap does not come from training on MS MARCO. It does not come from special training data either, as Ours-9B, trained on MS MARCO alone, matches Prism-9B. Up to 9B, decision fine-tuning hardly changes the base model: its better mode lies between 3.5 points below and 3.2 points above the base average, with significant differences on at most five collections (†). Reranker fine-tuning adds 5 to 32 points. Only Kev-27B clearly improves on its base model (by 3.7 points, significant on eight collections). It is the best system in our study (61.1), but only slightly ahead of reranker fine-tunes a third of its size (59.4).

Joint vs. isolated. Scoring all candidates together helps only models trained on long states, and only a little: Kev-27B gains 1.3 points and Jev 1.0 (Table 2).

Table 2. Other systems, same candidates (nDCG@10 ×100, means). †: includes published numbers [1, 33]; –: not all collections available. Best in bold, second best underlined.

System	Type	DL	BEIR	Avg	ZS
BM25		39.3	47.1	43.2	45.2
RankGPT-4	listwise	–	56.9†	–	<u>57.1</u>†
RankZephyr-7B	listwise	61.4	53.3†	57.3†	51.7†
monoT5-3B	cross-encoder	60.4	54.6†	57.5†	52.5†
bge-reranker-v2-m3	cross-encoder	60.4†	52.8†	56.6†	52.2†
Set-Encoder-large	cross-encoder	**63.6**†	54.4	59.0†	53.8
Jev	System One, joint	<u>62.7</u>	**58.2**	**60.5**	**57.2**
Jev	System One, isolated	61.4	<u>57.6</u>	<u>59.5</u>	56.7
Laya	System One, isolated	47.3	40.7	44.0	43.7

Kev-9B and Clef stay within 0.3, Kev-4B and Clef-Flash lose 1.5 to 2, and Kev-0.6B, Kev-0.8B and Kev-8B lose 10.7 to 13.9 points, significantly on 6 to 10 collections (‡). Kev-0.8B and Kev-4B were trained on states of at most 7,552 tokens and Kev-27B on up to 32,768 [21] (Kev-8B's card gives no length), while a joint state has about 13k tokens on TREC DL and 40k or more on BEIR. Beyond the trained length the model loses track of which passage a question is about: Kev-0.6B in joint mode separates relevant from non-relevant passages only at chance level on DL 2019/2020.

Other systems. The open Kev-27B (61.1) matches the closed Jev (60.5, Table 2). Both are ahead of established rerankers (Set-Encoder-large 59.0, monoT5-3B 57.5), and so are Qwen3-Reranker-8B and Ours-9B (59.4). Laya (44.0) is barely above BM25 (43.2).

5 Are Decision Models Better Calibrated?

A model is well calibrated if its probabilities match how often passages are actually relevant; ECE measures the gap. Calibration is the main selling point of decision models, and the base models are indeed poorly calibrated (Table 3; ECE up to 0.750). Decision fine-tuning lowers their ECE on every model, but so does reranker fine-tuning. Compared with the reranker fine-tune of the same model, the decision fine-tune is worse calibrated at Qwen3-0.6B (0.579 vs. 0.511) and Qwen3.5-0.8B (0.357 vs. 0.243), about equal at Qwen3.5-4B (0.216 vs. 0.218) and Qwen3-8B (0.243 vs. 0.257), and better only at Qwen3.5-9B against Prism (Clef-Flash 0.140 vs. 0.242). For the same model, Ours-9B is the best calibrated system in our study (0.111), better than every decision model, including the 27B ones (0.147 and 0.156) and Jev (0.224). Good calibration thus comes from a loss that treats the score as a probability, not from decision fine-tuning. A count test, which compares the sum of a query's probabilities with its number of relevant passages, agrees: decision and reranker fine-tune tie at 4B and 8B, and Ours-9B counts best of all systems (7.3; Clef 8.4, Kev-27B 8.5, Jev 11.3).

Table 3. Calibration and one cutoff, means over TREC DL 2019–2023. Per foundation model: base model, decision fine-tunes in their better-calibrated mode (j/i: joint/isolated), reranker fine-tunes. N: native; T, P: temperature/Platt scaling fitted on MS MARCO dev. F_1@.5 (×100): set kept at $p \geq 0.5$; Regret: F_1 at each collection's best cutoff minus F_1@.5; $|S|$: passages kept at 0.5 (of 100). Count: mean absolute error of the summed probabilities against the number of relevant passages (always guessing the median count: 8.6).

	ECE			F_1@.5				
System	N	T	P	N	P	Regret	$\|S\|$	Count
Qwen3-0.6B								
Qwen3-0.6B	0.750	–	–	19.9	–	0.5	100.0	36.5
Kev-0.6B (i)	0.579	–	–	20.7	–	2.4	87.9	28.2
Qwen3-Reranker-0.6B	0.511	0.326	0.226	31.8	6.3	14.9	58.4	24.8
Qwen3-8B								
Qwen3-8B	0.383	–	–	37.8	–	3.8	43.5	17.5
Kev-8B (j)	0.243	–	–	36.0	–	4.6	33.7	12.8
Qwen3-Reranker-8B	0.257	0.237	0.227	46.3	7.4	9.0	32.2	12.9
Qwen3.5-0.8B								
Qwen3.5-0.8B	0.716	–	–	20.0	–	12.3	98.6	34.8
Kev-0.8B (i)	0.357	–	–	24.7	–	3.5	56.2	18.0
Prism-0.8B	0.243	0.229	0.237	46.9	5.7	2.8	26.5	12.7
Qwen3.5-4B								
Qwen3.5-4B	0.296	–	–	40.3	–	7.1	38.0	14.7
Kev-4B (i)	0.216	–	–	41.0	–	4.6	30.5	11.5
Prism-4B	0.218	0.202	0.238	51.0	5.7	2.8	23.1	11.5

	ECE			F_1@.5				
System	N	T	P	N	P	Regret	$\|S\|$	Count
Qwen3.5-9B								
Qwen3.5-9B	0.283	–	–	42.1	–	7.4	36.8	14.1
Kev-9B (j)	0.237	–	–	41.0	–	4.6	32.2	12.2
Clef-Flash (j)	0.140	–	–	46.6	–	2.6	21.4	8.9
Prism-9B	0.242	0.233	0.238	50.7	5.7	4.0	26.0	12.3
Ours-9B	0.111	–	–	46.6	–	6.4	8.7	7.3
Qwen3.8-27B								
Qwen3.8-27B	0.166	–	–	52.2	–	2.4	24.2	8.9
Kev-27B (j)	0.156	–	–	55.1	–	2.8	22.8	8.5
Clef (j)	0.147	–	–	52.5	–	3.1	23.3	8.4
Other systems								
Jev (j)	0.224	–	–	49.9	–	6.2	29.1	11.3
monoT5-3B	0.312	0.257	0.232	42.0	5.8	9.9	35.6	15.2
bge-reranker-v2-m3	0.231	0.226	0.236	48.2	5.7	3.8	29.3	12.1
Set-Encoder-large	0.495	0.250	0.236	31.6	5.7	21.1	52.2	24.3

One cutoff for every collection. A practical use of calibration is to keep every passage with $p \geq 0.5$, e.g. to decide which passages reach a generator. With this rule, the best reranker fine-tune selects the better set for every model where both exist (F_1@.5, e.g. Prism-4B 51.0 vs. Kev-4B 41.0, Prism-9B 50.7 vs. Clef-Flash 46.6). Decision models are also not the only ones for which 0.5 is close to the best cutoff (low regret): Prism (2.8 to 4.0), bge (3.8) and the base Qwen3.8-27B (2.4) are as close as Clef-Flash (2.6), Kev-27B (2.8) and Clef (3.1), and closer than Jev (6.2). A low ECE alone is not enough, though: Ours-9B is too cautious on TREC DL, keeps only 8.7 passages per query and has a regret of 6.4.

Calibrated after training. Fitted on MS MARCO dev, temperature scaling lowers every reranker's ECE (e.g. Qwen3-Reranker-0.6B from 0.511 to 0.326), but none gets below 0.20. Platt scaling brings all of them to about 0.23 but empties the set at 0.5 (F_1@.5 of 5.7 to 7.4), because MS MARCO dev judges only about one passage per query. A well calibrated model is better, but it need not be a decision model, as Ours-9B shows.

6 Conclusion

Do System One models make better rerankers? No. On the same foundation model, reranker fine-tuning beats decision fine-tuning, which adds little to the untuned model. Their calibration is no advantage either: reranker fine-tunes are as well calibrated, select better passages at a fixed threshold, and can be trained to be better calibrated than any decision model. Despite the hype and first uses as rerankers, decision models are currently of no use for reranking, neither for ranking nor for their calibration.

References

1. Abdallah, A., Piryani, B., Mozafari, J., Ali, M., Jatowt, A.: How Good are LLM-based Rerankers? An Empirical Analysis of State-of-the-Art Reranking Models. In: Findings of the Association for Computational Linguistics: EMNLP 2025 (2025), arXiv:2508.16757
2. Bahri, D., Tay, Y., Zheng, C., Metzler, D., Tomkins, A.: Choppy: Cut Transformer for Ranked List Truncation. In: Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval (2020)
3. Chen, J., Xiao, S., Zhang, P., Luo, K., Lian, D., Liu, Z.: BGE M3-Embedding: Multi-Lingual, Multi-Functionality, Multi-Granularity Text Embeddings Through Self-Knowledge Distillation. arXiv preprint arXiv:2402.03216 (2024)
4. Cloudflare: Clef and Clef-Flash: open-weight Jev-compatible System One models. https://huggingface.co/Cloudflare/clef, https://huggingface.co/Cloudflare/clef-flash (2026), Hugging Face model cards, accessed 2026-10-07
5. ConvAI Innovations: Laya: an open System One model. https://huggingface.co/convaiinnovations/laya (2026), Hugging Face model card, accessed 2026-10-07
6. Craswell, N., Mitra, B., Yilmaz, E., Campos, D.: Overview of the TREC 2020 Deep Learning Track. arXiv preprint arXiv:2102.07662 (2021)
7. Craswell, N., Mitra, B., Yilmaz, E., Campos, D., Lin, J.: Overview of the TREC 2021 Deep Learning Track. In: Proceedings of the Thirtieth Text REtrieval Conference (TREC 2021) (2021)
8. Craswell, N., Mitra, B., Yilmaz, E., Campos, D., Lin, J., Voorhees, E.M., Soboroff, I.: Overview of the TREC 2022 Deep Learning Track. In: Proceedings of the Thirty-First Text REtrieval Conference (TREC 2022) (2022)
9. Craswell, N., Mitra, B., Yilmaz, E., Campos, D., Voorhees, E.M.: Overview of the TREC 2019 Deep Learning Track. arXiv preprint arXiv:2003.07820 (2020)
10. Craswell, N., Mitra, B., Yilmaz, E., Rahmani, H.A., Campos, D., Lin, J., Voorhees, E.M., Soboroff, I.: Overview of the TREC 2023 Deep Learning Track. In: Proceedings of the Thirty-Second Text REtrieval Conference (TREC 2023) (2023)
11. Elastic Search Labs: E-Commerce Search Reranking: An LLM Alternative with Jev. https://www.elastic.co/search-labs/blog/ecommerce-search-reranking-llm-alternative-jev (2026), Blog post, accessed 2026-10-05
12. Guo, C., Pleiss, G., Sun, Y., Weinberger, K.Q.: On Calibration of Modern Neural Networks. In: Proceedings of the 34th International Conference on Machine Learning (ICML). pp. 1321–1330 (2017)
13. jev-rerank. https://github.com/hev/jev-rerank (2026), GitHub repository, accessed 2026-10-05
14. Kahneman, D.: Thinking, Fast and Slow. Farrar, Straus and Giroux (2011)
15. LanceDB: How Jev Compares to Other Rerankers. https://www.lancedb.com/blog/how-jev-compares-to-other-rerankers (2026), Blog post, accessed 2026-10-05
16. Lin, J., Ma, X., Lin, S.C., Yang, J.H., Pradeep, R., Nogueira, R.: Pyserini: A Python Toolkit for Reproducible Information Retrieval Research with Sparse and Dense Representations. In: Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval. pp. 2356–2362 (2021)
17. Ma, X., Wang, L., Yang, N., Wei, F., Lin, J.: Fine-Tuning LLaMA for Multi-Stage Text Retrieval. arXiv preprint arXiv:2310.08319 (2023)

18. Nguyen, T., Rosenberg, M., Song, X., Gao, J., Tiwary, S., Majumder, R., Deng, L.: MS MARCO: A Human Generated MAchine Reading COmprehension Dataset. In: Proceedings of the Workshop on Cognitive Computation (CoCo@NIPS) (2016)
19. Nogueira, R., Cho, K.: Passage Re-ranking with BERT. arXiv preprint arXiv:1901.04085 (2019)
20. Nogueira, R., Jiang, Z., Pradeep, R., Lin, J.: Document Ranking with a Pretrained Sequence-to-Sequence Model. In: Findings of the Association for Computational Linguistics: EMNLP 2020. pp. 708–718 (2020)
21. Palmer, J.: Kev model cards (kev-0.6b, kev-0.8b, kev-4b, kev-8b, kev-9b, kev-27b). https://huggingface.co/jaredpalmer (2026), Hugging Face model cards, accessed 2026-10-09
22. Palmer, J.: Kev: open Jev-like System One adapters. https://github.com/jaredpalmer/kev (2026), GitHub repository, accessed 2026-10-07
23. Penha, G., Hauff, C.: On the Calibration and Uncertainty of Neural Learning to Rank Models for Conversational Search. In: Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics (EACL). pp. 160–170 (2021)
24. Pradeep, R., Sharifymoghaddam, S., Lin, J.: RankZephyr: Effective and Robust Zero-Shot Listwise Reranking is a Breeze! arXiv preprint arXiv:2312.02724 (2023)
25. Pyserini: Two-Click Reproductions (2CR): MS MARCO v1/v2 passage and BEIR. https://github.com/castorini/pyserini/tree/master/pyserini/2cr (2026), Accessed 2026-10-07
26. S1Rank: Reranking with Jev. https://github.com/zaesho/S1Rank (2026), GitHub repository, accessed 2026-10-05
27. Schlatt, F., Fröbe, M., Scells, H., Zhuang, S., Koopman, B., Zuccon, G., Stein, B., Potthast, M., Hagen, M.: Set-Encoder: Permutation-Invariant Inter-Passage Attention for Listwise Passage Re-Ranking with Cross-Encoders. In: Advances in Information Retrieval. 47th European Conference on IR Research (ECIR 2025). Lecture Notes in Computer Science, Springer (2025). https://doi.org/10.1007/978-3-031-88711-6_1
28. Laya as a Relevance Gate before Recall. https://github.com/zero8dotdev/smriti/issues/87 (2026), GitHub issue, accessed 2026-10-05
29. Sun, W., Yan, L., Ma, X., Wang, S., Ren, P., Chen, Z., Yin, D., Ren, Z.: Is ChatGPT Good at Search? Investigating Large Language Models as Re-Ranking Agents. In: Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP) (2023)
30. Thakur, N., Reimers, N., Rücklé, A., Srivastava, A., Gurevych, I.: BEIR: A Heterogeneous Benchmark for Zero-shot Evaluation of Information Retrieval Models. In: Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks (2021)
31. TypeSafe AI: Introducing System One Models & Jev. https://typesafe.ai/blog/introducing-system-one-models-and-jev (2026), Blog post, 15 September 2026, accessed 2026-10-12
32. Vectorize: Adding a Jev Reranker: What We Learned. https://hindsight.vectorize.io/blog/2026/09/24/adding-jev-reranker-what-we-learned (2026), Blog post, accessed 2026-10-05
33. Webis: webis/set-encoder-large (model card). https://huggingface.co/webis/set-encoder-large (2025), Hugging Face model card, accessed 2026-10-07
34. Zhang, D.: Prism-Reranker: Beyond Relevance Scoring – Jointly Producing Contributions and Evidence for Agentic Retrieval. arXiv preprint arXiv:2604.23734 (2026)

35. Zhang, Y., Li, M., Long, D., Zhang, X., Lin, H., Yang, B., Xie, P., Yang, A., Liu, D., Lin, J., Huang, F., Zhou, J.: Qwen3 Embedding: Advancing Text Embedding and Reranking Through Foundation Models. arXiv preprint arXiv:2506.05176 (2025)