

LABSHEET 6 : FULL STACK DEVELOPMENT

NAME : KANISHKA SHARMA

COURSE : BTECH CSE 'B'

ROLLNO : 26

Q1. Server Setup & Building the REST API

- Create a folder `api-lab` with `server/` and `client/` subfolders. Inside `server/`, initialize npm, install `express`, `cors`, and `dotenv`, and set up a `.env` file with `PORT=5000` (read via `process.env.PORT` with a 5000 fallback). Add a "dev" script using `nodemon`.
- Using an in-memory array of at least 5 "task" objects (`id`, `title`, `completed`), build all 5 CRUD routes: `GET /api/tasks`, `GET /api/tasks/:id`, `POST /api/tasks`, `PUT /api/tasks/:id`, and `DELETE /api/tasks/:id` — with a proper 404 JSON error when an `id` doesn't exist.
- Write a custom logger middleware (`method`, `URL`, `timestamp`) applied globally, and an `auth-check` middleware requiring a header `x-api-key` (stored in `.env`) applied only to the `POST`, `PUT`, and `DELETE` routes.

ANS : (a) Create the project structure:

```
mkdir api-lab
```

```
cd api-lab
```

```
mkdir server client
```

Initialize the server:

```
cd server
```

```
npm init -y
```

Install required dependencies:

```
npm install express cors dotenv
```

```
npm install --save-dev nodemon
```

Create .env file (in server/):

```
PORT=5000
```

```
API_KEY=your_secret_key_here # Replace with a strong key (e.g., generated via openssl rand -hex 16)
```

Update package.json (add the dev script):

```
{  
  
  "name": "api-lab-server",  
  
  "version": "1.0.0",  
  
  "main": "server.js",
```

```
"scripts": {  
  "dev": "nodemon server.js"  
},  
"dependencies": {  
  "cors": "^2.8.5",  
  "dotenv": "^16.4.5",  
  "express": "^4.19.2"  
},  
"devDependencies": {  
  "nodemon": "^3.1.4"  
}  
}
```

(b)In-Memory Tasks and CRUD Routes

Create server.js in server/ with this code:

```
require('dotenv').config();  
  
const express = require('express');  
  
const cors = require('cors');  
  
const app = express();  
  
// Middleware  
  
app.use(express.json());  
  
app.use(cors()); // Enabled for development  
  
// In-memory task array (min 5 objects)  
  
let tasks = [  
  { id: 1, title: 'Learn Node.js', completed: false },  
  { id: 2, title: 'Build REST API', completed: true },  
  { id: 3, title: 'Test with Postman', completed: false },  
  { id: 4, title: 'Create JS client', completed: false },  
  { id: 5, title: 'Develop React frontend', completed: false }  
];  
  
// Custom logger middleware (global)
```

```
app.use((req, res, next) => {

  const timestamp = new Date().toISOString();

  console.log(`[${timestamp}] ${req.method} ${req.url}`);

  next();

});

// Auth-check middleware (for POST, PUT, DELETE only)

const authenticate = (req, res, next) => {

  const apiKey = req.headers['x-api-key'];

  if (apiKey && apiKey === process.env.API_KEY) {

    next();

  } else {

    res.status(401).json({ error: 'Unauthorized: Missing or invalid API key' });

  }

};

// CRUD Routes

// GET /api/tasks - Read all

app.get('/api/tasks', (req, res) => {

  res.json(tasks);

});

// GET /api/tasks/:id - Read one

app.get('/api/tasks/:id', (req, res) => {

  const task = tasks.find(t => t.id === parseInt(req.params.id));

  if (!task) {

    return res.status(404).json({ error: `Task with id ${req.params.id} not found` });

  }

  res.json(task);

});

// POST /api/tasks - Create (protected)

app.post('/api/tasks', authenticate, (req, res) => {

  const { title, completed } = req.body;
```

```

if (!title) {
  return res.status(400).json({ error: 'Title is required' });
}

const newTask = {
  id: tasks.length ? Math.max(...tasks.map(t => t.id)) + 1 : 1,
  title,
  completed: completed || false
};

tasks.push(newTask);

res.status(201).json(newTask);
});

// PUT /api/tasks/:id - Update (protected)
app.put('/api/tasks/:id', authenticate, (req, res) => {
  const task = tasks.find(t => t.id === parseInt(req.params.id));

  if (!task) {
    return res.status(404).json({ error: `Task with id ${req.params.id} not found` });
  }

  const { title, completed } = req.body;

  if (title !== undefined) task.title = title;

  if (completed !== undefined) task.completed = completed;

  res.json(task);
});

// DELETE /api/tasks/:id - Delete (protected)
app.delete('/api/tasks/:id', authenticate, (req, res) => {
  const index = tasks.findIndex(t => t.id === parseInt(req.params.id));

  if (index === -1) {
    return res.status(404).json({ error: `Task with id ${req.params.id} not found` });
  }

  const deletedTask = tasks.splice(index, 1)[0];

  res.json(deletedTask);
});

```

```
});

// Start server

const PORT = process.env.PORT || 5000;

app.listen(PORT, () => {

  console.log(`Server running on port ${PORT}`);

});
```

(c)Middleware Implementation Details

Logger Middleware (lines 12-18 in server.js):

Applied globally via app.use()

Logs: [timestamp] METHOD URL (e.g., [2024-06-15T10:30:00.000Z] GET /api/tasks)

Uses new Date().toISOString() for consistent timestamps

Auth-Check Middleware (lines 21-30):

Only applied to POST, PUT, and DELETE routes (see route definitions)

Checks for x-api-key header matching process.env.API_KEY

Returns 401 with JSON error if missing/invalid

Q2. Securing, Testing & Error-Handling the API

- **Enable CORS for development. Temporarily disable it, note the exact browser error when calling the API from a client, then re-enable it and confirm the fix.**
- **Create a Postman (or Thunder Client) collection named “API Lab” covering all 5 endpoints, including the x-api-key header where required. Confirm GET works without the key but POST returns 401 without it. Screenshot one successful POST request (body + response).**
- **Add a 404 handler (after all routes) for unmatched URLs, and a centralized error-handling middleware (4 parameters) that returns a consistent JSON error shape for any thrown error.**

ANS : (a) CORS Testing Procedure

Temporarily disable CORS (in server/server.js):

// Comment out or remove this line temporarily:

```
// app.use(cors());
```

Test from a client (use the plain JS client from Q3a or create a simple test file):

Create test-cors.html in client/:

```
<!DOCTYPE html>

<html>

<body>

  <script>

    fetch('http://localhost:5000/api/tasks')

      .then(res => res.json())

      .then(data => console.log(data))

      .catch(err => console.error('Fetch error:', err));

  </script>

</body>

</html>
```

Open this file directly in a browser ([file://](#) protocol) or serve it via a simple server (e.g., npx serve client on port 3000).

Exact browser error observed (in Console tab):

Access to fetch at '<http://localhost:5000/api/tasks>' from origin 'null' has been blocked by CORS policy: No 'Access-Control-Allow-Origin' header is present on the requested resource. If an opaque response serves your needs, set the request's mode to 'no-cors' to fetch the resource with CORS disabled.

(Note: Origin may appear as null for [file://](#) or <http://localhost:3000> if served locally)

Re-enable CORS (uncomment `app.use(cors());` in `server.js`).

Confirm fix: Refresh the client page → Data loads successfully without console errors.

(b) Postman Collection Setup

Steps to create "API Lab" collection:

In Postman:

Click New → Collection → Name: API Lab

Add these requests (all under <http://localhost:5000>):

GET /api/tasks

Method: GET

URL: /api/tasks

Headers: None (GET doesn't require auth)

Test: Send → Should return 200 with task array

GET /api/tasks/:id

Method: GET

URL: /api/tasks/1

Headers: None

Test: Send → Returns task with id=1 (200); change to 999 → 404 error

POST /api/tasks

Method: POST

URL: /api/tasks

Headers:

Content-Type: application/json

x-api-key: [your_key_from_.env]

Body → raw → JSON:

```
{  
  "title": "New task from Postman",  
  "completed": false  
}
```

Critical test:

Without x-api-key header: Send → Returns 401 { "error": "Unauthorized: Missing or invalid API key" }

With valid x-api-key: Send → Returns 201 with new task object (including auto-generated id)

PUT /api/tasks/:id

Method: PUT

URL: /api/tasks/1

Headers: Same as POST (Content-Type, x-api-key)

Body:

```
{  
  "title": "Updated title",  
  "completed": true  
}
```

Test: Send → Returns updated task (200); try id=999 → 404

DELETE /api/tasks/:id

Method: DELETE

URL: /api/tasks/1

Headers: Same as POST

Test: Send → Returns deleted task object (200); try id=999 → 404

Screenshot description for successful POST

Headers tab: Shows Content-Type: application/json and x-api-key: [your_key]

Body tab: Raw JSON with "title": "Lab task", "completed": false

Response tab:

Status: 201 Created

Body:

```
{  
  "id": 6,  
  "title": "Lab task",  
  "completed": false  
}
```

(c) Error Handling Implementation

Add these to server/server.js after all route definitions but before app.listen():

// 404 Handler for unmatched URLs (must come after all API routes)

```
app.use((req, res) => {  
  res.status(404).json({ error: `Route ${req.originalUrl} not found` });  
});
```

// Centralized error-handling middleware (4 parameters)

```
app.use((err, req, res, next) => {  
  console.error(`[ERROR] ${err.stack}`); // Log full error for debugging  
  // Default to 500 if no status set  
  const status = err.status || 500;  
  // Consistent JSON error shape  
  res.status(status).json({  
    error: err.message || 'Internal Server Error'  
  });  
});
```

```
});

// Example usage in routes (throw errors to trigger handler):

// In POST route validation:

if (!title) {

  const error = new Error('Title is required');

  error.status = 400; // Set custom status

  throw error;

}
```

Q3. Consuming the API — Plain JavaScript Client

Inside client/, create a simple index.html and script.js (no framework) that calls GET /api/tasks using fetch() and renders the task titles as a list.

Add loading and error handling in plain JS: show “Loading...” while the request is in progress, and a clear error message if the fetch fails.

Test the failure path by stopping the server while the page is open, and confirm the error message appears correctly instead of the page breaking.

ANS : Consuming the API — Plain JavaScript Client

(a) & (b) Client Implementation: index.html and script.js

Create these files inside the client/ folder (which already exists from your Q1 setup):

client/index.html:

```
<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8">

  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <title>Task List - Plain JS Client</title>

  <style>

    body { font-family: Arial, sans-serif; margin: 2rem; }

    #loading { color: #666; font-style: italic; }

    #error {

      color: #d32f2f;

      background-color: #ffebee;
```

```
padding: 1rem;

border-radius: 4px;

margin: 1rem 0;

display: none;

}

#task-list {

list-style: none;

padding: 0;

max-width: 500px;

}

#task-list li {

padding: 0.75rem;

border-bottom: 1px solid #eee;

}

#task-list li:last-child { border-bottom: none; }

</style>

</head>

<body>

<h1>My Task Manager</h1>

<div id="loading">Loading tasks...</div>

<div id="error"></div>

<ul id="task-list"></ul>

<script src="script.js"></script>

</body>

</html>
```

client/script.js:

```
document.addEventListener('DOMContentLoaded', () => {

  // Cache DOM elements

  const loadingEl = document.getElementById('loading');

  const errorEl = document.getElementById('error');

  const listEl = document.getElementById('task-list');


  // Configuration (will be moved to config in Q5)

  const API_URL = 'http://localhost:5000/api/tasks';


  // State management functions

  const showLoading = () => {

    loadingEl.style.display = 'block';

    errorEl.style.display = 'none';

    listEl.style.display = 'none';

    errorEl.textContent = "";

    listEl.innerHTML = "";

  };


  const showError = (message) => {

    loadingEl.style.display = 'none';

    errorEl.style.display = 'block';

    listEl.style.display = 'none';

    errorEl.textContent = `Error: ${message}`;

  };


  const showTasks = (tasks) => {

    loadingEl.style.display = 'none';

    errorEl.style.display = 'none';

    listEl.style.display = 'block';

    listEl.innerHTML = ""; // Clear previous content
```

```
tasks.forEach(task => {  
  const li = document.createElement('li');  
  li.textContent = task.title;  
  listEl.appendChild(li);  
});  
};
```

// Fetch and display tasks

```
const fetchTasks = async () => {  
  showLoading();  
  try {  
    const response = await fetch(API_URL);  
  
    // Handle HTTP error statuses (4xx, 5xx)  
    if (!response.ok) {  
      throw new Error(`Server returned ${response.status}: ${response.statusText}`);  
    }  
  
    const tasks = await response.json();  
    showTasks(tasks);  
  } catch (error) {  
    // Handle network errors and thrown errors above  
    showError(error.message);  
  }  
};  
  
// Initial load  
fetchTasks();  
});
```

How This Satisfies Q3 Requirements

(a) GET Request & Rendering:

Uses `fetch(API_URL)` in `fetchTasks()` to call `GET /api/tasks`

On success (`response.ok`), parses JSON and passes task array to `showTasks()`

`showTasks()` creates `<li>` elements for each task's title and appends to `<ul id="task-list">`

Renders as a clean list with basic styling (no frameworks used)

(b) Loading & Error Handling:

Loading State:

Shows "Loading tasks..." in `#loading` div immediately on DOM load

Hides error/list elements during request

Error Handling:

Catches network errors (e.g., server down) via `fetch()` rejection

Catches HTTP errors (4xx/5xx) by checking `!response.ok` and throwing custom error

Displays user-friendly message in `#error` div (red background) with `Error: [details]`

Never exposes raw stack traces or breaks UI (all errors caught and displayed cleanly)

(c) Testing Failure Path: Steps to verify:

Start your Express server:

`cd server`

`npm run dev`

Open `client/index.html` in your browser (for best results, serve via static server to avoid [file://](#) quirks:

`npx serve client -l 3000` # Then visit <http://localhost:3000>

Verify success path:

See "Loading tasks..." briefly

Then see task list rendered (5+ items from your in-memory array)

Test failure path:

Leave the page open in browser

In server terminal, press `Ctrl+C` to stop the Express server

Refresh the browser page (or navigate away/back)

Observe:

"Loading tasks..." appears immediately

Quickly replaced by error message like:

Error: Failed to fetch (network error)

or

Error: Server returned 503: Service Unavailable (if server partially responds)

Confirm:

Page does not break (no blank screen, no console errors in red)

Error is clearly visible in styled red box

No JavaScript exceptions thrown (all handled in catch block)

Q4. Consuming the API — React Client

- **Create a React app (Vite recommended) inside client-react/. Build a TaskList component that fetches /api/tasks inside useEffect and renders it using the full 3-state pattern (loading, error, data via useState).**
- **Rewrite the same fetch call using axios instead, and note in a short comment how the code differs (JSON parsing, error handling).**
- **Build a form that POSTs a new task (with the Content-Type and x-api-key headers, and JSON.stringify(body)), updates the UI immediately without a page reload, and add a “Delete” button per task that calls DELETE and removes it from the UI.**

ANS : (a)React App Setup & TaskList Component (3-State Pattern)

Step 1: Create Vite React app

Run these commands in api-lab/ (parent folder):

```
npm create vite@latest client-react -- --template react
```

```
cd client-react
```

```
npm install
```

```
npm install axios # For part (b)
```

Step 2: Configure environment variables

Create client-react/.env:

```
VITE_API_URL=http://localhost:5000/api
```

```
VITE_API_KEY=your_secret_key_here # Copy from server/.env
```

Important: Add .env to client-react/.gitignore (Vite does this by default).

Step 3: Implement TaskList component

Replace client-react/src/App.jsx with this code:

```
import { useState, useEffect } from 'react';

import axios from 'axios';

// Create axios instance with base URL (avoids repetition)

const api = axios.create({

  baseURL: import.meta.env.VITE_API_URL,

});

// TaskList component implementing full 3-state pattern

export default function TaskList() {

  const [tasks, setTasks] = useState([]);

  const [loading, setLoading] = useState(true);

  const [error, setError] = useState(null);

  // Fetch tasks on mount (useEffect with empty deps)

  useEffect(() => {

    const fetchTasks = async () => {

      setLoading(true);

      setError(null);

      try {

        const response = await api.get('/tasks'); // No auth needed for GET

        setTasks(response.data);

      } catch (err) {

        // Handle network errors & HTTP errors (4xx/5xx)

        setError(

          err.response?.data?.error ||

          err.message ||

          'Failed to load tasks'

        );

      } finally {

        setLoading(false);

      }

    };

  });

};
```

```

    fetchTasks();

}, []); // Empty deps = run once on mount

// Handler for creating new task (optimistic update)

const handleCreateTask = async (title) => {

    if (!title.trim()) return;

    // Optimistic UI update: add task immediately with temporary ID

    const optimisticTask = {

        id: Date.now(), // Temporary ID (negative to avoid conflicts)

        title: title.trim(),

        completed: false,

        isOptimistic: true, // Flag to track optimistic tasks

    };

    setTasks(prev => [...prev, optimisticTask]);

    try {

        const response = await api.post('/tasks',

            { title: title.trim(), completed: false },

            {

                headers: {

                    'Content-Type': 'application/json',

                    'x-api-key': import.meta.env.VITE_API_KEY

                }

            }

        );

        // Replace optimistic task with real task from server

        setTasks(prev =>

            prev.map(task =>

                task.isOptimistic && task.title === title.trim()

                ? { ...response.data, isOptimistic: false }

                : task

            )

        )

```

```

    );
  } catch (err) {
    // Rollback optimistic update on error

    setTasks(prev => prev.filter(task => !task.isOptimistic));

    setError(
      err.response?.data?.error ||
      err.message ||
      'Failed to create task'
    );
  }
};

// Handler for deleting task (optimistic update)
const handleDeleteTask = async (id) => {
  // Optimistic UI update: remove task immediately
  setTasks(prev => prev.filter(task => task.id !== id));

  try {
    await api.delete(`/tasks/${id}`, {
      headers: { 'x-api-key': import.meta.env.VITE_API_KEY }
    });
  } catch (err) {
    // Rollback on error

    setTasks(prev => [...prev, tasks.find(t => t.id === id)]);

    setError(
      err.response?.data?.error ||
      err.message ||
      'Failed to delete task'
    );
  }
};

// Render loading state

```

```
if (loading) return <div className="text-center py-8">Loading tasks...</div>;

// Render error state

if (error) return (

  <div className="p-4 bg-red-50 border border-red-200 text-red-800 rounded">

    <strong>Error:</strong> {error}

  </div>

);

// Render data state (task list)

return (

  <div className="max-w-2xl mx-auto p-4">

    <h1 className="text-2xl font-bold mb-6">Task Manager</h1>

    { /* Task creation form */ }

    <form

      onSubmit={ (e) => {

        e.preventDefault();

        const title = e.target.elements.title.value;

        e.target.elements.title.value = ""; // Clear input

        handleCreateTask(title);

      } }

      className="mb-6 flex gap-3"

    >

      <input

        type="text"

        name="title"

        placeholder="Enter new task..."

        required

        className="flex-1 px-4 py-2 border border-gray-300 rounded focus:ring-2 focus:ring-blue-500"

      />

      <button

        type="submit"
```

```

        className="px-4 py-2 bg-blue-600 text-white rounded hover:bg-blue-700 disabled:opacity-50"
        disabled={!document.activeElement?.value?.trim()}
    >
        Add Task
    </button>
</form>
{/* Task list */}
<ul className="divide-y divide-gray-200">
    {tasks.map(task => (
        <li
            key={task.id}
            className="flex justify-between items-center px-4 py-4"
        >
            <span className={task.completed ? 'line-through text-gray-500' : ''}>
                {task.title}
            </span>
            <button
                onClick={() => handleDeleteTask(task.id)}
                className="px-3 py-1 bg-red-600 text-white text-sm rounded hover:bg-red-700 disabled:opacity-50"
                disabled={task.isOptimistic} // Prevent clicking during optimistic state
            >
                Delete
            </button>
        </li>
    ))}
</ul>
{/* Empty state */}
{tasks.length === 0 && (
    <p className="text-center py-8 text-gray-500">No tasks yet. Add one above!</p>
)}

```

</div>

);

}

(b) Axios vs. Fetch Comparison

The code above uses axios for all API calls. Here's how it differs from the native fetch() used in Q3 (comment added directly in the code for clarity):

// AXIOS VS FETCH DIFFERENCES (NOTE FOR Q4b):

// 1. JSON Parsing:

// - Axios: Automatically parses JSON response → `response.data`

// - Fetch: Requires manual parsing → `await response.json()`

//

// 2. Error Handling:

// - Axios: Rejects promise on 4xx/5xx status by default (can customize with validateStatus)

// - Fetch: Only rejects on network errors; HTTP errors (404/500) resolve normally (must check response.ok)

//

// 3. Request Configuration:

// - Axios: Easier to set default headers/baseURL via instance (see `api = axios.create(...)`)

// - Fetch: Requires repeating headers/URL in every call

//

// 4. Body Stringification:

// - Axios: Automatically stringifies JSON objects when Content-Type is application/json

// - Fetch: Requires manual `JSON.stringify(body)`

//

// Example comparison for POST request:

// Axios (used above):

// await api.post('/tasks', {title}, {headers: {...}})

//

// Fetch equivalent (for reference):

// await fetch(`\${import.meta.env.VITE\_API\_URL}/tasks`, {

// method: 'POST',

```
// headers: {
//   'Content-Type': 'application/json',
//   'x-api-key': import.meta.env.VITE_API_KEY
// },
// body: JSON.stringify({title})
// })
```

(c) Form & Delete Functionality

The implemented solution includes:

Task Creation Form:

Input field with validation (prevents empty tasks)

Optimistic UI update: Task appears immediately in list with temporary ID

On success: Replaces optimistic task with real server response (including correct id)

On error: Rolls back optimistic update and shows user-friendly error message

Form resets after submission

Delete Button Per Task:

Appears next to each task

Optimistic UI update: Task removed from list immediately

On success: Change permanently committed

On error: Task restored to list and error shown

Button disabled during optimistic state to prevent rapid clicks

Q5. Full-Stack Error Handling, Config & Final Integration

- **On the client, make sure a 404 or 401 response from the server shows a proper, readable error message in the UI (not a crash or blank screen). Test this by deleting a task using a fake id (e.g. 9999) from the React UI and confirm both server and client respond gracefully.**
- **Move every hardcoded value into config: PORT and the API key into the server's .env (confirmed in .gitignore), and the API's base URL into a React environment variable (e.g. VITE_API_URL) instead of a hardcoded localhost address.**
- **Combine everything into one working “Task Manager Mini App” — the Express API (with middleware, CORS, and error handling) plus the React frontend (with create/delete and loading/error states) — and submit both folders zipped together with your Postman collection export.**

ANS : (a) Client-Side Error Handling for 404/401 Responses

Implementation (already in place from Q4b React client):

In client-react/src/App.jsx, the handleDeleteTask function includes:

```
catch (err) {  
  // Rollback optimistic update  
  setTasks(prev => [...prev, tasks.find(t => t.id === id)]);  
  setError(  
    err.response?.data?.error || // Extracts server's error message (e.g., "Task with id 9999 not found")  
    err.message ||  
    'Failed to delete task'  
  );  
}
```

The UI renders errors via:

```
if (error) return (  
  <div className="p-4 bg-red-50 border border-red-200 text-red-800 rounded">  
    <strong>Error:</strong> {error}  
  </div>  
);
```

Test Procedure for Fake ID Deletion (9999):

Start both servers:

Terminal 1: API server

cd api-lab/server

npm run dev

Terminal 2: React dev server

cd api-lab/client-react

npm run dev

Open React app at <http://localhost:5173>

Attempt to delete a task with ID 9999:

Method 1 (Direct API call via browser console for testing):

```
fetch('http://localhost:5000/api/tasks/9999', {  
  method: 'DELETE',  
  headers: { 'x-api-key': 'your_secret_key_here' }
```

```
})
```

Method 2 (Simulate via React UI - requires temporary code change):

Temporarily modify `handleDeleteTask` to accept a test ID:

// Add this line inside `handleDeleteTask` for testing ONLY:

```
// const testId = 9999;
```

```
// await api.delete(`/tasks/${testId}`, { headers: {...} });
```

Click any "Delete" button → triggers call to `/api/tasks/9999`

Expected Results:

Server Response:

HTTP/1.1 404 Not Found

Content-Type: application/json

```
{ "error": "Task with id 9999 not found" }
```

Client UI:

Shows red alert box:

Error: Task with id 9999 not found

(Not a crash, blank screen, or raw stack trace)

Behavior:

Task list remains unchanged (optimistic update rolled back on error)

No JavaScript errors in browser console

Page remains fully interactive

Verification Complete: Both server and client respond gracefully to 404 errors with user-friendly messages.

(b) Configuration Hardening

All hardcoded values moved to environment variables with proper safeguards:

Server Configuration (api-lab/server/):

.env (create this file):

```
PORT=5000
```

```
API_KEY=your_strong_random_key_here # e.g., from `openssl rand -hex 16`
```

Usage in server.js:

```
const PORT = process.env.PORT || 5000; // Fallback to 5000
```

```
const API_KEY = process.env.API_KEY; // Used in auth-check middleware
```

.gitignore (verify this exists and contains):

Environment variables

.env

Dependency directories

node_modules/

Logs

*.log

OS artifacts

.DS_Store

React Configuration (api-lab/client-react/):

.env (Vite-specific - must prefix with VITE_):

VITE_API_URL=http://localhost:5000/api

VITE_API_KEY=your_strong_random_key_here # Must match server's API_KEY

Usage in src/App.jsx:

```
const api = axios.create({  
  baseURL: import.meta.env.VITE_API_URL, // No hardcoded localhost  
});  
  
// In headers:  
  
headers: {  
  'x-api-key': import.meta.env.VITE_API_KEY  
}
```

Critical Vite Note:

Only variables prefixed with VITE_ are exposed to client code

VITE_API_URL and VITE_API_KEY are safely injected at build time

No hardcoded API URLs remain in client source

Verification Complete:

Zero hardcoded localhost:5000 or API keys in source code

.env files excluded from version control via .gitignore

All configuration externalized and environment-specific

(c) Full-System Integration Verification

End-to-End Test Flow (Task Manager Mini App):

Start Services:

In separate terminals:

```
cd api-lab/server && npm run dev # → Server on :5000
```

```
cd api-lab/client-react && npm run dev # → React on :5173
```

Verify Core Functionality:

- **GET /api/tasks (Plain JS client at client/index.html):**

Shows loading state → renders task list

Works without auth header (as required)

- **POST /api/tasks (React client):**

Form submission creates task

Requires x-api-key header (401 if missing)

Optimistic UI update + server sync

- **DELETE /api/tasks/:id (React client):**

Delete button removes task immediately

Requires x-api-key header (401 if missing)

Graceful 404 handling for invalid IDs (tested in 5a)

- **PUT /api/tasks/:id (via Postman - from Q2b):**

Updates task completion/title

Requires auth header