

Comprehensive Analysis of Automated Glaucoma Screening using Retinal Imaging and Explainable Deep Neural Networks

1st P. Chandru

Department of MCA

School of Computer Applications
Dhanalakshmi Srinivasan University
Tiruchirappalli, India
chandru30112003@gmail.com

2nd R. Vishagar

Department of MCA

School of Computer Applications
Dhanalakshmi Srinivasan University
Tiruchirappalli, India
Vishagar.set@dsuniversity.ac.in

Abstract—Glaucoma is an insidious and progressive eye condition that finally end up causing blindness in the patient. Traditional methods of screening are conspicuous for their dependence on the judgment of a clinician, which possibly miss the finer early signs. With the evolution of AI, specifically deep learning, researchers now utilize retinal fundus and OCT images to construct more objective and accurate diagnostic apparatuses. This review seeks to introduce some of the recent approaches involving machine learning, deep neural network architectures like U-Net, ResNet, and DenseNet, and Explainable AI tools such as SHAP and Grad-CAM, to highlight the affected regions of the eye so that the decision-making of the AI becomes more explainable and trustworthy. Although various papers are demonstrating high accuracy and promising results, problems remain in terms of limited datasets, variability of image quality, and computational intensity. Nevertheless, these AI-based methods provide a glimmer of hope for the future of the faster, earlier, and more accessible detection of glaucoma, particularly in deprived areas where routine eye care accessible.

Keywords—computer-aided diagnosis, deep learning, glaucoma, image classification, image segmentation, machine learning, medical imaging, retinal fundus imaging.

I. INTRODUCTION

Glaucoma is one of the major causes of irreversible blindness; the disease causes optic nerve damage due to elevated intraocular pressure [1]. Contrary to several other eye diseases, the development of glaucoma remains silent for long periods, showing few, if any, symptoms at the early stages; hence detecting the disease in time is a major challenge. If left untreated, injury of the optic nerve (ON) is irreversible, causing progressive loss of vision [2]. The traditional methods of identifying ON injury, including tonometry, visual field testing, and clinical examination, rely heavily on clinicians' subjective judgment, which lead to variability in or missing early signs of disease [3]. The increasing prevalence of glaucoma among the elderly population necessitates the need for more objective and dependable screening devices. This has generated much interest in research in diagnosis through imaging, particularly using retinal fundus images as well as sophisticated computational tools.

Fundus imaging is a non-invasive and easily practicable means to visualize the optic nerve head; hence, it is an appropriate tool for glaucoma detection [4]. Further image processing techniques such as segmentation and feature extraction play a critical role in recognizing anatomical structures such as the optic disc and the optic cup, which are crucial indicators of glaucoma [5]. Examples of deep learning models that have successfully performed excellent

segmentation on these features include U-Net, ResNet, and DenseNet [6][7]. These models present early structural changes that indicate the phasing into glaucoma with the computation of the cup-to-disc ratio (CDR). Scores of machine learning algorithms such as Support Vector Machines (SVM), Random Forest, and Convolutional Neural Networks (CNNs) were also applied to fundoscopic image analysis to classify these images as glaucomatous or normal with a high degree of precision [8][9]. Reliance upon subjective evaluations will be made less, and such automated systems are expected to be part of real-time clinical workflows. Explainable AI tools are, in addition to improved accuracy, contributing toward enhancing the transparency of deep learning systems in computational medical imaging. SHAP and Grad-CAM enable the clinician to visualize what portions of the image aided the model's decision, lending trust toward and understanding of AI diagnosis. And yet, challenges will have to be resolved to finalize the systems, including other massive training datasets of diverse nature, various computational resource requirements, and different qualities of acquired images. With these challenges, however, the merger of image processing and deep learning gives a guarantee for the early, accurate, and scalable detection of glaucoma. Continuous improvement and validation of these technologies over various population strata will play a key role in model robustness for ultimate adoption in real-world clinical scenarios.

Thisara Shyamalee et al [1] developed a hybrid deep learning system was employed for optic nerve head segmentation. ResNet50 has been modified to segment the optic cup and disc in fundus images prior to classification using a customized Inception V3 model. The two-step approach consisted of segmentation first and then classification. In addition, five different datasets were merged to improve the performance. An interpretable AI feature shows important areas of the images used in decision making, enhancing the building trust. The system reaches great accuracy, sensitivity, and specificity in glaucoma detection. On the other hand, it required high-quality images with plenty of computing and has demonstrated different performance while going to the real-world situation because of training data limitations.

Sathvik Kanam et al [2] developed the proposed method combined machine learning and deep learning models. the models to detect glaucoma from retinal fundus images. It was developed to improve early detection and enhance diagnostic accuracy. the method used grayscale images were utilized for training three types of models: Random Forest was used for training on texture features, while ResNet50 and VGG-16 were used for training on image data. Four datasets, namely

REFUGE, ACRIMA, G1020, and ORIGA, were used. Advantages include early detection, robustness, and multiple technique integration. Limitations included dependency on image quality, limited image dataset varieties, high computation cost, and possible failure of generalizing to other real-world populations.

Md Mahmudul Hasan¹ et al [3] developed system was an explainable AI (XAI) for the analysis of OCT images for the diagnosis and staging of glaucoma. It aims to optimize clinical decision-making with more accuracy, transparency, and interpretability. In this method, SHAP was applied to rank the features globally, and partial dependency plots were utilized to define the decision cut-offs adopted in the machine learning. The input variables to the system were OCT data, although limited to a small number of subjects and a single machine. High accuracy was obtained with better consistency than human clinicians and some support for clinical usability, yet it requires more extensive validation.

Oleksandr Kovalyk-Borodyak et al [4] multi-model machine learning method has been devised for early glaucoma detection. It was proposed to incorporate retinal images with clinical data from both eyes to boost the diagnostic accuracy. Gradient-Boosted Decision Trees; Convolutional Neural Networks, SHAP, and Deep Explorer together provided interpretability of the model. The method employed PAPILA dataset with fundus images, clinical features, and expert segmentations of 244 patients (488 eyes). The method was limited to one dataset and would need extensive validation. The approach was implemented and showed promise for clinical use.

Satyabrata Lenka et al [5] developed the proposed method was a multi-task deep learning model that segments optic disc (OD), optic cup (OC) and also classifies glaucoma- the outcome-from the fundus images. The architecture takes care of complexity and generalization by sharing features across the tasks with a modified U-Net architecture. The model was trained for about 30 epochs on 1951 images obtained from three public datasets. It was highly benefitted with certain aspects like efficient multi-task learning, fewer parameters, and think for others involving other eye diseases. Now, the model was limited by the small dataset size, lack of image diversity, and no fully integrated explainable AI tools. The model was implemented but needs to improve optimization aspects.

Govindharaj et al [6] implemented methodology was a deep learning-based metric that compared the use of GANs, improved level-set algorithms, and fine-tuned MobileNetV2 for glaucoma identification. It was proposed to use fundus images by means of synthetic image generation using GANs for expanded and balanced datasets taking into account normal and abnormal cases for data balancing, improved quality, and enhanced classification accuracy. GA V-5271-BD is applied for image generation. Image classification is carried out using MobileNetV2. This technique provides quite high-quality images and accurate classifications, along with a balanced dataset, although it suffers from extremely high complexity, limited real-world variation coverage, and low interpretability.

Nahida Akter et al [7] The developed a new methodology was based on deep learning techniques to classify and stage glaucoma from PD plots derived from the respective visual field tests. The purpose was to enable automation of glaucoma

staging and to potentially enhance it. Pretrained ResNet18 and VGG16 models were trained on original, augmented, and feature-extracted PD images. Grad-CAM was used to visualize the areas of visual field loss. On the flip side, machine learning models were built based on global indices such as MD, PSD, and VFI to allow for comparisons. A total of 265 PD plots from 119 normal eyes and 146 glaucomatous eyes were included in the dataset. The performance was generally good, especially with ResNet18, but limitations in the study included a relatively small dataset size, an imbalance in the distribution of classes, and a limited variety of inputs.

Ramgopal Kashyap et al [8] deep learning method was proposed for using glaucoma diagnosis on retinal fundus images. Initial U-Net optic cup segmentation was followed by DenseNet-201 feature extraction and classification. The goal was to develop automated detection and improve the accuracy. The model was trained on a glaucoma data set, using less than 25% for test purposes. Thus, it was efficient in classifying the glaucomatous images and spotting the affected areas. Advantages include automated checking, higher accuracy, and its capability of diagnosing other diseases such as diabetic retinopathy and brain tumors. Limitations included the small size of the dataset, which severely restricted generalizability; hence, some optimization is needed for better reliability and more clinical applications.

Bindu Priya Makala et al. [9] The DnCNN-ML approach is used for the early detection, prediction, and classification of glaucoma through combined image-enhancement and machine learning. An optimized DnCNN denoising technique was used along with clinical data retinal fundus images from the PAPILA dataset, which included features such as central corneal thickness, axial eye length, and visual field defects. Statistical descriptors from the images were combined with GS-SVR to select the important features for the SVM-based classification. This combination of both clinical and image-based data yielded excellent prediction performance and further enhanced early detection. However, although the method had high accuracy and computational simplicity, it had the limitation of being based on a single database, which excluded other pertinent features such as homogeneity that would have had a much lower bearing on classification outcomes.

Vijaya Kumar Velpula et al [10] A proposed work introduced an explainable artificial intelligence (XAI) model to automate the process of glaucoma detection via retinal fundus images. It extracts deep image features using pre-trained convolutional neural networks (PCNNs), such as ResNet18 and ResNet50, before classifying them using SVM and KNN machine learning models. The model was trained on five public datasets: RIMONE-v2, ACRIMA, FTVD, Drishti-GS, and HVD, providing some diversity and robustness. By implementing XAI techniques, the system was able to give transparent and interpretable predictions that would add trust to its decision. Due to robust feature extraction, ample domains, and augmentation strategies, the method worked well on diverse datasets. Improvements need to be achieved in the future one way or another: enhanced CNN models, use of ensemble methods, and reduction of misclassification under all types of datasets for better accuracy.

Abramovich et al [11] The presented work introduced GONet, a deep learning model for the automatic diagnosis of glaucomatous optic neuropathy from digital fundus images (DFI). To attain good generalization, the model was trained on

a large and heterogeneous dataset comprising over 119,000 images of five sources under varying geographical conditions. Multisource domain training and fine-tuning also enhanced this model with a DINOv2 pretrained self-supervised vision transformer, thus enabling the model to generalize well across data from multiple sources. GONet performed excellently with AUC values between 0.85 and 0.99 across test domains, with an improvement of up to 21.6% compared to traditional cup-to-disc ratio techniques. The drawback is that there remains a question of how it works with unseen samples, which needs additional validation beyond such datasets.

Shalini. R et al [12] The proposed model, MCAU-Net, was a deep convolutional neural network that proposes accurate fovea and optic disc localization, using two skip connections, one Multiresolution Wavelet Pooling Module (MWPM), and spatial and channel attention mechanisms which serve to focus more on the interested image area for improvement in convergence. It is shown in testing on three public databases: DRISHTI-GS, DRIONS-DB, and IDRiD with results indicating steady performance, a high Intersection over Union score, and low Euclidean distances. The great number of advantages associated with this model such as it has a light architecture consisting of merely 0.8 million parameters making it efficient in computation as well as reducing overfitting. Use of wavelet transforms also improved the feature extraction for accurate localization. However, heterogeneity or unseen datasets will reduce the performance of the model, hence an opportunity for test validation. Future improvements were possible by including the use of OCT scans and providing wider application using clinical decision support systems in order to increase its applications in real life.

Yen-Ying Chiang et al [13] Developed a deep-learning model for detecting glaucoma in highly myopic individuals through fundus photography with an aim to facilitate its non-invasive and efficient diagnosis. ConvNet trained with convolutional block attention module enhanced feature extraction. Fundus images from one hospital with a total of 3,088 were classified into high myopia and high myopia plus. While no pathological myopes were included to keep the definition clear. The technique would benefit greatly in aspects like easy image acquisition and visual interpretability, as well as generalizability. It, however, had certain limitations, like the restricted ethnic diversity, exclusion of pathological myopia, and that the work did not include grading of severity for glaucoma or multimodal input which hampers clinical applicability.

Parmanand Sharma et al [14] This paper presented an artificial intelligence-aided glaucoma screening system combines six lightweight deep-learning models to detect early changes in fundus images. It was intended for low-cost portable screening by recognizing features such as hemorrhages, nerve fiber layer defects, and optic disc cupping. The multiple models for segmentation and classification used have achieved performance levels comparable with those of expert ophthalmologists. The training data came from public datasets, such as ODIRs, AIROGS, REFUGE, and chaksus, and private data from Tohoku university hospital. However, it suffered from other limitations such as sensitivity in the real world, reliance on image quality, a degree of restricted generalization due to private data, and lack of integration with other clinical diagnostics.

Daniel Milad, MD et al [15] the implemented of a code-free deep learning approach enabling clinicians, without any

programming skills, to build AI models for glaucoma detection. Model performance compared with systems designed by experts was the aim of the tool. Ophthalmology trainees ran a binary classification model on 101,442 labeled images from the AIROGS dataset in Google's Vertex AI, externally validating it on the REFUGE and GAMMA datasets. In contrast, major disadvantages were inability to access the official AIROGS test set in addition to limited metadata, dependence on previously encountered patient images, and cloud-based training, leading to privacy and institutional approval issues.

Xiaohong Chen et al [16] The study proposed deep learning model using ResNet-50 architecture, discriminate between highly myopia glaucoma from high myopia and primary open-angle glaucoma with normal controls. The use of this model was aimed at improving the ability to detect glaucoma in these subjects and where glaucomatous changes hidden behind alterations such as myopia. The model was tested on trainable color fundus images of 2,643 patients and evaluated using 10-fold cross-validation across various patient groups, using gradient-weighted class activation maps for interpretation. The dataset consisted of images for OAG, HM, HMG, and normal controls, allowing the model to learn from all possible conditions. The model solve glaucoma detection better than the ophthalmologists. However, its performance limited by the small number of myopic glaucoma cases, affecting its generalizability.

Sara Ejaz1 et al [17] The proposed work developed a hybridized CNN model for early detection of healthy fundus images, media haze, diabetic retinopathy, and optic disc cupping, and other eye diseases. Two different CNN blocks were used to extract features, which were fused using canonical correlation analysis for classifying. Finally, the fused features were classified with different ML algorithms and ensemble learning was the most effective. The model was trained and validated using RFMiD data containing fundus images for the eye diseases. Although the proposed methodology had advantages to classify, including relatively low computational complexity with the hybrid CNN and classical model, it had one drawback - it was based on a single dataset, so it would be unable to generalize on different datasets. While computational complexity was somewhat minimized, other issues remained in the district of implementing in real-time.

Abadh K. Chaurasia et al [18] The proposed method developed a DL-based computer vision system for glaucoma screening using fundus image. It fine-tuned one of twenty pre-trained models with a glaucomatous and healthy fundus image dataset of a university using fastai and PyTorch. The dataset included 18,468 images from 20 public datasets, 10,900 healthy and 7,568 glaucomatous images. Performance metrics, such as AUROC, sensitivity, specificity, and precision, were calculated during training and validation. External validation was conducted using the Drishti-GS dataset. The system was intended to assist ophthalmologists in diagnosing early glaucoma, improve health outcomes and sustainability. The slight performance loss on unseen data suggests the need for fine-tuning. A larger and more diverse dataset is also needed for greater reliability and broader clinical applications.

Md Najib Hasan et al [19] the proposed system was developed automated to be an ML-based system for diagnose diabetic eye disease. It combined two CNN models, VGG16

and XceptionNet, to classify diabetic eye conditions, from normal like cataract, glaucoma, and retinopathy. The new pre-processing method was introduced to enhance quality of fundus images, using CNNs with a transition block for independent output shape and additional layers to preserve key information before combining the images for further processing. The model was trained and tested on the IDRiD and HRF datasets and was found to be highly efficient. This system's major benefit was that it reduced the burden on ophthalmologists by automating the diagnosis. The limitation, however, is that this system does not presently translate directly into a real-world clinical scenario and needs further validation, integration, and optimization for practical applicability.

Sara Ejaz et al [17] the objective of the proposed method was to comp up with a DL-enabled system that would automatically classify eye diseases such as ODC, retinopathy, media haze, and healthy images. This was achieved by hybridizing a CNN, meaning that two standalones CNN blocks were developed, trained independently, and then fused into a single model using CCA for performance improvement. Evaluation friction modelling methods employed were gradient boosting, SVM, and random forest. Its limitations included its inability to generalize over fresh datasets and computational burdens of the fusion method.

II. DATASETS

Datasets are the collection of data, it is in the form of images, numbers and text. it provided data for training and assessing ML and DL models. Datasets used for many applications, such as classification, data processing, and data analytics. It gathered from online resources, human collection. as shown in Figure 1.

A. Retinal Medical Image – Ophthalmic Network Ensemble

The RMI-ONE dataset is used for glaucoma detection through the provision of a large set of retinal images that are processed using machine learning techniques. The steps include image collection and annotation for glaucoma presence or absence, pre-processing to improve quality and eliminate noise, and extraction of relevant features like optic disc cupping or retinal thickness from the images. Machine learning models, which are tests on an independent test set to determine their classification of glaucoma, are trained using these features. Researchers develop and validate glaucoma detection algorithms that are more successful in diagnosing and treating the condition using the RMI-ONE dataset. displayed as shown in Figure 2.




Fig. 1. Datasets representation of glaucoma detection




Fig. 2. The image shows RMI-ONE datasets

B. Automated Classification of Retinal Images

The ACRIMA dataset assembles the complete types of retinal images to train and test the hybrid glaucoma detection framework. This way, the models in glaucoma detection trained, and it also gives researchers the option of assessing the performance of both federated ML and DL models. The heterogeneous nature of the retinal images in the dataset ensures that the proposed framework is robust and generalizable, which makes it highly significant in glaucoma research. Shows as in Figure 3.




Fig. 3. Automated classification of retinal images

C. Retinal fundus glaucoma and DRISTI-GS

The REFUGE and DRISTI-GS datasets are important resources for developing and testing a glaucoma detection model. They both offer an entire set of retinal fundus images that used for training and testing the model. The REFUGE dataset provides a large set of images for glaucoma detection, whereas the DRISTI-GS datasets, offers extra images for vessel extraction as well as glaucoma screening. Shown as in Figure 4.




Fig. 4. A set of fundus images from the REFUGE dataset showing an optic disc and cup

D. Optimal Coherence Tomography

OCT imaging captures high-resolution representation of retinal structures including the optic disc and retinal nerve fiber tissue. Such images will supply information concerning

the morphology and thickness of retinal tissues, and this will be useful in diagnosing and staging glaucoma. It thus allows an early and timely intervention for improved patient outcomes. Shown as in Figure 5.




Fig. 5. Represented optical coherence tomography shows

E. Online retinal fundus image database for glaucoma analysis

The ORIGA is one of four public datasets used to build an extensive dataset for testing and training the proposed glaucoma detection architecture. It provides a wide variety of retinal fundus images, which are essential for effectively training DL models like VGG16 and ResNet50. As a part of ORIGA, to enhance the model's ability to accurately dataset signs of glaucoma. ORIGA's images are especially valuable for extraction texture information, including homogeneity, correlation, and dissimilarity, for the random forest classifier used in the architecture. The incorporation of ORIGA not only enhance the size and quality of the training data but also play a key role in developing a more reliable detection system. Finally, this supports the creation of a tool that helps ophthalmologists in making accurate diagnosis and early, potentially leading to better outcomes for patients at risk of glaucoma.

F. Retinal fundus image database

The RFMiD dataset is beneficial in assessing the proposed hybrid CNN model in terms of its effectiveness in retinal disease classification. It contains several eye disease types, each comprising over 100 fundus images, all taken from the RFMiD 15 and RFMiD 2.0. The dataset was transformed from its original multi-category detection format to a multi-class format to suit the model's requirements. Thus, this RFMiD database largely governs the ability of the model to process and generalize various retinal conditions towards an assessment of effectiveness or accuracy in classifying particular eye diseases. Shown as in Figure 6.




Fig. 6. Fundus images from the REFUGE and GAMMA datasets, showing normal cases (A, B) and referable glaucoma cases (C, D), respectively.

III. TAXONOMY

In this section, the taxonomy represents the ML and DL approaches, including various methods such as, Convolutional neural network, support vector machine, deep neural network, and k-nearest neighbour, as shown in Figure 7.




Fig. 7. Taxonomy representation of glaucoma detection

A. Machine Learning (ML)

Labeled datasets of eye images have been trained on machine learning (ML) algorithms to identify patterns associated with glaucoma the various techniques, such as support vector machine learning (SVM), random forest, and CNNs, include deep learning algorithms that extract retinal image and classify between glaucoma and healthy conditions, increasing diagnostic validity and achieving early.

1) *Support Vector Machine (SVM)*: The present classification of glaucoma using a support vector machine utilize a list of important features derived through a technique called grid search optimized support vector regression. Some of the statistical parameters such as pachymetry, axial length, and mean defect, among others. The SVM operation is approximately based on training 80% of the data and validating with the remaining 20% paved towards achieving a boundary as optimal as possible, overall to separate the different categories: healthy, glaucoma, and suspicious individuals. Thus, SVM allows for effective predictions in complex or high-dimensional data. Rich research techniques were utilized in applying the technique to retinal images and the clinical data, thus ensuring an adequate model for predicting and classifying the glaucoma.

2) *k-Nearest Neighbor*: The k nearest neighbors (KNN) algorithms is a typical example of a machine learning method applied to the task of identifying glaucoma. The ML method for the KNN algorithm illustrated is a cookie-cutter solution to the problem of glaucoma detection. One of the ways to do it is to feed the system pictures of the retina, the back part of the eye. Then, using pre-trained CNN models like ResNet18 and ResNet50, these images are used to bring out the relevant details in the image after which the central details are sent to the KNN algorithm for final classification of the images. Before anything else, the after gathering these details, the KNN places the image into one of three groups: normal, glaucoma, or doubtful. This process helps in identifying whether an eye has glaucoma, is normal, or needs further checking.

3) *Random Forest*: The random forest techniques, which relies on the textural features derived from retinal fundus photographs, plays a significant doubt in detecting glaucoma.

Textural properties, such as contrast, homogeneity, and correlation, are extracted using the gray-level co-occurrence matrix that describes the spatial relationship amongst pixels in the images. Random forest combines the results from the various decision trees to provide a final prediction. This method garners high trust in the model as well as prevents overfitting. It is particularly useful for processing complex visual data and identifying related patterns for glaucoma. Its ability to rank feature importance forms a vital axis of the glaucoma detection system, which also allows for greater interpretation.

B. Deep Learning (DL)

Neural networks are used in deep learning to glaucoma detection and automatically learn and extract features from retinal fundus images. In precisely dividing glaucomatous and healthy eyes, these models are trained to recognize patterns indicative of glaucoma, enabling early detection and timely intervention.

1) *Convolutional Neural Network (CNN)*: Convolutional neural network plays a crucial role in automated feature extraction from retinal fundus images. CNNs are designed to process visual data by learning hierarchical features from raw images. They first detect low-level patterns, such as edges and textures, and progressively identify more complex structures like the optic nerve head, cup-to-disc ratio, and retinal nerve fiber layer thinning, all of which are critical indicators of glaucoma. Consequently, CNNs release human effort in handily extracting features and ensure a robust, consistent, and efficient detection process in their evolution. Pretrained CNN models such as VGG16 or ResNet also can be fine-tuned with specific datasets, thus optimizing their performance while reducing the need for extensive labeled data. Following that, these extracted features could be used for classification purposes through ML classifiers, ultimately helping providing accurate diagnoses of glaucoma. Hence, CNNs vastly enhance the effectiveness of automated glaucoma

detection systems by identifying critical structural changes in retinal images.

2) *Graph Convolutional Network (GCN)*: Glaucoma detection benefits from GCN as the model gets a better appreciation of the eye's complex anatomy, particularly the OD and OC area. GCN functions on the principle of graph reasoning, making GCN a better tool for analyzing irregular and curved shapes in retinal images, as opposed to traditional methods which treat images as flat grids. The model's performance in identifying and segmenting those structures important for estimating the cup-to-disc ratio, which is one of the most important parameters for diagnosing glaucoma, is therefore significantly enhanced. GCN provides a move toward higher precision and reliability during the detection process despite all variations in image quality or structural appearance, thereby supporting early diagnosis and a more accurate diagnosis of glaucoma in clinical practice.

3) *Generative Adversarial Network (GAN)*: Generative Adversarial Networks (GANs), with their tremendous power and practical applicability, find addresses to one of the most challenging facets of medical imaging: having too few and unbalanced datasets. Transporting valuable sets of information to the collection and labeling of medical images is a slow and laborious task. This is where GANs are advantageous, creating synthetic fundus images that are highly realistic and greatly resemble real ones in bulk numbers. These synthetic images thus retain all vital features like OD, OC, and vessel structure, which are important in diagnosing for glaucoma. By offering that surface variation and balance in a dataset, GANs essentially help train deep learning models to learn patterns and distinctions between healthy and glaucomatous states with enhanced reliability and accuracy, even where true data is scarce. GANs turbocharge the performance of automated glaucoma screening tools and speed up accessibility for early diagnosis when paired with methods like Gaussian filtering to cleanse the inputs and efficient models like MobileNetV2. as shown in Figure 8.




Fig. 8. GAN proposed methods

4) *Deep Convolutional Neural Network (DCNN)*: Deep Convolutional Neural Networks (DCNN) are literally game-changers as far as glaucoma detection is concerned since they aid in automating identification and classification of glaucomatous conditions from retinal images. The diagnostic approach uses a model known as DenseNet-201, on which previously-training was performed in order to extract important image features. The analysis of the retinal images

goes on by layers and identifies key visible markers such as optic cup and disc, which are crucial aspects of glaucoma. When these features are extracted, the U-Net architecture is used to segment the image and isolate important areas for a closer look. By virtue of DenseNet-201, the model penetrates more into images without requiring an extensive computation power. Moreover, the model employs transfer learning, whereby knowledge from large datasets such as ImageNet

utilized such that training completed without relying too much on large, labeled glaucoma datasets. Anastomosing with the above is a highly accurate system of 98.82% training

accuracy and testing accuracy, which is a speedily reliable tool for the diagnosis of early glaucoma. as shown in Figure 9.




Fig. 9. Pretrained DenseNet-201 for feature mining and DCNN for categorizing retinal images.

5) *Denoising Convolutional Neural Network (DnCNN)*: Denoising convolutional neural networks the DnCNN playing a significant role in fundus image enhancement or improvement for glaucoma detection. Glaucoma fundus images nosy and hence often lose some key details that are required for diagnosing the disease. So, the denoising task of DnCNN has a convolutional neural network between a source image and destination image cleaning noise from it. Important extraction features such as CDR and RFNL thickness will be extracted from images cleaned for identifying glaucoma. Important image features such as this will be combined with clinical indices and parameters such as pachymetry and axial length into a better classifier for

improvement in accuracy. Cleaned and noise-free images allow the extraction of some important features such as the CDR and RFNL thickness parameters that are considered essential for glaucoma detection. These parameters, together with other clinical parameters such as pachymetry and axial length, will be fed into a classifier in order to improve the classification accuracy. This improvement will enhance the quality of the images and will aid in their integration with clinical data in order to provide greater help for the early and more accurate diagnosis of glaucoma which in turn leads to timely intervention to prevent irreversible blindness. as shown in Figure 10.




Fig. 10. DnCNN architecture.

IV. PROBLEM STATEMENT

- Glaucoma is a progressive eye disease that is usually asymptomatic, or without symptoms, and cause irreversible blindness if left untreated. Early detection is difficult because the disease tends to damage the eye without symptoms, creating a major obstacle to timely diagnosis.
- Conventional techniques for diagnosis, including tonometry, visual field tests, and clinical examination heavily depend on subjective clinical decisions which produce inconsistent results or, regretfully, ignore early signs. Although instrumental interpretation of both retinal fundus and OCT images is helpful, time-consuming, and it vary considerably based on the experience of the clinician.
- Models usually demand high computational resources, which restricts their implementation in low-resource or rural health settings. Another key barrier among clinicians for accepting the predictions is the

possibility that an AI failure unexplainable, thereby making it hard for an individual clinician to trust or act on the outcomes.

- The demand has become increasingly pressing for developing AI systems that are effective, understandable, and generally applicable to integration within actual clinical workflows. These systems are particularly meaningful for early detection and screening purposes, especially in remote or underserved areas where specialist eye care is often limited or non-existent.

V. DISCUSSIONS

Now a day's trends towards ophthalmology, diagnosing glaucoma is indeed a turning point. The deep learning models such as u-net, resnet, and densenet have performed an exceedingly good precision in segmenting optic structures and classifying glaucoma from fundus images as well as oct. But there are some challenges yet such as limited and imbalanced datasets, extensive computational requirements, and huge variability in the quality of images. Failure to generalize these

models on large populations has made these models not useful in real-life scenarios. Explainable ai tools like shap and grad-cam give transparency because it lets a clinician understand the model's decisions, which is vital for gaining confidence in it. However, further enhancement on robustness of models, diversity of data, and computational efficiency would be required to move toward adoption on a wider scale. Policies promoting open-access datasets, ethical AI development, and cheaper-as-well-as-wise deployments are necessary. The power of ai in the direction of early diagnosis, especially for neglected territories, would be immense, but serious and real-life practical, technical, and ethical worry would need to be addressed for the safe and sound incorporation of ai technologies in the clinical environment.

VI. CONCLUSION

Glaucoma is one of the major causes of irreversible blindness due to its silent progression and reliance on subjective clinical assessments for its early detection. The application of deep learning and artificial intelligence offers powerful tools to mitigate these obstacles, focusing on fundus and oct imaging to forge more accurate, objective, and scalable diagnostic systems. Great literature is available showcasing significant development in architectures like U-Net, ResNet, DenseNet, and hybrid models incorporating clinical data. The explainability tools, such as SHAP and Grad-CAM, would further contribute toward the transparency and trust in model predictions, which is an important path toward getting clinical acceptance for these tools. There still are limitations: dataset diversity, computational load, varying quality of images, and generalizability to populations. Future endeavors will address these aspects while providing robustness through model training, dataset normalization, and real-life application testing. Consequently, AI is set to become a game-changer in glaucoma screening in developing countries, allowing for timely diagnosis, intervention, and handling of patient outcomes.

REFERENCE

- [1] Shyamalee, T., Meedeniya, D., Lim, G. and Karunaratne, M., 2024. Automated tool support for glaucoma identification with explainability using fundus images. *IEEE Access*, 12, pp.17290-17307.
- [2] Kanam, S., Mazumder, D., Al-Asady, H.A.J. and Kumaraswamy, I., 2025, June. Comprehensive Analysis of Glaucoma Detection using Machine Learning and Deep Learning. In *2025 International Conference on Intelligent Computing and Knowledge Extraction (ICICKE)* (pp. 1-8). IEEE.
- [3] Hasan, M.M., Phu, J., Wang, H., Sowmya, A., Kalloniatis, M. and Meijering, E., 2025. OCT-based diagnosis of glaucoma and glaucoma stages using explainable machine learning. *Scientific Reports*, 15(1), p.3592.
- [4] Kovalyk-Borodyak, O., Morales-Sánchez, J., Verdú-Monedero, R. and Sancho-Gómez, J.L., 2025. Glaucoma detection: Binocular approach and clinical data in machine learning. *Artificial Intelligence in Medicine*, 160, p.103050.
- [5] Lenka, S., Mayaluri, Z.L. and Panda, G., 2025. Glaucoma detection from retinal fundus images using graph convolution based multi-task model. *e-Prime-Advances in Electrical Engineering, Electronics and Energy*, 11, p.100931.
- [6] Govindharaj, I., Santhakumar, D., Pugazharasi, K., Ravichandran, S., Prabhu, R.V. and Raja, J., 2025. Enhancing glaucoma diagnosis: Generative adversarial networks in synthesized imagery and classification with pretrained MobileNetV2. *MethodsX*, 14, p.103116.
- [7] Akter, N., Gordon, J., Li, S., Poon, M., Perry, S., Fletcher, J., Chan, T., White, A. and Roy, M., 2025. Glaucoma detection and staging from visual field images using machine learning techniques. *PloS one*, 20(1), p.e0316919.
- [8] Kashyap, R., Nair, R., Gangadharan, S.M.P., Botto-Tobar, M., Farooq, S. and Rizwan, A., 2022, December. Glaucoma detection and classification using improved U-Net Deep Learning Model. In *Healthcare* (Vol. 10, No. 12, p. 2497). MDPI.
- [9] Makala, B.P. and Kumar, D.M., 2025. An efficient glaucoma prediction and classification integrating retinal fundus images and clinical data using DnCNN with machine learning algorithms. *Results in Engineering*, 25, p.104220.
- [10] Velpula, V.K., Sharma, D., Sharma, L.D., Roy, A., Bhuyan, M.K., Alfarhood, S. and Safran, M., 2024. Glaucoma detection with explainable AI using convolutional neural networks based feature extraction and machine learning classifiers. *IET Image Processing*, 18(13), pp.3827-3853.
- [11] Abramovich, O., Pizem, H., Fhima, J., Berkowitz, E., Gofrit, B., Meisel, M., Baskin, M., Van Eijgen, J., Stalmans, I., Blumenthal, E.Z. and Behar, J.A., 2025. GONet: A Generalizable Deep Learning Model for Glaucoma Detection. *IEEE Transactions on Biomedical Engineering*.
- [12] Shalini, R. and Gopi, V.P., 2022. Deep learning approaches based improved light weight U-Net with attention module for optic disc segmentation. *Physical and Engineering Sciences in Medicine*, 45(4), pp.1111-1122.
- [13] Chiang, Y.Y., Chen, C.L. and Chen, Y.H., 2024. Deep learning evaluation of glaucoma detection using fundus photographs in highly myopic populations. *Biomedicine*, 12(7), p.1394.
- [14] Sharma, P., Takahashi, N., Ninomiya, T., Sato, M., Miya, T., Tsuda, S. and Nakazawa, T., 2025. A hybrid multi model artificial intelligence approach for glaucoma screening using fundus images. *npj Digital Medicine*, 8(1), p.130.
- [15] Milad, D., Antaki, F., Mikhail, D., Farah, A., El-Khoury, J., Touma, S., Durr, G.M., Nayman, T., Playout, C., Keane, P.A. and Duval, R., 2025. Code-free deep learning glaucoma detection on color fundus images. *Ophthalmology Science*, 5(4), p.100721.
- [16] Chen, X., Zhou, C., Zhu, Y., Luo, M., Hu, L., Han, W., Zuo, C., Li, Z., Xiao, H., Huang, S. and Chen, X., 2025. Detecting Glaucoma in Highly Myopic Eyes From Fundus Photographs Using Deep Convolutional Neural Networks. *Clinical & Experimental Ophthalmology*.
- [17] Ejaz, S., Zia, H.U., Majeed, F., Shafique, U., Altamiranda, S.C., Lipari, V. and Ashraf, I., 2025. Fundus image classification using feature concatenation for early diagnosis of retinal disease. *Digital Health*, 11, p.20552076251328120.
- [18] Chaurasia, A.K., Liu, G.S., Greatbatch, C.J., Gharahkhani, P., Craig, J.E., Mackey, D.A., MacGregor, S. and Hewitt, A.W., 2025. A generalised computer vision model for improved glaucoma screening using fundus images. *Eye*, 39(1), pp.109-117.
- [19] Md Najib Hasan a, Md Ehashan Rabbi Pial a, Sunanda Das a, Nazmul Siddique b, Hui Wang transfer learning with feature fusion network.