

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/392759109>

# Development of a Vision-Based Mobile Robot with Artificial Neural Networks (ANN) for Classification of Tomato Ripeness

Article in *Engineering Letters* · June 2025

CITATIONS

0

READS

90

7 authors, including:



**Lintang Patria Patria**

Indonesia Open University

18 PUBLICATIONS 27 CITATIONS

SEE PROFILE



**Mokhairi Makhtar**

Sultan Zainal Abidin University

77 PUBLICATIONS 787 CITATIONS

SEE PROFILE



**Aceng Sambas**

Independent Researcher

306 PUBLICATIONS 3,268 CITATIONS

SEE PROFILE



**Shahrizan Jamaludin**

University of Malaysia, Terengganu

46 PUBLICATIONS 460 CITATIONS

SEE PROFILE

# Development of a Vision-Based Mobile Robot with Artificial Neural Networks (ANN) for Classification of Tomato Ripeness

Lintang Patria, Mokhairi Makhtar, Aceng Sambas, Rizki Multajam, Ahmad Faisal Mohamad Ayob, Shahrizan Jamaludin, W S Mada Sanjaya, and Ong Yew Chuan

**Abstract**—This study presents the development of a vision-based mobile robot equipped with Artificial Neural Networks (ANN) to classify tomato ripeness in agricultural settings. The primary aim is to automate the process of monitoring and categorizing tomatoes into three ripeness levels—ripe, unripe, and partially ripe—thereby enhancing efficiency and accuracy in precision agriculture. The robot autonomously navigates farming areas, captures images of tomatoes using an ESP32-CAM module, and extracts visual features such as color and texture. An ANN model, trained on a labeled dataset of 1,000 tomato images with predefined ripeness categories, is employed for classification. Field tests were conducted under varying environmental conditions to validate the robot's navigation and classification capabilities. Results: The system achieved a classification accuracy of 94.5% based on RGB feature analysis. The ANN required 200 epochs for optimal training, with a validation loss reduction of 0.8% between epochs 180 and 200. Real-time classification processed images in 0.15 seconds per frame, demonstrating the system's efficiency. Additionally, the robot successfully navigated 95% of designated test plots without collisions or significant delays, achieving an average mapping speed of 0.8 m/s. The integration of robotics, computer vision, and ANN in this system provides a robust solution for automating fruit monitoring.

**Index Terms**—Smart Farming; ANN; Robotic; Vision system; RGB feature, Precision agriculture.

Manuscript received Oct 26, 2024; revised Mar 21, 2025.

This project was funded by the Universitas Terbuka with contract number B/571/UN31.LPPM/PT.01.03/2023

Lintang Patria is an Assistance Professor in the Department of Information, Universitas Terbuka, Tangerang Selatan 15437, Banten, Indonesia, (Corresponding author phone: +6282125421710; fax: 0217434691; e-mail: lintang@ecampus.ut.ac.id).

Mokhairi Makhtar is a Professor in the Faculty of Informatics and Computing, Universiti Sultan Zainal Abidin, Campus Besut, 22200, Terengganu, Malaysia and Artificial Intelligence for Sustainability and Islamic Research Center (AISIR), Universiti Sultan Zainal Abidin, Gongbadak 21300, Terengganu, Malaysia (e-mail: mokhairi@unisza.edu.my).

Aceng Sambas is an Assistance Professor in the Faculty of Informatics and Computing, Universiti Sultan Zainal Abidin, Campus Besut, 22200, Terengganu, Malaysia (e-mail: acengsambas@unisza.edu.my).

Rizki Multajam is a postgraduate student at the Faculty of Ocean Engineering Technology and Informatics, Universiti Malaysia Terengganu, Kuala Nerus, 21030, Malaysia (e-mail: r.multajam@gmail.com).

Ahmad Faisal Mohamad Ayob is an Associate Professor at the Faculty of Ocean Engineering Technology and Informatics, Universiti Malaysia Terengganu, Kuala Nerus, 21030, Malaysia (e-mail: ahmad.faisal@umt.edu.my).

Shahrizan bin Jamaludin is an Assistance Professor at the Faculty of Ocean Engineering and Technology, Universiti Malaysia Terengganu, Kuala Nerus, 21030, Malaysia (e-mail: shahrizan@umt.edu.my).

W. S. Mada Sanjaya is an Associate Professor at the Department of Physics, Faculty of Science and Technology, Universitas Islam Negeri Sunan Gunung Djati, Bandung, 40614, Indonesia (e-mail: madasws@gmail.com).

Ong Yew Chuan is an Assistance Professor in the Faculty of Informatics and Computing, Universiti Sultan Zainal Abidin, Campus Besut, 22200, Terengganu, Malaysia (e-mail: yewchuan@unisza.edu.my).

## I. INTRODUCTION

MODERN agriculture has witnessed significant advancements with the integration of automation and artificial intelligence technologies [1], [2]. Among the many challenges faced in fruit production, particularly in tomato cultivation, is the accurate determination of fruit ripeness [3], [4]. Ripeness not only affects the quality and taste of the produce but also its economic value. Currently, most ripeness monitoring and classification processes are performed manually, which are time-consuming, labor-intensive, and prone to human error. As the demand for precision agriculture grows, the need for an automated, efficient, and reliable system to classify fruit ripeness has become paramount [5], [6].

Research on fruit ripeness classification has become a major focus in the application of smart technology in the agricultural sector. Worasawate et al. [7] develop and evaluate machine learning (ML) classifiers to automate the classification of mango ripeness stages—unripe, ripe, and overripe—based on biochemical, physical, and electrical data. Elwirehardja and Prayoga [8] develop a mobile application for classifying the ripeness levels of oil palm fresh fruit bunches using lightweight CNN models based on the MobileNetV1 and EfficientNetB0. Castro et al. [9] evaluated the effectiveness of different ML techniques combined with various color spaces for classifying the ripeness levels of Cape gooseberry fruits and explored the impact of combining color spaces using PCA on model performance. Bazame et al. [10] implemented a computer vision algorithm for detecting and classifying coffee fruits and mapping their maturation stages during harvest. They provided precise spatial information by assigning geographic coordinates to each frame, enabling the mapping of detection summaries across coffee rows. Azarmdel et al. [11] developed a machine vision system combined with AI techniques for classifying mulberry fruit ripeness (unripe, ripe, and overripe) based on geometrical, color, and texture characteristics. They enhanced accuracy and efficiency in ripeness classification by applying feature reduction CFS-CONS and leveraging ANN-SVM as classification models for contributes to the automation of mulberry ripeness evaluation, enabling precise and efficient fruit grading for agricultural applications.

A key aspect of vision robots is their capability to interpret and process visual data [12]. Employing a precise vision system for real-time fruit classification and analysis is essential to ensure the robot's efficiency and cost-effectiveness [13]. Halstead et al. [14] developed a robotic vision system capable of accurately detecting, estimating ripeness, and tracking

sweet peppers (*Capsicum annuum* L) in unstructured farm environments. By integrating the FasterRCNN framework with a novel parallel layer for ripeness estimation, the system aims to improve classification accuracy and efficiency compared to traditional multiclass implementations. Altaheri et al. [15] proposed an efficient machine vision framework for harvesting robots to classify and analyze date fruits in real time, addressing the lack of research in machine vision systems for date fruits in orchard environments. Tapia-Mendez et al. [16] designed an intelligent system based on deep learning techniques to classify various types of fruits and vegetables and evaluate the ripeness level of selected classes by using MobileNet V2 architecture.

Recent developments in mobile robotics, vision-based systems, and ANN offer promising solutions to address this challenge [17]. Mobile robots, equipped with intelligent navigation and image-capturing systems, can autonomously survey agricultural fields, while ANN models process complex data to make precise classifications [18]. The integration of these technologies has shown potential in reducing labor dependency, improving classification accuracy, and streamlining workflows in agriculture [19]. Previous studies have successfully demonstrated the use of vision systems and ANN for ripeness classification in fruits like mango and mulberry. However, the adaptation of these methods for tomatoes, especially under real-world field conditions, remains an area requiring further exploration.

This paper presents the development of a vision-based mobile robot designed to classify tomato ripeness into three categories—ripe, unripe, and semi-ripe. The system employs an ESP32-CAM module for image acquisition and an ANN model trained on a labeled dataset of 1,000 tomato images. Through the fusion of robotics and ANN, the robot is capable of autonomous navigation, real-time image processing, and ripeness classification with a high degree of accuracy.

The main contribution and novelty of this paper are summarized as follows:

- 1) This work developed an autonomous mobile robot equipped with ANN to classify tomato ripeness, providing a practical solution to replace manual monitoring in agriculture.
- 2) Our work show the robust ANN-based classification system validated under real-world conditions, achieving 94.5% accuracy despite environmental challenges.
- 3) The system improves workflow efficiency by processing images in 0.15 seconds per frame and autonomously navigating fields at 0.8 m/s, reducing labor and operational costs.

This paper is organized as follows. Section 1 provides an introduction to the challenges of ripeness monitoring in agriculture and the need for automation using robotics and artificial intelligence. Section 2 describes the theoretical background, including key concepts of mobile robotics, wireless communication systems, camera-based vision systems, and ANN. Section 3 outlines the methodology, focusing on the design and development of the vision-based mobile robot, the experimental stages, and the training of the ANN model for tomato ripeness classification. Section 4 presents the results and discussion, highlighting the robot's navigation performance, classification accuracy, and real-time processing capabilities under varying environmental

conditions. Section 5 contains the conclusions of this study, emphasizing its contributions to precision agriculture and suggesting directions for future research to enhance system scalability and robustness.

## II. THEORETICAL BACKGROUND

### A. Mobile Robotics Technology in Agriculture

Mobile robotics technology has revolutionized agricultural practices by automating a wide range of tasks, including crop monitoring, harvesting, pesticide application, and field mapping [20]. These robots are equipped with advanced sensors, vision cameras, GPS-based navigation, and machine learning algorithms, enabling them to operate autonomously and efficiently in dynamic farm environments [21]. Mobile robots can perform precise operations, such as identifying fruit ripeness and picking crops, while minimizing human labor and ensuring consistent quality. For example, robots equipped with computer vision systems can detect the ripeness of fruits like tomatoes and strawberries in real time, allowing for timely harvesting. This level of precision not only enhances productivity but also reduces resource wastage by applying inputs such as water, fertilizers, and pesticides only where needed [22].

The adoption of mobile robotics in agriculture also provides significant environmental and economic benefits. By leveraging real-time data collected through sensors and vision systems, farmers can make informed decisions that optimize resource usage and reduce environmental impact [23]. Additionally, the automation of repetitive tasks lowers operational costs and addresses labor shortages, which are common challenges in the agricultural sector. Despite these advancements, challenges remain, such as adapting robotics to unstructured environments and developing cost-effective solutions for small-scale farmers. Ongoing research and innovation in mobile robotics technology, including improvements in machine learning algorithms and hardware efficiency, are key to overcoming these barriers and achieving widespread adoption in precision agriculture.

### B. Wireless Communication System

The advantage of wireless communication for a vision-based mobile robot utilizing ANN for tomato ripeness classification lies in its ability to enable real-time, remote data processing and decision-making without physical constraints. Wireless connectivity allows the robot to transmit captured images and classification results to a central server or cloud-based system, where more computationally intensive ANN models can run efficiently. This enhances processing speed, reduces onboard computational load, and enables seamless integration with other smart farming technologies. Additionally, wireless communication facilitates remote monitoring and control, allowing farmers to oversee operations and make timely interventions, ultimately improving efficiency, scalability, and adaptability in automated agricultural systems.

Wireless control systems utilizing the NRF24L01 incorporate essential components, including controllers, actuators, and wireless communication modules. Operating at a frequency of 2.4 GHz, the NRF24L01 facilitates dependable communication via the SPI protocol, enabling the controller to transmit control signals wirelessly to devices or robots.




Fig. 1. NRF24L01 Datasheet

One critical aspect of this system is communication delay, which can be represented mathematically as

$$T_{delay} = T_{transmit} + T_{Propagation} + T_{processing} \quad (1)$$

and data packet loss

$$P_{loss} = \frac{N_{lost}}{N_{total}} \times 100\% \quad (2)$$

which affect the reliability of signal transmission. The system often controls a differential drive robot, where the dynamics are described by

$$x = v \cos(\theta) \quad (3)$$

$$y = v \sin(\theta) \quad (4)$$

$$\theta = \frac{v_r - v_l}{L} \quad (5)$$

Where  $v_r$  and  $v_l$  are the speeds of the right and left wheels, and  $L$  is the distance between the wheels. Control inputs, such as linear speed  $v$  and rotational speed  $\omega$ , are transmitted wirelessly, and the wheel speeds are adjusted according to

$$v_r = v + \frac{\omega L}{2} \quad (6)$$

and

$$v_l = v - \frac{\omega L}{2} \quad (7)$$

A PID control algorithm is used to maintain stability and performance, with the control signal expressed as

$$u(t) = K_p e(t) + K_i \int e(t) dt + K_d \frac{de(t)}{dt} \quad (8)$$

Where  $e(t)$  is the error between the reference and actual values. However, delays and packet loss can degrade the performance of the PID controller, causing slower system response and instability. Proper PID tuning and delay compensation are crucial for achieving effective control in wireless systems that utilize the NRF24L01 module. In this design project, a controller unit is developed using the NRF24L01 wireless transceiver module and an Arduino Uno R3 to manage multiple pieces of equipment. Figure 1 illustrates the NRF24L01 module along with its datasheet.

### C. Camera-Based Vision System

Figure 2 demonstrates the functionality of a vision-based color detection system, which is a critical component in applications like fruit ripeness classification or robot navigation. The system works by detecting the color of objects in its field of view and calculating their distances from the camera. This capability is particularly useful for distinguishing objects based on color attributes and estimating their positions in real-time, which is essential for dynamic environments.




Fig. 2. Vision-based Color Detection

In agricultural settings, this system enables robots to classify fruits based on ripeness by analyzing color features such as hue and intensity. Similarly, it aids in robot navigation by identifying color-coded markers or objects, ensuring precise movement and task execution. The figure encapsulates the integration of digital imaging and computational algorithms to facilitate these practical and efficient operations.

### D. ESP32-CAM

The ESP32-CAM is a versatile, low-cost camera module that integrates an ESP32 microcontroller with a 2MP OV2640 image sensor, making it an ideal solution for embedded vision and IoT applications. This module is designed to capture high-quality images and videos while supporting Wi-Fi and Bluetooth connectivity, enabling real-time wireless data transmission. With its compact size and built-in features, the ESP32-CAM is well-suited for applications requiring efficient data processing and communication, such as security systems, home automation, and agricultural monitoring.

Figure 3 is equipped with a 2MP OV2640 camera sensor, capable of capturing images and video, and supports Wi-Fi and Bluetooth connectivity, enabling wireless data transmission.

In agricultural robotics, the ESP32-CAM is particularly advantageous due to its ability to process visual data locally. This module can be programmed to run machine learning models, such as ANNs, directly on the device, eliminating the need for external servers. For example, in a vision-based mobile robot, the ESP32-CAM can capture images of crops, analyze features like color and texture, and classify them into categories such as ripeness levels. Its ability to perform real-time image processing ensures quick responses to environmental changes, making it a reliable component in precision agriculture.

Additionally, the ESP32-CAM's low power consumption and small form factor make it an excellent choice for mobile applications where space and energy efficiency are critical. Despite its affordability, the module offers robust performance, supporting various resolutions and image processing capabilities. Its open-source development environment further enhances its flexibility, allowing developers to adapt it for diverse use cases. Whether used in robotics, smart farming, or IoT projects, the ESP32-CAM serves as a powerful tool for integrating vision-based technologies.



Fig. 3. ESP32-CAM Module

#### E. Artificial Neural Network (ANN)

The main advantage of ANN for the classification of tomato ripeness over other methods, such as traditional image processing, statistical classifiers, or rule-based approaches, lies in their ability to learn complex patterns and features from large datasets without requiring manual feature extraction. ANN models, particularly deep learning architectures like CNNs, can automatically recognize subtle color, texture, and shape variations associated with different ripeness stages, leading to higher accuracy and robustness under varying lighting and environmental conditions. Additionally, ANN models can generalize well to new datasets, enabling reliable and scalable classification, which is crucial for applications in precision agriculture and automated harvesting systems.

ANNs are computational models inspired by the human brain, designed to process complex patterns and relationships in data [24]. These networks consist of interconnected nodes, or neurons, organized into layers: input, hidden, and output layers. The input layer receives raw data, such as visual features like color and texture, while the hidden layers extract and process intricate patterns. The output layer then provides predictions or classifications, making ANNs highly effective for applications like image recognition, natural language




Fig. 4. Artificial Neural Network Architectures

processing, and predictive analytics [25]. Figure 4 show the architecture of an ANN with multiple hidden layers.

From Figure 4, the use of loss functions such as cross-entropy and backpropagation algorithms with optimizers like Stochastic Gradient Descent (SGD) or Adam accelerates weight updating processes and minimizes prediction errors. Each neuron receives several inputs. Several inputs  $x_1, x_2, \dots, x_n$  with each input having an associated weight  $w_1, w_2, \dots, w_n$ . The total input received by the neuron is computed as a linear combination of these inputs:

$$z = \sum_{i=1}^n w_i x_i + b \quad (9)$$

Where  $b$  is the bias, which shifts the activation function. After computing the input  $z$ , the result is passed through an activation function  $f(z)$ . Common activation functions include ReLU, Sigmoid, and Softmax:

ReLU (Rectified Linear Unit):

$$f(z) = \max(0, z) \quad (10)$$

Sigmoid:

$$f(z) = \frac{1}{1 + e^{-z}} \quad (11)$$

Softmax (used for multi-class classification):

$$f(z_i) = \frac{e^{z_i}}{\sum_{j=1}^k e^{z_j}} \quad (12)$$

where  $z_i$  is the input to class  $i$ , and  $k$  is the number of classes. After calculating the activation function, the neuron produces the output  $y$  as:

$$y = f(z) \quad (13)$$

The weights are updated during training using the gradient rule, a process known as backpropagation. The weight updates are based on the derivative of the error function  $E$  with respect to the weight  $z_i$ :

$$w_i \leftarrow w_i - \eta \frac{\delta E}{\delta w_i} \quad (14)$$

By using these mathematical equations, ANN learns by adjusting the weights  $w$  until the error  $E$  is minimized. These computations form the foundation for understanding the underlying structure and operations of the ANN architecture, as

depicted in Figure 4 below, which illustrates the architecture of an ANN utilizing multiple hidden layers.

In the context of agricultural robotics, ANNs are invaluable for tasks like fruit ripeness classification. By analyzing RGB color data captured by vision systems such as the ESP32-CAM, ANNs can categorize fruits into predefined ripeness levels—unripe, semi-ripe, and ripe. This process involves training the ANN on labeled datasets containing features specific to each ripeness stage. Using techniques like backpropagation, the network adjusts its weights and biases to minimize errors, achieving high accuracy in classification. Once trained, the ANN processes new data in real-time, enabling robots to perform tasks like sorting or selective harvesting efficiently [26].

The adaptability and scalability of ANNs make them ideal for diverse agricultural applications. They can be tailored to handle various crops and environmental conditions by incorporating additional features like shape, size, and texture into the training process. Advanced techniques, such as dropout and early stopping, help prevent overfitting, ensuring robust performance even with noisy or limited data. As a core component of intelligent systems, ANNs facilitate automation, reduce dependency on manual labor, and enhance precision, ultimately contributing to improved productivity and sustainability in agriculture [27].

### III. METHODOLOGY

#### A. Experimental Framework

The experimental framework for this study is designed to develop and evaluate a vision-based mobile robot system equipped with ANN for classifying tomato ripeness. The project involves multiple stages, beginning with identifying the problem and objectives, designing the robotic system, implementing the software and algorithms, and conducting field tests to validate the system's performance. The primary goal is to automate the classification of tomato ripeness into three categories: ripe, unripe, and semi-ripe, thereby improving efficiency in agricultural workflows.




Fig. 5. System of Vision-based Mobile Robot for Classification of Tomato Ripeness

The framework starts with the preparation and integration of the robot's hardware and software components. Figure 5 illustrates the overall system architecture, where a transmitter acts as the control center, managing the robot

through wireless communication. The robot, equipped with an ESP32-CAM, autonomously navigates agricultural areas, capturing images of tomatoes. These images are processed using RGB color analysis to extract visual features critical for ripeness classification. The processed data is then transmitted wirelessly to a computer for ANN-based classification and result display.

The experimental stages involve training the ANN model with a labeled dataset comprising 1,000 images of tomatoes. The training process includes feature extraction from images, ANN model optimization, and performance evaluation using metrics like accuracy and validation loss. The ANN model is fine-tuned to ensure high accuracy in classifying ripeness levels despite variations in lighting and environmental conditions. The methodology is designed to allow the robot to perform real-time classification with minimal latency, achieving practical application in precision agriculture.




Fig. 6. General System of Vision-based Mobile Robots

Field tests were conducted to evaluate the robot's navigation and classification capabilities in real-world environments. These tests included operating the robot in varying terrain types and under diverse lighting conditions to assess its robustness and adaptability. As shown in Figure 6, the system flowchart outlines the detailed experimental stages, from hardware setup and data acquisition to classification and result validation. The tests aimed to measure key performance indicators, such as navigation accuracy, classification

speed, and overall system reliability.

This structured approach ensures that the experimental framework is comprehensive and results-oriented, focusing on both technical and practical aspects of deploying the mobile robot in agricultural settings. By leveraging robotics, computer vision, and ANN technologies, the study demonstrates a scalable and efficient solution for automating ripeness monitoring and classification, addressing a critical need in modern precision agriculture.

### B. Hardware Components and Setup

The hardware components and setup for the vision-based mobile robot are integral to achieving efficient navigation and tomato ripeness classification. The system consists of a transmitter unit for remote control and a receiver unit on the mobile robot, both designed to ensure seamless communication and functionality. These components are carefully integrated to support real-time data acquisition, processing, and communication, enabling the robot to operate autonomously in agricultural fields.

The transmitter system, as detailed in Table I, includes an Arduino Nano microcontroller, a 2-axis joystick module for directional control, an NRF24L01 wireless communication module, and a 7V LiPo battery for power. The joystick generates control signals for movement along the X and Y axes, such as forward, backward, and turning directions. These signals are transmitted wirelessly to the receiver system via the NRF24L01 module, which operates at a frequency of 2.4 GHz. The lightweight design and reliable power supply ensure the transmitter is portable and efficient.

TABLE I. Transmitter System

| No | Name of Componen       | Function                                     |
|----|------------------------|----------------------------------------------|
| 1  | Arduino Nano           | versatile microcontroller platform           |
| 2  | Module Joystick 2 axis | Control the movement and direction of robots |
| 3  | NRF24L01               | wireless communication                       |
| 4  | Battery Li-Po 7V       | Power Supply                                 |

The receiver system, outlined in Table II, is mounted on the mobile robot and includes multiple components for control, navigation, and data processing. Central to this system are the Arduino Mega and Arduino Uno microcontrollers, which handle complex tasks such as sensor data processing and motor control. An additional NRF24L01 module receives signals from the transmitter, enabling precise execution of control commands. The system is powered by an 11V LiPo battery for electronics and a 12V accumulator for high-power components like motors.

The robot is equipped with an ESP32-CAM module, which serves as a visual sensor to capture real-time images of tomatoes. This compact camera module integrates seamlessly with the Arduino microcontrollers and communicates wirelessly with a computer for data processing. Its ability to capture high-resolution images, coupled with its low power consumption, makes it ideal for mobile applications in precision agriculture. The ESP32-CAM also supports local processing, enabling the robot to perform initial feature extraction tasks before sending data for ANN-based classification.

Figure 7 depicts the design of a differential drive robot, including key components essential for its operation. The

TABLE II. Receiver System

| No | Name of Componen       | Function                                          |
|----|------------------------|---------------------------------------------------|
| 1  | Arduino Mega           | Microcontroller for Mobile Robot                  |
| 2  | Arduino UNO            | Microcontroller for movement Servo at ESP32-CAM   |
| 3  | NRF24L01               | wireless communication                            |
| 4  | Battery Li-Po 11V      | Power Supply Arduino                              |
| 5  | Accumulator 12V        | Power Supply Mobile Robot                         |
| 6  | ESP32-CAM              | Wireless camera realtime                          |
| 7  | Module Relay 8 Channel | Robot wheel gearbox controller                    |
| 8  | Metal plat             | Body of mobile robots                             |
| 9  | LCD 16x2               | Display function                                  |
| 10 | DC Motor 12V           | Mobile actuator                                   |
| 11 | Gearbox Ratio 20:80    | for robot speed and torque                        |
| 12 | Wheel (D28xL10)        | Controlling the direction of the robot's movement |




Fig. 7. Mechanical design of agriculture mobile robots

robot has two wheels, each connected to a motor, allowing independent control of wheel speeds for movement and turning. The motors are powered by a battery and controlled through a motor driver, which acts as an interface between the motors and the microcontroller. The microcontroller serves as the brain of the system, processing sensor inputs and sending control signals to the motor driver for navigation. The robot's structure is enclosed within a casing to protect the internal components, ensuring durability and operational stability.

Figure 8 illustrates a motor control system designed for a mobile robot, integrating motor driver controllers, a microcontroller unit (MCU), and a power supply. At the center, the MCU serves as the brain of the system, managing inputs from the UART camera and sending control signals to the motor driver controllers. The motor driver controllers receive commands from the MCU and translate them into the required power levels for the motors, enabling precise control over movement. Each motor driver unit handles a pair of motors (left and right), and the system is symmetric, allowing balanced operation for forward, backward, and turning movements.

The power supply for the system is distributed through a battery module, providing 5V at 1A for the MCU and 5V at 2A for the motors. This ensures that both the processing unit and the motors have adequate and stable power for optimal performance. The diagram also highlights the modular nature of the design, making it easier to troubleshoot, expand, or adapt to specific needs, such as integrating additional




Fig. 8. Motor control system mobile robot

sensors or refining the control algorithms. The use of UART communication allows seamless integration of the camera for real-time image processing and decision-making.

Mechanically, the robot is built on a sturdy metal frame designed to withstand field operations. The frame provides structural support for components such as the 8-channel relay module, motors, and wheels. The DC motors, controlled via the relay module, enable smooth movement across various terrains, while the wheels (D28xL10) offer stability and adaptability. A gearbox with a 20:80 ratio ensures the robot achieves the optimal balance between speed and torque, critical for navigating crop rows.

To facilitate monitoring, the robot includes a 16x2 LCD display that provides real-time feedback on system status and sensor readings. This display is especially useful for debugging and ensuring the robot operates as intended during field tests. The entire system is powered efficiently to ensure uninterrupted operation, with energy distribution optimized between the transmitter and receiver components.




Fig. 9. Design of Agriculture Mobile Robots

Figure 9 illustrates the complete design of the mobile robot, showcasing the arrangement of hardware components, including the ESP32-CAM, control modules, power supplies, and actuators. This setup is compact yet robust, measuring

50 cm in height, 56 cm in length, and 47 cm in width, with a total weight of approximately 20 kg. This compact design allows the robot to navigate between crop rows while maintaining stability and efficiency during operation.



Fig. 10. Receiver System Tools kit

Figure 10 illustrates the receiver system toolkit integrated into the mobile robot. It highlights the arrangement of key components, including the Arduino Mega and Arduino Uno microcontrollers, which serve as the core controllers for sensor data processing and movement coordination. The NRF24L01 module, shown within the setup, facilitates wireless communication with the transmitter, ensuring reliable control. The ESP32-CAM module is also visible, capturing real-time images for ripeness classification. Additionally, the figure showcases the 8-channel relay module responsible for managing motor operations and the power supply system, which includes an 11V LiPo battery and a 12V accumulator for efficient energy distribution. The compact yet robust design of the receiver system ensures stable and precise performance, enabling the mobile robot to function effectively in agricultural environments.

This comprehensive hardware setup ensures the mobile robot is well-equipped to perform its intended tasks, from navigating agricultural fields to capturing and processing data for ripeness classification. By integrating reliable communication systems, robust power supplies, and precision hardware, the system demonstrates the potential for scalability and adaptation to other agricultural applications.

### C. Software Implementation and Algorithms

In this section, we develop a vision-based mobile robot equipped with ANN for tomato ripeness classification. This innovative solution integrates robotics, computer vision, and machine learning to enhance precision agriculture. A key feature is the ESP32-CAM module, which captures real-time images and processes them for ripeness classification using RGB color analysis. The ANN model is trained with a dataset of 1,000 tomato images, enabling accurate classification of tomatoes into ripe, unripe, and semi-ripe categories.

The software's algorithmic backbone includes several critical steps. The RGB features extracted from the images are analyzed to determine ripeness. The ANN, structured with multiple hidden layers, uses backpropagation and activation functions like ReLU to optimize its learning process. The integration of these methods achieves a classification accuracy of 94.5% under diverse environmental conditions, ensuring robust performance in real-world agricultural settings.

Figure 11 in the article visually illustrates the three ripeness stages: (a) ripe, with a deep red hue; (b) unripe,



Fig. 11. The three ripeness stages

characterized by green color; and (c) semi-ripe, marked by yellow or orange tones. This differentiation demonstrates the algorithm's ability to categorize tomatoes based on color and texture effectively. Such visual representation highlights the ANN's precision in handling RGB data for ripeness classification.

The implementation of this software provides a significant leap in agricultural automation. By enabling real-time classification and seamless integration with mobile robotics, the system reduces labor dependency and operational costs. This technological advancement not only simplifies the ripeness monitoring process but also contributes to improving crop quality and overall efficiency in modern farming practices.

#### IV. RESULTS AND DISCUSSION

##### A. Robot Navigation Performance

The mobile robot's navigation performance was evaluated under diverse environmental conditions to assess its adaptability and efficiency in agricultural fields. The system leveraged a combination of NRF24L01 wireless communication, Arduino microcontrollers, and robust hardware integration to ensure precise movement and control.

The robot successfully navigated 95% of the designated test plots without collisions or significant delays. Its average mapping speed was recorded at 0.8 m/s, demonstrating its capability to traverse typical agricultural terrains efficiently. On flat surfaces, the robot maintained consistent performance with minimal deviations. However, on rugged terrains, minor navigation errors were observed, resulting in a 5% decrease in overall precision. These deviations were attributed to uneven ground, which occasionally affected wheel traction and stability.

Testing in various lighting conditions further highlighted the system's robustness. The robot's sensors and vision-based navigation system remained effective despite changes in light intensity, ensuring uninterrupted operation during daylight hours. The wireless control system, employing the NRF24L01 module, provided reliable communication within a range of 50 meters in open fields. However, slight signal delays (averaging 0.3 seconds) were noted in obstructed areas, suggesting potential areas for improvement in future designs.

Figure 12 illustrates the robot's testing in outdoor environments, showcasing its ability to navigate rough terrains while maintaining stability. The image captures the robot's integration of real-time visual feedback and remote control capabilities, underscoring its functionality in practical agricultural applications.



Fig. 12. Outdoor Testing of Mobile Robots

##### B. Data for Tomato Ripeness Classification Based on RGB Color

The classification of tomato ripeness in this study relied on RGB color data, which was meticulously analyzed to determine the ripeness levels of tomatoes. This approach uses the red (R), green (G), and blue (B) components of color detected from the tomato's surface to differentiate between ripe, unripe, and semi-ripe tomatoes. By assigning specific RGB ranges to each ripeness stage, the system was able to process visual data effectively and provide accurate classifications.

TABLE III. Training data for ripe Tomatoes

| No | R  | G  | B  | Target      |
|----|----|----|----|-------------|
| 1  | 14 | 1  | 76 | Ripe Tomato |
| 2  | 19 | 0  | 76 | Ripe Tomato |
| 3  | 19 | 0  | 76 | Ripe Tomato |
| 4  | 20 | 1  | 77 | Ripe Tomato |
| 5  | 29 | 3  | 80 | Ripe Tomato |
| 6  | 28 | 10 | 85 | Ripe Tomato |
| 7  | 35 | 11 | 81 | Ripe Tomato |
| 8  | 35 | 11 | 81 | Ripe Tomato |
| 9  | 35 | 11 | 81 | Ripe Tomato |
| 10 | 35 | 11 | 81 | Ripe Tomato |
| 11 | 35 | 11 | 81 | Ripe Tomato |
| 12 | 35 | 11 | 81 | Ripe Tomato |
| 13 | 35 | 13 | 76 | Ripe Tomato |
| 14 | 35 | 11 | 81 | Ripe Tomato |
| 15 | 43 | 21 | 84 | Ripe Tomato |
| 16 | 38 | 14 | 84 | Ripe Tomato |
| 17 | 28 | 12 | 81 | Ripe Tomato |
| 18 | 24 | 10 | 85 | Ripe Tomato |
| 19 | 23 | 8  | 87 | Ripe Tomato |
| 20 | 25 | 4  | 85 | Ripe Tomato |

Table III details the RGB values for ripe tomatoes, characterized by high red values and significantly lower green and blue components. For example, ripe tomatoes had R values ranging from 14 to 43, G values from 1 to 21, and B values from 76 to 87. These values highlight the dominance of red hues in fully mature tomatoes, making them easily distinguishable from other ripeness stages. The consistent RGB patterns across the dataset ensured reliable training data for the ANN.

In contrast, Table IV provides the RGB values for unripe tomatoes, which exhibited a predominant green color. The R values for unripe tomatoes ranged between 56 and 63, while the G values were significantly higher, ranging from 103 to 110. The B values varied from 90 to 95. These distinct characteristics allowed the ANN to recognize the green dominance and classify these tomatoes as unripe with high

TABLE IV. Training Data for Unripe Tomatoes

| No | R  | G   | B  | Target        |
|----|----|-----|----|---------------|
| 1  | 61 | 107 | 92 | Unripe Tomato |
| 2  | 56 | 109 | 94 | Unripe Tomato |
| 3  | 61 | 107 | 92 | Unripe Tomato |
| 4  | 62 | 108 | 94 | Unripe Tomato |
| 5  | 61 | 107 | 92 | Unripe Tomato |
| 6  | 61 | 107 | 92 | Unripe Tomato |
| 7  | 62 | 108 | 94 | Unripe Tomato |
| 8  | 56 | 109 | 94 | Unripe Tomato |
| 9  | 56 | 109 | 94 | Unripe Tomato |
| 10 | 60 | 106 | 91 | Unripe Tomato |
| 11 | 62 | 110 | 90 | Unripe Tomato |
| 12 | 63 | 109 | 95 | Unripe Tomato |
| 13 | 62 | 108 | 94 | Unripe Tomato |
| 14 | 59 | 104 | 90 | Unripe Tomato |
| 15 | 58 | 103 | 89 | Unripe Tomato |
| 17 | 60 | 106 | 91 | Unripe Tomato |
| 18 | 59 | 104 | 90 | Unripe Tomato |
| 19 | 62 | 110 | 90 | Unripe Tomato |
| 20 | 59 | 104 | 90 | Unripe Tomato |

accuracy. The consistency of green values across samples demonstrated the effectiveness of this data for machine learning.

TABLE V. Training Data for Semi-ripe Tomatoes

| No | R  | G  | B  | Target           |
|----|----|----|----|------------------|
| 1  | 34 | 66 | 78 | Semi-ripe tomato |
| 2  | 30 | 69 | 74 | Semi-ripe tomato |
| 3  | 31 | 66 | 71 | Semi-ripe tomato |
| 4  | 21 | 53 | 66 | Semi-ripe tomato |
| 5  | 28 | 60 | 73 | Semi-ripe tomato |
| 6  | 28 | 60 | 73 | Semi-ripe tomato |
| 7  | 28 | 60 | 73 | Semi-ripe tomato |
| 8  | 26 | 57 | 70 | Semi-ripe tomato |
| 9  | 28 | 62 | 68 | Semi-ripe tomato |
| 10 | 29 | 63 | 69 | Semi-ripe tomato |
| 11 | 20 | 59 | 70 | Semi-ripe tomato |
| 12 | 20 | 59 | 70 | Semi-ripe tomato |
| 13 | 22 | 58 | 70 | Semi-ripe tomato |
| 14 | 27 | 61 | 67 | Semi-ripe tomato |
| 15 | 26 | 57 | 70 | Semi-ripe tomato |
| 16 | 28 | 60 | 73 | Semi-ripe tomato |
| 17 | 29 | 61 | 74 | Semi-ripe tomato |
| 18 | 26 | 57 | 70 | Semi-ripe tomato |
| 19 | 28 | 60 | 73 | Semi-ripe tomato |
| 20 | 26 | 57 | 70 | Semi-ripe tomato |

Table V presents the RGB values for semi-ripe tomatoes, which represented a transitional stage between unripe and ripe. These tomatoes displayed a mix of red and green hues, with R values ranging from 20 to 34, G values from 53 to 69, and B values from 66 to 78. The overlap of RGB ranges with both ripe and unripe categories posed a challenge for the ANN, requiring careful training to ensure accurate classification. This stage's intermediate characteristics were critical for the ANN to differentiate between fully ripe and still-developing tomatoes.

The RGB data from Tables III, IV, and V were used to train the ANN model, which processed this information to identify and classify ripeness levels. By learning the unique RGB patterns of each category, the ANN achieved a classification accuracy of 94.5%. This high performance underscores the importance of well-defined and consistent training data in machine learning applications. The use of distinct RGB thresholds for each ripeness level was pivotal in enabling the system to make precise distinctions.

### C. The Results of the Tomato Ripeness System Testing

The testing of the tomato ripeness classification system demonstrated its effectiveness in accurately identifying the three ripeness stages—ripe, unripe, and semi-ripe—based on RGB color analysis. The system, integrated into a vision-based mobile robot, utilized an ESP32-CAM to capture real-time images, which were processed and classified by an Artificial Neural Network (ANN). With a classification accuracy of 94.5%, the results validated the ANN's capability to distinguish between ripeness levels using predefined RGB thresholds. These findings underscore the reliability of the RGB-based approach in agricultural applications, particularly for automating sorting and monitoring tasks.

Field testing was conducted to evaluate the system's performance in varying environmental conditions, such as changes in lighting and terrain. The robot's ability to capture and process images in real-time ensured seamless operation, with each frame processed in an average of 0.15 seconds. Figure 13 highlights the testing process, showcasing the mobile robot capturing images of tomatoes and transmitting classification results to a control center. This setup allowed users to monitor ripeness levels remotely, enhancing the system's practicality for large-scale agricultural operations.

Despite its success, the system encountered minor challenges, particularly in low-light conditions where classification accuracy slightly decreased. Adjustments to preprocessing methods, such as image enhancement techniques, could further improve performance. Nonetheless, the combination of robotics, image processing, and ANN in this system offers a scalable and efficient solution for modern precision agriculture. The results demonstrate the potential of integrating advanced technologies to automate critical processes, ultimately reducing labor costs and increasing productivity.

## V. CONCLUSION

This study demonstrated the successful integration of robotics, computer vision, and Artificial Neural Networks (ANN) to classify tomato ripeness into three distinct stages: ripe, unripe, and semi-ripe. The developed vision-based mobile robot achieved an overall classification accuracy of 94.5%, with ripe tomatoes exhibiting the highest accuracy at 98%, followed by unripe (92%) and semi-ripe (89%). The system processed images in an average of 0.15 seconds per frame, highlighting its efficiency in real-time applications. The robot autonomously navigated 95% of test plots without collisions, achieving an average speed of 0.8 m/s. These results underscore the system's potential to enhance agricultural productivity by reducing labor dependency and increasing precision.

Quantitatively, the ANN's performance was validated through the analysis of training and validation losses, which showed a consistent reduction during training. Between epochs 180 and 200, the validation loss decreased by 0.8%, demonstrating the model's ability to generalize well to unseen data. Additionally, the robot's navigation success rate was calculated as the ratio of successfully navigated plots to the total plots tested. With 95 successful plots out of 100, the success rate was 95%, reaffirming the reliability of the navigation system. In classification tasks, the precision, recall, and F1 scores for each ripeness stage further validated




Fig. 13. Result System Testing

the ANN's robustness, with an average F1 score of 0.93 across all categories.

The findings of this research highlight the transformative potential of integrating ANN and robotics in precision agriculture. By automating the ripeness classification process, the system not only improves efficiency but also ensures consistent quality in agricultural output. Future work could focus on enhancing the system's adaptability to diverse environmental conditions, such as varying lighting or crop types, and optimizing energy consumption for prolonged field operations. The scalable design of this solution paves the way for its application across various crops, making it a valuable tool for modernizing farming practices.

#### REFERENCES

- [1] Shafi U, Mumtaz R, García-Nieto J, Hassan S A, Zaidi S A R, and Iqbal N, "Precision agriculture techniques and practices: From considerations to applications." *Sensors*, vol. 19, no. 17, art. id. 3796, 2019.
- [2] Akkem Y, Biswas S K, and Varanasi A, "Smart farming using artificial intelligence: A review." *Engineering Applications of Artificial Intelligence*, vol. 120, art. id. 105899, 2023.
- [3] Aishwarya N, Praveena N G, Priyanka S, and Pramod J, "Smart farming for detection and identification of tomato plant diseases using light weight deep neural network." *Multimedia Tools and Applications*, vol. 82, no. 12, pp. 18799-18810, 2023.
- [4] Kim J, Ha I D, Kwon S, Jang I, and Na M H, "A smart farm DNN survival model considering tomato farm effect." *Agriculture*, vol. 13, no. 9, art. id. 1782, 2023.
- [5] Agurob M C, Bano A J, Paradelo I, Clar S, Aleluya E R, and Salaan C J, "Autonomous Vision-based Unmanned Aerial Spray System with Variable Flow for Agricultural Application." *IAENG International Journal of Computer Science*, vol. 50, no. 3, pp. 1058-1073, 2023.
- [6] Kganyago M, Adjorlolo C, Mhangara P, and Tsoeleng L, "Optical remote sensing of crop biophysical and biochemical parameters: An overview of advances in sensor technologies and machine learning algorithms for precision agriculture." *Computers and Electronics in Agriculture*, vol. 218, art. id. 108730, 2024.
- [7] Worasawate D, Sakunasinha P, and Chiangga, S., "Automatic classification of the ripeness stage of mango fruit using a machine learning approach." *Archives of Control Sciences*, vol. 4, no. 1, pp. 32-47, 2022.
- [8] Elwirehardja G N and Prayoga J S, "Oil palm fresh fruit bunch ripeness classification on mobile devices using deep learning approaches." *Computers and Electronics in Agriculture*, vol. 188, art. id. 106359, 2021.
- [9] Castro W, Oblitas J, De-La-Torre M, Cotrina C, Bazán K, and Avila-George H, "Classification of cape gooseberry fruit according to its level of ripeness using machine learning techniques and different color spaces." *IEEE Access*, vol. 7, pp. 27389-27400, 2019.
- [10] Bazame H C, Molin J P, Althoff D and Martello M. , "Detection, classification, and mapping of coffee fruits during harvest with computer vision." *Computers and Electronics in Agriculture*, vol. 183, art. id. 106066, 2021.
- [11] Azarmdel H, Jahanbakhshi A, Mohtasebi S S, and Muñoz A R, "Evaluation of image processing technique as an expert system in mulberry fruit grading based on ripeness level using artificial neural networks (ANNs) and support vector machine (SVM)." *Postharvest Biology and Technology*, vol. 166, art. id. 111201, 2020.
- [12] Rizzo M, Marcuzzo M, Zangari A, Gasparetto A and Albarelli A, "Fruit ripeness classification: A survey." *Artificial Intelligence in Agriculture*, vol. 7, pp. 44-57, 2023.
- [13] Hou G, Chen H, Jiang M, and Niu R, "An Overview of the Application of Machine Vision in Recognition and Localization of Fruit and Vegetable Harvesting Robots." *Agriculture*, vol. 13, no. 9, art. id. 1814, 2023.
- [14] Halstead M, McCool C, Denman S, Perez T and Fookes C, "Fruit quantity and ripeness estimation using a robotic vision system." *IEEE robotics and automation Letters*, vol. 3, no. 4, pp. 2995-3002, 2018.
- [15] Altaheri H, Alsulaiman M and Muhammad G, "Date fruit classification for robotic harvesting in a natural environment using deep learning." *IEEE Access*, vol. 7, pp. 117115-117133, 2019.
- [16] Tapia-Mendez E, Cruz-Albarran I A, Tovar-Arriaga S, and Morales-Hernandez L A, "Deep learning-based method for classification and ripeness assessment of fruits and vegetables." *Applied Sciences*, vol. 13, no. 22, art. id. 12504, 2023.
- [17] Azadnia R, Fouladi S, and Jahanbakhshi A, "Intelligent detection and waste control of hawthorn fruit based on ripening level using machine vision system and deep learning techniques." *Results in Engineering*, vol. 17, art. id. 100891, 2023.
- [18] Zhang L, Jia J, Gui G, Hao X, Gao W and Wang M., "Deep learning based improved classification system for designing tomato harvesting robot." *IEEE Access*, vol. 6, pp. 67940-67950, 2018.
- [19] Ashtiani S H M, Javanmardi S, Jahanbanifard M, Martynenko A, and Verbeek F J, "Detection of mulberry ripeness stages using deep learning models." *IEEE Access*, vol. 9, pp. 100380-100394, 2021.
- [20] Patria L, Sambas A, Sulaiman I M, Mohamed M A, Rusyn V, and Samila, A. , "Weed detection on carrots using convolutional neural network and internet of thing based smartphone." *Informatyka, Automatyka, Pomiary w Gospodarce i Ochronie Środowiska*, vol. 14, no. 3, pp. 96-100, 2024.
- [21] Cho S, Kim T, Jung D H, Park S H, Na Y, Ihn Y S, and Kim K, "Plant growth information measurement based on object detection and image fusion using a smart farm robot." *Computers and electronics in agriculture*, vol. 207, art. id. 107703, 2023.
- [22] Ren J, "A Reliable Night Vision Image De-Noising Based on

- Optimized ACO-ICA Algorithm.” IAENG International Journal of Computer Science, vol. 51, no. 3, pp. 169-177, 2024.
- [23] Mohamed E S, Belal A A, Abd-Elmabod S K, El-Shirbeny M A, Gad A, and Zahran M B, “Smart farming for improving agricultural management.” The Egyptian Journal of Remote Sensing and Space Science, vol. 24, no. 3, pp. 971-981, 2021.
  - [24] Sambas A, Zhang X, Moghrabi I A, Vaidyanathan S, Benkouider K, Alçın M, and Johansyah M D, “ANN-based chaotic PRNG in the novel jerk chaotic system and its application for the image encryption via 2-D Hilbert curve.” Scientific Reports, vol. 14, no. 1, art. id. 29602, 2024.
  - [25] Aljebory K M, Yashar M J, and Mohammed T S, “Classification of EMG Signals: Using DWT Features and ANN Classifier.” IAENG International Journal of Computer Science, vol. 51, no. 1, pp. 23-31, 2024.
  - [26] Yang X, Bist R B, Paneru B, Liu T, Applegate T, Ritz C, and Chai L, “Computer vision-based cybernetics systems for promoting modern poultry farming: a critical review.” Computers and Electronics in Agriculture, vol. 225, art. id. 109339, 2024.
  - [27] Pal A, Leite A C and From P J, “A novel end-to-end vision-based architecture for agricultural human–robot collaboration in fruit picking operations.” Robotics and Autonomous Systems, vol. 172, art. id. 104567, 2024.



**Lintang Patria** is currently a Lecturer at Universitas Terbuka, Indonesia’s Open University. He has contributed to diverse research areas, including the application of Convolutional Neural Networks (CNN) for agricultural automation, edge detection using image processing techniques, and the evaluation of LoRa technology for autonomous vehicles. He also explores innovative methodologies in open and distance learning, enhancing student engagement and educational services. His research interests encompass artificial intelligence, image processing, IoT applications, and educational technologies.



**Mokhairi Makhtar** completed his Ph.D. in 2012 at the University of Bradford in the United Kingdom. Presently, he holds the position of Professor in the Department of Computer Science at Universiti Sultan Zainal Abidin, located in Terengganu, Malaysia. His research interests encompass various areas, including Machine Learning, Ensemble Methods, Data Mining, Soft Computing, Timetabling and Optimization, Natural Language Processing, E-Learning, and Deep Learning.



**Aceng Sambas** received the Doctor of Philosophy (Ph.D.) degree in mathematics from Universiti Sultan Zainal Abidin (UniSZA), Malaysia, in 2020. He has been a Lecturer with UniSZA and Universitas Muhammadiyah Tasikmalaya (UM-TAS), Indonesia. His current research interests include chaotic signals, nonlinear dynamical systems, control systems, electrical engineering, circuits, robotics, signal processing, embedded systems, and artificial intelligence (AI).



**Rizki Multajam** received his Bachelor’s degree in Physics in 2016 from the State Islamic University of Sunan Gunung Djati Bandung, Indonesia. In 2023, he pursued a Master’s degree in Mechanical Engineering specializing in Maritime Engineering and Technology at Universiti Malaysia Terengganu, Malaysia. His current research focus includes instrumentation physics, robotics, control systems, automation systems, mechatronics, signal processing, computer vision, underwater vehicles, artificial intelligence, and machine learning.



**Ahmad Faisal Mohamad Ayob** is an Associate Professor in Maritime Technology at the Universiti Malaysia Terengganu, obtained his Ph.D. in Mechanical Engineering from the University of New South Wales @ Australian Defence Force Academy in 2011. His focus area is hull performance design, specifically high-speed boat. Other than hull design, Dr. Faisal is also focusing on software-hardware development, specifically ship simulators with the marine engineering and marine industry. He has published technical manuscripts

in journals, conference and chapter in books. Subject taught by Dr. Faisal are Engineering Dynamics and Marine Engineering Design. He served as an Executive Committee member for IEEE-Ocean.



**Shahrizan bin Jamaludin** is a senior lecturer in the Maritime Technology and Naval Architecture program, Faculty of Ocean Engineering Technology, Universiti Malaysia Terengganu, Malaysia. In this role, he is responsible for the development of computer vision and image processing algorithm for marine structures maintenance. He brings 16 years’ experience as project engineer and research officer to the role. He is a graduate of the Electronic and Computer Engineering program from Universiti Teknikal Malaysia Melaka and Universiti Kebangsaan Malaysia.

His research interests include image processing, computer vision, pattern recognition, computer engineering, electronics, automation, robotic and remote sensing of marine applications, among others..



**W S Mada Sanjaya** received his Ph.D in Mathematics from the University Malaysia Terengganu, Malaysia in 2012. He was first appointed as a Lecturer at the UIN Sunan Gunung Djati Bandung, Indonesia in 2009. His research interests include nonlinear dynamical systems, chaotic systems, artificial intelligence, soft computing and robotic systems.



**Ong Yew Chuan** is currently a Lecturer at Universiti Sultan Zainal Abidin, Terengganu, Malaysia. He received his Ph.D. in Computer Science from the University of Sheffield in 2022. His current research focuses on machine learning, natural language processing, social computing, and social cybersecurity. He also leads a research project on hate speech detection. Yew Chuan is a member of the Institute of Electrical and Electronics Engineers (IEEE) and the International Association of Engineers (IAENG). He has also served as a

reviewer for various conferences, including I2CACIS 2023 and SCDM 2024.