










6.2.1 Current, potential difference and resistance

6.2.1.1 Standard circuit diagram symbols

Content	Key opportunities for skills development
Circuit diagrams use standard symbols.  switch (open)  lamp  switch (closed)  fuse  cell  voltmeter  battery  ammeter  diode  thermistor  resistor  variable resistor  LDR  LED Students should be able to draw and interpret circuit diagrams.	WS 1.2

6.2.1.2 Electrical charge and current

Content	Key opportunities for skills development
For electrical charge to flow through a closed circuit the circuit must include a source of potential difference.	

Content	Key opportunities for skills development
Electric current is a flow of electrical charge. The size of the electric current is the rate of flow of electrical charge. Charge flow, current and time are linked by the equation: <i>charge flow = current × time</i> $[Q = I t]$ charge flow, Q, in coulombs, C current, I, in amperes, A (amp is acceptable for ampere) time, t, in seconds, s A current has the same value at any point in a single closed loop.	MS 3b, c Students should be able to recall and apply this equation.

6.2.1.3 Current, resistance and potential difference

Content	Key opportunities for skills development
The current (I) through a component depends on both the resistance (R) of the component and the potential difference (V) across the component. The greater the resistance of the component the smaller the current for a given potential difference (pd) across the component. Questions will be set using the term potential difference. Students will gain credit for the correct use of either potential difference or voltage.	
Current, potential difference or resistance can be calculated using the equation: <i>potential difference = current × resistance</i> $[V = I R]$ potential difference, V, in volts, V current, I, in amperes, A (amp is acceptable for ampere) resistance, R, in ohms, Ω	MS 3b, c Students should be able to recall and apply this equation.




Required practical activity 15: use circuit diagrams to set up and check appropriate circuits to investigate the factors affecting the resistance of electrical circuits. This should include:

- the length of a wire at constant temperature
- combinations of resistors in series and parallel.

AT skills covered by this practical activity: physics AT 1, 6 and 7.

This practical activity also provides opportunities to develop WS and MS. Details of all skills are given in [Key opportunities for skills development](#) (page 185).

6.2.1.4 Resistors

Content	Key opportunities for skills development
Students should be able to explain that, for some resistors, the value of R remains constant but that in others it can change as the current changes. The current through an ohmic conductor (at a constant temperature) is directly proportional to the potential difference across the resistor. This means that the resistance remains constant as the current changes.  The resistance of components such as lamps, diodes, thermistors and LDRs is not constant; it changes with the current through the component. The resistance of a filament lamp increases as the temperature of the filament increases.  The current through a diode flows in one direction only. The diode has a very high resistance in the reverse direction. 	

Content	Key opportunities for skills development
The resistance of a thermistor decreases as the temperature increases. The applications of thermistors in circuits eg a thermostat is required. The resistance of an LDR decreases as light intensity increases.	
The application of LDRs in circuits eg switching lights on when it gets dark is required. Students should be able to:	WS 1.2, 1.4
- explain the design and use of a circuit to measure the resistance of a component by measuring the current through, and potential difference across, the component - draw an appropriate circuit diagram using correct circuit symbols.	AT 6 Investigate the relationship between the resistance of a thermistor and temperature. Investigate the relationship between the resistance of an LDR and light intensity.
Students should be able to use graphs to explore whether circuit elements are linear or non-linear and relate the curves produced to their function and properties.	WS 1.2, 1.4 MS 4c, 4d, 4e

Required practical activity 16: use circuit diagrams to construct appropriate circuits to investigate the I–V characteristics of a variety of circuit elements, including a filament lamp, a diode and a resistor at constant temperature.

AT skills covered by this practical activity: physics AT 6 and 7.

This practical activity also provides opportunities to develop WS and MS. Details of all skills are given in [Key opportunities for skills development](#) (page 186).