

Ficha sintética D01, sin certificación

Sistemas

system_code = FICHA-D01; name = Sistema de prueba 60; system_family = CASEMENT; material = PVC; depth_mm = 60.00; chamber_count = 5; sash_overlap_mm = 8.00; glass_clearance_white_mm = 3.00; glass_clearance_foil_mm = 5.00; corner_bracket_loss_mm = 0.00; hook_depth_mm = 0.00; door_threshold_mm = 30.00; door_bottom_clearance_mm = 20.00; door_leaf_side_clearance_mm = 7.00; rebate_depth_mm = 15.00; end_milling_overlap_mm = 4.00; finishes = ["WHITE", "FOILED"]; version = 1; is_active = True

Perfiles

system_code = FICHA-D01; sku = DEMO_60-MARCO; name = PVC practicable 60 mm · MARCO; role = FRAME; material = PVC; face_width_mm = 60.00; commercial_length_mm = 6000.00; weight_kg_m = 1.1535; steel_weight_kg_m = 1.7000

Roles y reglas de corte

system_code = FICHA-D01; sku = DEMO_60-MARCO; role = FRAME; angle_degrees = 45; welding_loss_per_end_mm = 3.00; joint_deduction_per_end_mm = 0.00; meeting_deduction_mm = 0.00; cut_step_mm = 0.01; rounding = UP

Refuerzos

system_code = FICHA-D01; sku = DEMO_60-MARCO; reinforcement_sku = DEMO_60-ACERO-MARCO; reinforcement_type = Acero galvanizado DEMO; minimum_length_mm = 1000.00; required_finishes = ["FOILED", "DARK"]; required_non_white = True; cut_deduction_mm = 30.00; screws_per_m = 4.0000; screw_sku = DEMO_60-TORNILLO-REF; screw_weight_kg = 0.003000

Perfiles

system_code = FICHA-D01; sku = DEMO_60-HOJA; name = PVC practicable 60 mm · HOJA; role = SASH; material = PVC; face_width_mm = 75.00; commercial_length_mm = 6000.00; weight_kg_m = 1.3550; steel_weight_kg_m = 1.7000

Roles y reglas de corte

system_code = FICHA-D01; sku = DEMO_60-HOJA; role = SASH; angle_degrees = 45; welding_loss_per_end_mm = 3.00; joint_deduction_per_end_mm = 0.00; meeting_deduction_mm = 0.00; cut_step_mm = 0.01; rounding = UP

Refuerzos

system_code = FICHA-D01; sku = DEMO_60-HOJA; reinforcement_sku = DEMO_60-ACERO-HOJA; reinforcement_type = Acero galvanizado DEMO; minimum_length_mm = 1000.00; required_finishes = ["FOILED", "DARK"]; required_non_white = True; cut_deduction_mm = 30.00; screws_per_m = 4.0000; screw_sku = DEMO_60-TORNILLO-REF; screw_weight_kg = 0.003000

Perfiles

system_code = FICHA-D01; sku = DEMO_60-POSTE-V; name = PVC practicable 60 mm · POSTE-V; role = MULLION_V; material = PVC; face_width_mm = 80.00; commercial_length_mm = 6000.00; weight_kg_m = 1.6066; steel_weight_kg_m = 1.7000

Roles y reglas de corte

system_code = FICHA-D01; sku = DEMO_60-POSTE-V; role = MULLION_V; angle_degrees = 90; welding_loss_per_end_mm = 0.00; joint_deduction_per_end_mm = 0.00; meeting_deduction_mm = 0.00; cut_step_mm = 0.01; rounding = UP

Refuerzos

system_code = FICHA-D01; sku = DEMO_60-POSTE-V; reinforcement_sku = DEMO_60-ACERO-POSTE-V; reinforcement_type = Acero galvanizado DEMO; minimum_length_mm = 1000.00; required_finishes = ["FOILED", "DARK"]; required_non_white = True; cut_deduction_mm = 10.00; screws_per_m = 4.0000; screw_sku = DEMO_60-TORNILLO-REF; screw_weight_kg = 0.003000

Perfiles

system_code = FICHA-D01; sku = DEMO_60-POSTE-H; name = PVC practicable 60 mm · POSTE-H; role = MULLION_H; material = PVC; face_width_mm = 80.00; commercial_length_mm = 6000.00; weight_kg_m = 0.8499; steel_weight_kg_m = 1.7000

Roles y reglas de corte

system_code = FICHA-D01; sku = DEMO_60-POSTE-H; role = MULLION_H; angle_degrees = 90; welding_loss_per_end_mm = 0.00; joint_deduction_per_end_mm = 0.00; meeting_deduction_mm = 0.00; cut_step_mm = 0.01; rounding = UP

Refuerzos

system_code = FICHA-D01; sku = DEMO_60-POSTE-H; reinforcement_sku = DEMO_60-ACERO-POSTE-H; reinforcement_type = Acero galvanizado DEMO; minimum_length_mm = 1000.00; required_finishes = ["FOILED", "DARK"]; required_non_white = True; cut_deduction_mm = 10.00; screws_per_m = 4.0000; screw_sku = DEMO_60-TORNILLO-REF; screw_weight_kg = 0.003000

Perfiles

system_code = FICHA-D01; sku = DEMO_60-JQ-24; name = PVC practicable 60 mm · JQ-24; role = GLAZING_BEAD; material = PVC; face_width_mm = 24.00; commercial_length_mm = 6000.00; weight_kg_m = 1.1705

Roles y reglas de corte

system_code = FICHA-D01; sku = DEMO_60-JQ-24; role = GLAZING_BEAD; angle_degrees = 90; welding_loss_per_end_mm = 0.00; joint_deduction_per_end_mm = 0.00; meeting_deduction_mm = 0.00; cut_step_mm = 0.01; rounding = UP

Perfiles

system_code = FICHA-D01; sku = DEMO_60-JQ-14; name = PVC practicable 60 mm · JQ-14; role = GLAZING_BEAD; material = PVC; face_width_mm = 14.00; commercial_length_mm = 6000.00; weight_kg_m = 1.1660

Roles y reglas de corte

system_code = FICHA-D01; sku = DEMO_60-JQ-14; role = GLAZING_BEAD; angle_degrees = 90; welding_loss_per_end_mm = 0.00; joint_deduction_per_end_mm = 0.00; meeting_deduction_mm = 0.00; cut_step_mm = 0.01; rounding = UP

Perfiles

system_code = FICHA-D01; sku = DEMO_60-JQ-10; name = PVC practicable 60 mm · JQ-10; role = GLAZING_BEAD; material = PVC; face_width_mm = 10.00; commercial_length_mm = 6000.00; weight_kg_m = 1.4243

Roles y reglas de corte

system_code = FICHA-D01; sku = DEMO_60-JQ-10; role = GLAZING_BEAD; angle_degrees = 90; welding_loss_per_end_mm = 0.00; joint_deduction_per_end_mm = 0.00; meeting_deduction_mm = 0.00; cut_step_mm = 0.01; rounding = UP

Límites

system_code = FICHA-D01; opening_type = FIXED; min_leaf_width_mm = 200.00; max_leaf_width_mm = 4500.00; min_leaf_height_mm = 200.00; max_leaf_height_mm = 3000.00; min_aspect_ratio = 0.2000; max_aspect_ratio = 6.0000

Límites

system_code = FICHA-D01; opening_type = TURN_LEFT; min_leaf_width_mm = 200.00; max_leaf_width_mm = 1600.00; min_leaf_height_mm = 200.00; max_leaf_height_mm = 2500.00; max_leaf_weight_kg = 150.0000; min_aspect_ratio = 0.2000; max_aspect_ratio = 6.0000

Límites

system_code = FICHA-D01; opening_type = TURN_RIGHT; min_leaf_width_mm = 200.00; max_leaf_width_mm = 1600.00; min_leaf_height_mm = 200.00; max_leaf_height_mm = 2500.00; max_leaf_weight_kg = 150.0000; min_aspect_ratio = 0.2000; max_aspect_ratio = 6.0000

Límites

system_code = FICHA-D01; opening_type = TILT_TURN_LEFT; min_leaf_width_mm = 200.00; max_leaf_width_mm = 1600.00; min_leaf_height_mm = 200.00; max_leaf_height_mm = 2500.00; max_leaf_weight_kg = 150.0000; min_aspect_ratio = 0.2000; max_aspect_ratio = 6.0000

Límites

system_code = FICHA-D01; opening_type = TILT_TURN_RIGHT; min_leaf_width_mm = 200.00; max_leaf_width_mm = 1600.00; min_leaf_height_mm = 200.00; max_leaf_height_mm = 2500.00; max_leaf_weight_kg = 150.0000; min_aspect_ratio = 0.2000; max_aspect_ratio = 6.0000

Límites

system_code = FICHA-D01; opening_type = AWNING; min_leaf_width_mm = 200.00; max_leaf_width_mm = 1600.00; min_leaf_height_mm = 200.00; max_leaf_height_mm = 2500.00; max_leaf_weight_kg = 45.0000; min_aspect_ratio = 0.2000; max_aspect_ratio = 6.0000

Colores y SKU por color

system_code = FICHA-D01; sku = DEMO_60-MARCO; finish = WHITE; commercial_sku = COMPRA-MARCO-BLANCO; physical_stock_identity = MARCO-BLANCO

Vidrios

system_code = FICHA-D01; sku = DEMO_60-VIDRIO-4-16-4; glass_spec = 4-16-4 Float Incoloro; purchasing_sku = DEMO_60-VIDRIO-4-16-4; manufacturer_name = Proveedor de prueba; version = 1

Vidrios

system_code = FICHA-D01; sku = DEMO_60-VIDRIO-4; glass_spec = 4 Float Incoloro; purchasing_sku = DEMO_60-VIDRIO-4; manufacturer_name = Proveedor de prueba; version = 1

Herrajes

system_code = FICHA-D01; sku = DEMO_60-KIT-TURN; name = Kit PVC practicable 60 mm · practicable; opening_type = TURN; min_leaf_width_mm = 200.00; max_leaf_width_mm = 1600.00; min_leaf_height_mm = 200.00; max_leaf_height_mm = 2500.00; max_leaf_weight_kg = 150.00; weight_kg = 2.50; rail_type = dual; carriages_qty = 0; stay_arms_qty = 1; is_active = True; contents = [{"sku": "DEMO_60-MANILLA", "name": "Manilla DEMO", "qty": "1", "unit": "EA", "category": "HANDLE"}, {"sku": "DEMO_60-BISAGRA", "name": "Bisagra DEMO", "qty": "2", "unit": "EA", "category": "HINGE"}]

Herrajes

system_code = FICHA-D01; sku = DEMO_60-KIT-TILT_TURN; name = Kit PVC practicable 60 mm · oscilobatiente; opening_type = TILT_TURN; min_leaf_width_mm = 200.00; max_leaf_width_mm = 1600.00; min_leaf_height_mm = 200.00; max_leaf_height_mm = 2500.00; max_leaf_weight_kg = 150.00; weight_kg = 2.50; rail_type = dual; carriages_qty = 0; stay_arms_qty = 1; is_active = True; contents = [{"sku": "DEMO_60-MANILLA", "name": "Manilla DEMO", "qty": "1", "unit": "EA", "category": "HANDLE"}, {"sku": "DEMO_60-BISAGRA", "name": "Bisagra DEMO", "qty": "2", "unit": "EA", "category": "HINGE"}]

Herrajes

system_code = FICHA-D01; sku = DEMO_60-KIT-AWNING; name = Kit PVC practicable 60 mm · proyectante; opening_type = AWNING; min_leaf_width_mm = 200.00; max_leaf_width_mm = 1600.00; min_leaf_height_mm = 200.00; max_leaf_height_mm = 2500.00; max_leaf_weight_kg = 45.00; weight_kg = 2.50; rail_type = dual; carriages_qty = 0; stay_arms_qty = 2; is_active = True; contents = [{"sku": "DEMO_60-MANILLA", "name": "Manilla DEMO", "qty": "1", "unit": "EA", "category": "HANDLE"}, {"sku": "DEMO_60-BISAGRA", "name": "Bisagra DEMO", "qty": "2", "unit": "EA", "category": "HINGE"}]