



**Hochschule für Technik  
und Wirtschaft Berlin**

**University of Applied Sciences**

# **Automatic Interaction Diagram Generation of Vue.js-based Web Applications**

A thesis submitted for the degree of  
**Master of Science (M.Sc.)**

at

Hochschule für Technik und Wirtschaft Berlin

in the degree course

Applied Computer Science (Master)

1. Supervisor: Prof. Dr. Gefei Zhang

2. Supervisor: Prof. Dr.-Ing. Hendrik Gärtner

submitted by: B.Sc. Anton Karakochev

matriculation number: 553324

date of submission: February 8, 2021

## **Abstract**

In this thesis an implementation of an n=gram based language model using the Modified Kneser=Ney smoothing algorithm with the open source Apache Spark large scale data processing engine and the open source document oriented database MongoDB will be presented. This language model will then be used to generate sentences from input sets of keywords.

This thesis aims to further explore the concept of interaction diagrams for scenario testing introduced by [ZZ19]. It is applied to a different framework (Vue.js) ... how scenarios in Gherkin generated and extended lists.

—

automatically generate!!!

—

# Contents

<b>1</b>	<b>Introduction</b>	<b>5</b>
<b>2</b>	<b>Fundamentals and State of The Art</b>	<b>6</b>
2.1	State of the Art . . . . .	6
2.1.1	TODO some papers . . . . .	6
2.2	Scenario Testing of AngularJS-based Single Page Web Applications . . . . .	6
2.2.1	Abstract Syntax . . . . .	6
2.2.2	Interaction Diagrams . . . . .	7
2.2.3	Testing and Interactions . . . . .	7
2.2.4	Coverage Criteria . . . . .	8
2.3	Scenario Testing . . . . .	8
2.4	Behavior-Driven Development . . . . .	9
2.4.1	the other one(forgot name) . . . . .	9
2.4.2	Gherkin Language . . . . .	9
2.5	Model-View-ViewModel . . . . .	9
2.5.1	View . . . . .	10
2.5.2	View-Model . . . . .	10
2.5.3	Model . . . . .	10
2.6	Vue.js . . . . .	10
2.6.1	Components . . . . .	10
2.6.2	Reactivity . . . . .	11
2.6.3	Directives . . . . .	11
2.6.4	Data Binding . . . . .	11
2.6.5	Vue.js directives . . . . .	11
2.6.6	Structure of a Component . . . . .	11
2.7	ESLint . . . . .	11
2.7.1	Architecture . . . . .	11
2.8	Rules . . . . .	12
2.8.1	AST Explorer . . . . .	13
2.8.2	ESTree AST . . . . .	13

2.8.3	ESLint Parser Vue AST . . . . .	13
<b>3</b>	<b>Concept</b>	<b>14</b>
3.1	Parsing Vue.js . . . . .	15
3.1.1	Assumptions . . . . .	15
3.1.2	Limitations . . . . .	15
3.1.3	AST . . . . .	15
3.2	Interaction Diagram Generation . . . . .	19
3.2.1	Variable Identifiers . . . . .	20
3.2.2	Object representation . . . . .	20
3.2.3	List representation . . . . .	21
3.2.4	Method representation . . . . .	22
3.3	Scenario Generation . . . . .	23
<b>4</b>	<b>Implementation</b>	<b>25</b>
4.1	Project Structure and Overview . . . . .	26
4.1.1	Project structure . . . . .	26
4.2	Parsing Vue.js . . . . .	27
4.2.1	Top Level Properties . . . . .	27
4.2.2	Bindings . . . . .	27
4.2.3	Method Definitions . . . . .	28
4.3	Interaction Diagram Generation . . . . .	28
4.4	Scenario Generation . . . . .	28
<b>A</b>	<b>Appendix</b>	<b>29</b>

## Chapter 1

# Introduction

## Chapter 2

# Fundamentals and State of The Art

### 2.1 State of the Art

TODO

#### 2.1.1 TODO some papers

### 2.2 Scenario Testing of AngularJS-based Single Page Web Applications

Zhang and Zhao [ZZ19] present a method with the goal of achieving better understanding of AngularJS-based single page applications (SPAs) and also devised a way to specify test coverage criteria based on it. At the center of the proposed method are interaction diagrams, which are used to model the overall data and control flow of an application.[ZZ19]

#### 2.2.1 Abstract Syntax

Zhang and Zhao [ZZ19] model a AngularJS-based SPA as a tuple  $(T, C, D, E)$ , where

- $T$  is a HTML template, consisting of a set of HTML tags (widgets) ( $T = \{h\}$ )
- $C$  is a controller (view-model), written in JavaScript. It is modeled as a tuple  $(V, F, \$scope)$ , where  $F$  and  $V$  are top level variables and functions respectively and  $\$scope \in V$  is a distinguished element of  $V$ . Further  $V(\$scope)$  and  $F(\$scope)$  denote all variables and functions of  $\$scope$  respectively.  $W = V \setminus \{\$scope\}$  denotes top level variables not in scope. Additionally  $init \in F$  is defined as an initialization function
- $D$  is a set of data bindings between HTML tags and variable properties of  $\$scope$   $D \subseteq \{(h, V(\$scope) \cup F(\$scope))\}$ . Given  $d = (n, o)$   $source(d) = n$  and  $target(d) = o$ . For Two-way bindings  $D' \subseteq D$  and  $\forall d \in D'$   $target(d) \in V(\$scope)$ .

- $E$  a set of event handler bindings between HTML tags and function properties of  $\$scope$ :  $E \subset \{(h, F(\$scope))\}$ . In addition, for each function  $f \in F \cup F(\$scope)$ ,  $R(f) \subseteq V \cup V(\$scope)$  and  $W(f) \subseteq V \cup V(\$scope)$  are defined as the values that the given function reads from and writes to.  $Inv(f) \in F$  are defined as the functions invoked by  $f$ . [ZZ19]

### 2.2.2 Interaction Diagrams

Zhang and Zhao [ZZ19] define interaction diagrams as a directed graph  $(N, E)$  where the set of nodes  $N$  is defined as the union of  $N_H$  (HTML tag nodes),  $N_{\$scope}$  (TODO name),  $N_js$  (TODO name).  $N_H = \{n_h | (h, v) \in D\}$

$$N_{\$scope} = \{n_v | (h, v) \in D\} \cup \{n_e | (h, e) \in E\}$$

$$N_js = \{n_v | v \in W\} \cup \{n_f | f \in F\}$$

$n_{init}$  is distinguished by an incoming arrow without a starting vertex

Edges:

bindings

$$e_d = (target(d), source(d)) \quad E_{data} = \{e_d | d \in D\}$$

additionally if  $d \in D'$  also create  $e'_t = (source(t), target(t))$  and  $E'_{data} = \{e_d | d \in D'\}$

for events ( $E_{event}$ )  $(h, f) \in E$ ,

write  $E_W (f, v)$  where  $f \in F \cup F(\$scope), v \in W(f)$

read  $E_R (v, f)$  where  $f \in F \cup F(\$scope), v \in R(f)$

invoked  $E_{Inv} (f, v)$  where  $f \in F \cup F(\$scope), v \in I(f)$

$E_{init}$  default values of widgets for each  $h \in T$  where  $\nexists v | (h, v) \in D$  create an edge  $(h, v)$  explained in a lot of detail in [ZZ19, p. 9]

### 2.2.3 Testing and Interactions

Zhang and Zhao [ZZ19] define an interaction as a round of user input including updates to the widgets by the application. Interaction can be triggered explicitly by the user (by invoking an event handler) or implicitly while the user is updating data. [ZZ19]

Given the interaction diagrams as described in 2.2.2 it is possible to derive which widgets get updated by a user input action or set up by the initial function. Zhang and Zhao [ZZ19] define it formally as follows:

Given a node  $n \in N_H \cup \{init\}$ , we say a node  $m \in N_H$  reacts to  $n$  iff

1.  $\exists n_0, n_1, n_2, \dots, n_k \in N, n_0 = n, n_k = m$  such that for each  $0 \leq i < k$   $(n_i, n_{i+1}) \in E$ , and
2.  $\forall n_p, 1 < p \leq k$  and  $\forall e \in E, target(e) = n_p$  it holds that  $e \notin E_{event}$

We write  $l(n)$  for the set of all nodes representing the widgets that react to  $n$ . This set contains the widgets that are automatically updated upon user input, and thus constitute an interaction.

For example, in order for the widget  $n$ , which was clicked by the user, to update the widget  $m$ ,  $m$  must be reachable from  $n$  by following the directed edges of the interaction diagram and only the first edge can be an event-handling edge.

What is crucial is that the interactions  $l(n)$  define an upper bound of what can be updated, i.e. what might get updated. Nevertheless, this information is sufficient in order to be able to define coverage criteria [ZZ19].

## 2.2.4 Coverage Criteria

Interactions should not be tested in isolation and in order for tests to make sense, interactions as preconditions are required [ZZ19]. In order to define coverage criteria, Zhang and Zhao [ZZ19] extend their notation, as described in 2.2.2, by defining  $\mathcal{I} = \{w \in T \mid l(w) \neq \emptyset\}$  all widgets, that result updates.

A sequence of user interactions, including the initial function is referred to as a *scenario*  $A = (a_0, a_1, \dots, a_n)$  where  $a_0 = \text{init}$  and  $\forall 0 < k \leq n, a_k \in \mathcal{I}$ . The widgets, to which a scenario reacts, are equal to the widgets to which the last widget in the scenario reacts -  $l(A) = l(a_n)$ .

The set of scenarios is generated by starting with the initial scenario, containing only the initial function  $S_0 = \{\text{init}\}$  and prolonging it iteratively by each widget, where the user can take an action. This is terminated once all  $i \in \mathcal{I}$  are included in at least one scenario. Formally: For  $n > 0, S_{n+1} = \{p \in S_n, x \in l(p) \cap \mathcal{I}\}$

Based on the scenario sets Zhang and Zhao [ZZ19] define the following coverage criteria:

- Each set  $S_n$  of test scenarios should be tested.
- For each given  $S_n$ , each  $p \in S_n$  should be tested.
- For each given  $p$ , each  $w \in l(p)$  should be tested. That is, there should be a test case for each widget that may be modified after the scenario  $p$ .

.. example, which will be implemented here in vue and described in sec xyz.

## 2.3 Scenario Testing

Scenario testing, was originally introduced in Kaner [Kan03] and later as Kaner [Kan13]. The author defines scenarios as hypothetical stories, which aid a person in understanding a complex system or problem. Scenario tests are tests, which are based on such scenarios. [Kan13, p. 1] Further, [Kan03, pp. 2–5] defines five characteristics, which make up a good scenario test as follows: A Scenario test must be

- based on a story - based on a description of how the program is being used
- motivating - stakeholders have interest in this test succeeding and would see to it's resolution
- credible - probable to happen in the real world



- complex - complex use, data or environment
- easy to evaluate - it should be easy to tell if the test succeeded or failed based on the results

Kaner [Kan13] describes the biggest advantages of scenario testing to be - understanding and learning the product in early stages of development(1), connecting of testing and requirement documentations(2), exposing shortcomings in delivering of desired benefits(3), exploration of expert use of the program(4), expose requirement related issues(5).

## 2.4 Behavior-Driven Development

Behavior-Driven Development (BDD), pioneered by North [Nor06] is a software development process, that combines principles from Test-Driven Development and Domain-Driven design [EE04].

Its main goal is to specify a system in terms of its functionality (i.e. its behaviors) with a simple domain-specific language (DSL) making use of English-like sentences. This stimulates collaboration between developers and non-technical stakeholders and further results in a closer connection between acceptance criteria for a given function and matching tests used for its validation.

BDD splits a user story into multiple scenarios, each formulated in the form of *Given*, *When*, *Then* statements, respectively specifying the prerequisite/context, event and outcomes of a scenario.

[TODO] example here

At present ... there based on the division of behavior descriptions and behaviors. Such as Jest/Jasmine combine behavior descriptions and behaviors into one, whereas as Cucumber uses a DSL named Gherkin to specify the behavior descriptions and provides a set of tools to generate behaviors.

### 2.4.1 the other one(forgot name)

splitting into ...

### 2.4.2 Gherkin Language

## 2.5 Model-View-ViewModel

Model-View-ViewModel (MVVM) is a design pattern, which helps in creating a clear separation between business and presentation logic and User interface (UI) of an application. [Bri17, pp. 7–9]

In MVVM there are three core components - the view, model and view model. Those components are clearly separated from each other - the view is aware of the view model and the view model is aware of the model. However, this does not hold in reverse - the model is unaware of the view model and the view model is unaware of the view.




Figure 2.1: MVVM design pattern overview, adapted from [Bri17, p. 7]

### 2.5.1 View

The view is what the user sees. It is responsible for the structure, layout and appearance of the application.

### 2.5.2 View-Model

The view model implements event handlers and properties, to which the view can bind to. It also notifies the view of any changes to the underlying data. It defines the functionality, offered by the UI, but the view determines how it is presented.

### 2.5.3 Model

The model encapsulates the data of the application and validation its logic.

## 2.6 Vue.js

Vue.js [vue21a] is a progressive front end framework for building user interfaces and single-page applications based on the MVVM design pattern described in 2.5 [Mac18] [21a].

### 2.6.1 Components

At the core of Vue.js are components, which are small, self-contained, composable and often reusable custom elements. Almost any type of application can be represented as a tree of components [21a].

In more concrete terms, a Vue.js component is a single file with the extension of *.vue*, which consists of a *template*, *script* and optional *style* part. The *template* is a HTML-based template, which can be parsed specification compliant browsers and HTML parsers. It can contain other components or html elements and is equivalent to the *view* in MVVM.

The *code* section of a Vue.js component includes the view-model of the component. It has a special json object *data*, which is equivalent to the MVVM model. The *script* part of a computed includes css-like styles.

data binding is a general technique that binds data sources from the provider and consumer together and synchronizes them.

### 2.6.2 Reactivity

... enables data binding

### 2.6.3 Directives

Vue.js enables one way bindings(from source - data to target - component or html tag) via the *v-bind* (line X,Y) or *moustache* syntax (line Z). Bindings can contain expressions (line X,Y).

Two way binding can be achieved using the *v-model* directive (line,X,Y,Z). Event handlers can be bound by the method name or also expressions.

### 2.6.4 Data Binding

Vue.js provides support for various forms of Data Binding via a special syntax. Both the data and computed objects of a *Vue.js* component are reactive

Via a special syntax *Vue.js* - one way - two way - event bindings - inline expressions - computed properties

### 2.6.5 Vue.js directives

### 2.6.6 Structure of a Component

(template, code etc.)

bindings two way, one way

g - data - computed properties

template part code part bindings

## 2.7 ESLint

ESLint [21b] is a linting tool (linter) for ECMAScript/JavaScript. Linters are static code analysis tool, which can be used to flag and potentially automatically fix common code issues and enforce consistent code styling.

### 2.7.1 Architecture

At a very high level, ESLint consists of




Figure 2.2: ESLint Architecture taken from [21c]

## 2.8 Rules

At the core of ESLint are rules. Rules are extensible pieces of code, bundled as plugins, which can be used to verify various aspects of code. An example would be a rule, which checks for matching closing paranthesis. Each rule consists of a *metadata* object and a *create* function. The metadata object includes metadata such as documentation strings, the type of the rule and whehter it is fixable or not.

Based on type, rules can be either *suggestions*, *problems* or *layout*. Suggestions indicate some

improvement, but are not required and would not cause the linting to fail. Problems on the other hand would result in a linting failure. Layouts are rules that care mainly about the formatting of code, such as whitespaces, semicolons, etc.

If the *fixable* property is specified, it indicates that the errors reported by this rule can be automatically fixed. This can be applied via the `--fix` command line option. It has two possible values - *code* or *whitespace* indicating the type of fixes, that this rule would apply. For example in Integrated development environments (IDEs) fixable *code* errors would show a fix shortcut displayed next to them and *whitespace* rules could be applied when saving the file.

The *create* function of rules takes as arguments a *context* and returns an object of methods which are called by ESLint for each node based on the Visitor pattern while traversing the Abstract syntax tree (AST). ESLint provides a very powerful matching mechanism for specifying what nodes to match called selectors [21d] inspired by estools [est21a].

TODO custom architecture image

TODO what are selectors

TODO what does context provide?

### 2.8.1 AST Explorer

An incredibly useful tool when working with ASTs is AST Explorer, developed by Kling [Kli21]. It enables the exploration of syntax tree generated by various parsers and also includes the vue-eslint-parser [vue21b]

### 2.8.2 ESTree AST

By default ESLint uses the [esl21] parser to parse JavaScript source code into an AST as defined by ESTree specification [est21b]. When Parsing *.vue* files ESLint uses this parser for the code inside the *<script>* tag.

### 2.8.3 ESLint Parser Vue AST

In order to parse the *<template>* section of *.vue* files, ESLint uses the vue-eslint-parser [vue21b]. This parser outputs an AST compliant with their own ASTspecification, defined in [vue21c].

A B

## Chapter 3

## Concept

## 3.1 Parsing Vue.js

### 3.1.1 Assumptions

It is assumed that the Vue.js code, for which interaction diagrams are going to be generated, compiles and does not contain syntactical errors. No checks are performed in order to verify that. Naturally, logical errors are not an issue.

### 3.1.2 Limitations

In order to be able to generate interaction diagrams, which capture every aspect of Vue.js, the generation must be directly based on an AST, which covers every possible syntax, such as [vue21b].

This thesis only includes the following features of Vue.js:

- Event handlers (including anonymous method syntax and method reference syntax)
- Any one or two-way binding expressions (*v-model*, *v-bind*, "moustache", *v-if*) excluding *v-else*
- nested *v-for* statements for lists, excluding iterating through properties of an object or iteration with index (property zipped with index)
- distinguishing between properties and computed properties
- complex object and lists (non-nested) models
- methods, including the resolution of arguments, they have been called with (excluding methods called with other methods as arguments)

### 3.1.3 AST

```
grammar js_simplified;
2
program: bindings methodDefinitions createdMethod topLevelProperties
      computedProperties;
4
topLevelProperties: thisIdentifier*;
6 methodDefinitions: methodDefinition*;
  createdMethod: methodDefinition;
8 computedProperties: (thisIdentifier reads writes calls)*;

10 methodDefinition: thisIdentifier methodArgs reads writes calls;

12 methodArgs: NAME_IDENTIFIER*;
  reads: accesedVariable*;
14 writes: accesedVariable*;
```

```

calls: calledMethod*;
16
calledMethod: calledMethodIdentifier '(' calledArgs ')';
18
accesedVariable: identifier;
calledArgs: (calledMethod | accesedVariable)*;
20
bindings: binding*;
22
binding: tag accesedVariable | calledMethod BINDING_TYPE;

24
tag: name tagId loc;
tagId: LINE '_' COLUMN '_' LINE '_' COLUMN;
26
name: UNICODE | identifier;
loc: start end;
28
start: LINE COLUMN;
end: LINE COLUMN;

30
calledMethodIdentifier: THIS id* NAME_IDENTIFIER | id* NAME_IDENTIFIER;
32
thisIdentifier: THIS identifier;
34
identifier: NAME_IDENTIFIER id*;

36
id: NUMERIC_INDEX | GENERIC_INDEX | NAME_IDENTIFIER;

38 //terminals, tokens
LINE: [0-9]+;
40
COLUMN: [0-9]+;

42
BINDING_TYPE: 'event' | 'one-way' | 'two-way';
GENERIC_INDEX: 'i' | 'j' | 'k' | 'l' | 'm' | 'n';
44
THIS: 'this';

46
NUMERIC_INDEX: [0-9];
NAME_IDENTIFIER: JS_IDENTIFIER;
48
JS_IDENTIFIER: (UNICODE | '$' | '-') (UNICODE | '$' | '-' | [0-9])*;
UNICODE: [\u0000-\uFFFF];

```

A Vue.js SPA, including all the necessary information for 3.1.2, can be defined using the above grammar.

The application consists of *bindings* *methodDefinitions* a *createdMethod*, *topLevelProperties* and *computedProperties*.

The *topLevelProperties* represent the *data* object of the Vue.js *script* tag. Each property will be represented flattened, as a list of identifiers and prefixed with *this*, in order to indicate it belongs to the top level data object. For example *problem:{a:0, b:0}* will be represented as follows:






Figure 3.1: AST for top-level example

Bindings can be obtained from the Vue.js *template*.

Each binding consists of an HTML tag, an a list of binding sources for that tag - pairs of variable or method call and a binding type. The binding type represents the type of the binding - either event, one-way or two-way. Two-way bindings are only valid with properties, whereas for events and one-way bindings, both method calls and properties are possible, since in Vue.js a binding source could be an expressions defined as an inline anonymous functions ( `<div v-if="value === true"/>` ). The binding sources are a list, since a tag could have multiple different bound properties, or a bound expression. The information about how exactly the properties are bound, if it is the same type of binding, is discarded.

Method calls include the parameters they have been called with - other methods or just variables. It is also possible to call methods with binary expressions - those are represented as a special method, which takes 2 parameters - the left and right side operators of the binary expression. Expressions with multiple terms can be represented as multiple binary expressions. This representation loses information such as the order of operations, but since we are only interested in which properties are being accessed, this loss does not pose an issue.

A special case is accessing lists. For example `<div v-bind="problems[0].a"/>` would result in the following:




Figure 3.2: AST for example

*v-for* statements, are substituted:

```

<ul>
2  <li v-for="subject in subjects" :key="subject.id">
    {{ subject.problems[0] }}
4  </li>
</ul>

```

results in

```

1  subjects[i].problems[0]

```

which in term produces the following AST:



Figure 3.3: AST for example

Nested lists are also possible and would result in multiple generic indices being added.

Each tag includes its location in the source code (starting and ending line and column), which can also be used as an identifier. Tags also have humanly readable names, which are either equal to the the text of the tag, if it exists, or to the identifier of the first binding.

*methodDefinitions* include all methods definitions from the *method* object of the *view-model*. Each method definition consists of the following

- identifier - an identifier, equal to *this* followed by the name of the method
- arguments - names of arguments, each of which is a simple name identifiers
- reads - variable it reads from
- writes - varaibles it writes to
- calls - method calls, including arguments, same as for bindings

*computedProperties* are similar to *methodDefinitions* with the exception that they do not have arguments. Albeit bad practise, it is still possible for computed properties to have side effects and therefore it was decided to model them as methods.

## 3.2 Interaction Diagram Generation

The simplified Vue.js AST can be used to create a directed graph, which will represent the interaction diagrams. It is hard to directly generate this graph, therefore the capabilities of a directed, compoundend graph will be leveraged and later on converted to a directed graph.

Vertices in this graph have the following properties

1. Globally Unique Identifier (GUID) - used to reference and globally identify the vertex
2. *label* - the name of the vertex, which is going to be displayed
3. *type* - the type of the vertex (data, tag or method). Additionally for data vertices: numeric, generic or undefined (representing simple data vertices)
4. *loc* - defined only on tag verices. Their location in the source code
5. *parent* - defined only on vertices of type 'data'. A GUID of another vertex, used for a child/parent relationship (compound graph).

Edges in the graph are directed and each have a label property, which is one of 'event', 'calls' or 'simple'.

### 3.2.1 Variable Identifiers

Variable identifiers are represented by *identifier* and *thisIdentifier* in the AST 3.1.3. For the *this* and for each *id* node in the *identifier* or *thisIdentifier* a vertex is created in order. Those vertices are connected using unidirection edges, labeled with 'data' and also each vertex (excluding the first one) has its parent set to the previous.

Each vertex has a GUID equal to the value of its terminal symbol (*NUMERIC\_INDEX*, *GENERIC\_INDEX* or *NAME\_IDENTIFIER*), concatenated with the value of the previous vertex. The *label* of those vertices are equal to the terminal symbol in case of *NAME\_IDENTIFIER* and in case of *GENERIC\_INDEX* and *NUMERIC\_INDEX*, combined with the *label* of the previous vertex using square braces. Set the type of each vertex to 'data'.




Figure 3.4: Example Graph obtained for the identifier *this.problems[0].a*

### 3.2.2 Object representation

Using the representation for identifiers in the previous section, objects will result in being displayed dynamically, based on which properties are accessed. Nodes and edges are created on a 'create if non-existent' basis. In the example below, if *this.problem.b* is accessed after *this.problem.a* it will only result in the creation of the node *a* and edge *this.problem -> this.problem.b*.




Figure 3.5: Example Graph generated obtained for the following object accesses - *this.problem.a*, *this.problem.b*, *this.problem.author.name*

Furthermore, updates can be formulated nicely with the above representation. If *problem* were to be changed, it would result in a cascade update of all properties. If *author* would be change, it would only result in a cascading change in *name*.

### 3.2.3 List representation

Lists will be represented based on the principle shown in 3.6 for a list named *P*.




Figure 3.6: Generic List representation

Concrete elements, which are accessed, are denoted as  $P_{<index>}$  and additionally a vertex  $P_{all}$ ,

which can be updated to all elements of a list and their properties, is created. Another vertex  $P_{any}$  is also created, which can be used to observe once any vertex of  $P_1, P_2, P_3, \dots P_n$  changes. If  $P_1$  were to be updated by any method, it would not result in updates to any of  $P_2, P_3, \dots P_n$

The same construct can be leveraged also when it comes to properties of list elements and will be described in more detail in




Figure 3.7: Concrete example of a list representation

### 3.2.4 Method representation

Methods have two related AST nodes - *methodDefinition*, representing the definition of a method and *calledMethod* representing a call of a method.

First it should be determined if a vertex needs to be created for an *calledMethod* node. This is done by looking up based on the name of the *calledMethod* in *methodDefinition*, ignoring *THIS*. If the lookup is succesful a vertex should be created as described below. If not, it should be checked if the method is a method call on a top level property instance. This can be done by comparing if it starts in the same way as one of *topLevelProperties*. If that's the case, it is assumed, that it mutates whole property and the method should instead be treated as a write operation. If both of the above fail, the called method does not belong to context and is of no interest.

The next step is to resolve the names of the arguments it has been called with *calledArgs*. Every argument, that can neither be found in *computedProperties* nor *topLevelProperties* is replace by a fixed word such as *OTHER* or *\**. In order to obtain the GUID of the vertex, the name of the *methodDefinitionIdentifier* is taken, *THIS* is excluded, and concatenated with the the resolved arguments, which are joined with *,* and surrounded with brackets. The *label* of this node is equal to its name, excluding *THIS* from arguments.

The vertex for the method call is now completed. Multiple calls of this method with the same arguments will all result in the same vertex.

Now vertices for nodes the method interacts with, based on its *methodDefinition*, have to be created. Those include the variables it reads - *reads*, and writes - *writes* and methods it calls - *calls*.

Firstly, the arguments from the *methodDefinition* need to be substituted with the resolved arguments the method was actually called with and update all *reads*, *writes* *calls* referencing them. All of them, which do not start with *THIS* can be discarded, since they do not belong to the context. Once filtered out, create a list of vertices for each variable in *reads* and *writes* as described in 3.2.1 and connect the most precise of those (the last of each list) to the method vertex. For the vertices resulting from *writes*, this edge has a label of 'writes' and the property vertex as the source and method vertex as the sink. For the vertices resulting from *reads*, this edge has the method vertex as the source and property vertex as the sink. Finally the process described in this section is repeated recursively for each *calledMethod* node in *calls* and an edge labeled 'calls' is added from the current method vertex to the resulting ones.

## Computed property representation

### Combining it all together

Interaction diagrams can be generated from the simplified Vue.js AST in the following way:

For each *binding* in *bindings*: - for each *tag*, *bindingSource* in *binding*:

Create a vertex for *tag*, with a GUID *tagId* and label *name* and type 'tag'.

if the *binding* is an *accessedVariable*, determine if it is a computed property by looking it up in *computedProperties* and if so, treat it as a computed property, and create vertices as described in 3.2.4. Otherwise determine if it as top level property, by doing a lookup on *topLevelProperties*, treat it as a property and create vertices for it as described in 3.2.1. In either cases, connect it to the *tag* vertex, based on the binding type. If the *accessedVariable* is neither, it does not belong to context and can be discarded.

if the *binding* is an *calledMethod* create a vertices for it as described in 3.2.4. Connect it to the *tag* vertex, based on the binding type.

Based on binding type, the following edges are created: A) If the binding type is an event binding, create an edge with the tag vertex as a source and the binding vertex as sink and label it 'event'. B) If the binding type is one-way, create an edge with the binding vertex as source and the tag vertex as sink. C) If the binding type is two-way, create both edges - A) and B).

For the initial method - *createdMethod*, create a vertex with GUID and name equal to *created* and create vertices for its *reads*, *writes* and *calls* analogous to methods as described in 3.2.4.

## 3.3 Scenario Generation

In order to generate scenarios in Gherkin, interactions can be sliced in a similar manner as described by Zhang and Zhao [ZZ19] and summarized in 2.2.2.

Let  $N$  denote the set of all nodes in the graph and  $E$  denote all edges in the graph. Let  $n \in N$ ,  $m \in N$  be any two nodes in the graph and let  $(n, m) \in E$  represent an edge from  $n$  to  $m$ . Let  $type(n)$  be a function, that returns the type of a node and  $label(n, m)$  be a function that returns

the label of the edge from  $n$  to  $m$ . Let  $E_{out}(n)$  be a function, which returns all outgoing edges of  $n$ . Let  $E_{in}(n)$  be a function, which returns all incoming edges to  $n$ .

Let  $N_I$  denote all nodes, that the user can interact with. A node  $n \in N$  is also in  $N_I$  if  $\exists e \in E_{out}(n)$  where  $label(e) = event$ . Let  $N_H$  denote all html tag nodes. a node  $n \in N$  is also in  $N_H$  if  $type(n) = tag$ . Given a node  $n_H \in N_H \cup created$ , a node  $m_H \in N_H$  reacts to  $n$  iff

1.  $\exists n_0, n_1, n_2, \dots, n_k \in N, n_0 = n_H, n_k = m_H$  such that for each  $0 \leq i < k$   $(n_i, n_{i+1}) \in E$ , and  $label((n_i, n_{i+1})) \neq event$  and if  $label(n_i, n_{i+1}) \neq calls \forall n_{i+1_{in}} E_{in}(n_{i+1}) label(n_{i+1_{in}}) \neq event$

Analogous to [ZZ19] let  $l(n)$  denotes all nodes, that react to  $n$ . A sequence of user interactions, starting with the initial function is referred to as a *scenario*  $A = (a_0, a_1, \dots, a_n)$  where  $a_0 = created$  and  $\forall 0 < k \leq n, a_k \in N_I$ .

Define the HTML tags, to which a scenario reacts, to be equal to the tags to which the last tag in the scenario reacts -  $l(A) = l(a_n)$ .

The set of scenarios is generated by starting with the initial scenario, containing only the initial function  $S_0 = \{(created)\}$ . It is then prolonged by all tags  $n \in N_I$ , representing that the user can click anywhere resulting in  $N_I$  scenarios of length 2. Scenarios of length 3 are generated by taking the previous ones of length 2  $S_2$  and for each scenario  $S$  in  $S_2$  generate up to  $N_I$  new scenarios by prolonging  $S$  with  $n | n \in l(S) \cap N_I$ . This is repeated up to  $k$  times, where  $k$  is a constant set by the user. Then each set is collapsed() and later only unique interaction are generated.

and prolonging it iteratively by each widget, where the user can take an action.

Gherkin scenarios templated can then be obtained by the following template: Scenario -  $n_0, n_1 \dots n_k$  Given -  $n_0, n_1 \dots n_{k-1}$  When -  $n_k$  Then -  $l(n_k)$



## Chapter 4

# Implementation

## 4.1 Project Structure and Overview

The application is written mostly in TypeScript using npm as a package manager and Node.js as a runtime environment.

Notable dependencies are TypeScript, for stricter syntax and types, lodash for enrichening of collections, babel as a transcompiler, eslint, estree and eslint-plugin-vue for parsing Vue.js code, d3-graphviz in combination with light-server for visualization of the generated interaction diagrams. The full list of dependencies can be found in the *package.json* of the project.

### 4.1.1 Project structure

The main source files of the project and their tests are included in the *src* directory and structured in several packages, each corresponding to a step in the process, except common, which is shared among all steps. Each will be described in more detail in the following sections. Each package includes a models directory, which includes the data types defined and used in this section. The *web* directory contains code used to view the resulting diagram in the browser. The *scripts* directory includes helper bash scripts, *results* holds snapshots of the results throughout development (with the latest being the current) and *resources* hold various additional files needed.

```

    root :.
2  |-- resources
    |   |-- output
4  |
    |-- results
6  |
    |-- scripts
8  |
    |-- src
10 |   |-- common
    |   |   |-- models
12 |   |
    |   |-- main.ts
14 |   |
    |   |-- generator
16 |   |   |-- models
    |   |
18 |   |-- parsing
    |   |   |-- builders
20 |   |   |-- models
    |   |   |-- visitors
22 |   |
```

24

```

|   |-- scenarios
|
|-- web

```

## 4.2 Parsing Vue.js

Instead of implementing a parser, which directly outputs the simplified Vue.js AST described in 3.1.3 the capabilities of **eslint** and [vue21b] were used. The source files, which handle the parsing reside in the *parsing* directory. The file *eslint*.ts provides a wrapper around the ESLint Node.js API of eslint. Custom visitors were implemented in order to extract the necessary nodes from the AST of ESLint. Each visitor has a matching file in *models*, which holds the models specific to that visitor, and a *builder*, which keeps track of the visited nodes and builds the result data type. There are a total of three visitors - one for top level properties, another for bindings and the last one for method definitions, computed properties and init.

### 4.2.1 Top Level Properties

The top level properties visitor is the simplest of all since it only reacts to the top level *data* node inside the *script* tag of the Vue.js SPA, which is a *ObjectExpression* 2.8.3. It can be selected via the following selector:

2

```

"Property[key.name = data] ReturnStatement > ObjectExpression"(node){
  ...
}

```

For each of its properties 2.8.3 the name of the key (identifier) is stored. If the property is an object (value of *ObjectExpression* 2.8.3) it is already concatenated with the previously obtained key. Finally all properties are prefixed with 'this'.

### 4.2.2 Bindings

The ESLint AST nodes, which are interesting when parsing the bindings are *VElement* 2.8.3, *Identifier* 2.8.3, *MemberExpression* 2.8.3 and *CallExpression* 2.8.3.

A property identifier can be a single *Identifier* or a *MemberExpression*, which can contain other *Identifier* nodes or *MemberExpression* nodes. Property Identifiers are extracted by

*VElement* nodes represent any HTML tag. Whenever any ends

```
"VAttribute[key.name.name=on] > VExpressionContainer :matches(MemberExpression, Identifier, CallExpression)"( node )
```

```
Two-way "VAttribute[key.name.name=model] > VExpressionContainer :matches(MemberExpression, Identifier, CallExpression)"( node )
```

```
//other identifiers ":not(:matches(VAttribute[key.name.name=on], VAttribute[key.name.name=model], VAttribute[key.name.name=for])) > VExpressionContainer :matches(MemberExpression, Identifier, CallExpression)"( node
  vfor containing
  velement exited
```

### 4.2.3 Method Definitions

eslint -> ast defined previously

wrappper eslint -> eslint (encapsulate eslint, wrapper) - visitors (using selectors extract) -  
 builders transformation  
 how what captured in detail  
 - builders transformation wrapper  
 not exact by types, more general, handled by eslint. also the assumption that code good

## 4.3 Interaction Diagram Generation

- as described in concept - takes models from previous section
  - method cache to abstract from being resolved twice - method resolver
  - custom graph type, "create if not exist"
  - for each in init resolve - for each in bindings resolve
  - indirectly called in the end - add edges for numeric

## 4.4 Scenario Generation

traversal print to ui, but can ...  
 ... usage?

Appendix A

Appendix

# List of Figures

2.1	MVVM design pattern overview, adapted from [Bri17, p. 7]	10
2.2	ESLint Architecture taken from [21c]	12
3.1	AST for top-level example	17
3.2	AST for example	18
3.3	AST for example	19
3.4	Example Graph obtained for the identifier <i>this.problems[0].a</i>	20
3.5	Example Graph generated obtained for the following object accesses - <i>this.problem.a</i> , <i>this.problem.b</i> , <i>this.problem.author.name</i>	21
3.6	Generic List representation	21
3.7	Concrete example of a list representation	22

## List of Tables





# Bibliography

- [ZZ19] Gefei Zhang and Jianjun Zhao. “Scenario Testing of AngularJS-Based Single Page Web Applications”. In: *International Conference on Web Engineering*. Springer. 2019, pp. 91–103.
- [Kan03] Cem Kaner. “The Power of ‘What If... and Nine Ways to Fuel Your Imagination: Cem Kaner on Scenario Testing’”. In: *Software Testing and Quality Engineering* 5 (2003), pp. 16–22.
- [Kan13] Cem Kaner. “An introduction to scenario testing”. In: *Florida Institute of Technology, Melbourne* (2013), pp. 1–13.
- [Nor06] Dan North. “Behavior modification”. In: *Better Software* 8.3 (2006), p. 26. URL: <https://dannorth.net/introducing-bdd/>.
- [EE04] Eric J Evans and Eric Evans. *Domain-driven design: tackling complexity in the heart of software*. Addison-Wesley Professional, 2004.
- [Bri17] David Britch. *Enterprise Application Patterns using Xamarin. Forms*. 2017. URL: <https://github.com/dotnet-architecture/eBooks/blob/master/current/xamarin-forms/Enterprise-Application-Patterns-using-XamarinForms.pdf>.
- [vue21a] vuejs. *vue*. [Online; accessed 29. Jan. 2021]. Jan. 2021. URL: <https://github.com/vuejs/vue>.
- [Mac18] Callum Macrae. *Vue.js: Up and Running: Building Accessible and Performant Web Apps*. " O’Reilly Media, Inc.", 2018.
- [21a] *Introduction Vue.js*. [Online; accessed 29. Jan. 2021]. Jan. 2021. URL: <https://vuejs.org/v2/guide>.
- [21b] *ESLint - Pluggable JavaScript linter*. [Online; accessed 25. Jan. 2021]. Jan. 2021. URL: <https://eslint.org>.
- [21c] *Architecture*. [Online; accessed 27. Jan. 2021]. Jan. 2021. URL: <https://eslint.org/docs/developer-guide/architecture>.
- [21d] *Selectors*. [Online; accessed 27. Jan. 2021]. Jan. 2021. URL: <https://eslint.org/docs/developer-guide/selectors>.

- [est21a] estools. *Esquery*. [Online; accessed 27. Jan. 2021]. Jan. 2021. URL: <https://github.com/estools/esquery>.
- [Kli21] Felix Kling. *AST Explorer*. [Online; accessed 27. Jan. 2021]. Jan. 2021. URL: <https://github.com/fkling/astexplorer>.
- [vue21b] vuejs. *vue-eslint-parser*. [Online; accessed 27. Jan. 2021]. Jan. 2021. URL: <https://github.com/vuejs/vue-eslint-parser#readme>.
- [esl21] eslint. *Espree*. [Online; accessed 25. Jan. 2021]. Jan. 2021. URL: <https://github.com/eslint/espree>.
- [est21b] estree. *estree*. [Online; accessed 27. Jan. 2021]. Jan. 2021. URL: <https://github.com/estree/estree>.
- [vue21c] vuejs. *vue-eslint-parser*. [Online; accessed 27. Jan. 2021]. Jan. 2021. URL: <https://github.com/vuejs/vue-eslint-parser/blob/master/docs/ast.md>.