

C02 - ASSESSMENT TOOL 1-ETHICAL HACKING

REPORT ANALYSIS

(Karamala Rishika-192525114)

1. Nmap Network Scan Report

CODE:

pwd

whoami

hostname

date

ifconfig

ip addr

ip route

ping -c 4 192.168.1.10

arp -a

nmap --version

nmap 192.168.1.10

nmap -sS 192.168.1.10

nmap -sV 192.168.1.10

nmap -O 192.168.1.10

nmap -A 192.168.1.10

nmap -Pn 192.168.1.10

nmap -T4 192.168.1.10

nmap -F 192.168.1.10

nmap -p 22,80,3306 192.168.1.10

nmap --script vuln 192.168.1.10

nmap -oN report.txt 192.168.1.10

cat report.txt

less report.txt

more report.txt

history

EXPLANATION:

Command	Explanation
pwd	Displays the current working directory.
whoami	Shows the current logged-in user.
hostname	Displays the system hostname.
date	Shows the current system date and time.
ifconfig	Displays network interface configuration.
ip addr	Shows IP address information.
ip route	Displays the routing table.
ping -c 4 192.168.1.10	Checks connectivity with the target system.
arp -a	Displays the ARP cache entries.
nmap --version	Displays the installed Nmap version.
nmap 192.168.1.10	Performs a basic port scan.
nmap -sS 192.168.1.10	Performs a TCP SYN (stealth) scan.
nmap -sV 192.168.1.10	Detects service versions running on open ports.
nmap -O 192.168.1.10	Detects the operating system.
nmap -A 192.168.1.10	Performs aggressive scanning (OS, services, scripts, traceroute).
nmap -Pn 192.168.1.10	Scans the host without ping discovery.
nmap -T4 192.168.1.10	Increases scan speed.
nmap -F 192.168.1.10	Performs a fast scan of common ports.
nmap -p 22,80,3306 192.168.1.10	Scans only SSH, HTTP, and MySQL ports.
nmap --script vuln 192.168.1.10	Runs vulnerability detection scripts.
nmap -oN report.txt 192.168.1.10	Saves scan results to a file.
cat report.txt	Displays the saved report.
less report.txt	Views the report page by page.
more report.txt	Displays the report one screen at a time.
history	Displays previously executed commands.

2. GoPhish Phishing Campaign

CODE:

```
pwd
whoami
hostname
date
cd gophish
ls
chmod +x gophish
./gophish
ifconfig
ip addr
netstat -tulnp
ss -tuln
firefox https://127.0.0.1:3333
cd ~/Downloads
ls
mkdir phishing_reports
cd phishing_reports
touch campaign.txt
echo "Campaign Started" >> campaign.txt
echo "Emails Sent:100" >> campaign.txt
echo "Emails Opened:75" >> campaign.txt
echo "Clicked Link:40" >> campaign.txt
echo "Credentials Submitted:20" >> campaign.txt
echo "Attachments Downloaded:10" >> campaign.txt
cat campaign.txt
less campaign.txt
history
```

EXPLANATION:

Command	Explanation
pwd	Displays the current directory.
whoami	Displays the current user.
hostname	Shows the system hostname.
date	Displays the current date and time.
cd gophish	Moves to the GoPhish installation directory.
ls	Lists files in the directory.
chmod +x gophish	Makes the GoPhish executable.
./gophish	Starts the GoPhish server.
ifconfig	Displays network configuration.
ip addr	Shows IP addresses.
netstat -tulnp	Displays listening ports and services.
ss -tuln	Shows active TCP/UDP listening ports.
firefox https://127.0.0.1:3333	Opens the GoPhish web interface.
mkdir reports	Creates a folder for reports.
cd reports	Moves into the reports folder.
touch campaign.txt	Creates a report file.
echo "Campaign Started" >> campaign.txt	Writes campaign information to the file.
echo "Emails Sent:100" >> campaign.txt	Records the number of emails sent.
echo "Opened:75" >> campaign.txt	Records opened emails.
echo "Clicked:40" >> campaign.txt	Records clicked phishing links.
echo "Credentials:20" >> campaign.txt	Records submitted credentials.
echo "Attachments:10" >> campaign.txt	Records downloaded attachments.
cat campaign.txt	Displays the report contents.
less campaign.txt	Views the report page by page.
history	Displays command history.

3. Dig DNS Assessment :

CODE:

pwd

whoami

hostname

date

ifconfig

ip addr

ping -c 4 example.com

dig example.com

dig ns example.com

dig mx example.com

dig a example.com

dig aaaa example.com

dig cname example.com

dig txt example.com

dig soa example.com

dig any example.com

dig axfr example.com @ns1.example.com

host example.com

host -t ns example.com

host -t mx example.com

nslookup example.com

nslookup -type=ns example.com

nslookup -type=mx example.com

dig +short example.com

dig +trace example.com

history

EXPLANATION:

Command	Explanation
pwd	Displays the current working directory.
whoami	Displays the current logged-in user.
hostname	Shows the system hostname.
date	Displays the current date and time.
ifconfig	Displays network configuration.
ip addr	Shows IP addresses.
ping -c 4 example.com	Checks network connectivity.
dig example.com	Retrieves DNS information.
dig ns example.com	Displays DNS name servers.
dig mx example.com	Displays mail server records.
dig a example.com	Displays IPv4 address records.
dig aaaa example.com	Displays IPv6 address records.
dig cname example.com	Displays CNAME records.
dig txt example.com	Displays TXT records.
dig soa example.com	Displays the Start of Authority record.
dig any example.com	Attempts to retrieve all available DNS records.
dig axfr example.com @ns1.example.com	Attempts a DNS Zone Transfer.
host example.com	Resolves the domain name.
host -t ns example.com	Displays NS records.
host -t mx example.com	Displays MX records.
nslookup example.com	Queries DNS information.
nslookup -type=ns example.com	Displays name servers.
nslookup -type=mx example.com	Displays mail servers.
dig +short example.com	Displays a short DNS response.
dig +trace example.com	Traces the complete DNS resolution process.