

PAY — progress log


[BUILD.md](#) is the plan. **This file is the record** — what was actually built, what is proven, what was decided, and what is still open. Updated at the end of every checkpoint.

Last updated: 2026-08-15 · **Branch:** `pay/x402-poc` · **Owner:** PAY (D1 Payments Lead)

C1	C2	C3	C4	C5	C6	C7
						

100 tests passing · 0 lint errors · typecheck clean · build clean · 7 real settlements on Base Sepolia

1. What this division built



The red box is the product. Everything else exists so a policy decision can sit there, before anything irreversible happens.

2. Status board

C	Checkpoint	Status	Evidence
C1	Real x402 payment settles	● green	tx <code>0x364612...4eda9</code> , balance \$20.00 → \$19.99
C2	Header codecs	● green	12 tests against real C1 captures
C3	SDK adapter + facilitator types	● green	7 tests + a live settlement through the split
C4	Intent build + hash	● green	19 tests · hash moves on all 9 judged terms
C5	allowToken + signer	● green	10 tests · 3 mutation runs · live attack paths refused
C6	Gateway orchestrator	● green	34 tests · release proven on 6 failure paths
C7	<code>POST /api/gw/request</code>	● half	endpoint live and settling; engine swap waits on CORE

Legend: ● green · ● partly done · ● not started · ● blocked

3. Test inventory

File	Tests	Covers
<code>tests/headers.test.ts</code>	12	codecs, malformed input, dollars-vs-minor-units, settlement failure
<code>tests/adapter.test.ts</code>	7	the read/sign/read split, offline EIP-3009 signing, offer narrowing
<code>tests/intent.test.ts</code>	19	field mapping, minor units, hash sensitivity per term, key-order independence
<code>tests/signer.test.ts</code>	10	tamper, replay, expiry, wrong-intent token, wrong merchant
<code>tests/forward.test.ts</code>	19	header stripping by prefix, signature injection
<code>tests/orchestrator.test.ts</code>	15	happy path, BLOCK/HOLD, 6 failure paths releasing the reservation
<code>tests/gw-request.test.ts</code>	12	the frozen contract, auth, SSRF, 429, secret leakage
<code>tests/fixtures.ts</code>	—	pinned real captures shared by the suite
Total	94	plus 6 inherited from <code>src/core/tests/money.test.ts</code>

Mutation testing

Passing tests prove nothing if they would also pass with the protection removed. Each guard was deleted in turn and the suite re-run:

Guard removed	Tests killed
<code>verifyAllowToken</code> call	4
signer's term-by-term offer match	3
signer's intentHash integrity check	1
orchestrator's <code>releaseBudget</code> call	6

4. On-chain evidence

Every settlement below is a real transaction on Base Sepolia, paid in test USDC from `0x0D3CaC5f27705C4c72185B8B74A543F3530F84ef`.

#	Checkpoint	txHash	What it proved
1	C1	<code>0x164317...3c2b</code>	the SDK settles at all (paid the agent's own address)
2	C1	<code>0x364612...4eda9</code>	payer and payee distinct, \$20.00 → \$19.99
3	C3	<code>0x9e060e...8f15</code>	the manual read/sign/retry split is accepted by the facilitator
4	C3	<code>0x939b5b...1092</code>	the split again, with no env override
5	C5	<code>0x7c54c3...7191</code>	a signature produced by <code>wallet/signer.ts</code> settles
6	C6	<code>0xa9f002...bec2</code>	the full orchestrator, with smuggled headers stripped
7	C7	<code>0x5ff0eb...13c4</code>	the public HTTP endpoint, end to end

Balance: **\$20.00** → **\$19.93**. Gas on every one was paid by the facilitator's signer `0xd407e4...f1bf`, never by the agent — the agent wallet has held **0 ETH** throughout.

5. Checkpoint detail

C1 — prove x402 works

Files. `scripts/fund-wallet.ts`, `scripts/poc-seller.ts`, `scripts/poc-x402.ts`,
`app/api/gw/poc-seller/route.ts`

x402 was the only dependency the team does not control, so it was proven before any product code.

Finding	Detail
Package line	The scoped <code>@x402/fetch</code> <code>@x402/evm</code> <code>@x402/next</code> at 2.22.0 is protocol v2. The unscoped <code>x402-fetch@1.2.0</code> is the old line
Network id	The wire says <code>eip155:84532</code> , not <code>base-sepolia</code> — raised as B3
Header names	v2 really does use <code>PAYMENT-REQUIRED</code> / <code>-SIGNATURE</code> / <code>-RESPONSE</code> . <code>X-PAYMENT</code> is v1 legacy
Gas	<code>exact</code> is EIP-3009: the buyer signs, the facilitator broadcasts and pays. The agent needs USDC, not ETH
Amount	<code>"10000"</code> — integer minor units, never dollars

DEMO's sandbox was still a stub and the public fallback `x402.org/protected` returned 500, so PAY stood up a throwaway seller under `app/api/gw/`, a namespace PAY owns.

C2 — header codecs

Files. `x402/headers.ts`, `tests/headers.test.ts`

`@x402/core/http` only regexes the base64 and `JSON.parse`s — **no schema validation**, so a header encoding `{}` decodes "successfully" to an empty object. `headers.ts` adds the layer the SDK omits.

Input	Result
real capture	decoded, typed
not base64 / empty / malformed JSON	<code>INVALID_PAYMENT_REQUIREMENTS</code> (422)
valid JSON but <code>{}</code> or <code>accepts: []</code>	<code>INVALID_PAYMENT_REQUIREMENTS</code>
<code>amount: "0.01"</code> — dollars, not minor units	<code>INVALID_PAYMENT_REQUIREMENTS</code>
settlement <code>success: false</code>	<code>SETTLEMENT_FAILED</code> (502)
<code>success: true</code> , unusable tx hash	<code>SETTLEMENT_FAILED</code>

Errors throw `PaymentHeaderError`, carrying an `ERROR_CODES` key so the gateway maps it straight into `fail()`.

C3 — SDK adapter

Files. `x402/adapter.ts`, `x402/facilitator.ts`, `mock/index.ts`, `tests/adapter.test.ts`

```

readPaymentRequired(response)  -> the price, decoded
    ^ CORE.evaluatePayment goes HERE ^
narrowToOffer(required, offer) -> binds the SDK to the approved entry
createPaymentSignature(...)    -> signs, returns the header value
readSettlement(response)      -> the proven tx hash

```

`wrapFetchWithPayment` does all four in one call and signs before any policy code runs. It is used in the spike and **must never** appear in the orchestrator.

`narrowToOffer` closes threat T9 at the SDK boundary: `createPaymentPayload` runs its own selector over `accepts[]`, so a merchant offering two entries could be paid on the one CORE did not approve.

C4 — intent build and hash

Files. `intent/build.ts`, `intent/hash.ts`, `tests/intent.test.ts`

Intent field	Source
<code>amountMinor</code>	<code>BigInt(requirements.amount)</code> — ⚠️ not <code>toMinor()</code>
<code>asset</code>	the contract address, the only unforgeable identifier
<code>network</code>	<code>eip155:84532</code> as it arrives
<code>recipient</code>	<code>payTo</code> , regex-checked
<code>merchant</code>	<code>new URL(requestUrl).host</code> , with port
<code>resource</code>	<code>`\${METHOD} \${pathname}`</code> , query dropped
<code>nonce</code>	16 random bytes, fresh per intent

The factor-of-10⁶ trap. BUILD.md specifies `toMinor`. That converts a *dollar* string, so `toMinor("10000")` returns `100000000000n` — a \$10,000 payment where \$0.01 was quoted. The wire already sends minor units. A test pins it.

The hash covers nine terms, not the seven the stub listed: `merchant` and `reason` were added. `merchant` is the exact key CORE's allowlist matches on, so leaving it unbound would permit the very swap the hash exists to prevent. `intentId` and `createdAt` are excluded and a test asserts they do not move the hash.

C5 — allowToken and signer

Files. `wallet/allowToken.ts`, `wallet/signer.ts`, `tests/signer.test.ts`

#	Guard	Stops
1	recompute the hash from the intent's own terms	a term mutated after evaluation
2	find the offer matching on amount, asset, network, payTo	a similar-but-different offer
3	offer's <code>resource.url</code> host must equal the approved <code>merchant</code>	an offer replayed from elsewhere
4	<code>verifyAllowToken</code> — authenticity, expiry, replay, atomically consumed	forged, stale or reused authorisation

The token is consumed **last** on purpose, so a mismatch in 1–3 never burns a valid one.

`v1.<expiresAtMs>.<evaluationId>.<hmac>`, 60 s TTL. The `intentHash` is never *carried* in the token, only fed into the MAC — a stolen token discloses nothing and is useless elsewhere. Compared with `timingSafeEqual`. Verify and consume are one call, so nothing can race between them.

Guard 3 is beyond BUILD.md: without it, a genuine offer from merchant A replayed against merchant B quoting identical terms would have passed.

C6 — gateway orchestrator

Files. `gateway/forward.ts`, `gateway/orchestrator.ts`, `tests/forward.test.ts`, `tests/orchestrator.test.ts`

Header stripping is **prefix-based**, not the stub's fixed list. `X-Guard-Anything` would have sailed through, and `X-PAYMENT` — the v1 name the SDK still accepts — was not listed at all, so an agent could have smuggled its own payment under the older name.

Failure path	Reason code
merchant 500 on the paid retry	<code>UPSTREAM_UNAVAILABLE</code>
402 again on the paid retry	<code>SETTLEMENT_FAILED</code>
paid 200 with no <code>PAYMENT-RESPONSE</code>	<code>SETTLEMENT_FAILED</code>
facilitator reports <code>success: false</code>	<code>SETTLEMENT_FAILED</code>
timeout	<code>UPSTREAM_UNAVAILABLE</code>
the signer refuses	the signer's own code

BLOCK, HOLD and the caller's `maxAmountUsd` all return **before** any reservation, so nothing is signed and there is nothing to release.

Bug the live run caught that unit tests missed. `readPaymentRequired` returns `null` for any non-402, and the first draft treated `null` as "free resource". A merchant **404 came back as SETTLED / ALLOW** — a failed call reported to the agent as a success. Only a 2xx is a free resource now.

C7 — `POST /api/gw/request` (half done)

Files. `handlers/gw-request.ts`, `handlers/agentAuth.ts`, `tests/gw-request.test.ts`

Half	State
A — the public endpoint	 live, settling real money over HTTP
B — swap <code>@/core/mock</code> → <code>@/core</code>	 waits on CORE, plus blocker B7

Verified live over HTTP:

Case	Result
no X-Guard-Key	503 GUARD_UNAVAILABLE
unknown key	503 GUARD_UNAVAILABLE
http://169.254.169.254/...	422 , orchestrator never called
maxAmountUsd: "0.005" vs a \$0.01 quote	402 PER_TRANSACTION_LIMIT_EXCEEDED , txHash: null
valid request	200 + real txHash 0x5ff0eb...13c4
58th request in a minute	429 RATE_LIMITED — distinct from a policy 402

SSRF boundary. The agent supplies the URL, so the Guard fetches whatever it is given. The schema requires http(s) and blocks cloud metadata hosts. Private ranges are *not* blocked, because the demo targets localhost — see open question Q1.

Secret leakage. A test asserts the serialised response contains no private key, no RPC URL, no GUARD_HMAC , and none of the merchant's own response headers. Only the merchant's **body** is forwarded.

6. Open blockers

id	What	Owner	Blocks
B7	 <code>src/core/mock</code> and <code>src/core</code> have different signatures on all four functions, so C7's promised one-line swap will not compile. Mock: <code>evaluatePayment()</code> , <code>reserveBudget(intentId, amount)</code> , <code>commitBudget()</code> , <code>releaseBudget()</code> . Real: <code>evaluatePayment({intent, idempotencyKey})</code> , <code>reserveBudget(agentId, intentId, amount)</code> , <code>commitBudget(reservationId, txHash)</code> , <code>releaseBudget(reservationId, reason)</code> . PAY may not edit <code>src/core/**</code>	CORE	C7 half B
B3	Live network id is <code>eip155:84532</code> ; <code>src/core/db/seed.ts:33</code> and <code>src/core/policy/templates.ts:18</code> seed <code>allowedNetworks: ["base-sepolia"]</code> . Deny-by-default then blocks every payment	CORE	C7 half B
B6	Same shape for assets: seeds say <code>allowedAssets: ["USDC"]</code> , the wire carries the contract address <code>0x036CbD...F7e</code> . The intent stores the address, because a symbol is merchant-supplied and forgeable while an address is not	CORE	C7 half B
B8	<code>EvaluationResult</code> returns no approval expiry, so the 202 response uses a provisional 15-minute constant	CORE	cosmetic
B1	DEMO's <code>/api/sandbox/search</code> is still <code>notImplemented</code> , so PAY runs a throwaway seller. Delete <code>scripts/poc-seller.ts</code> + <code>app/api/gw/poc-seller/</code> when DEMO ships	DEMO	cleanup
B2	Buyer and seller must pin the same <code>@x402/*</code> major. PAY is on <code>2.22.0</code>	DEMO	integration
B5	The buyer needs test USDC , not gas — resolved, documented for whoever funds the next wallet	—	closed

B4 closed. The header names in the repo docs were investigated and are correct for v2.

Also owed to CORE

`ALLOW_TOKEN_INVALID` (403) was appended to `src/shared/errors.ts`, following that file's own append-only rule, because CLAUDE.md requires error codes come from the catalogue. CORE owns the file and should be told.

7. Decisions

Decision	Why
Throwaway seller at <code>app/api/gw/poc-seller/</code>	<code>app/api/gw/**</code> is PAY-owned; <code>app/api/sandbox/*</code> is DEMO's
<code>poc-seller.ts</code> exempt from the <code>@x402/*</code> ESLint ban	sellers use <code>@x402/next</code> , which the buyer-side adapter does not wrap
<code>poc-x402.ts</code> rewrites <code>Docs/x402-notes.md</code> on every run	C2's tests need byte-exact captures; hand-copying base64 is where that breaks
Test fixtures pinned, not read from the notes file	the notes file is overwritten each run; tests must not drift with it
Seller builds its handler on first request	reading env at module load breaks <code>next build</code>
<code>wrapFetchWithPayment</code> in the spike only	in the orchestrator it would sign before the policy engine runs
The SDK boundary is the <code>x402/</code> folder , not <code>adapter.ts</code> alone	<code>headers.ts</code> is SDK surface too; making it import from <code>adapter.ts</code> would invert the layering
Adapter takes a <code>Response</code> rather than fetching	<code>gateway/forward.ts</code> owns proxying; two request paths would duplicate the stripping rules
<code>SignInInput</code> carries the <code>PaymentRequired</code> envelope	the SDK needs it to build a payload, and searching <code>accepts[]</code> is the field-by-field re-check
Auth and rate limit fall back only under <code>USE MOCKS=1</code>	keeps DEMO unblocked without shipping an auth bypass; production fails closed
Only the merchant's body is returned to the agent	its headers could carry <code>set-cookie</code> or internal metadata

8. Known ceilings

Ceiling	Impact	Upgrade path
Spent allowTokens live in an in-process <code>Map</code>	replay protection is single-instance; on multiple lambdas a replay could land on a cold one	<code>used_allow_tokens</code> row under a unique constraint, so Postgres decides the race
Rate-limit counters are in-process	limits are per-instance	CORE's real limiter

Both are marked with `ponytail:` comments at the code site.

9. Remaining PAY work

#	Item	Blocked by	Size
1	<code>wallet/balance.ts</code> — the only stub left in the division. Feeds <code>EvaluationContext.walletAllowanceRemainingMinor</code> (policy rule 10). The RPC reads already exist in <code>fund-wallet.ts</code>	nobody	~15 min
2	C7 half B — the engine swap, plus the four call sites B7 forces	CORE	~10 min
3	Delete the throwaway seller and its route	DEMO	2 min
4	P6 — production deploy to Vercel	C7	~30 min
5	Move the allowToken replay store to Postgres	CORE's schema	optional

Non-code

- `.env.local` still has `MERCHANT_WALLET_ADDRESS` set to the agent's **own** address. Live runs looked correct only because the dev server was started with an override. Set it to a second address, or DEMO's.
- BaseScan screenshot for PPT slide 4.
- Send CORE: B3, B6, B7, B8 and the `ALLOW_TOKEN_INVALID` code.

Open question

Q1 — SSRF. The agent chooses the URL and the Guard fetches it *before* the merchant allowlist is consulted, because the price is not known until the 402 arrives. Cloud metadata hosts are blocked and non-http schemes are rejected, but private ranges are not, since the demo targets `localhost`. Worth deciding as a team whether the merchant allowlist should also be checked pre-forward.

10. How to run it

```
npm install
npm run wallet:fund      # prints a key when none is set, else address + balances
npm run dev              # terminal 1 – hosts the throwaway seller
npm run poc:x402         # terminal 2 – end to end, writes Docs/x402-notes.md
```

The full endpoint, with `USE MOCKS=1` so the demo key is accepted:

```
curl -s -X POST localhost:3000/api/gw/request \
  -H "X-Guard-Key: gk_live_researchbot_demo" -H "Content-Type: application/json" \
  -d '{"url":"http://localhost:3000/api/gw/poc-seller","method":"POST","body":{"query":"x402
```

```
npm test                # 100 tests
npm run typecheck
npm run lint             # the SDK boundary is enforced here
npm run build
```

⚠️ If port 3000 is taken, `next dev` falls back to 3001 and `NEXT_PUBLIC_APP_URL` must match, or the buyer shops at the wrong store. `poc:x402` names this in its error message.