



IBM Developer  
SKILLS NETWORK

# Winning Space Race with Data Science

Prathamesh Karande  
30 September 2025



# Outline

---

- Executive Summary
- Introduction
- Methodology
- Results
- Conclusion
- Appendix

# Executive Summary

---

- Summary of methodologies:
  1. Data Collection through API
  2. Data Collection with Web Scraping
  3. Data Wrangling
  4. Exploratory Data Analysis with SQL
  5. Exploratory Data Analysis with Data Visualization
  6. Interactive Visual Analytics with Folium
  7. Machine Learning Prediction
- Summary of all results:
  1. Exploratory Data Analysis result
  2. Interactive analytics in screenshots
  3. Predictive Analytics result

# Introduction

---

- Project background and context

Space X advertises Falcon 9 rocket launches on its website with a cost of 62 million dollars; other providers cost upward of 165 million dollars each, much of the savings is because Space X can reuse the first stage. Therefore, if we can determine if the first stage will land, we can determine the cost of a launch. This information can be used if an alternate company wants to bid against space X for a rocket launch. This goal of the project is to create a machine learning pipeline to predict if the first stage will land successfully.

- Problems you want to find answers-

What factors determine if the rocket will land successfully?- The interaction amongst various features that determine the success rate of a successful landing.- What operating conditions need to be in place to ensure a successful landing program.



Section 1

# Methodology

# Methodology

---

## Executive Summary

- Data collection methodology:
  - Data from SpaceX was obtained from 2 sources:
    - SpaceX API (<https://api.spacexdata.com/v4/rockets/>)
    - Web Scraping ([https://en.wikipedia.org/wiki/List\\_of\\_Falcon/\\_9/\\_and\\_Falcon\\_Heavy\\_launches](https://en.wikipedia.org/wiki/List_of_Falcon/_9/_and_Falcon_Heavy_launches))
- Perform data wrangling
  - Collected data was enriched by creating a landing outcome label based on outcome data after summarizing and analyzing features

# Executive Summary

- Perform exploratory data analysis (EDA) using visualization and SQL
- Perform interactive visual analytics using Folium and Plotly Dash
- Perform predictive analysis using classification models
  - Data that was collected until this step were normalized, divided in training and test data sets and evaluated by four different classification models, being the accuracy of each model evaluated using different combinations of parameters.

# Data Collection

---

- Describe how data sets were collected.
- You need to present your data collection process use key phrases and flowcharts
  - Datasets were collected from SpaceX API (<https://api.spacexdata.com/v4/rockets/>) and from Wikipedia ([https://en.wikipedia.org/wiki/List\\_of\\_Falcon/\\_9/\\_and\\_Falcon\\_Heavy\\_launches](https://en.wikipedia.org/wiki/List_of_Falcon/_9/_and_Falcon_Heavy_launches)), using web scraping technics.



# Data Collection – SpaceX API

---

- SpaceX offers a public API from where data can be obtained and then used; • This API was used according to the flowchart beside and then data is persisted.
- Source code: [Data Collection](#)



# Data Collection - Scraping

---


- Data from SpaceX launches can also be obtained from Wikipedia;
- Data are downloaded from Wikipedia according to the flowchart and then persisted.
- Source code: [Data Collection with Web Scraping](#)



# Data Wrangling

---

- Initially some Exploratory Data Analysis (EDA) was performed on the dataset.
- Then the summary launches per site, occurrences of each orbit and occurrences of mission outcome per orbit type were calculated.
- Finally, the landing outcome label was created from Outcome column.



- Source code: [Data Wrangling](#)

# EDA with Data Visualization


---

- The following SQL queries were performed:
  - Names of the unique launch sites in the space mission;
  - Top 5 launch sites whose name begins with the string 'CCA';
  - Total payload mass carried by boosters launched by NASA (CRS);
  - Average payload mass carried by booster version F9 v1.1;
  - Date when the first successful landing outcome in ground pad was achieved;
  - Names of the boosters which have success in drone ship and have payload mass between 4000 and 6000 kg;
  - Total number of successful and failure mission outcomes;
  - Names of the booster versions which have carried the maximum payload mass;
  - Failed landing outcomes in droneship, their booster versions, and launch site names for in year 2015; and
  - Rank of the count of landing outcomes (such as Failure (droneship) or Success (ground pad)) between the date 2010-06-04 and 2017-03-20.

# EDA with SQL

---

- To explore data, scatterplots and bar plots were used to visualize the relationship between pair of features:
- Payload Mass X Flight Number, Launch Site X Flight Number, Launch Site X Payload Mass, Orbit and Flight Number, Payload and Orbit
- Source code: [EDA with SQL](#)





# Build an Interactive Map with Folium

---

- Markers, circles, lines and marker clusters were used with Folium Maps
- Markers indicate points like launch sites;
- Circles indicate highlighted areas around specific coordinates, like NASA Johnson Space Center;
- Marker clusters indicates groups of events in each coordinate, like launches in a launch site; and
- Lines are used to indicate distances between two coordinates.
- Source code: [Build an Interactive Map with Folium](#)

# Build a Dashboard with Plotly Dash

---

- We built an interactive dashboard with Plotly dash
- We plotted pie charts showing the total launches by a certain sites
- We plotted scatter graph showing the relationship with Outcome and Payload Mass (Kg) for the different booster version.
- [The link to the notebook is here.](#)

# Predictive Analysis (Classification)

---

- We loaded the data using numpy and pandas, transformed the data, split our data into training and testing.
- We built different machine learning models and tune different hyperparameters using GridSearchCV.
- We used accuracy as the metric for our model, improved the model using feature engineering and algorithm tuning.
- We found the best performing classification model.
- [The link to the notebook is here.](#)

# Results

---

- Exploratory data analysis results:
  - Space X uses 4 different launch sites;
  - The first launches were done to Space X itself and NASA;
  - The average payload of F9 v1.1 booster is 2,928 kg;
  - The first success landing outcome happened in 2015 five year after the first launch;
  - Many Falcon 9 booster versions were successful at landing in drone ships having payload above the average;
  - Almost 100% of mission outcomes were successful;
  - Two booster versions failed at landing in drone ships in 2015: F9 v1.1 B1012 and F9 v1.1 B1015;
  - The number of landing outcomes became as better as years passed.

# Results

- Using interactive analytics was possible to identify that launch sites use to be in safety places, near sea, for example and have a good logistic infrastructure around.
- Most launches happens at east cost launch sites.





The background of the slide is an abstract composition. It features a dark blue base color. Overlaid on this are numerous diagonal streaks in shades of red and cyan. A faint, light blue grid pattern is also visible, particularly in the lower half of the image. The overall effect is dynamic and technological.

Section 2


# Insights drawn from EDA



# Flight Number vs. Launch Site

---

- From the plot, we found that the larger the flight amount at a launch site, the greater the success rate at a launch site.




# Payload vs. Launch Site

---

- Payload vs. Launch Site




The greater the payload mass for launch site CCAFS SLC 40 the higher the success rate for the rocket.



# Success Rate vs. Orbit Type


- From the plot, we can see that ES-L1, GEO, HEO, SSO, VLEO had the most success rate.



# Flight Number vs. Orbit Type

---

- The plot below shows the Flight Number vs. Orbit type. We observe that in the LEO orbit, success is related to the number of flights whereas in the GTO orbit, there is no relationship between flight number and the orbit.






# Payload vs. Orbit Type

---


- We can observe that with heavy payloads, the successful landing are more for PO, LEO and ISS orbits.



# Launch Success Yearly Trend

---

- From the plot, we can observe that success rate since 2013 kept on increasing till 2020



# All Launch Site Names

---

- We used the key word DISTINCT to show only unique launch sites from the SpaceX data.

Display the names of the unique launch sites in the space mission

```
In [10]: task_1 = '''  
          SELECT DISTINCT LaunchSite  
          FROM SpaceX  
          ...  
          create_pandas_df(task_1, database=conn)
```

Out[10]:

	launchsite
0	KSC LC-39A
1	CCAFS LC-40
2	CCAFS SLC-40
3	VAFB SLC-4E

# Launch Site Names Begin with 'CCA'

- We used the query above to display 5 records where launch sites begin with 'CCA'

Display 5 records where launch sites begin with the string 'CCA'

```
In [11]: task_2 = '''
        SELECT *
        FROM SpaceX
        WHERE LaunchSite LIKE 'CCA%'
        LIMIT 5
        '''
        create_pandas_df(task_2, database=conn)
```

Out[11]:

	date	time	boosterversion	launchsite	payload	payloadmasskg	orbit	customer	missionoutcome	landingoutcome
0	2010-04-06	18:45:00	F9 v1.0 B0003	CCAFS LC-40	Dragon Spacecraft Qualification Unit	0	LEO	SpaceX	Success	Failure (parachute)
1	2010-08-12	15:43:00	F9 v1.0 B0004	CCAFS LC-40	Dragon demo flight C1, two CubeSats, barrel of...	0	LEO (ISS)	NASA (COTS) NRO	Success	Failure (parachute)
2	2012-05-22	07:44:00	F9 v1.0 B0005	CCAFS LC-40	Dragon demo flight C2	525	LEO (ISS)	NASA (COTS)	Success	No attempt
3	2012-08-10	00:35:00	F9 v1.0 B0006	CCAFS LC-40	SpaceX CRS-1	500	LEO (ISS)	NASA (CRS)	Success	No attempt
4	2013-01-03	15:10:00	F9 v1.0 B0007	CCAFS LC-40	SpaceX CRS-2	677	LEO (ISS)	NASA (CRS)	Success	No attempt

# Total Payload Mass

---

- We calculated the total payload carried by boosters from NASA as 45596 using the query below

```
Display the total payload mass carried by boosters launched by NASA (CRS)
```

```
In [12]: task_3 = '''
          SELECT SUM(PayloadMassKG) AS Total_PayloadMass
          FROM SpaceX
          WHERE Customer LIKE 'NASA (CRS)'
          '''
          create_pandas_df(task_3, database=conn)
```

```
Out[12]:
```

	total_payloadmass
0	45596



# Average Payload Mass by F9 v1.1

---

- We calculated the average payload mass carried by booster version F9 v1.1 as 2928.4

```
Display average payload mass carried by booster version F9 v1.1

In [13]: task_4 = '''
          SELECT AVG(PayloadMassKG) AS Avg_PayloadMass
          FROM SpaceX
          WHERE BoosterVersion = 'F9 v1.1'
          '''

          create_pandas_df(task_4, database=conn)

Out[13]:
```

	avg_payloadmass
0	2928.4

# First Successful Ground Landing Date

---

- We observed that the dates of the first successful landing outcome on ground pad was 22nd December 2015

```
In [14]: task_5 = '''  
          SELECT MIN(Date) AS FirstSuccessfull_landing_date  
          FROM SpaceX  
          WHERE LandingOutcome LIKE 'Success (ground pad)'  
          '''  
  
          create_pandas_df(task_5, database=conn)
```

```
Out[14]:
```

	firstsuccessfull_landing_date
0	2015-12-22

## Successful Drone Ship Landing with Payload between 4000 and 6000

---

- We used the WHERE clause to filter for boosters which have successfully landed on drone ship and applied the AND condition to determine successful landing with payload mass greater than 4000 but less than 6000

```
In [15]: task_6 = '''
          SELECT BoosterVersion
          FROM SpaceX
          WHERE LandingOutcome = 'Success (drone ship)'
             AND PayloadMassKG > 4000
             AND PayloadMassKG < 6000
          ...
          create_pandas_df(task_6, database=conn)
```

```
Out[15]:
```

	boosterversion
0	F9 FT B1022
1	F9 FT B1026
2	F9 FT B1021.2
3	F9 FT B1031.2

# Total Number of Successful and Failure Mission Outcomes

- We used wildcard like '%' to filter for WHERE MissionOutcome was a success or a failure.

```
List the total number of successful and failure mission outcomes

In [16]: task_7a = '''
          SELECT COUNT(MissionOutcome) AS SuccessOutcome
          FROM SpaceX
          WHERE MissionOutcome LIKE 'Success%'
          '''

          task_7b = '''
          SELECT COUNT(MissionOutcome) AS FailureOutcome
          FROM SpaceX
          WHERE MissionOutcome LIKE 'Failure%'
          '''

          print('The total number of successful mission outcome is:')
          display(create_pandas_df(task_7a, database=conn))
          print()
          print('The total number of failed mission outcome is:')
          create_pandas_df(task_7b, database=conn)

The total number of successful mission outcome is:
  successoutcome
0              100

The total number of failed mission outcome is:
Out[16]:  failureoutcome
0              1
```

# Boosters Carried Maximum Payload

---

- We determined the booster that have carried the maximum payload using a subquery in the WHERE clause and the MAX() function

List the names of the booster\_versions which have carried the maximum payload mass. Use a subquery

```
In [17]: task_8 = '''
          SELECT BoosterVersion, PayloadMassKG
          FROM SpaceX
          WHERE PayloadMassKG = (
              SELECT MAX(PayloadMassKG)
              FROM SpaceX
          )
          ORDER BY BoosterVersion
          ...
          create_pandas_df(task_8, database=conn)
          '''
```

Out[17]:

	boosterversion	payloadmasskg
0	F9 B5 B1048.4	15600
1	F9 B5 B1048.5	15600
2	F9 B5 B1049.4	15600
3	F9 B5 B1049.5	15600
4	F9 B5 B1049.7	15600
5	F9 B5 B1051.3	15600
6	F9 B5 B1051.4	15600
7	F9 B5 B1051.6	15600
8	F9 B5 B1056.4	15600
9	F9 B5 B1058.3	15600
10	F9 B5 B1060.2	15600
11	F9 B5 B1060.3	15600

# 2015 Launch Records

---

- We used a combinations of the WHERE clause, LIKE, AND, and BETWEEN conditions to filter for failed landing outcomes in drone ship, their booster versions, and launch site names for year 2015

List the failed landing\_outcomes in drone ship, their booster versions, and launch site names for in year 2015

```
In [18]: task_9 = '''
        SELECT BoosterVersion, LaunchSite, LandingOutcome
        FROM SpaceX
        WHERE LandingOutcome LIKE 'Failure (drone ship)'
        AND Date BETWEEN '2015-01-01' AND '2015-12-31'
        ...
        create_pandas_df(task_9, database=conn)
```

Out[18]:

	boosterversion	launchsite	landingoutcome
0	F9 v1.1 B1012	CCAFS LC-40	Failure (drone ship)
1	F9 v1.1 B1015	CCAFS LC-40	Failure (drone ship)

# Rank Landing Outcomes Between 2010-06-04 and 2017-03-20

---

- We selected Landing outcomes and the COUNT of landing outcomes from the data and used the WHERE clause to filter for landing outcomes BETWEEN 2010-06-04 to 2017-03-20.
- We applied the GROUP BY clause to group the landing outcomes and the ORDER BY clause to order the grouped landing outcome in descending order.

Rank the count of landing outcomes (such as Failure (drone ship) or Success (ground pad))

```
In [19]: task_10 = '''
        SELECT LandingOutcome, COUNT(LandingOutcome)
        FROM SpaceX
        WHERE DATE BETWEEN '2010-06-04' AND '2017-03-20'
        GROUP BY LandingOutcome
        ORDER BY COUNT(LandingOutcome) DESC
        '''
        create_pandas_df(task_10, database=conn)
```

Out[19]:

	landingoutcome	count
0	No attempt	10
1	Success (drone ship)	6
2	Failure (drone ship)	5
3	Success (ground pad)	5
4	Controlled (ocean)	3
5	Uncontrolled (ocean)	2
6	Precluded (drone ship)	1
7	Failure (parachute)	1



A satellite view of Earth from space, showing the curvature of the planet and city lights at night. The image is a composite of a dark blue sky with stars and a view of the Earth's surface from space. The Earth's surface is mostly dark blue, with a thin layer of white clouds. A bright, glowing arc of city lights is visible along the horizon, indicating a coastal or urban area. The text "Section 3" is overlaid on the left side of the image.

Section 3

# Launch Sites Proximities Analysis




# All launch sites global map markers


---



# Markers showing launch sites with color labels



# Launch Site distance to landmarks








Section 4

# Build a Dashboard with Plotly Dash

## Pie chart showing the success percentage achieved by each launch site

---


Total Success Launches By all sites



*We can see that KSC LC-39A had the most successful launches from all the sites*


## Pie chart showing the Launch site with the highest launch success ratio

---



## Scatter plot of Payload vs Launch Outcome for all sites, with different payload selected in the range slider

---



*We can see the success rates for low weighted payloads is higher than the heavy weighted payloads*





Section 5

# Predictive Analysis (Classification)



# Classification Accuracy

---

- The decision tree classifier is the model with the highest classification accuracy

```
models = {'KNeighbors': knn_cv.best_score_,
          'DecisionTree': tree_cv.best_score_,
          'LogisticRegression': logreg_cv.best_score_,
          'SupportVector': svm_cv.best_score_}

bestalgorithm = max(models, key=models.get)
print('Best model is', bestalgorithm, 'with a score of', models[bestalgorithm])
if bestalgorithm == 'DecisionTree':
    print('Best params is:', tree_cv.best_params_)
if bestalgorithm == 'KNeighbors':
    print('Best params is:', knn_cv.best_params_)
if bestalgorithm == 'LogisticRegression':
    print('Best params is:', logreg_cv.best_params_)
if bestalgorithm == 'SupportVector':
    print('Best params is:', svm_cv.best_params_)
```


Best model is DecisionTree with a score of 0.8732142857142856

Best params is : {'criterion': 'gini', 'max\_depth': 6, 'max\_features': 'auto', 'min\_samples\_leaf': 2, 'min\_samples\_split': 5, 'splitter': 'random'}

# Confusion Matrix

---

- The confusion matrix for the decision tree classifier shows that the classifier can distinguish between the different classes. The major problem is the false positives .i.e., unsuccessful landing marked as successful landing by the classifier



# Conclusions

---

- We can conclude that:
  - The larger the flight amount at a launch site, the greater the success rate at a launch site.
  - Launch success rate started to increase in 2013 till 2020.
  - Orbits ES-L1, GEO, HEO, SSO, VLEO had the most success rate. • KSC LC-39A had the most successful launches of any sites.
  - The Decision tree classifier is the best machine learning algorithm for this task

Thank you!

