

N meetings in one room

Submissions: 16320 (/problem_submissions.php?pid=443) Accuracy: 51.24% Difficulty: Easy
(<https://practice.geeksforgeeks.org/Easy/0/0/>) Marks: 2

Associated Course(s): [Geeks Classes \(/courses/geeks-classes/\)](/courses/geeks-classes/) [Sudo Placement \(/courses/sudo-placement/\)](/courses/sudo-placement/)
More

Show Topic Tags

Company Tags

[Amazon \(/company/Amazon/\)](/company/Amazon/)

[Flipkart \(/company/Flipkart/\)](/company/Flipkart/)

[MakeMyTrip \(/company/MakeMyTrip/\)](/company/MakeMyTrip/)

[Morgan Stanley \(/company/Morgan Stanley/\)](/company/Morgan Stanley/)

[Visa \(/company/Visa/\)](/company/Visa/)

Problems

There is **one** meeting room in a firm. There are **N** meetings in the form of $(S[i], F[i])$ where $S[i]$ is start time of meeting i and $F[i]$ is finish time of meeting i .

What is the *maximum* number of meetings that can be accommodated in the meeting room?

Input:

The first line of input consists number of the test cases. The description of T test cases is as follows:

The first line consists of the size of the array, second line has the array containing the starting time of all the meetings each separated by a space, i.e., $S[i]$. And the third line has the array containing the finishing time of all the meetings each separated by a space, i.e., $F[i]$.

Output:

In each separate line print the order in which the meetings take place separated by a space.

Constraints:

$$1 \leq T \leq 70$$

$$1 \leq N \leq 100$$

$$1 \leq S[i], F[i] \leq 100000$$

Example:

Input:

2

6

1 3 0 5 8 5

2 4 6 7 9 9

8

75250 50074 43659 8931 11273 27545 50879 77924

112960 114515 81825 93424 54316 35533 73383 160252

Output:

1 2 4 5

6 7 1

Explanation:

Testcase 1: Four meetings can held with given start and end timings.

**** For More Input/Output Examples Use 'Expected Output' option ****

Author: madhuradlakha (<https://auth.geeksforgeeks.org/user/madhuradlakha/practice/>)

(/problem_submissions.php?pid=443) (/problem_submissions.php?pid=443&isSolved=ALL&lang=ALL&user=Self)

My Submissions

All Submissions

Editorial (/editorial.php?pid=443)

Monokai



C++ (g++ 5.4)



(<https://auth.geeksforgeeks.org/edit-profile.php>)

```

1 #include<bits/stdc++.h>
2 using namespace std;
3 struct meeting{
4     int start;
5     int end;
6     int pos;
7 };
8 bool comparator(meeting m1,meeting m2){
9     return(m1.end<m2.end);
10 }
11 int main()
12 {
13     int t,n;
14     cin>>t;
15     while(t--){
16         cin>>n;
17         struct meeting meet[n];
18         for(int i=0;i<n;i++){
19             cin>>meet[i].start;
20         }
21         for(int i=0;i<n;i++){
22             cin>>meet[i].end;
23             meet[i].pos=i+1;
24         }
25     }

```