State-Filtered Deliberation: Stage-Isolated Context Management for Small Open-Weight Software Engineering Agents

Karandeep Singh Sodhi
Independent Researcher (`https://github.com/KarandeepSinghSodhi/gemma-sfd-agent`)
Submitted to the Gemma 4 Developer Agent Challenge (Paper Track) — October 2026

Abstract

Autonomous software engineering (SWE) agents built on small open-weight language models (such as 4-bit quantized Gemma 4 E2B and E4B) face tight context and capability constraints when executing multi-turn debugging trajectories. On the official `gemma-4-developer-agent` benchmark (snapshot stored in `results/leaderboard_snapshot_2026_10_26.json`, retrieved 2026-10-26 UTC), while 31B submissions with fine-tuned LoRA adapters reach public resolution rates of 22.0%–24.0%, all 197 participating teams on the official Small Model Prize leaderboard (`results/small_model_leaderboard_2026_10_24.csv`, updated 2026-10-24 23:58 UTC) score between 0.0% and 10.0%, with a median of 5.0% and 92.9% of teams (183/197) scoring $\leq 6.0\%$.

We study **State-Filtered Deliberation (SFD)**, a declarative three-stage `SequentialAgent` architecture built on Google's Agent Development Kit (ADK) and the `swegemma` harness. SFD partitions the repair workflow into three role-restricted sub-agents —`TriageAgent` (read-only localization), `PatchAgent` (code editing), and `VerifierAgent` (targeted testing and submission)—and configures `include_contents: "none"` on `PatchAgent` and `VerifierAgent` so that intermediate tool calls and observations from preceding stages are sliced out of the prompt context at stage boundaries while passing structured text state variables (`localization_packet` and `patch_manifest`) through `session.state`. Crucially, SFD deterministically bounds **stage-entry** prompt context rather than total or within-stage peak context (`TriageAgent` itself is not reset). Across a paired evaluation on `gemma-4-e4b-it-qat-w4a16-ct` ($n = 16$ tasks across all four competition repositories on 4x NVIDIA L4 GPUs) against both the official competition starter kit (`flat_starter`, using a discretionary `code_analyzer AgentTool`) and an unconfounded single-agent baseline (`flat_controlled`, sharing identical tools, prompts, and sampling parameters), SFD resolves 1/16 tasks (6.2%, 95% Wilson CI [1.1%, 28.3%]) compared to 1/16 (6.2%) for `flat_starter` (McNemar $p = 1.0000$) and 0/16 (0.0%) for `flat_controlled` (McNemar $p = 1.0000$). While SFD resets stage-entry prompts from a mean `TriageAgent` peak of 10922.1 tokens down to 1500.9 tokens at `PatchAgent` entry (a −86.3% peak-to-entry reset) and reduces mean single-call peak prompt tokens across tasks (11291.9 vs. 13029.3 and 13550.8), maximum trajectory peak tokens remain comparable (16146 vs. 15281 and 16154), and SFD's single resolved task (`rich_4077`) is attributable to an accurate one-line fix specification produced during the dedicated triage stage rather than relief from context overflow. All execution traces (`ATIF-v1.7`), leaderboard snapshots, and aggregation scripts are publicly available at `https://github.com/KarandeepSinghSodhi/gemma-sfd-agent`.

1. Introduction & Motivating Hypotheses

Repository-level software engineering benchmarks such as SWE-bench ((Jimenez et al., 2024)) evaluate whether language model agents can diagnose bug reports, navigate multi-file codebases, synthesize patches, and pass unit test suites. While frontier models and 31B open-weight models achieve strong resolution rates using iterative ReAct loops ((Yao et al., 2023); (Yang et al., 2024); (Wang et al., 2024)), deploying autonomous coding agents on local developer workstations requires compact, quantized open-weight models such as the Gemma 4 family (E2B, E4B, 12B, 31B) ((Gemma Team, Google DeepMind, 2026)).

Empirical data from the Google Gemma 4 Developer Agent Challenge highlights the severity of this capability gap. In our archived leaderboard snapshots (`results/leaderboard_snapshot_2026_10_26.json`, retrieved 2026-10-26 UTC, and `results/small_model_leaderboard_2026_10_24.csv` from `ryanholbrook/gemma-4-developer-agent-small-model-leaderboard`, updated 2026-10-24 23:58 UTC), the official competition starter baseline running on `gemma-4-31b-it-qat-w4a16-ct` with fine-tuned LoRA adapters achieves a 22.0% (`0.22`) public resolution rate and the top 31B submissions reach 24.0% (`0.24`). By contrast, across all $N = 197$ participating teams on the official Small Model Prize leaderboard (restricted to E2B/E4B models), public resolution scores range from 0.0% (`0.00`) to 10.0% (`0.10`), with a median of 5.0% (`0.05`), a mean of 4.23% (`0.0423`), and 183 of 197 teams (92.9%) scoring $\leq 6.0\%$ (`0.06`). (Our own full-set competition submission, Ref `#57643078` submitted 2026-10-25 21:22:35 UTC, remained in `SubmissionStatus.PENDING` (`public_score: null`) in the asynchronous evaluation queue at the time of snapshot retrieval on 2026-10-26 UTC.)

We investigate how agent workflow structure and stage-boundary context slicing affect `gemma-4-e4b-it-qat-w4a16-ct` under the competition's declarative Google Agent Development Kit (ADK) and `swegemma` harness. We formulate and test three specific hypotheses:

1. **Prompt-Length Error Correlation Hypothesis (Hypothesis 1):** In multi-turn trajectories, as per-call prompt length P_t increases with accumulated tool observations, we hypothesize that tool call errors (malformed `edit_file` search blocks or

invalid arguments) and duplicate file reads occur more frequently. We test this observationally by bucketing all recorded LLM calls by prompt token length P_t.

2. **Discretionary Sub-Agent Under-Utilization Hypothesis (Hypothesis 2):** The official competition starter kit (`sample_submission/agent.yaml`) already provides a read-only `code_analyzer` sub-agent wrapped as an `AgentTool` (`skip_summarization: true`) alongside all nine built-in `swegemma` tools on the root `swe_baseline_agent`. Because invoking `code_analyzer` is discretionary, we hypothesize that a 4B model rarely delegates to `code_analyzer` and instead executes exploratory file reads directly inside its root context window.
3. **Stage-Entry Context Reset & Role Partitioning Hypothesis (Hypothesis 3):** Replacing discretionary delegation with a mandatory `SequentialAgent` pipeline (`TriageAgent` → `PatchAgent` → `VerifierAgent`) that sets `include_contents: "none"` on `PatchAgent` and `VerifierAgent` deterministically bounds **stage-entry** prompt length (though not `TriageAgent` or within-stage peak prompt length) and separates localization from code editing.

2. Context Mechanics in `swegemma` and Google ADK

2.1 Prompt Growth and the Token Signal Ratio

Consider an agent trajectory across LLM calls $t \in \{1, 2, ..., T\}$. Let P_t denote the prompt token count and C_t the completion token count on call t. In a continuous single-agent session (`include_contents: "default"`), the prompt at call t concatenates the system instruction s_0, the initial harness task prompt u_0, and all prior assistant turns a_i and tool observations o_i:

$$P_t = |s_0| + |u_0| + \sum_{i=1}^{t-1}(|a_i| + |o_i|)$$

In the `swegemma` harness, even at call $t = 1$, $|s_0| + |u_0|$ spans 1,900–4,800 tokens because `build_agent_prompt()` embeds the problem statement, budget rules, tool schemas, and up to 200 breadth-first directory tree entries under `/workspace`. Furthermore, `swegemma` configures Google ADK's `EventsCompactionConfig` (`compaction_interval=15`, `token_threshold=14336`, `event_retention_size=5`) to compact long histories after 15 turns.

2.2 Exact Stage-Boundary Slicing via `include_contents: "none"` in Google ADK

Inspection of `google-adk==1.36.1` (`google/adk/flows/llm_flows/contents.py` and `functions.py`) establishes the exact runtime behavior when `SequentialAgent` transitions between sub-agents:

- When a sub-agent executes a tool call, `functions.py` records both the `function_call` event and the resulting `function_response` event with `event.author = invocation_context.agent.name`.
- When `include_contents: "none"` is configured on `PatchAgent` (or `VerifierAgent`), `_ContentLlmRequestProcessor` calls `_get_current_turn_contents(branch, session.events, agent.name)`. This function scans `session.events` backward from `len(events) - 1` and stops at the first event where `event.author == "user"` or `_is_other_agent_reply(agent.name, event)` is `True`—which is the **immediately preceding sub-agent's final text emission event** e_k.
- `_get_current_turn_contents` slices `session.events[k:]`, excluding `events[:k]` (both `events[0]`, the initial 200-entry workspace layout tree, and all intermediate `function_call`, `function_response`, and thought blocks from earlier stages).
- Crucially, within the active sub-agent's own multi-step loop, all new tool calls and responses (`events[k+1:]`) have `event.author == agent.name`, so the backward scan retains the sub-agent's complete within-stage tool history. Thus, `include_contents: "none"` bounds **stage-entry** prompt length by construction, but does **not** bound within-stage prompt growth if a sub-agent makes many tool calls.

3. Architecture & Runtime-Enforced vs. Prompt-Requested Rules

All configurations execute inside `swegemma`, which provides nine built-in tools: `run_command`, `read_file`, `edit_file`, `write_file`, `get_status`, `submit_patch`, and the pre-computed NetworkX AST call-graph and `.npz` symbol-embedding tools `search_similar_code`, `get_code_neighbors`, and `get_code_subgraph`. SFD (`sub_sfd`) chains three sub-agents under a root `SequentialAgent`:

1. **`TriageAgent` (`include_contents: "default"`, `output_key: "localization_packet"`):** Restricted in YAML to five read-only tools (`search_similar_code`, `get_code_neighbors`, `get_code_subgraph`, `read_file`, `get_status`).
2. **`PatchAgent` (`include_contents: "none"`, `output_key: "patch_manifest"`):** Restricted in YAML to four workspace tools (`read_file`, `edit_file`, `write_file`, `get_status`). Interpolates `{problem_description?}` and `{localization_packet?}` via `inject_session_state()`.
3. **`VerifierAgent` (`include_contents: "none"`):** Configured with `run_command`, `read_file`, `edit_file`, `get_status`, and `submit_patch`. Interpolates `{problem_description?}`, `{localization_packet?}`, and `{patch_manifest?}`.

Table 1 separates constraints enforced in code/YAML from behaviors requested only via prompts. Importantly, we did **not** tune or alter the SFD code/YAML design after inspecting evaluation traces.

Mechanism / Rule	Enforced in Code / YAML Config	Prompt-Requested Only (Unenforced)
Stage execution & tool separation	`SequentialAgent` order; per-stage `tools:` lists in `sub_agents/*.yaml`	Stopping after ≤ 3 tool calls in `TriageAgent` / `PatchAgent`
Cross-stage context reset	`include_contents: "none"` slices `events[k:]` at stage entry	Within-stage prompt growth & per-stage tool call count
State packet handoff	`output_key` writes final text to `session.state`; `{var?}` interpolation	Formatting text inside `<localization_packet>` / `<patch_manifest>` tags
Observation size caps	`read_file` ≤ 150 lines / 10k chars; `run_command` stdout ≤ 5k chars	Reading narrow `start_line..end_line` slices
Test & workspace hygiene	`strip_protected_files_from_patch` strips edits to `tests/*`, `pytest.ini`, `conftest.py`	Running targeted `pytest` (not bare `pytest`); putting scratch scripts in `/tmp/`
Task session budgets	Global session caps: `max_tool_calls=15`, `max_turns=20`, `max_time_minutes=2.5`	Calling `submit_patch` before global budget exhaustion

Table 1: Separation between runtime-enforced constraints (`swegemma` / `google-adk`) and prompt-level directives.

4. Experimental Setup & Paired Evaluation Results

4.1 Hardware, Sampling Design, and Unconfounded Baselines

All experiments were executed on Kaggle's 4x NVIDIA L4 GPU environment (`machine_shape: "NvidiaL4"`, 96 GB total VRAM, `tensor_parallel_size=4`, `vLLM` serving `gemma-4-e4b-it-qat-w4a16-ct` with `max_model_len=32768`, `tool_call_parser="gemma4"`, `reasoning_parser="gemma4"`). Every configuration shares identical generation parameters (`temperature: 0.0`, `seed: 42`, `max_output_tokens: 8192`, `thinking_budget: 1536`, `include_thoughts: true`) and global task budgets (`max_tool_calls: 15`, `max_turns: 20`, `max_time_minutes: 2.5`, `timeout_seconds: 60`, `verification_timeout_seconds: 120`). The evaluated dataset ($n = 16$ unique tasks, 48 primary paired runs plus 16 rerun reproducibility runs = 64 total `swegemma` runs on 4x L4 GPUs) comprises two disjoint 8-task cohorts stratified across `fastapi/fastapi`, `Textualize/rich`, `psf/requests`, and `encode/httpx`: **Cohort 1** (first k_r tasks per repo in canonical `tasks.jsonl` order, $n = 8$) yielded 1/8 (12.5%) for `sfd` (`rich_4077`), 0/8 (0.0%) for `flat_starter`, and 0/8 (0.0%) for `flat_controlled`; **Cohort 2** (disjoint seeded-random stratified sample using `random.Random(42)`, $n = 8$) yielded 0/8 (0.0%) for `sfd`, 1/8 (12.5%) for `flat_starter` (`fastapi_9753`), and 0/8 (0.0%) for `flat_controlled`.

On each task, we evaluate three configurations back-to-back:

- **`flat_starter`**: Official competition starter kit (`sample_submission/agent.yaml` with `code_analyzer` `AgentTool` and `prompts/system.md`, adapted to `gemma-4-e4b-it-qat-w4a16-ct`).
- **`flat_controlled`**: Single `LlmAgent` with the exact same 9 tools and combined 3-phase prompt instructions as `sfd`, isolating the effect of `SequentialAgent` + `include_contents: "none"` + stage tool partitioning.
- **`sfd`**: Our 3-stage `SequentialAgent` pipeline.

4.2 Aggregate Resolution, Patch Failure Split, and Context Metrics

Table 2 reports the aggregate metrics computed by `scripts/aggregate.py` from the ATIF v1.7 traces (`traces/`). To separate budget exhaustion from incorrect code edits, the **Fail: No Patch / Wrong Patch** column explicitly splits unresolved tasks into those that produced no patch due to time/tool budget exhaustion (`timeout_or_budget_no_patch`) versus those that generated a non-empty patch that failed Phase 2 `pytest` verification (`test_verification_failed`). **Mean Peak P_t** is the mean across tasks of each task's maximum single-call `prompt_tokens` ($\max_t P_t$), while **Max Peak P_t** is the maximum single-call `prompt_tokens` across all calls and tasks.

Configuration	Resolved	95% Wilson CI	Non-Empty Patch	Fail: No / Wrong Patch	Mean Peak P_t	Max Peak P_t	Mean Cum. Tokens	Mean Tools	Mean Time
Official Starter Kit (`agent_tool` pattern)	1/16 (6.2%)	[1.1%, 28.3%]	13/16 (81.2%)	3 / 12	13029.3	15281	103350.1	9.9	97.3s
Controlled Single-Agent (`LlmAgent`)	0/16 (0.0%)	[0.0%, 19.4%]	14/16 (87.5%)	2 / 14	13550.8	16154	119664.4	10.5	92.2s
State-Filtered Deliberation (`SequentialAgent`)	1/16 (6.2%)	[1.1%, 28.3%]	14/16 (87.5%)	2 / 13	11291.9	16146	88909.5	11.2	89.4s

Table 2: Paired evaluation results on `gemma-4-e4b-it-qat-w4a16-ct` ($n = 16$ tasks on 4x NVIDIA L4 GPUs). **Mean Tools** reports budget-counted tool calls (`session.state["tool_calls_used"]`).

Statistical Comparison & Power Considerations:

- **`sfd` vs. `flat_starter`:** Absolute difference $\Delta = -0.00\%$, 95% paired bootstrap CI $[-18.75\%, +18.75\%]$, discordant pairs $(b = 1, c = 1)$, exact two-sided McNemar $p = 1.0000$.
- **`sfd` vs. `flat_controlled`:** Absolute difference $\Delta = +6.25\%$, 95% paired bootstrap CI $[-0.00\%, +18.75\%]$, discordant pairs $(b = 1, c = 0)$, exact two-sided McNemar $p = 1.0000$.
- **Rerun Reproducibility under `vLLM` Tensor Parallelism (`tp=4, temperature=0.0, seed=42`):** Rerunning `sfd` ($n = 8$) and `flat_controlled` ($n = 8$) on Cohort 1 (`traces/rerun_results/`) produced 8/8 (100.0%) and 7/8 (87.5%) `resolved` agreement (`6/8` and `8/8` patch-presence agreement), with a mean absolute peak prompt drift of 2427.2 tokens (max 5292) for `sfd` and 1797.4 tokens (max 4457) for `flat_controlled` due to non-associative parallel GPU reductions. Notably, while `sfd_rerun` again resolved `rich_4077` (1/8), `flat_controlled_rerun` also generated `self.__file.isatty()` and resolved `rich_4077` (1/8), demonstrating that the 1-task difference on `rich_4077` in Run 1 lies within `tp=4` floating-point run-to-run variance.

Stage-Entry Context Reset vs. Trajectory Peak Context: The trace data demonstrate an important distinction between **stage-entry** prompt length and **trajectory-peak** prompt length. Across the `sfd` runs ($n = 16$), `TriageAgent` (which has `include_contents: "default"` and is never reset) reaches a mean peak prompt of **10922.1 tokens** and a maximum of **16146 tokens** (hitting `16,146` on `rich_4076`, `15,605` on `fastapi_14459`, `14,528` on `rich_3944`, `14,454` on `fastapi_15589`, and `14,446` on `requests_7502`). When `SequentialAgent` transitions to `PatchAgent` (`include_contents: "none"`), the entry prompt on `PatchAgent`'s first LLM call drops to a mean of **1500.9 tokens** (max **2126 tokens**)—a **−86.3% cross-boundary peak-to-entry reset** that holds by construction because `_get_current_turn_contents()` slices out prior tool history and `events[0]` and injects only the problem statement and `<localization_packet>`. Similarly, `VerifierAgent` entry resets to a mean of **1470.2 tokens** (max **2165 tokens**) after `PatchAgent` reaches a within-stage mean peak of **5355.9 tokens** (max **12680 tokens**). While this lowers mean single-call peak prompt tokens across tasks by 13.3% vs. `flat_starter` (11291.9 vs. 13029.3) and 16.7% vs. `flat_controlled` (11291.9 vs. 13550.8), SFD does **not** bound trajectory peak prompt length: SFD's maximum peak (16146) is virtually identical to `flat_starter` (15281) and `flat_controlled` (16154), and on tasks such as `requests_7502` (`14,446` vs. `10,436` / `11,238`) and `rich_4076` (`16,146` vs. `12,860` / `14,849`), SFD peaked higher than both baselines.

5. Per-Task Trace Analysis, Hypothesis Tests & Failure Audit

Task ID	Repository	`flat_starter` (Peak P_t)	`flat_controlled` (Peak P_t)	`sfd` (Peak P_t)
fastapi_14099	fastapi/fastapi	Fail (test verification failed) (15281)	Fail (timeout or budget no patch) (13933)	Fail (test verification failed) (15961)
fastapi_14361	fastapi/fastapi	Fail (test verification failed) (10191)	Fail (test verification failed) (15010)	Fail (test verification failed) (9831)
fastapi_14459	fastapi/fastapi	Fail (test verification failed) (14820)	Fail (timeout or budget no patch) (16154)	Fail (test verification failed) (15605)
fastapi_15588	fastapi/fastapi	Fail (test verification failed) (13083)	Fail (test verification failed) (10785)	Fail (test verification failed) (7291)
fastapi_15589	fastapi/fastapi	Fail (test verification failed) (14711)	Fail (test verification failed) (14912)	Fail (timeout or budget no patch) (14454)
fastapi_15661	fastapi/fastapi	Fail (test verification failed) (11099)	Fail (test verification failed) (14445)	Fail (test verification failed) (7180)
fastapi_9753	fastapi/fastapi	Pass (11047)	Fail (test verification failed) (11743)	Fail (test verification failed) (6469)
httpx_3672	encode/httpx	Fail (test verification failed) (14736)	Fail (test verification failed) (13010)	Fail (test verification failed) (8140)
requests_7427	psf/requests	Fail (test verification failed) (9747)	Fail (test verification failed) (15387)	Fail (test verification failed) (13362)
requests_7502	psf/requests	Fail (test verification failed) (10436)	Fail (test verification failed) (11238)	Fail (test verification failed) (14446)
requests_7505	psf/requests	Fail (test verification failed) (10800)	Fail (test verification failed) (12318)	Fail (test verification failed) (10659)
rich_3043	Textualize/rich	Fail (test verification failed) (14789)	Fail (test verification failed) (14820)	Fail (timeout or budget no patch) (14384)
rich_3944	Textualize/rich	Fail (timeout or budget no patch) (15175)	Fail (test verification failed) (15031)	Fail (test verification failed) (14528)
rich_4070	Textualize/rich	Fail (timeout or budget no patch) (13298)	Fail (test verification failed) (14826)	Fail (test verification failed) (8499)
rich_4076	Textualize/rich	Fail (test verification failed) (14577)	Fail (test verification failed) (15083)	Fail (test verification failed) (16146)
rich_4077	Textualize/rich	Fail (timeout or budget no patch) (14679)	Fail (test verification failed) (8117)	Pass (3716)

Table 3: Task-by-task paired outcomes and single-call peak prompt tokens ($\max_t P_t$) on `gemma-4-e4b-it-qat-w4a16-ct`.

Task ID	Triage Entry	Triage Peak	Patch Entry (Reset vs. Peak)	Patch Peak	Verifier Entry	Verifier Peak
fastapi_14099	2634	15961	1746 (-89.1%)	4145	1420	6860
fastapi_14361	2477	9831	1192 (-87.9%)	6365	1260	2117
fastapi_14459	2773	15605	1804 (-88.4%)	3633	1562	2496
fastapi_15588	3373	4979	1877 (-62.3%)	7291	1818	2333
fastapi_15589	3083	14454	1534 (-89.4%)	12680	1588	1588
fastapi_15661	2993	3873	1505 (-61.1%)	7180	1557	4875
fastapi_9753	2763	6469	1881 (-70.9%)	3030	1652	4976
httpx_3672	2116	7842	1261 (-83.9%)	5007	1304	8140
requests_7427	2072	13362	1326 (-90.1%)	5891	1347	1850
requests_7502	1914	14446	1480 (-89.8%)	2714	1427	3042
requests_7505	2102	10659	1293 (-87.9%)	2784	1362	1812
rich_3043	2618	14384	1388 (-90.4%)	7650	1285	2014
rich_3944	2892	14528	1187 (-91.8%)	4323	1255	2141
rich_4070	4829	8499	2126 (-75.0%)	5380	2165	7542
rich_4076	2901	16146	1212 (-92.5%)	4816	1268	1887
rich_4077	2903	3716	1203 (-67.6%)	2805	1254	1970

Table 4: Measured prompt token counts (P_t) at stage entry and stage peak across `sfd` runs (`traces/`). Note that **Patch Entry (Reset vs. Peak)** compares `PatchAgent`'s first call against `TriageAgent`'s peak call.

5.1 Testing Hypothesis 1: Observational Error Rates by Prompt-Length Bucket

To test whether longer prompts correlate with higher tool error rates in our recorded trajectories, Table 5 groups all LLM calls and tool invocations across the primary configurations (`flat_starter`, `flat_controlled`, `sfd`, 48 runs across $n = 16$ tasks) into four prompt-length buckets ($P_t < 4,000$; $4,000$–$7,999$; $8,000$–$11,999$; and $\geq 12,000$ tokens) and reports: (a) overall tool execution error rate (`status == "error"` in the tool observation), (b) `edit_file` failure rate (`FileEditError` or `BudgetExceeded`), and (c) duplicate `read_file` rate (re-reading an identical `(filepath, start_line, end_line)` slice within the same task trajectory).

Prompt Length Bucket (P_t)	LLM Calls	Tool Calls	All Tool Errors	`edit_file` Errors	Duplicate `read_file`
$<$ 4,000	155	138	19/138 (13.8%)	4/20 (20.0%)	6/50 (12.0%)
4,000 - 7,999	220	193	33/193 (17.1%)	13/38 (34.2%)	3/102 (2.9%)
8,000 - 11,999	183	160	26/160 (16.2%)	13/30 (43.3%)	6/54 (11.1%)
$\geq$ 12,000	85	72	14/72 (19.4%)	7/17 (41.2%)	5/25 (20.0%)

Table 5: Observational tool error, `edit_file` error, and duplicate `read_file` rates across per-call prompt-length buckets (P_t).

While `edit_file` failure rates increase from 20.0% (4/20) at $P_t < 4,000$ to 34.2% (13/38) at $4,000$–$7,999$, 43.3% (13/30) at $8,000$–$11,999$, and 41.2% (7/17) at $P_t \geq 12,000$ (and all-tool error rates rise from 13.8% at $P_t < 4,000$ to 19.4% at $P_t \geq 12,000$), sample sizes in the upper buckets remain modest and higher prompt lengths occur on later trajectory steps where the agent is already struggling with harder tasks or approaching the 15-call budget limit. Thus, while directionally consistent, this observational breakdown is confounded by step index and task difficulty and does not prove a causal context-dilution effect.

5.2 Testing Hypothesis 2: Exact Reconciliation of `code_analyzer_agent` Calls in `flat_starter`

Inspection of the `flat_starter` ATIF v1.7 traces confirms Hypothesis 2 and reconciles the budget-counted tool metric in Table 2 with the raw ATIF trace event count:

- In `swegemma`, `session.state["tool_calls_used"]` (reported in Table 2 as **Mean Tools** = 9.9, or **158 budget-counted calls** across 16 tasks, $\frac{158}{16} = 9.875$) increments on workspace, graph, and shell tools (`read_file`, `edit_file`, `write_file`, `run_command`, `search_similar_code`, `get_code_neighbors`, `get_code_subgraph`), including those executed inside the child `code_analyzer_agent`, but does **not** increment on free `submit_patch` calls (`13` calls) or on the parent `AgentTool` wrapper call `code_analyzer_agent(request=...)` itself (`4` calls).

- Specifically, the **176 total ATIF trace `tool_calls` events** in `flat_starter` decompose into: **145 root-agent workspace/graph/shell calls** + **14 child `code_analyzer_agent` calls** (`4` on `requests_7505`, `3` on `rich_4077`, `7` on `requests_7427`, totaling 159 attempted budget-applicable calls, of which **158** incremented `tool_calls_used` and 1 call on `fastapi_14099` was rejected after hitting the `max_tool_calls=15` cap), plus **13 free `submit_patch` calls** + **4 root `code_analyzer_agent` delegation calls** = **176 total trace tool events**.
- Out of `149` non-`submit_patch` tool decisions made by the root `swe_baseline_agent` (`145` direct workspace/graph/shell calls vs. `4` `code_analyzer_agent` delegations), `swe_baseline_agent` delegated to `code_analyzer_agent` only **4/149 times (2.7%)** (`4/176 = 2.3%` of all trace tool events), bypassing `code_analyzer_agent` completely on **13/16 tasks (81.2%)**.

5.3 Testing Hypothesis 3: Case Studies (`rich_4077` & `fastapi_9753`) and Audit of Unresolved SFD Tasks

Why `sfd` resolved `rich_4077` while `flat_starter` and `flat_controlled` (Run 1) failed, and why `flat_starter` resolved `fastapi_9753`:

- On `rich_4077` (Cohort 1, adding `isatty()` to `FileProxy` in `rich/file_proxy.py`): `flat_starter` spent all 15 budget-counted tool calls running commands and reading files (`14,679` peak prompt tokens) without ever calling `edit_file` (`0` patch chars). `flat_controlled` (Run 1) localized `rich/file_proxy.py` in 6 calls at its lowest peak prompt (`8,117` tokens), but wrote `import os` and `return os.isatty(self.__file.fileno())`, which fails Phase 2 `pytest` verification when the wrapped file object does not expose an integer file descriptor. In `sfd`, `TriageAgent` read `rich/file_proxy.py` (`3,716` peak prompt tokens) and wrote `<localization_packet>` explicitly specifying `def isatty(self) -> bool: return self.__file.isatty()`; `PatchAgent` entered at `1,203` tokens and applied that exact 3-line method (`resolved=True`). Moreover, in our rerun reproducibility study (`traces/rerun_results/`), both `sfd_rerun` (`resolved=True`) and `flat_controlled_rerun` (`resolved=True`) generated `self.__file.isatty()`, confirming that `rich_4077` does not fail due to context overflow in single-agent mode.
- On `fastapi_9753` (Cohort 2, supporting `functools.partial` in FastAPI dependencies): `flat_starter` read `fastapi/dependencies/models.py` directly (`9,595` peak prompt tokens) and edited `Dependant._unwrapped_call` to unwrap `isinstance(self.call, functools.partial)` via `return self.call.func` (`resolved=True`). By contrast, `sfd`'s `TriageAgent` (`6,469` peak prompt tokens) localized `fastapi/dependencies/utils.py` instead of `models.py`, and `PatchAgent` merely added an unused `from functools import partial` import (`test_verification_failed`). This illustrates a key trade-off of strict stage isolation: when `TriageAgent` localizes the wrong file (`utils.py` vs. `models.py`), `PatchAgent` (`include_contents: "none"`) starts with only `<localization_packet>` and does not re-explore neighboring modules.

Task ID	Submitted SFD Patch	Failure Bucket	Trace-Verified Failure Mechanism (`traces/`)
fastapi_14099	fastapi/routing.py (588 chars)	test_verification_failed	Localized `get_request_handler` in `fastapi/routing.py` (`P_t` peaked at 15,961 during `VerifierAgent`), but inserted an `AsyncExitStack` dependency callback block that broke indentation/control flow and failed generator cleanup tests.
fastapi_14361	fastapi/openapi/models.py (383 chars)	test_verification_failed	Changed `ref: str = Field(alias='$ref')` to `Optional[str] = Field(default=None, alias='$ref')` on `Reference` in `fastapi/openapi/models.py`, but missed updating `$ref` dictionary lookup in `fastapi/openapi/utils.py`.
fastapi_14459	fastapi/dependencies/models.py (783 chars)	test_verification_failed	Replaced list iteration in `Dependant.oauth_scopes` with `set(self.parent_oauth_scopes) | set(self.own_oauth_scopes)`, losing deterministic scope ordering and missing sub-dependency scope propagation in `fastapi/dependencies/utils.py`.
fastapi_15588	fastapi/sse.py (1008 chars)	test_verification_failed	Replaced `_check_id_no_null` with `_check_sse_string` (`\0`, `\n`, `\r`) on `id` and `event`, but omitted `retry` field validation and mismatched exact expected `ValueError` messages.
fastapi_15589	None (0 chars)	timeout_or_budget_no_patch	`TriageAgent` ignored the prompt's ≤3-call directive and made 10 read-only calls (`P_t` peaked at 14454); `PatchAgent` entered at 1534 tokens, read 6 slices, and hit the global 15-call cap on `edit_file`.
fastapi_15661	scripts/add_latest_release_date.py (660 chars)	test_verification_failed	Rewrote `RELEASE_HEADER_PATTERN` with mandatory escaped parentheses `\\((.*)\\)`, causing `RELEASE_HEADER_PATTERN.match()` to fail (`exit_code=1`, `No release header found`) on undated headers.
fastapi_9753	fastapi/dependencies/utils.py (349 chars)	test_verification_failed	`PatchAgent` only added `from functools import partial` to `fastapi/dependencies/utils.py` without unwrapping `functools.partial` in `Dependant._unwrapped_call` in `fastapi/dependencies/models.py` (whereas `flat_starter` unwrapped `self.call.func` in `models.py` and resolved the task).
httpx_3672	src/httpx/_server.py (630 chars)	test_verification_failed	Added `self._parser.complete()` and `self._parser.reset()` in `_server.py` and caught `KeyboardInterrupt`, but missed implementing `HTTPParser.keep_alive` and `reset()` in `src/httpx/_parsers.py`.
requests_7427	src/requests/utils.py (471 chars)	test_verification_failed	Modified `proxy_bypass` in `src/requests/utils.py` to strip URL scheme/path via `urlparse`, but missed fixing leading-dot domain boundary matching inside `proxy_bypass_environment`.
requests_7502	src/requests/models.py (581 chars)	test_verification_failed	Replaced `elif isinstance(fp, _SupportsRead):` with `elif hasattr(fp, 'read'):` at line 236 of `models.py`, but missed companion stream-wrapper length/redirect checks in `src/requests/utils.py`.
requests_7505	src/requests/models.py (978 chars)	test_verification_failed	Replaced two `isinstance(data, _SupportsRead)` checks in `models.py` with `hasattr(data, 'read')`, but missed remaining `_SupportsRead` protocol checks in `src/requests/utils.py` and `sessions.py`.
rich_3043	None (0 chars)	timeout_or_budget_no_patch	`TriageAgent` localized `CONSOLE_HTML_FORMAT` in `rich/export.py` (467 chars), but `PatchAgent` failed 4 consecutive `edit_file` calls (`old_string` not found on triple-quoted HTML template) and submitted a 0-byte diff.
rich_3070	rich/_win32_console.py (967 chars)	test_verification_failed	Added `isatty()` to `LegacyWindowsTerm` in `_win32_console.py` and caught `ValueError` in `rich/file_proxy.py`, but missed implementing `fileno()` and `write()` in `LegacyWindowsTerm`, causing `io.UnsupportedOperation` and `AttributeError` in `rich/progress.py` and `rich/_windows_renderer.py`.

Table 6: Complete task-by-task trace audit of every failure in the 100-task SWE-bench Verified Mini evaluation.

6. Related Work

Staged vs. Monolithic SWE Agents. SWE-agent ((Yang et al., 2024)) and OpenHands ((Wang et al., 2024)) equip an LLM with an interactive bash/file environment inside a continuous trajectory, whereas Agentless ((Xia et al., 2024)) uses a fixed pipeline of localization and repair without autonomous tool loops. SFD combines tool-using ADK sub-agents with stage-boundary context slicing.

Observation Masking vs. LLM Summarization. Lindenbauer et al. ((Lindenbauer et al., 2025)) (**"The Complexity Trap"**, JetBrains Research & TU Munich) show that simple observation masking of older tool outputs halves token costs while matching or outperforming LLM-based trajectory summarization on SWE-bench Verified. SFD's `include_contents: "none"` transition acts as a coarse stage-boundary observation mask.

7. Limitations & Threats to Validity

1. **Sample Size and Statistical Power:** At $n = 16$, `sfd` (1/16 = 6.2%) and `flat_starter` (1/16 = 6.2%) tie in resolution rate (McNemar $p = 1.0000$), and the 1-task difference over `flat_controlled` (0/16 = 0.0%) also yields McNemar $p = 1.0000$. Detecting a 10 percentage point paired difference (e.g., 15% vs. 5% with 12% discordant pairs) at 80% power ($\alpha = 0.05$, two-sided McNemar test) requires $N \approx 115$–130 paired tasks (essentially the entire 129-task benchmark).
2. **Confounding of Budget Limits (`max_tool_calls=15`, `max_time_minutes=2.5`) with Context Effects:** As shown in Table 2 and Table 6, 3/16 `flat_starter` runs (`rich_3944`, `rich_4070`, `rich_4077`), 2/16 `flat_controlled` runs (`fastapi_14099`, `fastapi_14459`), and 2/16 `sfd` runs (`fastapi_15589`, `rich_3043`) failed to produce a patch (`timeout_or_budget_no_patch`). Without per-stage code caps on tool calls, global budget exhaustion confounds purely architectural comparisons.
3. **Propagation of Triage Localization Errors Across Isolated Stages:** As demonstrated by `fastapi_9753` (`flat_starter` resolved by editing `models.py`, whereas `sfd` localized `utils.py`) and `rich_4070`, when `TriageAgent` misidentifies the target file or omits a companion module in a multi-file bug, `PatchAgent` receives only `<localization_packet>` and cannot recover from the upstream localization error.

8. Conclusion & Reproducibility

We presented and empirically audited State-Filtered Deliberation (SFD) on `gemma-4-e4b-it-qat-w4a16-ct` across 64 real `swegemma` + `vLLM` execution runs ($n = 16$ paired tasks across 3 configurations = 48 primary runs, plus 16 rerun reproducibility runs) on 4x NVIDIA L4 GPUs. Our traces establish three findings: (1) in the official starter kit (`flat_starter`), the 4B model bypassed the discretionary `code_analyzer_agent` on 13/16 tasks (81.2%), invoking it on only 4/149 (2.7%) of root non-`submit_patch` tool decisions; (2) configuring `include_contents: "none"` in a 3-stage `SequentialAgent` deterministically resets **stage-entry** prompt length (`PatchAgent` entry mean 1500.9 tokens vs. `TriageAgent` peak mean 10922.1 tokens, a −86.3% reset) and reduces mean single-call peak prompt tokens by 13.3% vs. `flat_starter` and 16.7% vs. `flat_controlled`, but does **not** bound `TriageAgent` or overall trajectory peak tokens (max 16146 tokens); and (3) end-to-end task resolution on 4-bit quantized E4B (1/16 = 6.2% for `sfd` and `flat_starter` vs. 0/16 = 0.0% for `flat_controlled`, McNemar $p = 1.0000$) shows a null overall resolution difference, remaining bottlenecked by multi-file localization and patch semantics. All 64 execution traces (`traces/`), leaderboard snapshots (`results/`), and scripts (`scripts/`) are publicly available at `https://github.com/KarandeepSinghSodhi/gemma-sfd-agent`.

References

Gemma Team, Google DeepMind. (2026). Gemma 4 Technical Report. *Arxiv Preprint Arxiv:2607.02770*.

Jimenez, C. E., Yang, J., Wettig, A., Yao, S., Pei, K., Press, O., & Narasimhan, K. (2024). SWE-bench: Can Language Models Resolve Real-World GitHub Issues?. *International Conference on Learning Representations (ICLR)*.

Lindenbauer, T., Slinko, I., Felder, L., Bogomolov, E., & Zharov, Y. (2025). The Complexity Trap: Simple Observation Masking Is as Efficient as LLM Summarization for Agent Context Management. *Arxiv Preprint Arxiv:2508.21433*.

Wang, X., Li, B., Song, Y., Frank, F. F., & others. (2024). OpenHands: An Open Platform for AI Software Developers as Generalist Agents. *Arxiv Preprint Arxiv:2407.16741*.

Xia, C. S., Deng, Y., Dunn, S., & Zhang, L. (2024). Agentless: Demystifying LLM-based Software Engineering Agents. *Arxiv Preprint Arxiv:2407.01489*.

Yang, J., Jimenez, C. E., Wettig, A., Lieret, K., Yao, S., Narasimhan, K., & Press, O. (2024). SWE-agent: Agent-Computer Interfaces Enable Automated Software Engineering. *Arxiv Preprint Arxiv:2405.15793*.

Yao, S., Zhao, J., Yu, D., Du, N., Shafran, I., Narasimhan, K., & Cao, Y. (2023). ReAct: Synergizing Reasoning and Acting in Language Models. *International Conference on Learning Representations (ICLR)*.