

CSE201: Monsoon 2020, Section-A  
Advanced Programming

# **Lecture 10: Generic Programming**

Vivek Kumar

Computer Science and Engineering

IIT Delhi

[vivekk@iiitd.ac.in](mailto:vivekk@iiitd.ac.in)

# Last Lecture

- Class Object
  - Correct implementation of equals method
  - Comparing objects
    - Comparable interface
    - Comparator interface
  - Copying objects

```
public class Rectangle implements Comparable<Rectangle> {
    private int sideA, sideB, area;
    public Rectangle (int _a, int _b) { ... }
    @Override
    public int compareTo(Rectangle o) {
        if(area == o.area) return 0;
        else if(area < o.area) return -1;
        else return 1;
    }
}
```

```
public class BankAccount implements Cloneable {
    private String name;
    private List<String> transactions;
    public BankAccount clone() {
        try {
            // deep copy
            BankAccount copy = (BankAccount) super.clone();
            copy.transactions = new ArrayList<String>(transactions);
            return copy;
        } catch (CloneNotSupportedException e) {
            // this will never happen
            return null;
        }
    }
}
```

```
public class RectangleAreaComparator
    implements Comparator<Rectangle> {
    @Override
    public int compare(Rectangle r1, Rectangle r2) {
        return r1.getArea() - r2.getArea();
    }
}
```

```
1. public class Point {
2.     private int x, y;
3.     public Point(int _x, int _y) { ... }
4.     @Override
5.         public boolean equals(Object o1) {
6.             if(o1 != null && getClass() == o1.getClass()) {
7.                 Point o = (Point) o1; //type casting
8.                 return (x==o.x && y==o.y);
9.             }
10.            else {
11.                return false;
12.            }
13.        }
14.    }
15.    // subclass of Point
16.    class Point3D extends Point {
17.        private int z;
18.        public Point3D(int _z) { ... }
19.        @Override
20.            public boolean equals(Object o1) {
21.                if(o1 != null && getClass() == o1.getClass()) {
22.                    Point3D o = (Point3D) o1; //type casting
23.                    return (super.equals(o1) && z==o.z);
24.                }
25.            else {
26.                return false;
27.            }
28.        }
29.    }
30. }
```

# Today's Lecture

- Generic programming in Java
  - What?
  - Why?
  - How?
  - What not to do in generic programming?

# Question

- By using any of the concepts taught till now in this course, how best can you store different types of objects?
  - E.g., String, Integer, Float, etc. ?

# Approach 1

```
public class MyGenericList {
    private ArrayList myList;
    public MyGenericList() {
        myList = new ArrayList();
    }
    public void add(Object o) {
        myList.add(o);
    }
    public Object get(int i) {
        return myList.get(i);
    }

    public static void main(String[] args) {
        MyGenericList generic = new MyGenericList();
        generic.add("hello");
        generic.add(10);
        generic.add(10.23f);
        .....
        String str = (String) generic.get(0); // OK
        String str = (String) generic.get(1); // NOT OK
    }
}
```

© Vivek Kumar

- Using inheritance we know Object class can hold any type of objects
  - We can create ArrayList of objects
- **Problems we face:**
  - Mandatory type casting while getting the object from list
  - No error checking while adding objects as we are allowed to add any type of objects
    - Wrong type casting can land you with runtime errors

# Approach 2

```
public class MyGenericList {
    private ArrayList myList;
    public MyGenericList() {
        myList = new ArrayList();
    }
    public void add(Object o) {
        myList.add(o);
    }
    public Object get(int i) {
        return myList.get(i);
    }

    public static void main(String[] args) {
        MyGenericList generic = new MyGenericList();
        generic.add("hello");
        generic.add(10);
        generic.add(10.23f);
        .....
        String str = (String) generic.get(0); // OK
        if(generic.get(1) instanceof String) {
            String str = (String) generic.get(1); // OK
        }
    }
}
```

- We can use instanceof keyword to verify the type of object retrieved from get() function
  - Is this programmer friendly?
  - How many such “if” when you have several different types of objects in the list?

# Approach 3

```
public class MyStringList {
    private ArrayList myList;
    public MyStringList() {
        myList = new ArrayList();
    }
    public void add(String o) {
        myList.add(o);
    }
    public String get(int i) {
        return myList.get(i);
    }
}
```

```
public class MyIntList {
    private ArrayList myList;
    public MyIntList() {
        myList = new ArrayList();
    }
    public void add(Integer o) {
        myList.add(o);
    }
    public Integer get(int i) {
        return myList.get(i);
    }
}
```

```
public class MyTypeXList {
    private ArrayList myList;
    public MyTypeXList() {
        myList = new ArrayList();
    }
    public void add(TypeX o) {
        myList.add(o);
    }
    public TypeX get(int i) {
        return myList.get(i);
    }
}
```

```
public class Main {
    public static void main(String args[]) {
        MyStringList strList = new MyStringList();
        MyIntList intList = new MyIntList();
        MyTypeXList typeXList = new MyTypeXList();

        strList.add("hello");
        intList.add(1);
        ...
    }
}
```

- We can create one class to hold one type of object

- How many classes for N types of objects?
- How many lines of code?

- Is this programmer friendly?
  - NO !!

# Solution: Generic Programming



- Our generic cup can hold different types of liquid
- In the notation  $\text{Cup}\langle T \rangle$ :
  - $T = \text{Coffee}$
  - $T = \text{Tea}$
  - $T = \text{Milk}$
  - $T = \text{Soup}$
  - .....

**Cup == Generic Container**



# Implementing generics

// a **parameterized** (generic) class

```
public class name<Type> {
```

or

```
public class name<Type1, Type2, ..., TypeN> {
```

- By putting the **Type** in < >, you are demanding that any client that constructs your object must supply a type parameter
  - You can require multiple type parameters separated by commas
- The rest of your class's code can refer to that type by name
- The type parameter is *instantiated* by the client. (e.g.  $E \rightarrow \text{String}$ )

# Solution to our Problem

```
public class MyGenericList <T> {  
    private ArrayList <T> myList;  
    public MyGenericList() {  
        myList = new ArrayList <T>();  
    }  
    public void add(T o) {  
        myList.add(o);  
    }  
    public T get(int i) {  
        return myList.get(i);  
    }  
}
```

- Using generic programming we don't have to implement different classes for different object types
  - Programmer friendly code!
- We just have to create different instances of MyGenericList for different objects

```
public class Main {  
    public static void main(String args[]) {  
        MyGenericList<String> strList = new MyGenericList<String>();  
        MyGenericList<Integer> intList = new MyGenericList<Integer>();  
  
        strList.add("hello");  
        intList.add(1);  
        ...  
    }  
}
```

# A Generic Class with Multiple Fields

- Let's create a class that could contain two different types of field, and type of both the fields are unknown

# Generic Class with Two Fields (1/3)

```
public class Pair <T1, T2> {  
    private T1 key;  
    private T2 value;  
    public Pair(T1 _k, T2 _v) {  
        key = _k; value = _v;  
    }  
    public T1 getKey() { return key; }  
    public T2 getValue() { return value; }  
}
```

```
public class Main {  
    public static void main(String args[]) {  
        MyGenericList<Pair> db =  
            new MyGenericList<Pair>();  
        db.add(new Pair<String, Integer>("John", 2343));  
        db.add(new Pair<String, Integer>("Susane", 8908));  
        Pair<String, Integer> p = db.get(0);  
    }  
}
```

- Why this code isn't correct?
  - There is no compilation error although (Warning)

\$ javac Generic1.java

Note: Generic1.java uses unchecked or unsafe operations.

Note: Recompile with -Xlint:unchecked for details.

- Database class instantiated without specifying the type of its two fields

# Generic Class with Two Fields (2/3)

```
public class Pair <T1, T2> {  
    private T1 key;  
    private T2 value;  
    public Pair(T1 _k, T2 _v) {  
        key = _k; value = _v;  
    }  
    public T1 getKey() { return key; }  
    public T2 getValue() { return value; }  
}
```

```
public class Main {  
    public static void main(String args[]) {  
        MyGenericList<Pair<String, Integer>> db =  
            new MyGenericList<Pair>();  
        db.add(new Pair<String, Integer>("John", 2343));  
        db.add(new Pair<String, Integer>("Susane", 8908));  
        Pair<String, Integer> p = db.get(0);  
    }  
}
```

- Why this code isn't correct
  - During instantiation we have to declare the type of fields in Database class on both RHS and LHS of statement
    - **Compilation error**

# Generic Class with Two Fields (3/3)

```
public class Pair <T1, T2> {  
    private T1 key;  
    private T2 value;  
    public Pair(T1 _k, T2 _v) {  
        key = _k; value = _v;  
    }  
    public T1 getKey() { return key; }  
    public T2 getValue() { return value; }  
}
```

- This is the correct implementation and usage of a generic class with multiple fields

```
public class Main {  
    public static void main(String args[]) {  
        MyGenericList<Pair<String, Integer>> db =  
            new MyGenericList<Pair<String, Integer>>();  
        db.add(new Pair<String, Integer>("John", 2343));  
        db.add(new Pair<String, Integer>("Susane", 8908));  
        Pair<String, Integer> p = db.get(0);  
    }  
}
```

# Goals for Generic Programming

- Writing code that can be reused for objects of many different types
  - Programmer friendly
- For example, you don't want to program separate classes to collect String and Integer objects

# Behind the Scene: Generics are Implemented using Type Erasures

```
public class MyGenericList <T> {
    private ArrayList <T> myList;
    public MyGenericList() {
        myList = new ArrayList <T>();
    }
    public void add(T o) {
        myList.add(o);
    }
    public T get(int i) {
        return myList.get(i);
    }
}

public class Main {
    public static void main(String args[]) {
        MyGenericList<String> strList = new
            MyGenericList<String>();
        strList.add("hello");
        String str = strList.get(0);
    }
}
```



→  
Compile  
Time

```
public class MyGenericList {
    private ArrayList myList;
    public MyGenericList() {
        myList = new ArrayList ();
    }
    public void add(Object o) {
        myList.add(o);
    }
    public Object get(int i) {
        return myList.get(i);
    }
}

public class Main {
    public static void main(String args[]) {
        MyGenericList strList = new MyGenericList();
        strList.add("hello");
        String str = (String) strList.get(0);
    }
}
```

- Compiler erases all parameter type information (type erasure)
- Compiler also ensures proper typecasting



# Restrictions (1/6)

- Which of the following is correct?

1. `MyGenericList <double> var = new MyGenericList<Double>();`
2. `MyGenericList <Double> var = new MyGenericList<Double>();`

Type Parameters Cannot Be Instantiated with Primitive Types !  
– No double, only Double

# Restrictions (2/6)

```
public class MyGenericClass<T> {  
    .....  
  
    public void doSomething() {  
        T my_var = new T(); // ERROR  
    }  
  
    public static void main(String[] arg){  
        .....  
    }  
}
```

- Instantiating Type variable is not allowed
  - Compile time error
  - Type erasure removes the type information at runtime and hence its impossible to figure out the type at runtime

# Restrictions (3/6)

```
public class MyGenericClass<T> {  
    .....  
  
    void doSomething(List<T> list) {  
        if(list instanceof ArrayList<Integer>) {  
            }  
        }  
  
    public static void main(String[] arg){  
        .....  
    }  
}
```

- Cannot use casts or instanceof with parameterized types
  - Compile time error
  - Type erasure removes the type information at runtime and hence its impossible to figure out the type at runtime

# Restrictions (4/6)

```
public class MyGenericClass<T> {  
    .....  
    private static T field;  
  
    public static void main(String[] arg){  
        MyGenericClass<Integer> c1 = new .....  
        MyGenericClass<String> c2 = new .....  
        MyGenericClass<Double> c3 = new .....  
        // What is the type of "field" now ?  
    }  
}
```

- Cannot declare static fields whose types are Type parameter
  - **Compilation error**
  - If it was allowed then in the code shown here what will be the Type of "field" as it's a static object hence shared by c1, c2 and c3

# Restrictions (5/6)




Image Source: Core Java, Volume-1

- Generic does not support sub-typing
  - If a class **Employee** is the superclass (parent) for a class **Manager**, then for a generic class **Pair<T>**, it does not mean **Pair<Employee>** also becomes the superclass (parent) for **Pair<Manager>**

# Restrictions (6/6)

```
public class MyGenericClass<T> {  
    .....  
  
    public void doSomething() {  
        T[] my_arr = new T[10]; // ERROR  
    }  
  
    public static void main(String[] arg){  
        // ERROR  
        MyGenericClass<String>[] str_array  
            = new MyGenericClass<String>[10];  
    }  
}
```

- Generic array creation is not allowed

- Solution: create array of Object and typecast that array to generic type

# Is there any Problem in Below Code?

```
public class Main {  
    .....  
    public static void print(ArrayList<Object> list){  
        for(Object o: list)  
            System.out.println(o);  
    }  
    public static void main(String[] arg){  
        ArrayList<Integer> I = new  
            ArrayList<Integer>();  
  
        I.add(1);  
        I.add(2);  
        ArrayList<String> S = new  
            ArrayList<String>();  
  
        S.add("Bob");  
        S.add("Paul");  
        print(I);  
        print(S);  
    }  
}
```

- The code won't compile
- Although Object is superclass for Integer and String class, it does not mean that in the print method, ArrayList<Object> can hold ArrayList<Integer> or ArrayList<String>
  - Restriction-5 discussed in this lecture
- How to resolve this issue?
  - Except removing "<Object>" in print method

# The WildCard to our Rescue !





# The WildCard “?” to our Rescue !

```
public class Main {
    ....
    public static void print(ArrayList<?> list){
        for(Object o: list)
            System.out.println(o);
    }
    public static void main(String[] arg){
        ArrayList<Integer> I = new
            ArrayList<Integer>();

        I.add(1);
        I.add(2);
        ArrayList<String> S = new
            ArrayList<String>();

        S.add("Bob");
        S.add("Paul");
        print(I);
        print(S);
    }
}
```

- We just need **one** change in our code
- Simply use a wildcard character as type variable in the parameter ArrayList in print method

# More Meaningful Example of Wildcard (1/2)

```
public class Main {
    .....
    static void print(ArrayList<? extends Car>
list){
        .....
    }
    public static void main(String[] arg){
        .....
    }
}
```

- Upper bounded wildcard
  - Here the print method will only accept ArrayList of Car type or its subclass type

# More Meaningful Example of Wildcard (2/2)

```
public class Main {  
    .....  
    static void print(ArrayList<? super Integer> list){  
        .....  
    }  
    public static void main(String[] arg){  
        .....  
    }  
}
```

- Lower bounded wildcard
  - Here the print method will only accept ArrayList of Integer or any Type that is **supertype** of Integer
    - Integer
    - Number
    - Object

# Next Lecture

- Exception Handling
- **Quiz-2 on Friday in lab slot**
  - **4.15pm-4.35pm**