

**Inventory API** 

## Authentication

To authenticate calls to the API, pass your Nox Anabel API access token as an HTTP request header named "X-Auth-Key".

Acquire Authentication key from Nox Anabel.

Please always check the HTTP status code returned from any API request. This API will return a status code between 200 and 299 when a request is successful. In any event that the request was not completed, an error code between 400 and 599 will be returned.

## **Get Active SKU List**

URL: GET http://api.noxanabel.com/API/inventory/ActiveSKUList?pgNo={pgNo}&pgSize={pgSize}

Query Parameters	Response
<ul><li>pgNo</li><li>pgSize</li></ul>	<pre>{     "Result": boolean,     "Message": null,     "Response": {         "PageNo": int,         "ListSize": int,         "SKUList": [</pre>

## Parameter

Field	Description	Value	Required
pgNo	Page number	Int	Yes
pgSize	Number of items per page in the SKU list, with a maximum limit of 500.	Int	Yes

## Response

Field	Description	Value
Result	Denotes the outcome of the data request	Boolean (T/F)
Message	Provides an error message if the result is false, otherwise null	String or null
Response	Contains a list of SKU details	List
PageNo	Specifies the page number request	Int
ListSize	Indicates the number of SKUs within the list	Int
SKUList	Contains a list of SKUs	String
TotalCount	The total number of active SKUs	Int

# Get Inventory By SKU

URL: GET http://api.noxanabel.com/API/Inventory/InventoryBySKU/{SKU#}

Query Parameters	Response
Required:  • SKU#	<pre>{     "Result": boolean,     "Message": "String",     "SKU": "String",     "SKUStatus": "String",     "Inventories": [</pre>

#### Parameter

Field	Description	Value	Required
SKU#	Style number	String	Yes

## Response

Field	Description	Value
Result	Denotes the outcome of the data request	boolean (T/F)
Message	Provides an error message if the result is false, otherwise null	String or null
Response	Contains a list of SKU details	List

SKU	Style number	String
SKUStatus	Style active status (Active/Inactive/Not Found)	String
Inventories	Style Inventory details (Color, Size, Stock quantity, Pre-order date)	List
Color	Style color	String
Size	Style sizes	String
StockQty	Number of stock in inventory	Int
PreOrderDate	Denotes the pre-order date in YYYY-MM-DDT00:00:00 format	date

# Post InventoriesBySKUs

URL: POST http://api.noxanabel.com/API/Inventory/InventoriesBySKUs

```
Request
                                              Response
                            {
  "SKUList": [
                                "Result": boolean,
     "String",
                                "Message": null,
                                "Response": [
     "String"
                                    {
                                        "SKU": "string",
}
                                        "SKUStatus": "string",
                                        "Inventories": [
                                            {
                                                 "Color": "string",
                                                 "Size": "string",
                                                 "StockQty": int,
                                                 "PreOrderDate": date
                                            },
                                    },
                                ]
```

## Request

Field	Description	Value	Required
SKUList	Contains a list of SKUs Can include up to 100 SKUs in the list	List of String	Yes

## Response

Field	Description	Value
Result	Denotes the outcome of the data request	Boolean (T/F)
Message	Provides an error message if the result is false, otherwise null	String or null
Response	Contains a list of SKU details	List
SKU	Style number	String

5	SKUStatus	Style active status (Active/Inactive/Not Found)	String
I	nventories	Style Inventory details (Color, Size, Stock quantity, Pre-order date)	List
	Color	Style color	String
	Size	Style sizes	String
	StockQty	Number of stock in inventory	Int
	PreOrderDate	Denotes the pre-order date in YYYY-MM-DDT00:00:00 format	date