

Flexx140-80W Kit 02

Bboxx Ltd.

Verify online:
<https://data.verasol.org/products/sek/bb-flx140-80W>
Valid until: December 31, 2025

Results based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-8



Meets the Requirements in IEC TS 62257-9-8:2020 for Size B kits



Mobile charging

PAYG

Pay-As-You-Go option available

5

Light point(s)



Plug-and-play



WARRANTY INFORMATION

2-year warranty that covers manufacturing defects of the control unit, PV module, and lights. Bboxx will repair by replacing a component or replacing the whole unit.

PERFORMANCE DETAILS

				Run time after a typical day of solar charging (assuming 5kWh/m ² /day)	
VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	4 Bulbs totalling 720 lumens and 5.2 W of power, and 1 tubelight totalling 230 lumens 1.6 W of power	20 hours	3.6 hours
yes	included	24" TV	24" diagonal television (9.6 W power consumption while in use)	22 hours	2 hours
yes	included	Torch	Torch (Li-ion battery: 2.5 Ah)	80 hours	4.5 hours
yes	included	Radio	Portable radio (Li-ion battery: 2.4 Ah, 3.7 V) with a power consumption of 0.72 W	160 hours	3.4 hours
no	not included	Mobile phone	Smart phone (5.7 Wh battery) with a power consumption of 5 W while in use	21 full charge(s)	1.1 full charge(s)
no	not included	16" Stand fan	16" Standing fan (9 W power)	23 hours	5.1 hours

Available daily electrical energy ^c (Wh/day)	200
---	-----



Performance measure	Brightness setting: One tubelight on High and 4 dimmable lights on high
Lighting full battery run time ^d for main unit (hours)	20
Lighting full battery run time of the torch powered by torch battery (hours)	70
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	19900

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.
^b Without any other loads used during the run time
^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.
^d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS

Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy ^e (lm/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
1.5 W Tubelight	1	3	High	230	150	81	6500	Wide	100%
1.3 W Dimmable bulb	4	3	High	180	130	82	6000	Wide	99%
Torch	1	3	High	180	130	83	6200	Wide	98%

^e Lumen efficacy is the power consumption at a light point during the light output test.
^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.
^g Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)
^h Percent of the original light output that remains after 2,000 hours of run time

SPECIAL FEATURES		
PAYG	★	Pay-As-You-Go enabled
PORTS		
2	USB 2.0 type A	 Mobile phones and radios can be charged. Adapters are included.
4	Barrel jack	 12 V ports available to charge devices and power appliances and light points.
DURABILITY		
Overall durability and workmanship		Pass
Durability tests passed		Switch test, Strain relief test, Physical ingress protection, PV durability tests
Level of water protection	Main Unit	Water ingress protection not tested, meant for indoor use only.
	PV module	Has protection from permanent outdoor exposure
	Tubelight	Water ingress protection not tested, meant for indoor use only.
	Torch	Has protection from occasional rain; met with appropriate warning label
	Radio	Water ingress protection not tested, meant for indoor use only.
SOLAR DETAILS		
PV module type		Polycrystalline silicon
PV maximum power		76 watts
MAIN UNIT BATTERY DETAILS		
Battery replaceability		Easily replaceable with common tools; however, the warranty is void if product is opened.
Battery chemistry		Lithium iron phosphate
Specific Li-ion battery chemistry		lithium iron phosphate
Battery package type		8x 32700
Battery capacity		11 Ah
Battery nominal voltage		12.8 V
Battery status/ other indicator lights		1 led light that indicates battery capacity
PRODUCT DETAILS		
Manufacturer name		Bboxx Ltd.
Product name		Flexx140-80W Kit 02
Product model / ID number		--
Contact information		c.baker-brian@bboxx.com
Website		https://www.bboxx.com/
Dimensions (entire product in package)		Multiple packages. Contact manufacturer for more information.
Mass		n/a
SSS INFORMATION		
Specs sheet expiration date		December 31, 2025
Revision		2025.11